

ADDENDUM NO. 7

June 9, 2022

**Greenfield Central High School Auditorium Renovation and
Addition – Bid Package No. 2
810 N. Broadway
Greenfield, IN 46140**

TO: ALL BIDDERS OF RECORD

This Addendum forms a part of and modifies the Bidding Requirements, Contract Forms, Contract Conditions, the Specifications, and the Drawings dated May 20, 2022, by Lancer+Beebe LLC. Acknowledge receipt of the Addendum in the space provided on the Bid Form. Failure to do so may subject the Bidder to disqualification.

This Addendum consists of Page ADD 7-1 through Add 7-2 and attached Lancer+Beebe LLC. Addendum No. 7, dated June 9, 2022, consisting of 5 pages, RFI Log consisting of 4 pages, and Drawing Sheets: LS001, S101L, S201, S401, S410, S411, A402, A511, A515, A720, A721L, A722L, M101L, M102L, M201L, M301L, M401, M501, M502, M503, M602, M603, and M604.

A. SECTION 00 31 00 BID FORM

1. Reissued entire section to include Alternate No. 7 – Natatorium Lighting and Alternate No. 8 – Natatorium Painting.

B. SECTION 01 23 00 ALTERNATES

1. Reissued entire section to include Alternate No. 7 – Natatorium Lighting and Alternate No. 8 – Natatorium Painting.

C. **SPECIFICATION SECTION 01 12 00 MULTIPLE CONTRACT SUMMARY**

1. Paragraph 3.03A Bid Categories

D. Bid Category No. 1 – General Trades

1. Delete the following specification section:

Section 11 61 13 Theatre Acoustic Shell (By Owner)

2. Add the following clarifications:

- 38. Site work demolition will require multiple mobilizations; maintain as much of the existing parking lot pavement as possible during site utilities and Natatorium foundation installation as possible; remove the existing pavement areas after discussion with and at the specific direction of the Site Manager.
- 39. Remove and replace existing ACT and drywall bulkheads as required for the installation of the new CHWS/CHWR and HWS/HWR piping as indicated on the Mechanical Drawings.

CONTRACTOR'S BID FOR PUBLIC WORKS FORM NO. 96

Format (Revised 2013)
(Amended for GCCSC)

**Greenfield Central High School Auditorium
Renovation and Addition – Bid Package No. 2**
(Greenfield Central Community School Corporation)
(Hancock County)

PART I

(To be completed for all bids. Please type or print)

Date (month, day, year): _____

BIDDER (Firm) _____

Address _____ P.O. Box _____

City/State/Zip ____

Telephone Number: _____ Email Address: _____

Person to contact regarding this Bid _____

Pursuant to notices given, the undersigned offers to furnish labor and/or materials necessary to complete the public works project of:

Insert Category No. (s) and Name(s)

Of public works project, ***Greenfield Central High School Auditorium Renovation and Addition- Bid Package No. 2***, in accordance with Plans and Specifications prepared by ***Lancer+Beebe, LLC, 220 N. College Avenue, Indianapolis, IN 46202***, as follows:

BASE BID

For the sum of _____
(Sum in words)

_____ DOLLARS (\$_____)
(Sum in figures)

Receipt of Addenda No. (s) _____

Bidder agrees that this Bid shall remain in force for a period of sixty (60) consecutive calendar days from the due date, and Bids may be accepted or rejected during this period. Bids not accepted within said sixty (60) consecutive calendar days shall be deemed rejected.

Attended pre-bid conference YES _____ NO _____

Has visited the jobsite YES _____ NO _____

The Bidder has reviewed the Guideline Schedule in Section 01 32 00 and the intent
Of the schedule can be met. YES NO

Bidder has included their Written Drug Testing Plan that covers all employees of the bidder who will perform work on the public work project and meets or exceeds the requirements set in IC 4-13-18-5 or IC 4-13-18-6. YES NO _____

The Skillman Corporation's diversity initiative is to create a program to encourage, assist and measure the active participation of Minority- Owned, Women-Owned, Veteran – Owned and Disabled Individual-Owned Businesses. The Program is to ensure that MWVDBEs are provided full and equal opportunity to participate in all Skillman Corporation's Projects.

Bidder has included:

DBE:	YES _____%	NO _____
MBE:	YES _____%	NO _____
WBE:	YES _____%	NO _____
VBE:	YES _____%	NO _____

The undersigned further agrees to furnish a bond or certified check with this Bid for an amount specified in the Notice to Bidders. If Alternate Bids apply, submit a proposal for each in accordance with the Plans and Specifications.

If additional units of material included in the contract are needed, the cost of units must be the same as that shown in the original contract if accepted by the governmental unit. If the bid is to be awarded on a unit bases, the itemization of the units shall be shown on a separate attachment.

The contractor and his subcontractors, if any, shall not discriminate against or intimidate any employee, or applicant for employment, to be employed in the performance of this contract, with respect to any matter directly or indirectly related to employment because of race, religion, color, sex, national origin or ancestry. Breach of this covenant may be regarded as a material breach of the contract.

CERTIFICATION OF USE OF UNITED STATES STEEL PRODUCTS
(if applicable)

I, the undersigned bidder or agent as a contractor on a public works project, understand my statutory obligation to use steel products made in the United States (I.C. 5-16-8-2). I hereby certify that I and all subcontractors employed by me for this project will use U.S. steel on this project if awarded. I understand that violations hereunder may result in forfeiture of contractual payments.

ALTERNATE BIDS

A blank entry or an entry of "No Bid", "N/A", or similar entry on any Alternate will cause the bid to be rejected as non-responsive only if that Alternate is selected. If no change in the bid amount is required, indicate "No Change".

****MARK "ADD" OR "DEDUCT" FOR EACH ALTERNATE****

Alternate Bid No. 1A – Ground Floor Epoxy Terrazzo

Change the Base Bid the sum of _____
(sum in words)
_____ DOLLARS (\$_____) ADD
(sum in figures) DEDUCT

Alternate Bid No. 1B – Level 2 Epoxy Terrazzo

Change the Base Bid the sum of _____
(sum in words)
_____ DOLLARS (\$_____) ADD
(sum in figures) DEDUCT

Alternate Bid No. 2A – AHU Manufacturer (Carrier)

Change the Base Bid the sum of _____
(sum in words)
_____ DOLLARS (\$_____) ADD
(sum in figures) DEDUCT

Alternate Bid No. 2B – AHU Manufacturer (Daikin)

Change the Base Bid the sum of _____
(sum in words)
_____ DOLLARS (\$_____) ADD
(sum in figures) DEDUCT

Alternate Bid No. 3A – Temperature Control Manufacturer (Alerton)

Change the Base Bid the sum of _____
(sum in words)
_____ DOLLARS (\$_____) ADD
(sum in figures) DEDUCT

Alternate Bid No. 3B – Temperature Control Manufacturer (ALC)

Change the Base Bid the sum of _____
(sum in words)
_____ DOLLARS (\$_____) ADD
(sum in figures) DEDUCT

Alternate Bid No. 4 – AHU-1 Heat Pipe

Change the Base Bid the sum of _____
(sum in words)
_____ DOLLARS (\$_____) ADD
(sum in figures) DEDUCT

Alternate Bid No. 5 – Theatre Rigging

Change the Base Bid the sum of _____
(sum in words)
_____ DOLLARS (\$_____) ADD
(sum in figures) DEDUCT

Alternate Bid No. 6 – SR1 Linear Fixtures

Change the Base Bid the sum of _____
(sum in words)
_____ DOLLARS (\$_____) ADD
(sum in figures) DEDUCT

Alternate Bid No. 7 – Natatorium Light Fixtures

Change the Base Bid the sum of _____
(sum in words)
_____ DOLLARS (\$_____) ADD
(sum in figures) DEDUCT

Alternate Bid No. 8 – Natatorium Painting

Change the Base Bid the sum of _____
(sum in words)

_____ DOLLARS (\$ _____) ADD
(sum in figures) DEDUCT

PART II

(For projects of \$150,000 or more – IC 36-1-12-4)

These statements to be submitted under oath by each bidder with and as a part of his bid. (Attach additional pages for each section as needed.)

SECTION I EXPERIENCE QUESTIONNAIRE

1. What public works projects has your organization completed for the period of one (1) year prior to the date of the current bid?

Contract Amount	Class of Work	Completion Date	Name and Address of Owner

2. What public works projects are now in process of construction by your organization?

Contract Amount	Class of Work	Completion Date	Name and Address of Owner

3. Have you ever failed to complete any work awarded to you?_____If so, where and why?

4. List references from private firms for which you have performed work.

SECTION II PLAN AND EQUIPMENT QUESTIONNAIRE

1. Explain your plan or layout for performing proposed Work. (Examples could include a narrative of when you could begin, complete the project, number of workers, etc. and any other information which you believe would enable the governmental unit to consider your bid.)

2. Please list the names and addresses of all subcontractors (i.e. persons or firms outside your own firm who have performed part of the work) that you have used on public works projects during the past five (5) years along with a brief description of the work done by each subcontractor.

3. If you intend to sublet any portion of the work, state the name and addresses of each subcontractor, equipment to be used by the subcontractor, and whether you will required a bond. However, if you are unable to currently provide a listing, please understand a listing must be provided prior to contract approval. Until the completion of the proposed project, you are under a continuing obligation to immediately notify the governmental unit in the event that you subsequently determine that you will use a subcontractor on the proposed project.

4. What equipment do you have available to use for the proposed Project? Any equipment used by subcontractors may also be required to be listed by the governmental unit.

5. Have you into contracts or received offers for all materials which substantiate the prices used in preparing your proposal? If not, please explain the rationale used which corroborate the process listed.

SECTION III CONTRACTOR'S FINANCIAL STATEMENT

Attachment of Bidder's financial statement is mandatory. Any Bid submitted without said financial statement as required by statute shall thereby be rendered invalid. The financial statement provided hereunder to the governing body awarding the Contract must be specific enough in detail so that said governing body can make a proper determination of the Bidder's capability for completing the Project if awarded.

SECTION IV CONTRACTOR NON-COLLUSION AFFIDAVIT

The undersigned Bidder or agent, being duly sworn on oath, says that he has not, nor has any other member, representative, or agent of the firm, company, corporation or partnership represented by him, entered into any combination, collusion or agreement with any person relative to the price to be bid by anyone at such letting nor to prevent any person from bidding nor to induce anyone to refrain from bidding, and that this Bid is made without reference to any other bid and without any agreement, understanding or combination with any other person in reference to such bidding.

He further says that no person or persons, firms, or corporations has, have, or will receive directly or indirectly, any rebate, fee, gift, commission, or thing of value on account of such contract.

SECTION V OATH AND AFFIRMATION

I HEREBY AFFIRM UNDER THE PENALTIES OF PERJURY THAT THE FACTS AND INFORMATION CONTAINED IN THE FOREGOING BID FOR PUBLIC WORKS ARE TRUE AND CORRECT

Dated at _____ this _____ day of _____, 20

(Name of Organization)

By

(Title of Person Signing)

ACKNOWLEDGEMENT

STATE OF _____)

) SS:

COUNTY OF _____)

Before me, a Notary Public, personally appeared the above-named

Swore that the statements contained in the foregoing document are true and correct.

Subscribed and sworn to before me this _____ day of _____,

(Title)

Notary Public

My Commission Expires: _____

County of Residence: _____

END OF SECTION 00 31 00

SECTION 01 23 00 - ALTERNATES

PART 1 - GENERAL

1.01 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including amended General Conditions and other Division 1 Specification Sections, apply to work of this Section.

1.02 PURPOSE

- A. The Bids for the Alternates described herein are required in order for the Owner to obtain information necessary for the proper consideration of the Project in its entirety.

1.03 ALTERNATES

- A. Definitions: Alternates are defined as alternate products, materials, equipment, installations or systems for the Work, which may, at Owner's option and under terms established by Instructions to Bidders, be selected and recorded in the Owner-Contractor Agreement to either supplement or displace corresponding basic requirements of Contract Documents. Alternates may or may not substantially change scope and general character of the Work; and must not be confused with "allowances", "unit prices", "change orders", "substitutions", and other similar provisions.

1.04 SCHEDULE OF ALTERNATES

- A. ALTERNATE NO. 1: EPOXY TERRAZZO FLOORING
 - 1. Base Bid: Luxury Vinyl Tile
 - 2. Alternate 1A: State cost to delete LVT and provide materials, labor, and equipment to install the Epoxy Terrazzo Flooring at Room Nos. L102, L104, L118 and B146 as indicated on A720 and A721L. Include precast terrazzo wraparound treads from L102 down to L104.
 - 3. Alternate 1B: State cost to delete LVT and provide materials, labor, and equipment to install the Epoxy Terrazzo Flooring at Room Nos. L201 and L202 as indicated on A720 and A722L. Include precast terrazzo stair treads from L202 down to L102.
- B. ALTERNATE NO. 2: AHU MANUFACTURER
 - 1. Base Bid: Trane
 - 2. Alternate 2A: State cost to provide AHU Equipment as manufactured by Carrier.
 - 3. Alternate 2B: State cost to provide AHU Equipment as manufactured by Daikin.

- C. ALTERNATE NO. 3: TEMPERATURE CONTROL MANUFACTURER
1. Base Bid: Trane

2. Alternate 3A: State cost to provide Temperature Controls as manufactured by Alerton.

3. Alternate 3B: State cost to provide Temperature Controls as manufactured by ALC.
- D. ALTERNATE NO. 4: AHU-1 HEAT PIPE
1. Base Bid: No Heat Pipe at AHU-1

2. Alternate: State cost to provide materials, labor, and equipment to install the heat pipe at AHU-1.
- E. ALTERNATE NO. 5: THEATRE RIGGING
1. Base Bid: (23) manual counterweight linesets and (8) fixed speed, motorized linesets.

2. Alternate: State cost to provide materials, labor, and equipment to upgrade (3) manual linesets to variable speed, motorized operation for a total of (20) manual and (11) motorized linesets.
- F. ALTERNATE NO. 6: SR1 LINEAR FIXTURES
1. Base Bid: No Work

2. Alternate: State cost to provide materials, labor, and equipment to install the SR1 linear light fixtures, wiring and controls as indicated in the AL series drawings.
- G. ALTERNATE NO. 7: NATATORIUM LIGHT FIXTURES
1. Base Bid: New H3 Fixtures per Key Note 1 on Sheet E201K-A.

2. Alternate: State cost to provide materials, labor, and equipment to remove and dispose of the existing Natatorium light fixtures and install new H3 fixtures per Key Note 2 on Sheet E201K-A.
- H. ALTERNATE NO. 8: NATATORIUM PAINTING
1. Base Bid: Paint walls indicated by Key Note 6 on Sheet A721L.

2. Alternate: State cost to provide materials, labor, and equipment to paint the existing Natatorium walls per Key Note 23 on Sheet A721L.

PART 2 - PRODUCTS, PART 3 - EXECUTION (Not Used)

END OF SECTION 01 23 00

LANCER + BEEBE, LLC

Project # 21107

ADDENDUM NO. SEVEN

PROJECT: GREENFIELD CENTRAL – AUDITORIUM RENOVATION AND ADDITION

PROJECT NUMBER: 21107

DATE OF ADDENDUM: JUNE 9, 2022



THIS ADDENDUM FORMS A PART OF THE CONTRACT DOCUMENTS AND IS ISSUED IN ACCORDANCE WITH THE INSTRUCTIONS TO BIDDERS. ACKNOWLEDGE RECEIPT OF THIS ADDENDUM BY SIGNING THE ADDENDUM ACKNOWLEDGMENT SECTION OF THE BID FORM.

Q+A LOG: PLEASE REVIEW THE ATTACHED QUESTION AND ANSWER LOG.

SPECIFICATIONS:

1. SPEC SECTION: 07 42 14 FORMED METAL WALL PANELS
CHANGE: ADD NEXGEN DESIGN SYSTEM MOSAIC FORMED PANELS AS A PRE-APPROVED EQUAL
2. SPEC SECTION: 07 46 16 WOODGRAIN ALUMINUM SOFFITS AND CEILINGS
CHANGE: ADD KNOTWOOD AS A PRE-APPROVED EQUAL
3. SPEC SECTION: 08 81 17 FIRE RATED GLASS
CHANGE: ADD SUPER CLEAR 45-HS-LI AS A PRE-APPROVED EQUAL

DRAWINGS:

1. S101L – Foundation Plan – Unit L
 - Added section for elevator pit footing
2. S201 – Enlarged Auditorium Foundation Plan
 - Adjusted orchestra pit and sloping slab approaching pit
3. S401 – Typical Foundation Sections
 - Adjusted detail 3
4. S410 – Foundation Sections
 - Adjusted detail 14
 - Added detail 20
5. S411 – Foundation Sections
 - Adjusted details 5 & 6

ARCHITECTURE:

1. LS001
 - TP-4 [DELETED]
 - TP-5 ADDED
 - REVISED PATH OF TRAVEL SCHEDULE
2. A402
 - REVISED DETAIL 2/A402
3. A511
 - REVISED DETAIL 7/A511
4. A515
 - REVISED DETAIL 1/A515
 - REVISED DETAIL 2/A515
 - REVISED DETAIL 7/A515
5. A720
 - RB-3 ADDED
 - CON-1 REVISED
 - CON-2 REVISED
6. A721L
 - FINISH PLAN NOTE 23 ADDED
7. A722L
 - REVISED L202 FINISH TAG

ATTACHMENTS: Q+A LOG.PDF | BID PACKAGE #1 ADDENDUMS

<https://lancerbeebe.egnyte.com/fl/OGOWJAmcJi> | DRAWINGS:

LS001, S101L, S201, S401, S410, S411, A402, A511, A515, A720, A721L, A722L

END OF ADDENDUM NO. SEVEN

Greenfield Central High School Auditorium Renovation & Addition

**Greenfield Central High School
Greenfield, Indiana**

ADDENDUM NO. 7

HEAPY PROJECT NO. 2021-07128

June 9, 2022

SPECIFICATIONS

ITEM NO. 1 23 33 00 – AIR DUCT ACCESSORIES

A. Paragraph 2.4.C:

- 1) Add Pottorff as an approved manufacturer.

ITEM NO. 2 23 34 00 – HVAC FANS

A. Paragraph 2.3.B:

- 1) Add Skyblade as an approved manufacturer.

ITEM NO. 3 23 51 17 – BREECHINGS, CHIMNEYS, AND STACKS

A. Paragraph 2.4:

- 1) Add Duravent as an approved manufacturer.

ITEM NO. 4 23 73 00 – MODULAR AIR HANDLING UNITS

A. Paragraph 2.6.Q:

- 1) Add the following to paragraph Q: “VFD shall be manufactured by ABB and factory installed and wired by the air handler manufacturer.”

ITEM NO. 5 23 82 16 – DUCT HEATING COILS

A. Paragraph 2.2:

- 1) Add Greenheck as an approved manufacturer.

ITEM NO. 6 26 41 00 – FACILITY LIGHTNING PROTECTION SYSTEM

A. Paragraph 2.1

- 1) Add Robbins Lightning, Inc, Maryville, Missouri as an approved manufacturer / provider.

DRAWINGS

- ITEM NO. 1 M101L - MECHANICAL DUCTWORK PLAN - FIRST FLOOR - UNIT L
- A. Add return air balancing dampers.
 - B. Modify plan note 16.
 - C. Add tags.
- ITEM NO. 2 M102L - MECHANICAL DUCTWORK PLAN - SECOND FLOOR - UNIT L
- A. Modify plan note 1.
 - B. Add tags.
- ITEM NO. 3 M201L - MECHANICAL PIPING PLAN - FIRST FLOOR - UNIT L
- A. Modify tag.
- ITEM NO. 4 M301L - MECHANICAL ROOF PLAN - UNIT L
- A. Modify plan note 3.
- ITEM NO. 5 M401 - ENLARGED MECHANICAL PLANS
- A. Modify flow arrows.
- ITEM NO. 6 M501 - MECHANICAL DETAILS
- A. Edit details 8, 9, 11, and 13.
- ITEM NO. 7 M502 - MECHANICAL DETAILS
- A. Edit details 2, 3, 6, and.
 - B. Add details 12 and 13.
- ITEM NO. 8 M503 - MECHANICAL DETAILS
- A. Modify AHU elevations.
- ITEM NO. 9 M602 - ATC DIAGRAMS
- A. Edit AHU-1 ATC diagram.
- ITEM NO. 10 M603 - ATC DIAGRAMS
- A. Edit AHU-1 ATC diagram.
- ITEM NO. 11 M604 - ATC DIAGRAMS
- A. Edit AHU-1 ATC diagram.

ATTACHMENTS

- ITEM NO. 1 M101L - MECHANICAL DUCTWORK PLAN - FIRST FLOOR - UNIT L
- ITEM NO. 2 M102L - MECHANICAL DUCTWORK PLAN - SECOND FLOOR - UNIT L
- ITEM NO. 3 M201L - MECHANICAL PIPING PLAN - FIRST FLOOR - UNIT L
- ITEM NO. 4 M301L - MECHANICAL ROOF PLAN - UNIT L
- ITEM NO. 5 M401 - ENLARGED MECHANICAL PLANS
- ITEM NO. 6 M501 - MECHANICAL DETAILS
- ITEM NO. 7 M502 - MECHANICAL DETAILS
- ITEM NO. 8 M503 - MECHANICAL DETAILS
- ITEM NO. 9 M602 - ATC DIAGRAMS
- ITEM NO. 10 M603 - ATC DIAGRAMS
- ITEM NO. 11 M604 - ATC DIAGRAMS

Greenfield Auditorium RFI Log

RFI Contact(s):
RFI Due Date/Time:
Bid Date/Time:

Published:06/10/2022


RFI LOG

No.	DATE SUBMITTED	RESPONSIBLE PARTY	QUESTION	DATE RECEIVED	FROM	RESPONSE
1	4/28/2022	L+B	Please note Item 2.4, A., in specification 034100. Is the precast mix on all panels to be all structural gray concrete? All exterior panels appear to be covered with thin brick. For thin brick clad panels, it is recommended to acid etch/rinse the precast panels to clean the thin brick and to etch between the thin brick pieces for consistency. Do you want the brick clad precast panels to be acid etched/rinsed or the leave the finished surface with the cast thin brick unfinished?	4/28/2022	CORES LAB	Structural gray concrete is acceptable. Acid etched/rinsed is desired on the exterior.
2	4/28/2022	L+B	Please note Item 2.13, A. in specification 034100. The interior precast panel faces, are they to have a smooth as cast from the form finish? And, can the precast panel (all) back finishes be a two-pass hard hand steel trowel?	4/28/2022	CORES LAB	Precast panel back finishes can be a two-pass hand steel trowel.
3	4/28/2022	L+B	Please note Item 2.14, B., 3.(thin brick type 3), per the Exterior Elevation Notes on sheets A201, 202, and 203, Glen Gery Brick noted should be Pearl River, Wire Cut, not Brazilwood, Wire cut. Please confirm? Please be advised that thin brick lead times are not controlled by the precaster and could affect the project schedule if the thin brick material is not available/received at the precast plant in time to meet the casting schedule	4/28/2022	CORES LAB	See revised specification issued in Addendum No. 5.
4	4/28/2022	TSC	Are electrical boxes and conduits going to need to be cast into the precast panels? If so, please confirm that the electrical hardware will be furnished by others to the precast plant prior to casting by Others. Also, can we be given an estimated quantity of electrical hardware that will need to be cast in?	4/28/2022	CORES LAB	Yes, these items will be furnished by the Electrical/Low Voltage Contractor to the Bid Category No. 2 Contractor. Please refer to the bid documents to determine quantities and locations.
5	4/28/2022	TSC	Please confirm the steel ledge angels shown, attached to steel embed cast in precast embed plates, are to be furnished and installed by Others. (Ex. details 7, 9, 10 – S610). And the precaster in those similar details is to furnish and cast in the flat embed plates only cast into the precast panel backs?	4/28/2022	Geiger & Peters	All connection steel shapes, attached to precast embed plates, required for the proper support of the structural steel system shall be provided by Bid Category No. 4 Contractor..
6	4/28/2022	L+B	Please reference specification 034100, page 7, Item 2.13, B. Can you confirm the size of all thin brick to be cast into the precast panels for the project is to be modular size, 2-1/4" x 7-5/8"?	4/28/2022	CORES LAB	See revised specification issued in Addendum No. 2.
7	5/13/2022	L+B	07 53 23 - The EPDM spec states the system is ballasted but also indicates the insulation is to be mechanically fastened. I assume this is a mistake and the insulation is to be loose laid. (fastening would defeat the cost advantage of ballast)	5/3/2022	Foster Contracting	Ballasted roof scope is limited to the Natatorium seating expansion (Unit K).

8	5/13/2022	L+B	07 53 23 - The EPDM spec lists Manville and Firestone as approved membrane manufacturers. I would assume Firestone and Manville would also be acceptable for the PVC membrane? I would think the school would prefer one manufacturer warranty.	5/3/2022	Foster Contracting	Yes - These manf. are acceptable. Manufacturers products must meet or exceed product performance and warranty listed in the specifications.
9	5/13/2022	L+B	07 54 19 - The PVC spec lists water based adhesive. Is solvent based adhesive also acceptable?	5/3/2022	Foster Contracting	Acceptable adhesives are per the manufacturer installation instructions/requirements.
10	5/13/2022	L+B	07 54 19 - The PVC spec lists light gray as the specified color for the membrane. This may / will significantly lengthen the lead time. I would advise proceeding with white membrane.	5/3/2022	Foster Contracting	Manufacturers standard white or grey is acceptable.
11	5/13/2022	L+B	Drawing A003 - Is R1c the only roof system that is the ballasted EPDM? I cannot tell which membrane goes where	5/3/2022	Foster Contracting	R1c is the only roof system that is ballasted. Roof types are labeled throughout the documents.
12	5/13/2022	TSC	What is the material for the wall rail (Note #46) and segmented handrail (note #49 and #59) on A112L? Are we responsible for these? Reason I ask is because we are not responsible for the Decorative Rail which is commonly aluminum or stainless. This would lead me to believe that the rails in question would be aluminum or stainless to match the deco rail and the deco rail vendor would be responsible for these.	5/10/2022	Almet, Inc.	Items mentioned here should be considered by the decorative metal contractor.
13	5/13/2022	L+B/TSC	Who is responsible for stair nosings? I see where they are supposed to go, but its not listed as to who is responsible for them.	5/10/2022	Almet, Inc.	AT THIS TIME WE DO NOT ANTICIPATE CAST IN NOSINGS.
14	5/13/2022	L+B	Where is detail 4/A517 cut? Its showing "Front of House" but I do not see where its cut. Also, it shows chain-link fencing along the "catwalk except as noted". This is the only detail that shows where it is noted. Is fencing needed all around the catwalk? Who is responsible for it? If we are, what is the spec for it? Its not listed anywhere.	5/10/2022	Almet, Inc.	See revised sheet A112L for sections.
15	5/13/2022	L+B	What is the spec or basis of design for the "Perforated Metal Riser"? Only thing listed is that I am to provide 14 GA if not stated elsewhere	5/10/2022	Almet, Inc.	Stairs in this project DO NOT have "Perforated Metal Risers"
16	5/13/2022	L+B	Would 8' precast panels be acceptable? We can improve our delivery date with 8' panels.	5/10/2022	FABCON	Design team does not recommend switching to an 8' panel as this will force redesign of exterior, interior structural, and MEP elements.
17	5/13/2022	TSC	Elevator Questions - Who is responsible for the elevator accessories 1. Elevator sill angles 2. Elevator sump pit grating We do plan on including the elevator hoist beam. This is common. The reason why we ask is that I see from the drawings that the elevator pit ladder is being supplied by the elevator MFG. (5/A402) Otherwise, we would add these with our bid.	5/10/2022	Almet, Inc.	1. Support angles for elevator sills by Elevator Subcontractor. 2. Elevator sump pit cover/grate by Bid Category No. 4 Contractor. 3. Hoist beams by Bid Category No. 4 Contractor. 4. Elevator pit ladders by Elevator Subcontractor.
18	5/13/2022	L+B/TSC	Is the Box Boom guardrail at detail 1 & 2/A517 the guardrail noted #61 on A112L? There are 6 total of different lengths. If its not Note #61, am I responsible for detail 1 & 2/A517 If so, how is it attached to the structure?	5/12/2022	Almet, Inc.	Bid Category No. 4 Contractor shall provide Box Boom and guard rail pipe assemblies. See revised plan notes on A112L in Addendum No. 5. Please refer to A303 for axon views of the areas in question.
19	5/16/2022	TSC	Who is building and maintaining the roadways for crane and truck access?	5/12/2022	High Concrete	Bid Category No. 1 General Trades

20	5/16/2022	TSC	Who is responsible for cleaning the footings from the mud and debris tracked by other trades prior to panel erection?	5/12/2022	High Concrete	Bid Category No. 1 General Trades
21	5/16/2022	TSC	Will there be any underground utilities our trucks/cranes should be aware of? The site changes drastically during construction and our team cannot be responsible for that.	5/12/2022	High Concrete	Refer to the Site Utilities drawing C400 within the Civil documents; contractor is to assume that the new structures will be in place and that road plates will be required to protect same. Bid Category No. 2 Contractor shall protect these utility structures as required during precast erection work.
22	5/16/2022	TSC	How long do we anticipate the braces being left on for until the steel is erected? 1 month additional is included, but sometimes it carries into the 2nd month	5/12/2022	High Concrete	Include two (2) months of bracing.
23	5/16/2022	TSC	Will there be requirements for flagmen and/or barricades, road closures	5/12/2022	High Concrete	Flagmen and barricades, as required to safely erect your work, are to be included. We do not anticipate requiring any road closures.
24	5/16/2022	L+B	Spec Section 34100 - 2.8A and 2.8B Insulated Flat Wall Panel Accessories indicates ship-lap edges and glass-fiber vinylester connectors for insulation and wythe connectors, which would indicate a Thermomass System. Will other systems be allowed if they meet the required structural design? Square edges and carbon-fiber wythe connectors have been used in similar school projects with equal to or better than designed capacities.	5/12/2022	High Concrete	We do not require 'ship lap' edges. It is not necessary and will not affect to any great degree the thermal performance of the panels. Butt edges for foam board will be allowed. The connectors are HK, non-metal and non-conductive and should be allowed; other non-conductive connectors like c-grid should also be acceptable.
25		L+B	Please confirm the external insulation and what type for the exposed duct in the auditorium from AHU-1 on M101L? The schedule on M702 says all the other exposed ducts call for dual wall insulated duct. Sec 230713 2.3 calls out fiberglass board insulation for exposed ductwork, board is for rectangular duct, but all the exposed duct is round.	6/8/2022	Lehman's	
26	6/9/2022	L+B	142400 - Elevators 1.1.3A1. This has all items listed, please confirm that there shall not be any seismic for this project. 2.1.4A1 and 1.5A – please confirm that the warranty/service for the elevator is one year and that the building listing, if any, is not applicable if different. I did not see a time listed. 3.2.9 A5e. please confirm that stainless steel can be provided, this ceiling is not available in powdercoat. 4.3.3 A. There is no time listed, and we take this to be the requirement IF elected by the GC. Please confirm that no Temporary use is to be included in the bid.	6/8/2022	TKE	1. Confirmed. 2. Confirmed. 3. Stainless steel is acceptable. 4. Confirmed
27		L+B	Is the expanded bleacher area, adjacent to the auditorium addition, outside of the new FP systems scope of work? There is not a fire protection system within the existing swimming pool area.	6/9/2022	Integrity	
28		L+B	Drawing 5/TP101 shows the stage right side of some platforms open to the pit, and thus visible to the audience. Would it be preferable to have these open sides covered with skirting, or open with black painted frames and legs?	6/9/2022	Wenger	


29		L+B	A121 Note 48 indicates a portable ADA ramp straight on with pit opening to seating area. 7/A314 appears to show this ADA ramp, but it does not reach the height of the seating area. Can it please be confirmed that the ADA ramp is to be per 5/TP101 & 6/TP101, and can A121 and 7/A314 please be revised to not include the straight on short ADA ramp?	6/9/2022	Wenger	
30		L+B	Drawing TP101 does not show a detail of the guard rails/hand rails on the platforms shown in 5/TP101. Are guard rails that restrict a sphere with a diameter larger than 4" to pass required? Are manufacturers standard guard rails acceptable?	6/9/2022	Wenger	
31		L+B	5/TP101 does not appear to show 5' diameter of clearance for a wheel chair to turn with the necessary overhanging ramp hand rails. Does the specified design meet the minimum clearance space required by the AHJ? If not, can a revised drawing please be provided?	6/9/2022	Wenger	
32		L+B	11 61 23 Theatre Portable Platforms - •2.2 E. specifies aluminum frames and leg assemblies that are not visible to the audience do not require black finish. 3.1 C. specifies all metal fabricated items shall be given at least one coat of primer and one coat of finish paint. Color: black. Can 2.2 E. please be confirmed that mill aluminum finish frames and legs are approved provided they are not visible to the audience? Can 3.1 C. please be removed?	6/9/2022	Wenger	



2 FIRESTOPPING PENETRATION MOCKUP PANEL

SCALE: 1/2" = 1'-0"

PATH OF TRAVEL		
MARK	LENGTH	
TP-1	19'1" - 2'9'10"	TP - TRAVEL PATH
TP-2	80" - 7'11 1/2"	
TP-3	248" - 2'	
TP-5	131" - 0'11'10"	



1 LIFE SAFETY PLAN - FIRST FLOOR

SCALE: 3/64" = 1'-0" REF. 3 / A142

BUILDING CODE SUMMARY

APPLICABLE CODES:

2014 INDIANA BUILDING CODE*
2014 INDIANA FIRE CODE
2009 INDIANA ELECTRICAL CODE
2014 INDIANA MECHANICAL CODE
2012 INDIANA PLUMBING CODE
2010 INDIANA ENERGY CONSERVATION CODE
ICC/ANSI A-117.1 STANDARD, 2009 EDITION
GENERAL ADMINISTRATIVE RULES (GAR)
*CODE REFERENCED UNLESS NOTED OTHERWISE

APPLICABILITY OF CODES:

ALTERATIONS ARE PERMITTED TO AN EXISTING BUILDING WITHOUT REQUIRING THE ENTIRE EXISTING BUILDING OR PORTIONS OF THE EXISTING BUILDING UNAFFECTED BY THE PROPOSED SCOPE OF RENOVATION TO BE BROUGHT INTO COMPLIANCE WITH CURRENT CODES. [RULE 4, SECTION 12, GAR]

SCOPE OF PROJECT:

THE PROJECT INVOLVES A RENOVATION AND AUDITORIUM ADDITION TO THE EXISTING HIGH SCHOOL.

OCCUPANCY CLASSIFICATIONS:

ASSEMBLY AREAS ASSOCIATED WITH AN E OCCUPANCY
- E OCCUPANCY [303.1.3]

OFFICES - B OCCUPANCY [304.1]

STORAGE - S-1 OCCUPANCY [311.2]

ASSEMBLY SPACES ACCESSORY TO AN E OCCUPANCY ARE NOT CONSIDERED SEPARATE OCCUPANCIES. [TABLE 302.3.3, FOOTNOTE E]

CONSTRUCTION TYPE:

TYPE IIB (NONCOMBUSTIBLE, UNPROTECTED) CONSTRUCTION EXISTING AND PROPOSED. ANY CONSTRUCTION TYPE PERMITTED BASED UPON COMPLYING WITH SECTION 507.4 FOR UNLIMITED AREA 2-STORY BUILDINGS OF GROUP B, E, F, M, OR S OCCUPANCY. [507.4]

ALLOWABLE AREA:

UNLIMITED AREA BASED UPON BEING SPRINKLERED THROUGHOUT AND HAVING AT LEAST 60 FEET OF OPEN SPACE ON ALL SIDES OF THE BUILDING MEASURED TO PROPERTY LINES OR THE OPPOSITE SIDE OF A PUBLIC WAY. [507.4]

ALLOWABLE HEIGHT:

2-STORIES AND 60 FEET BASED UPON COMPLYING WITH SECTION 507.4 [507.4]

BUILDING ELEMENTS - FIRE-RESISTIVE REQUIREMENTS:

STRUCTURAL FRAME, INTERIOR WALLS, FLOOR ASSEMBLIES, AND ROOF ASSEMBLIES ARE PERMITTED TO BE OF ANY CONSTRUCTION TYPE. [507.4]

OCCUPANCY SEPARATIONS:

OCCUPANCY SEPARATIONS NOT REQUIRED. BUILDING COMPLIES AS NON-SEPARATED MIXED USES. [506.3]

INCIDENTAL USE SEPARATIONS:

THE FOLLOWING ROOMS ARE REQUIRED TO BE PROVIDED WITH A NONRATED SEPARATION CONSISTING OF WALLS TERMINATING AT THE DECK, WITH SELF-CLOSING DOORS:
- FURNACE ROOMS WITH EQUIPMENT OVER 400,000 BTU/HOUR INPUT
- BOILER ROOMS WITH EQUIPMENT OVER 15 PSI AND 10 HP [TABLE 509]

ELECTRICAL TRANSFORMER ROOMS REQUIRED TO BE SEPARATED WITH 1-HOUR CONSTRUCTION IF CONTAINING OIL-INSULATED TRANSFORMERS OVER 75KVA, OR DRYTYPE TRANSFORMERS OVER 112.5KVA, AND THE TRANSFORMERS ARE LESS THAN A CLASS 155 INSULATION SYSTEM RATING. [450.42, 450.21(B), IEC]

SEPARATION OF DRESSING AND APPURTENANT ROOMS:

THE STAGE MUST BE SEPARATED FROM DRESSING ROOMS, STORAGE ROOMS, SCENE DOCKS, PROPERTY ROOMS AND OTHER ROOMS APPURTENANT TO THE STAGE MUST BE SEPARATED BY 1-HOUR FIRE BARRIERS. DRESSING ROOMS, STORAGE ROOMS AND OTHER ROOMS APPURTENANT TO THE STAGE MUST BE SEPARATED FROM EACH OTHER BY A 1-HOUR FIRE BARRIER. OPENINGS IN 1-HOUR FIRE BARRIERS MUST BE 45MINUTE RATED AND AUTOMATIC OR SELF-CLOSING. [410.5, TABLE 716.5]

FLOOR OPENINGS & SHAFT ENCLOSURES:

A 2-STORY FLOOR OPENING IS PERMITTED. [712.1.8]

EXIT STAIRS ARE REQUIRED TO BE ENCLOSED WITH 1-HOUR FIRE BARRIERS. FIRE BARRIERS MUST BE CONTINUOUS FROM THE FOUNDATION TO THE UNDERSIDE OF THE FLOOR SHEATHING, SLAB, DECK, OR ROOF ABOVE. OPENINGS IN MUST BE 60-MINUTE RATED. OPENINGS MUST BE SELF OR AUTOMATIC CLOSING. [713.4, TABLE 716.5, 716.5.9]

DUCTS THAT CONNECT NOT MORE THAN TWO STORIES ARE NOT REQUIRED TO BE ENCLOSED IN A SHAFT WHEN THE ANNUAL SPACE AROUND THE DUCT IS PROTECTED WITH AN APPROVED NONCOMBUSTIBLE MATERIAL THAT RESISTS THE FREE PASSAGE OF FLAME AND THE PRODUCTS OF COMBUSTION. [717.6.3, EXC 2]

SPRINKLER PROTECTION CAN BE OMITTED FROM ELEVATOR SHAFTS WHERE ENCLOSED WITH 2-HOUR CONSTRUCTION. IF SPRINKLERED THE ELEVATOR SHAFT MUST BE ENCLOSED WITH 1-HOUR RATED CONSTRUCTION. [803.3.1.1.1, 713.4]

FIRE AND SMOKE DAMPERS:

FIRE DAMPERS REQUIRED FOR DUCT PENETRATIONS OF RATED SHAFTS AND 2-HOUR FIRE BARRIERS. FIRE DAMPERS NOT REQUIRED FOR PENETRATIONS OF 1-HOUR FIRE BARRIERS BY DUCTED HVAC SYSTEMS WHERE DUCTS ARE CONSTRUCTED OF SHEET STEEL NOT LESS THAN NO. 26 GAGE THICKNESS AND ARE CONTINUOUS FROM THE AIR-HANDLING APPLIANCE OR EQUIPMENT TO THE AIR OUTLET AND INLET TERMINALS. SMOKE DAMPERS NOT REQUIRED. [717.5]

OCCUPANT LOAD FACTORS:

UNCONCENTRATED ASSEMBLY USE: 15 SQ. FT./OCC.
ROW SEATING - BLEACHERS: 18 IN./OCC.
STAGE: 15 SQ. FT./OCC.
OFFICE: 100 SQ. FT./OCC.
STORAGE/MECHANICAL: 300 SQ. FT./OCC. [TABLE 1004.1.2]

CORRIDORS:

CORRIDORS ARE PERMITTED TO BE NON-RATED BASED UPON SPRINKLER PROTECTION THROUGHOUT. [TABLE 1018.1]

CORRIDORS HAVING A CAPACITY OF 100 OR MORE MUST BE A MINIMUM 72 INCHES IN CLEAR AND UNOBSTRUCTED WIDTH. A MINIMUM OF 44 INCHES IS PERMITTED WHERE SERVING AN OCCUPANT LOAD LESS THAN 100 AND A MINIMUM OF 36 INCHES IS PERMITTED WHERE SERVING AN OCCUPANT LOAD LESS THAN 50. [TABLE 1018.2]

DEAD END CORRIDORS MUST NOT EXCEED 50 FEET [1018.4]

DOORS:

DOOR WIDTH MUST BE A MINIMUM OF 32 INCHES CLEAR AND 48 INCHES MAXIMUM. [1008.1.1]

EGRESS DOORS MUST SWING IN THE DIRECTION OF EGRESS WHEN SERVING 50 OR MORE OCCUPANTS. EGRESS DOORS ARE REQUIRED TO BE SIDE-HINGED SWINGING TYPE, EXCEPT FOR OFFICE AND STORAGE AREAS WITH AN OCCUPANT LOAD OF LESS THAN 10. MANUALLY OPERATED HORIZONTAL SLIDING DOORS PERMITTED FROM ROOMS WITH AN OCCUPANT LOAD THAT DOES NOT EXCEED 10. [1008.1.2]

PANIC HARDWARE:

PANIC HARDWARE IS REQUIRED FOR DOORS THAT LATCH IN E OCCUPANCIES WHERE THE ROOM OR AREA HAS AN OCCUPANT LOAD OF 50 OR MORE. EGRESS DOORS SERVING ELECTRICAL ROOMS WITH EQUIPMENT RATED 1,200 AMPERES OR MORE AND OVER 6 FEET WIDE THAT CONTAIN OVER-CURRENT DEVICES, SWITCHING DEVICES, OR CONTROL DEVICES MUST SWING IN THE DIRECTION OF EGRESS AND HAVE PANIC HARDWARE. [1008.1.10]

EXIT STAIRS:

STAIRWAYS MUST NOT BE LESS THAN 44 INCHES IN CLEAR AND UNOBSTRUCTED WIDTH WHERE SERVING 50 OR MORE OCCUPANTS. [1009.4]

A HEADROOM OF AT LEAST 6'8" MUST BE PROVIDED. [1009.5]

THE TREAD DEPTH MUST BE A MINIMUM OF 11" AND THE RISER HEIGHT MUST BE A MINIMUM OF 4" AND A MAXIMUM OF 7". [1009.7.2]

GUARDS:

MEANS OF EGRESS THAT ARE GREATER THAN 30 INCHES ABOVE THE FLOOR BELOW MUST BE PROVIDED WITH GUARDS. GUARDS ARE REQUIRED TO BE NOT LESS THAN 42 INCHES HIGH. GUARDS MUST HAVE INTERMEDIATE RAILS SUCH THAT A SPHERE 4 INCHES IN DIAMETER CAN NOT PASS THROUGH ANY OPENING UP TO A HEIGHT OF 34 INCHES. [1013.2]

HANDRAILS:

RAMP WITH A RISE GREATER THAN 6 INCHES AND STAIRS ARE REQUIRED TO HAVE HANDRAILS ON BOTH SIDES AND THE HANDRAILS MUST BE PROVIDED WITHIN 30 INCHES OF REACH ON THE STAIR. THE HANDRAILS MUST BE AT LEAST 34 INCHES IN HEIGHT AND NOT GREATER THAN 38 INCHES. [1009.15, 1012]

COMMON PATH OF TRAVEL IN ASSEMBLY OCCUPANCIES - AUDITORIUM:

A COMMON PATH OF TRAVEL OF 30 FEET IS PERMITTED FROM ANY POINT WHERE SERVING ANY NUMBER OF OCCUPANTS. A COMMON PATH OF TRAVEL OF 75 FEET IS PERMITTED FROM ANY POINT WHERE SERVING NOT MORE THAN 50 OCCUPANTS. [1028.8]

WHERE ONE OF THE TWO PATHS OF TRAVEL IS ACROSS THE AISLE THROUGH A ROW OF SEATS TO ANOTHER AISLE, THERE MUST BE NOT MORE THAN 24 SEATS BETWEEN THE TWO AISLES, AND THE MINIMUM CLEAR WIDTH BETWEEN ROWS FOR THE ROW BETWEEN THE TWO AISLES MUST BE 12 INCHES PLUS 0.6 INCH FOR EACH ADDITIONAL SEAT ABOVE SEVEN IN THE ROW BETWEEN AISLES. [1028.6.1]

EGRESS WIDTH FOR ASSEMBLY SEATING:

MINIMUM REQUIRED EGRESS WIDTH FOR STAIRS IS 0.3 INCHES PER OCCUPANT. WHERE EGRESS REQUIRES STAIR DESCENT, AT LEAST 0.075 INCH OF ADDITIONAL WIDTH FOR EACH OCCUPANT MUST BE PROVIDED ON THOSE PORTIONS OF STAIR WIDTH HAVING NO HANDRAIL WITHIN A HORIZONTAL DISTANCE OF 30 INCHES. 0.22 INCHES PER OCCUPANT MUST BE PROVIDED FOR RAMPED MEANS OF EGRESS WHERE SLOPES ARE STEEPER THAN ONE UNIT VERTICAL IN 12 UNITS HORIZONTAL. 0.2 INCHES PER OCCUPANT FOR LEVEL AREAS. IN ASSEMBLY AREAS WHICH CONTAIN SEATS, TABLES, AND DISPLAYS. [1028.6.1]

AISLE ACCESSWAYS SERVING SEATING IN ROWS - AUDITORIUM:

AISLE ACCESSWAYS BETWEEN ROWS OF SEATING WITH 14 OR FEWER SEATS MUST HAVE A MINIMUM CLEAR WIDTH OF 12 INCHES. ROWS OF SEATING WITH AISLES ON EACH SIDE CANNOT EXCEED 100 SEATS PER ROW AND MUST INCREASE THE MINIMUM CLEAR WIDTH BY 0.3 INCHES FOR EVERY SEAT OVER A TOTAL OF 14. THE AISLE ACCESSWAY IS NOT REQUIRED TO EXCEED 22 INCHES IN WIDTH. ROWS OF SEATING WITH AN AISLE AT ONLY ONE END CANNOT HAVE A PATH OF TRAVEL WHICH EXCEEDS 30 FEET IN LENGTH FROM ANY SEAT TO THE AISLE. THE MINIMUM CLEAR WIDTH, FOR ROWS OF SEATING WITH ONLY ONE AISLE AT THE END, MUST BE INCREASED BY 0.6 INCHES FOR EVERY SEAT OVER A TOTAL OF 7. [1028.10.2]

MINIMUM WIDTH OF AISLES - AUDITORIUM:

48 INCHES FOR STAIR AISLES WITH SEATING ON EACH SIDE OR 36 INCHES IF THE AISLE SERVES 50 OR FEWER SEATS. 36 INCHES FOR STAIR AISLES HAVING SEATING ON ONLY ONE SIDE. 28 INCHES BETWEEN A HANDRAIL AND SEATING. 42 INCHES FOR LEVEL OR RAMPED AISLES HAVING SEATING ON EACH SIDE OR 36 INCHES IF THE AISLE SERVES 50 OR FEWER SEATS. 36 INCHES FOR LEVEL OR RAMPED AISLES HAVING SEATING ON ONLY ONE SIDE. 23 INCHES BETWEEN A HANDRAIL OR GUARDRAIL AND SEATING WHEN THE AISLE SERVES FIVE ROWS OR FEWER ON ONE SIDE. [1028.9.1]

AISLE STAIR TREADS - AUDITORIUM:

AISLE STAIR TREADS MUST HAVE NO VARIATION IN THE DEPTH OF ADJACENT TREADS THAT EXCEEDS 3/16 INCHES. TREADS MUST BE AT LEAST 11 INCHES IN DEPTH, AND ALL TREADS MUST EXTEND THE FULL WIDTH OF THE AISLE. [1028.11.1]

THE AISLES ARE A COMBINATION OF TREADS AND LANDINGS. STAIR TREADS ARE PROVIDED BETWEEN LANDINGS WHERE THE RISER IS GREATER THAN 9 INCHES BETWEEN LANDINGS. SECTION 1009.8, STAIRWAY LANDINGS, HAS AN EXCEPTION FOR COMPLYING WITH THE REQUIREMENT FOR LANDINGS WHEN AISLE STAIRS COMPLY WITH SECTION 1028. SECTION 1028 DOES NOT REGULATE LANDINGS. THEREFORE THE LANDINGS DO NOT NEED TO MEET ANY SPECIFIC REQUIREMENTS.

AISLE STAIR RISERS - AUDITORIUM:

AISLE STAIR RISER HEIGHTS CANNOT BE LESS THAN 4 INCHES. HEIGHTS CANNOT EXCEED 8 INCHES, AND MUST BE UNIFORM. CONSTRUCTION-CAUSED NONUNIFORMITIES CANNOT EXCEED 3/16 INCHES BETWEEN ADJACENT RISERS. RISER HEIGHTS NOT EXCEEDING 9 INCHES IS PERMITTED WHERE THEY ARE NECESSITATED BY THE SLOPE OF THE ADJACENT SEATING AREAS TO MAINTAIN SIGHTLINES. [1028.11.2]

AISLE HANDRAILS - AUDITORIUM:

IN PLACES OF ASSEMBLY OR PORTIONS THEREOF WITH RAMPED OR TIERED CENTERLINE, WHERE SEATING EXISTS ON BOTH SIDES OF THE AISLE, THE HANDRAIL MUST BE NONCONTINUOUS WITH GAPS OR BREAKS AT INTERVALS NOT EXCEEDING 5 ROWS. THE GAPS OR BREAKS MUST HAVE A MINIMUM CLEAR WIDTH OF 22 INCHES AND A MAXIMUM CLEAR WIDTH OF 36 INCHES. THE ENDS OF THE HANDRAILS MUST BE ROUNDED AND WHERE A HANDRAIL IS PROVIDED IN THE MIDDLE OF THE AISLE, AN INTERMEDIATE HANDRAIL MUST BE PROVIDED 12 INCHES BELOW THE MAIN HANDRAIL. [1028.13]

AISLE MARKING - AUDITORIUM:

A CONTRASTING MARKING STRIPE MUST BE PROVIDED ON EACH TREAD AT THE NOSING OR LEADING EDGE. THE STRIPES MUST BE AT LEAST 1 INCH WIDE BUT NO GREATER THAN 2 INCHES. [1028.11.3]

SEAT STABILITY - AUDITORIUM:

IN PLACES OF ASSEMBLY OR PORTIONS THEREOF WITH RAMPED OR TIERED FLOORS FOR SEATING, AND WHERE THE SEATS INCLUDE MORE THAN 200 PERMANENT, PORTABLE OR FOLDING CHAIRS IN ANY COMBINATION ON EACH INDIVIDUAL RAMPED OR TIERED AREA, ALL SEATS ON THE RAMPED OR TIERED AREA SHALL BE FASTENED TOGETHER IN GROUPS OF NOT FEWER THAN THREE OR ALL SEATS SHALL BE FASTENED TO THE FLOOR. [1028.12, EXC. 3]

EXIT TRAVEL DISTANCE:

EXIT ACCESS TRAVEL DISTANCE IS PERMITTED TO BE A MAXIMUM OF 250 FEET FOR E AND S-1 OCCUPANCIES AND 300 FEET FOR B OCCUPANCIES. [TABLE 1016.2]

NUMBER OF EXITS:

2 EXITS REQUIRED PER FLOOR FOR AN OCCUPANT LOAD OF 1-500
 3 EXITS REQUIRED PER FLOOR FOR AN OCCUPANT LOAD OF 501-1,000
 4 EXITS REQUIRED FOR AN OCCUPANT LOAD OVER 1,000 [1021.2]
 AN EXIT CAPACITY OF 0.15 IN/OCCUPANT MUST BE PROVIDED FOR HORIZONTAL TRAVEL SUCH AS DOORS, RAMPS, ETC. AND 0.2 IN/OCCUPANCY MUST BE PROVIDED FOR STAIRS. [1005.3.2]

MEANS OF EGRESS:

TWO MEANS OF EGRESS MUST BE PROVIDED FROM ANY SPACE WHERE THE OCCUPANT LOAD EXCEEDS 49 FOR B AND E OCCUPANCIES AND 29 FOR S OCCUPANCIES OR WHERE THE COMMON PATH OF TRAVEL IS EXCEEDED. [TABLE 1015.1]

MEANS OF EGRESS - TECHNICAL PRODUCTION AREAS:

THE MAXIMUM EXIT ACCESS TRAVEL DISTANCE MUST NOT EXCEED 400 FEET. [410.6.3.2]

THE PATH OF EGRESS MUST BE AT LEAST 22 INCHES. [410.6.3.5]

COMMON PATH OF TRAVEL:

THE COMMON PATH OF TRAVEL IS PERMITTED TO BE A MAXIMUM OF 100 FEET FOR B AND S-1 OCCUPANCIES AND 75 FEET FOR E OCCUPANCIES. [TABLE 1014.3]

EXIT ACCESS DOORWAY ARRANGEMENT:

WHERE TWO EXITS ARE REQUIRED FROM A ROOM OR AREA, DOORS MUST BE PLACED A DISTANCE APART EQUAL TO NOT LESS THAN 1/3 OF THE LENGTH OF THE MAXIMUM OVERALL DIAGONAL DIMENSION OF THE ROOM OR AREA SERVED BY THE EXITS. [1015.2.1]

OCCUPANT LOAD POSTING:

A OCCUPANCIES WITH AN OCCUPANT LOAD OF 50 OR MORE MUST HAVE THE OCCUPANT LOAD OF THE ROOM OR SPACE POSTED IN A CONSPICUOUS PLACE, NEAR A MAIN EXIT OR EXIT ACCESS DOORWAY FROM THE ROOM OR SPACE. [1004.3]

EMERGENCY AND EGRESS LIGHTING:

EXIT SIGNS REQUIRED TO INDICATE THE DIRECTION OF EGRESS TRAVEL FOR ROOMS AND AREAS THAT REQUIRE MORE THAN ONE EXIT ACCESS. [1011.1]

EMERGENCY LIGHTING IS REQUIRED AT EXTERIOR LANDINGS IN BUILDINGS THAT REQUIRE MORE THAN ONE EXIT, IN CORRIDORS, AND REQUIRED IN ROOMS AND SPACES THAT REQUIRE TWO OR MORE MEANS OF EGRESS. [1006.3]

AUTOMATIC SPRINKLERS:

SPRINKLERS ARE REQUIRED THROUGHOUT ALL E OCCUPANCIES WITH A FIRE AREA GREATER THAN 12,000 SQUARE FEET AND TO PERMIT THE BUILDING TO BE UNLIMITED IN AREA. [903.2.3, 507.4]

STANDPIPES:

CLASS III WET STANDPIPE REQUIRED ON EACH SIDE OF STAGES WITH A 1 1/2 INCH HOSE CONNECTION. THE 1 1/2 INCH HOSE CONNECTIONS MUST BE EQUIPPED WITH SUFFICIENT LENGTHS OF 1 1/2 INCH HOSE TO PROVIDE FIRE PROTECTION FOR THE STATE AREA. PROPER CAP AND CHAIN MUST BE PROVIDED FOR THE HOSE CONNECTION VALVE ASSEMBLY. [410.8, 905.3.4]

FIRE ALARM SYSTEM:

FIRE ALARM SYSTEM REQUIRED THROUGHOUT - MANUAL PULL STATIONS ARE NOT REQUIRED BASED UPON AUTOMATIC SPRINKLER INITIATION OF THE SYSTEM [907.2.3, EXC. 3]

STAGE VENTILATION:

STAGE VENTILATION MUST BE PROVIDED BY ROOF VENTS IN ACCORDANCE WITH SECTION 410.3.7.1 OR SMOKE CONTROL IN ACCORDANCE WITH SECTION 410.3.7.2. [410.3.7]


SMOKE DETECTORS:

SMOKE DETECTORS ARE REQUIRED FOR HVAC SHUTDOWN FOR SYSTEMS DELIVERING IN EXCESS OF 2,000 CFM. [806 IMC]

SMOKE DETECTORS ARE REQUIRED FOR PHASE I ELEVATOR RECALL. [3002.2]

INTERIOR FINISHES:

CLASS B FINISHES ARE PERMITTED THROUGHOUT. CLASS C FINISHES ARE PERMITTED IN CORRIDORS, ROOMS, AND ENCLOSED SPACES. [TABLE 803.9]




1 FOUNDATION PLAN - UNIT L
3/32" = 1'-0"


FOUNDATION PLAN NOTES

- REF. S001 & S002 FOR STRUCTURAL NOTES, DESIGN DATA & SCHEDULES.
- ALL CONTRACTORS ARE REQUIRED TO COORDINATE THEIR WORK WITH ALL DISCIPLINES TO AVOID CONFLICTS. THE MECHANICAL, ELECTRICAL, AND PLUMBING ASPECTS ARE NOT IN THE SCOPE OF THESE DRAWINGS. THEREFORE, ALL REQUIRED MATERIALS AND WORK MAY NOT BE INDICATED.
- COORDINATE EXACT SIZE & LOCATION OF ALL MECHANICAL OPENINGS IN FOUNDATION WALLS WITH THE MECHANICAL, ELECTRICAL & PLUMBING CONTRACTORS.
- ALL ELEVATIONS ARE REFERENCED FROM THE FIRST FLOOR FINISH FLOOR ELEVATION (7'-0" (U.S.S. 803.10). REF. CIVIL DWGS.
- REF. ARCH. DRAWINGS FOR ALL DIMENSIONS NOT SHOWN. CONTRACTOR SHALL VERIFY ALL DIMENSIONS PRIOR TO CONSTRUCTION AND IMMEDIATELY NOTIFY ARCHITECT/ENGINEER OF ANY DISCREPANCIES.
- REF. S400 & S401 FOR TYPICAL FOUNDATION DETAILS.
- NOTE: PERIMETER WALL AND COLUMN FOOTINGS SHALL BE LOWERED AND/OR SLEEVED TO PASS BELOW PLUMBING LINES (I.E. SANITARY & STORM SEWERS, WATER LINES, ETC.) SHOWN ON THE PLUMBING DRAWINGS. PROVIDE FOOTING STEPS AS REQUIRED PER THE TYPICAL DETAILS ON S400.
- ALL SLAB RECESSES SHALL BE LOCATED PER THE ARCHITECTURAL DRAWINGS. COORDINATE DEPTHS OF ALL SLAB RECESSES WITH THE ARCHITECTURAL DRAWINGS AND/OR THE FLOORING SUPPLIER.
- COORDINATE REINFORCING DOVELS FOR CMU VERTICAL REINFORCING WITH REIN. NOTED ON PLANS & SECTIONS.
- GROUT ALL CORES OF CMU BELOW FINISH FLOOR SLAB.
- COLUMN FOOTINGS, TRENCH FOOTINGS AND WALL FOOTINGS SHALL BEAR ON APPROVED SOIL. UNDERCUT AS REQ'D TO SUITABLE BEARING MATERIAL AS DETERMINED BY THE GEOTECHNICAL TESTING AGENCY. REF. TYPICAL FOOTING UNDERCUT DETAIL ON S400. UNDERCUTTING TO SUITABLE BRG. MATERIAL IS NOT REQUIRED FOR GRADE BEAMS. REFERENCE ELEVATIONS IN PARENTHESES (XXX.X") FOR APPROXIMATE ELEVATION TO SUITABLE BEARING STRATA TO BE USED FOR BIDDING PURPOSES.
- COLUMN FOOTINGS SUPPORTING MORE THAN ONE COLUMN SHALL BE CENTERED AT THE MIDPOINT BETWEEN THE COLUMNS, UNLESS NOTED OTHERWISE ON PLAN.
- NOT USED.
- PROVIDE CONTINUOUS 4" x 1/2" W. VARIES CONCRETE CURB ON ACOUSTIC ISOLATION SLABS IN MECHANICAL ROOMS. CURBS TO SURROUND ALL PENETRATIONS THRU SLAB INCLUDING COLUMNS, PIPES, SNAPP PITS, ETC.
- ALL EX. CONSTRUCTION SHOWN IN PLAN AND/OR SECTION WAS DERIVED FROM EXISTING DRAWINGS AND MUST BE FIELD VERIFIED. IF ANY DISCREPANCIES ARE DISCOVERED BETWEEN INFO. SHOWN ON THE DRAWINGS AND ACTUAL CONDITIONS IMMEDIATELY CONTACT ARCHITECT/ENGINEER FOR DIRECTION BEFORE PROCEEDING WITH THE WORK.
- PROVIDE THICKENED SLAB UNDER ALL INTERIOR CMU WALLS WITHOUT FOOTINGS. SEE S401 FOR THICKENED SLAB DETAIL. LAYOUT THICKENED SLABS FROM DIMENSIONS ON THE ARCHITECT FLOOR PLANS.
- PROVIDE CONTROL/CONTRACTION JOINTS IN SLABS ON GRADE (REF. TYPICAL DETAILS ON SHEET S401). ALL JOINTS IN SLABS TO RECEIVE THIN OR THICK-SET TERRAZZO, CERAMIC OR PORCELAIN TILE, VINYL COMPOSITION TILE (VCT) OR VINYL SHEET GOODS, EPOXY OR SIMILAR THIN-FILM FINISH FLOORING SHALL BE CAREFULLY COORDINATED WITH THE FLOORING CONTRACTOR. THE CONTRACTOR SHALL SUBMIT SLAB JOINT LAYOUT TO ARCHITECT/ENGINEER FOR REVIEW PRIOR TO PLACING SLABS.
- WHERE PIERS OCCUR WITHIN A LARGER ARCH. PLASTER OR COLUMN ENCLOSURE (FOR EG. P24) WITHIN 40" SQUARE CANOPY PLASTERS PROVIDE PIER REINFC. CASE CENTERED ON THE GRID INTERSECTION. FORM OVERALL PIER TO PROFILE OF THE ARCHITECTURAL PLASTER OR COLUMN ENCLOSURE. LAYOUT PLASTERS FROM DIMENSIONS ON THE ARCHITECTURAL PLANS & DETAILS.
- FOR ARCHITECTURAL PLASTERS NOT SUPPORTING STEEL COLUMNS, CONSTRUCT AS FULLY-GROUTED MASONRY PIERS OR CAST-IN-PLACE CONCRETE PIERS REINFC. W/ #5 VERTICAL REINFORCING AT 12" O.C. ALL FACES, AT CONTRACTORS OPTION.
- NOT USED.
- PROVIDE CASTCONCREX ART-12.75 + UPC-8.625 / ART-324 + UPC-219 AT TOP AND BOTTOM OF COLUMN.
- PLAN LEGEND:

F.F.	DENOTES FINISH FLOOR
T/X	DENOTES TOP OF FTG., GRADE BEAM, SLAB, PIER, ETC.
B/X	DENOTES BOTTOM OF FTG., GRADE BEAM, ETC.
C.J.	DENOTES SLAB ON GRADE CONTROL/CONTRACTION JOINT
WF30-30'-0"	DENOTES WALL FOOTING MARK & TOP OF FOOTING ELEVATION (SEE WALL FOOTING SCHEDULE)
PC24/24	DENOTES PRECAST CONCRETE COLUMN SIZE, IN INCHES
N/A	NOT USED
CW16	DENOTES C.I.P. CONCRETE WALL MARK (SEE SCHEDULE)
PCW13	DENOTES PRECAST CONCRETE WALL MARK AND NOMINAL THICKNESS
S4	DENOTES 4" CONC. SLAB-ON-GRADE w/ FIBERFORCE 300 @ 1.5 LB/CY. (OR APPROVED EQUAL) & ES SYSTEM BY SPECIFICATION PRODUCTS, INC. CONSISTING OF: ES INTERNAL CURE ADMIXTURE @ 4 OZ/CYIT & ES CATALYST SPRAYED ON BETWEEN 800-1,000 SF/GAL OVER 15-MIL CLASS A VAPOR BARRIER OVER 6" COMPACTED GRANULAR FILL (NDOT No. 53)
S5	DENOTES 5" CONC. SLAB-ON-GRADE w/ FIBERFORCE 300 @ 1.5 LB/CY. (OR APPROVED EQUAL) & ES SYSTEM BY SPECIFICATION PRODUCTS, INC. CONSISTING OF: ES INTERNAL CURE ADMIXTURE @ 4 OZ/CYIT & ES CATALYST SPRAYED ON BETWEEN 800-1,000 SF/GAL OVER 15-MIL CLASS A VAPOR BARRIER OVER 6" COMPACTED GRANULAR FILL (NDOT No. 53)
U	DENOTES UTILITY PIPE/CONDUIT TO RUN THROUGH FOUNDATION WALL. NOT ALL MAY BE SHOWN ON THIS DRAWING.
W	DENOTES WALL FOOTING WITH STEPS, REF. TYP. DETAIL ON S400
F	FOOTING STEPS SHOWN ON PLAN REQUIRE COORDINATION BETWEEN TRADES AND MAY REQUIRE ADJUSTMENT
C	DENOTES COLUMN SIZE (REF. FRAMING PLANS FOR SLUB COL'S NOT ON FDS)
F	DENOTES COLUMN FOOTING MARK & TOP OF FTG. ELEVATION (SEE FTG. SCHED.)
P	DENOTES PIER MARK & TOP OF PIER ELEVATION (SEE PIER SCHED.)
F	COLUMN FOOTING CONCRETE PIER
S	STEEL COLUMN




2 ENLARGED FOUNDATION PLAN - UNIT L
1/8" = 1'-0"




REVISIONS:		
#	Date	Desc.
7	08.09.22	BID PKG. #2 ADD. #7

BID PACKAGE #2 - 100%
CONSTRUCTION DOCUMENTS
PROJECT: #21107
DATE: 05.20.2022
DRAWN BY: DJL


- NOTES:
1. IF BARS CANNOT BE PLACED AS DETAILED, REPLACE THE 2'-0" EXTENSION WITH 6" AND A STANDARD HOOK.
 2. COORDINATE FINAL LOCATION OF MECHANICAL PENETRATIONS WITH MECHANICAL CONTRACTOR BEFORE INSTALLATION OF THE REINFORCING.
 3. THIS DETAIL APPLIES TO ALL OPENINGS IN SLABS ON GRADE UNLESS OTHERWISE NOTED ON THE PLANS.




15 SLAB ON GRADE MECH. OPENING
3/4" = 1'-0"




14 NEW-TO-EXISTING SLAB DETAIL
3/4" = 1'-0"




13 TYPICAL CONCRETE STAIR DETAIL
3/4" = 1'-0"




12 TYPICAL CONCRETE PIER REINFORCING
3/4" = 1'-0"




11 THICKENED SLAB DETAILS
3/4" = 1'-0"




10 THICKENED SLAB AT STAIR POSTS
3/4" = 1'-0"




9 SLAB ON GRADE CONSTRUCTION
1" = 1'-0"




8 SLAB CONTROL/CONTRACTION JOINT
1" = 1'-0"




7 SLAB CONSTRUCTION JOINT
1" = 1'-0"




6 RECESSED SLAB DETAIL
3/4" = 1'-0"




5 MECHANICAL EQUIPMENT PAD
1" = 1'-0"



4 ELEVATOR SUMP PIT DETAIL
3/4" = 1'-0"






3 ELEVATOR PIT DETAIL - C.I.P.
3/4" = 1'-0"




- NOTES:
1. DRILL & GROUT THREADED ANCHOR RODS SOLIDLY INTO EX. CONCRETE USING HILTI HIT-HY 200 OR APPROVED 2-PART EPOXY ANCHORING SYSTEM.
 2. WHERE COLUMNS ARE TO BE INSTALLED BETWEEN TWO FIXED ELEVATIONS, SUCH AS BETWEEN THE BOTTOM OF AN EXISTING BEAM AND THE TOP OF AN EXISTING FOUNDATION, THE ANCHORS MAY BE INSTALLED AFTER THE COLUMN IS TEMPORARILY SET IN PLACE. IT IS THE RESPONSIBILITY OF THE STEEL ERECTOR TO ADEQUATELY BRACE THE COLUMN UNTIL THE ANCHOR BOLTS CAN BE INSTALLED AND TIGHTENED.
 3. THIS DETAIL SHALL BE USED ONLY FOR CONNECTION OF COLUMNS TO EXISTING FOUNDATIONS AND NOT FOR NEW COLUMNS SUPPORTED ON NEW FOUNDATIONS.


2 3/4" DIA. ANCHOR BOLTS TO EX. FOUNDATIONS
3/4" = 1'-0"



- NOTES:
1. LOCATION OF ANCHOR BOLTS MUST NOT VARY MORE THAN 1/8" CENTER-TO-CENTER OF ANY TWO BOLTS WITHIN AN ANCHOR BOLT GROUP.
 2. HOLD MAX. DEVIATION OF 1/4" CENTER-TO-CENTER OF ADJACENT ANCHOR BOLT GROUPS.
 3. HOLD ELEVATION OF THE TOP OF THE ANCHOR BOLTS TO +/- 1/2 INCH.
 4. HOLD MAXIMUM DEVIATION OF 1/4" FROM THE CENTER OF ANY ANCHOR BOLT GROUP TO THE ESTABLISHED COLUMN LINE THROUGH THAT GROUP.
 5. REFER TO THE ABC CODE OF STANDARD PRACTICE FOR ADDITIONAL INFORMATION.


1 ANCHOR ROD DETAILS
1 1/2" = 1'-0"






10 TYPICAL CONCRETE FILLED METAL PAN TREAD/RISER

SCALE: 3" = 1'-0" REF. 1 / A401




9 STAIR SECTION - PLINTH DETAIL

SCALE: 1/2" = 1'-0" REF. 5 / A401




8 ELEVATOR PIT SECTION AT SUMP

SCALE: 1/2" = 1'-0"



7 ENLARGED FLOOR PLAN

SCALE: 1/4" = 1'-0" REF. 1 / A112L




6 ENLARGED FLOOR PLAN

SCALE: 1/4" = 1'-0" REF. 1 / A101L


GENERAL NOTES - ARCHITECTURAL DETAILS

- REFERENCE SHEETS A002 AND A003 FOR WALL TYPES INDICATED BY WALL TYPE TAGS.
- REFERENCE A110 SERIES FOR DIMENSION PLANS.
- REFERENCE SHEET A003 FOR ROOF TYPES.
- REFERENCE SHEETS A011 AND A012 FOR FRAMING AND GLAZING TYPES.
- REFERENCE SHEET A400 SERIES FOR VERTICAL CIRCULATION DETAILS.
- REFERENCE SHEET A521 FOR MFR. STANDARD DETAILS FOR EXPANSION JOINT ASSEMBLIES.
- PROVIDE G-60 16 GA CONTINUOUS METAL PLATE BEHIND TRANSITION STRIPS. TERMINATION BARS AND BASE FLASHING WHEN ANCHORING THROUGH GYPSUM SHEATHING.
- AIR AND VAPOR BARRIERS INSTALLED ON MASONRY WALLS WHERE INDICATED ON DRAWINGS SHALL BE FLUID APPLIED.
- PROVIDE DRIP EDGE IN PRECAST TO ANY EXTERIOR DOOR OPENINGS.
- INSTALL MICROBIOBACIAL GYPSUM BOARD AT ALL WALLS BEING USED AS AN AIR PLENUM. REFERENCE M-SERIES FOR ADDITIONAL DETAILS AND LOCATIONS OF UNDERGROUND DUCT SUPPLY.




5 ELEVATOR PIT SECTION

SCALE: 1/2" = 1'-0"




4 ELEVATOR ENTRY AND MOUNTING HEIGHTS

SCALE: 3/8" = 1'-0"




3 RAMP SECTION

SCALE: 1/4" = 1'-0" REF. 1 / A111L




2 ELEVATOR SECTION

SCALE: 1/4" = 1'-0" REF. 6 / A402




1 STAIR SECTION


SCALE: 1/4" = 1'-0" REF. 2 / A202




12 SECTION DETAIL
SCALE: 3" = 1'-0" REF. 1 / A312




7 SECTION DETAIL
SCALE: 1 1/2" = 1'-0" REF. 6 / A311




4 SECTION DETAIL
SCALE: 1 1/2" = 1'-0" REF. 5 / A311




10 SECTION DETAIL
SCALE: 1 1/2" = 1'-0" REF. 3 / A313




11 SECTION DETAIL
SCALE: 1 1/2" = 1'-0" REF. 5 / A313




9 SECTION DETAIL
SCALE: 1 1/2" = 1'-0" REF. 4 / A313




8 SECTION DETAIL
SCALE: 1 1/2" = 1'-0" REF. 1 / A313




6 SECTION DETAIL
SCALE: 1 1/2" = 1'-0" REF. 6 / A312



5 SECTION DETAIL
SCALE: 1 1/2" = 1'-0" REF. 8 / A311



2 SECTION DETAIL
SCALE: 1 1/2" = 1'-0" REF. 7 / A311



1 SECTION DETAIL
SCALE: 1 1/2" = 1'-0" REF. 1 / A311

- GENERAL NOTES - ARCHITECTURAL DETAILS**
1. REFERENCE SHEETS A002 AND A003 FOR WALL TYPES INDICATED BY WALL TYPE TAGS.
 2. REFERENCE A110 SERIES FOR DIMENSION PLANS.
 3. REFERENCE SHEET A003 FOR ROOF TYPES.
 4. REFERENCE SHEETS A011 AND A012 FOR FRAMING AND GLAZING TYPES.
 5. REFERENCE A400 SERIES FOR VERTICAL CIRCULATION DETAILS.
 6. REFERENCE SHEET A521 FOR MFR. STANDARD DETAILS FOR EXPANSION JOINT ASSEMBLIES.
 7. PROVIDE G-60 16 GA CONTINUOUS METAL PLATE BEHIND TRANSITION STRIPS. TERMINATION BARS AND BASE FLASHING WHEN ANCHORING THROUGH GYPSUM SHEATHING.
 8. AIR AND VAPOR BARRIERS INSTALLED ON MASONRY WALLS WHERE INDICATED ON DRAWINGS SHALL BE FLUID APPLIED.
 9. PROVIDE DRIP EDGE IN PRECAST TO ANY EXTERIOR DOOR OPENINGS.
 10. INSTALL MICROBIOBIAL GYPSUM BOARD AT ALL WALLS BEING USED AS AN AIR PLENUM. REFERENCE M-SERIES FOR ADDITIONAL DETAILS AND LOCATIONS OF UNDERGROUND DUCT SUPPLY.



REVISIONS:		
#	Date	Desc.
7	06/09/22	BID PKG. #2 ADD. #7


BID PACKAGE #2 - 100%
CONSTRUCTION DOCUMENTS
PROJECT: #21107
DATE: 05/20/2022
DRAWN BY: KH/BM

**SECTION
DETAILS**

PLT DATE/TIME: 6/20/2022 3:33:45 PM


7 WALL SECTION

SCALE: 1 1/2" = 1'-0" REF. 1 / A111L




4 RECESSED TOE KICK DETAIL

SCALE: 3" = 1'-0" REF. 3 / A1515




6 SOLID SURFACE WALL CAP DETAIL

SCALE: 3" = 1'-0" REF. 2 / A515




3 WALL SECTION

SCALE: 1 1/2" = 1'-0" REF. 1 / A111L




10 SECTION DETAIL

SCALE: 1 1/2" = 1'-0" REF. 2 / A202




11 SECTION DETAIL

SCALE: 1" = 1'-0" REF. 3 / A313




2 SECTION DETAIL

SCALE: 1 1/2" = 1'-0" REF. 7 / A314




9 SECTION DETAIL

SCALE: 1 1/2" = 1'-0" REF. 6 / A314




1 SECTION DETAIL

SCALE: 1 1/2" = 1'-0" REF. 7 / A314



8 SECTION DETAIL

SCALE: 1 1/2" = 1'-0" REF. 5 / A401



GENERAL NOTES - ARCHITECTURAL DETAILS

- REFERENCE SHEETS A002 AND A003 FOR WALL TYPES INDICATED BY WALL TYPE TAGS.
- REFERENCE A110 SERIES FOR DIMENSION PLANS.
- REFERENCE SHEET A003 FOR ROOF TYPES.
- REFERENCE SHEETS A011 AND A012 FOR FRAMING AND GLAZING TYPES.
- REFERENCE A400 SERIES FOR VERTICAL CIRCULATION DETAILS.
- REFERENCE SHEET A521 FOR MFR. STANDARD DETAILS FOR EXPANSION JOINT ASSEMBLIES.
- PROVIDE G-60 16 GA CONTINUOUS METAL PLATE BEHIND TRANSITION STRIPS. TERMINATION BARS AND BASE FLASHING WHEN ANCHORING THROUGH GYPSUM SHEATHING.
- AIR AND VAPOR BARRIERS INSTALLED ON MASONRY WALLS WHERE INDICATED ON DRAWINGS SHALL BE FLUID APPLIED.
- PROVIDE DRIP EDGE IN PRECAST TO ANY EXTERIOR DOOR OPENINGS.
- INSTALL MICROBICROBIAL GYPSUM BOARD AT ALL WALLS BEING USED AS AN AIR PLENUM. REFERENCE M-SERIES FOR ADDITIONAL DETAILS AND LOCATIONS OF UNDERGROUND DUCT SUPPLY.

GREENFIELD CENTRAL HIGH SCHOOL
AUDITORIUM RENOVATION & ADDITION
810 N BROADWAY ST.
GREENFIELD, IN 46140



#	Date	Revised By	Drawn By
7	06/09/22	BD PHG, RD ADD, #7	

BID PACKAGE #2 - 100%
CONSTRUCTION DOCUMENTS
PROJECT: #21107
DATE: 05/20/2022
DRAWN BY: KHBM

SECTION
DETAILS

A515

LANCER+BEEBE, LLC
ARCHITECTURE | PLANNING | INTERIORS
220 N. COLLEGE AVE
INDIANAPOLIS, IN 46202

FINISH LEGEND

NOTES

ETR EXISTING TO REMAIN

FLOOR COVERING

CARPET TILE
CPT-1: MFG: INTERFACE
TYPE: 50CM X 50CM CARPET TILE
PATTERN: ICE BREAKER
COLOR: 105771 GRANITE
INSTALL: NON-DIRECTIONAL
LOCATION: AUDITORIUM/OFFICE

WOM-1: MFG: INTERFACE
TYPE: 50CM X 50CM WALK-OFF TILE
PATTERN: SR690 STEP REPEAT
COLOR: 104940 IRON
INSTALL: QUARTER TURN
LOCATION: VESTIBULE

RESILIENT FLOOR
LVT-1: MFG: INTERFACE
TYPE: 36"X36" SOLID VINYL TILE
PATTERN: 0347V ADMIX
COLOR: 00330 OYSTER
INSTALL: MONOLITHIC

LVT-2: MFG: INTERFACE
TYPE: 36"X36" SOLID VINYL TILE
PATTERN: 0347V ADMIX
COLOR: 00370 SHARK'S TOOTH
INSTALL: MONOLITHIC

LVT-3: MFG: INTERFACE
TYPE: 12"X12" SOLID VINYL TILE
PATTERN: H29V ADMIX ENCORE
COLOR: 00165 ORB
INSTALL: MONOLITHIC

LVT-4: MFG: INTERFACE
TYPE: 12"X12" SOLID VINYL TILE
PATTERN: H29V ADMIX ENCORE
COLOR: 00275 GLT
INSTALL: MONOLITHIC

LVT-5: MFG: INTERFACE
TYPE: 12"X12" SOLID VINYL TILE
PATTERN: H29V ADMIX ENCORE
COLOR: 0085 GALENA
INSTALL: MONOLITHIC

RUB-1: MFG: NORA
TYPE: RUBBER SHEET FLOORING W/
INTEGRAL STAIR TREAD
STRIP, TO BE CONFIRMED BY
ARCHITECT
PATTERN: NORAMENT HAMMERED
COLOR: 08M DUST GREY
INSTALL: MONOLITHIC
LOCATION: L111 STAIRS

EPX-1: MFG: SHERWIN WILLIAMS GENERAL
POLYMERS
TYPE: DECORATIVE MOSAIC EPOXY
COLOR: 18" FLAKES, MIX TBD
INSTALL: MONOLITHIC, 4" INTEGRAL
COVE BASE, REF. SPECS
LOCATION: GREENROOM AND RESTROOMS

RES-1: MFG: STAGELAM
TYPE: STAGELAM REF. SPECS
COLOR: BLACK MATTE
INSTALL: MONOLITHIC
LOCATION: STAGE, ORCHESTRA SHELL

TER-1: TYPE: TBD TERRAZZO
COLOR: WHITE (MIX TBD)
INSTALL: REF. PLAN DIMENSIONS;
COORDINATE FINAL DIMENSIONS W/
OWNER & BRAND STANDARDS
REMARKS: ALTERNATE FOR LVT-1 AND LVT-5

TER-2: TYPE: TBD TERRAZZO
COLOR: GRAY (MIX TBD)
INSTALL: REF. PLAN DIMENSIONS;
COORDINATE FINAL DIMENSIONS W/
OWNER & BRAND STANDARDS
REMARKS: ALTERNATE FOR LVT-2

TER-3: TYPE: TBD TERRAZZO
COLOR: BLUE (MIX TBD)
INSTALL: REF. PLAN DIMENSIONS;
COORDINATE FINAL DIMENSIONS W/
OWNER & BRAND STANDARDS
REMARKS: ALTERNATE FOR LVT-3

TER-4: TYPE: TBD TERRAZZO
COLOR: YELLOW (MIX TBD)
INSTALL: REF. PLAN DIMENSIONS;
COORDINATE FINAL DIMENSIONS W/
OWNER & BRAND STANDARDS
REMARKS: ALTERNATE FOR LVT-4

TILE FLOOR
FT-1: MFG: DALTILE
TYPE: 12"X24" PORCELAIN FLOOR
TILE
PATTERN: PORTFOLIO
COLOR: P209 CHARCOAL
INSTALL: VERTICAL STACKED, REF.
ELEVATIONS
LOCATION: RESTROOMS
REMARKS: WHEN USED TOGETHER WITH WT-1
ALIGN FLOOR WALL GROUT JOINTS

FT-2: MFG: DALTILE
TYPE: 2X2" MOSAIC TILE
PATTERN: KEYSTONE
COLOR: D182 SUEDE GRAY
INSTALL: MONOLITHIC
LOCATION: NATATORIUM

CONCRETE
CON-1 TYPE: SEALED CONCRETE,
REF. SPECS
CON-2 TYPE: SEALED CONCRETE,
REF. SPECS
CON-3 TYPE: PAINTED CONCRETE,
REF. SPECS

WALL BASE

RUBBER BASE
RB-1: MFG: JOHNSONITE
TYPE: 4" VINYL WALL BASE
COLOR: T&B BEDROCK
LOCATION: STANDARD UNLESS NOTED
OTHERWISE

RB-2: MFG: JOHNSONITE
TYPE: 4" VINYL WALL BASE
COLOR: T&B BLACK MAGIC
LOCATION: L202 AT WALL WITH WC-1
LOCATIONS

RB-3: MFG: JOHNSONITE
TYPE: 4" VINYL WALL BASE
COLOR: 45 SANDALWOOD WB
LOCATION: L202 AT WALL WITH WC-1

TILE BASE
TB-1: MFG: DALTILE
TYPE: MBSA BUILD UP BASE KEYSTONES
COLOR: SUEDE GRAY D182
INSTALL: INTEGRAL BASE, REF. SPECS
LOCATION: TO BE USED WITH FT-2 (POOL)

EPOXY BASE
EB-1: MFG: SHERWIN WILLIAMS
GENERAL POLYMERS
TYPE: 4" DECORATIVE MOSAIC
EPOXY WALL BASE
COLOR: 18" FLAKES, TB-910 SHADOW
INSTALL: INTEGRAL BASE, REF. SPECS
LOCATION: GREENROOM, GREENROOM
RESTROOMS

TERB-1: MFG: TBD
TYPE: 4" INTREGAL WALL BASE
COLOR: MATCH ADJACENT TERRAZZO
INSTALL: INTEGRAL BASE, REF. SPECS
LOCATION: LOBBY/CORRIDOR
REMARKS: ALTERNATE AT TERRAZZO FLOOR

PAINT/WALL FINISH

PAINT
PT-1: MFG: SHERWIN WILLIAMS
TYPE: REF. SPECS, EGGSHELL FINISH
COLOR: SW7070 SITE WHITE
LOCATION: STANDARD/COLUMNS

PT-1A: MFG: SHERWIN WILLIAMS
TYPE: REF. SPECS, FLAT FINISH
COLOR: SW7070 SITE WHITE
LOCATION: BALCONY WATERFALL

PT-1B: MFG: SHERWIN WILLIAMS
TYPE: REF. SPECS, CASHMERE PEARL
FINISH
COLOR: SW7070 SITE WHITE
LOCATION: BALCONY EDGE

PT-1C: MFG: SHERWIN WILLIAMS
TYPE: REF. SPECS, HIGH GLOSS FINISH
COLOR: SW7070 SITE WHITE
LOCATION: BALCONY EDGE

PT-2: MFG: SHERWIN WILLIAMS
TYPE: REF. SPECS, EGGSHELL FINISH
COLOR: SW7070 NETWORK GRAY
LOCATION: ACCENT

PT-3: MFG: SHERWIN WILLIAMS
TYPE: REF. SPECS, EGGSHELL FINISH
COLOR: SW7070 SOFTWARE
LOCATION: ACCENT

PT-4: MFG: SHERWIN WILLIAMS
TYPE: REF. SPECS, EGGSHELL FINISH
COLOR: SW7070 OYERSPACE
LOCATION: HM DOOR FRAMES/ACCENT/ STAIR
STRINGER

PT-5: MFG: SHERWIN WILLIAMS
TYPE: REF. SPECS, EGGSHELL FINISH
COLOR: SW6989 BLACK OF NIGHT
LOCATION: AUDITORIUM, EXPOSED
STRUCTURE

WALL TILE
WT-1: MFG: DALTILE
TYPE: 12"X24" PORCELAIN TILE
PATTERN: PORTFOLIO
COLOR: P206 IRON GRAY
INSTALL: VERTICAL STACKED, REF.
ELEVATIONS
REMARKS: RUN DIRECTLY TO FINISHED
FLOOR. WHEN USED TOGETHER
WITH FT-1 ALIGN FLOOR AND
WALL GROUT JOINTS

WT-2: MFG: DALTILE
TYPE: 12"X36" GLAZED CERAMIC TILE
PATTERN: AESTHETIC - GEOMETRIC AS23
INSTALL: HORIZONTAL STACKED, REF.
ELEVATIONS
REMARKS: WHEN USING AT WALL, RUN
DIRECTLY TO FINISHED FLOOR

WT-3: MFG: DALTILE
TYPE: 8"X24" GLAZED CERAMIC
WALL TILE
PATTERN: COLOR WHEEL - LINEAR
COLOR: 0180 CHALKBOARD
INSTALL: VERTICAL STACKED, REF.
DRAWING FOUNTAIN ELEVATIONS
REMARKS: WHEN USING AT WALL, RUN
DIRECTLY TO FINISHED FLOOR

WT-4: MFG: DALTILE
TYPE: 8"X24" GLAZED CERAMIC
WALL TILE
PATTERN: COLOR WHEEL - LINEAR
COLOR: X714 MATTE DESSERT GRAY
INSTALL: VERTICAL STACKED, REF.
DRAWING FOUNTAIN ELEVATIONS
REMARKS: WHEN USING AT WALL, RUN
DIRECTLY TO FINISHED FLOOR

WALLCOVERING
WC-1: MFG: SURFACE MATERIALS
TYPE: WALLCOVERING
PATTERN: WOOD WALL 2
COLOR: FAULOWNIA WRW 1051
INSTALL: VERTICAL GRAIN
LOCATION: AUDITORIUM LOBBY
WALL/AUDITORIUM

WC-4: MFG: TBD
TYPE: COLUGAR CUSTOM DIGITAL
WALLCOVERING GRAPHIC TO BE
DETERMINED BY ARCHITECT.
REF. PLAN FOR LOCATION AND
SIZES

WC-5: MFG: TBD
TYPE: GCHS CUSTOM DIGITAL
WALLCOVERING GRAPHIC TO BE
DETERMINED BY ARCHITECT.
REF. PLAN FOR LOCATION AND
SIZES

WC-6: MFG: TBD
TYPE: TIMELINE CUSTOM DIGITAL
WALLCOVERING GRAPHIC TO BE
DETERMINED BY ARCHITECT.
REF. PLAN FOR LOCATION AND
SIZES

PLASTIC LAMINATE/SOLID SURFACE

PLASTIC LAMINATE
PL-1: MFG: FORMICA
TYPE: PLASTIC LAMINATE
COLOR: 5883-58 PECAN WOODLINE (MATTE
FINISH)
INSTALL: MONOLITHIC, VERTICAL GRAIN
LOCATION: GREENROOM/CONCESSION

PL-2: MFG: FORMICA
TYPE: PLASTIC LAMINATE
COLOR: 928-58 MOUSE (MATTE FINISH)
INSTALL: MONOLITHIC
LOCATION: SCENE SHOP

SOLID SURFACE
SS-1: MFG: CORIAN
TYPE: 1" QUARTZ
COLOR: STORM LEATHERED GRAY
INSTALL: MONOLITHIC
LOCATION: RESTROOMS

SS-2: MFG: CORIAN
TYPE: 12" SOLID SURFACE WALL CAP
COLOR: DEEP TITANIUM
INSTALL: MONOLITHIC
LOCATION: AUDITORIUM

SS-3: MFG: CORIAN
TYPE: 12" SOLID SURFACE WALL CAP
COLOR: PEARL GRAY
INSTALL: MONOLITHIC
LOCATION: AUDITORIUM, GRAND STAIR

SS-4: MFG: CORIAN
TYPE: 12" SOLID SURFACE
COLOR: LAVAROCK
INSTALL: MONOLITHIC
LOCATION: GREENROOM

SS-5: MFG: CORIAN
TYPE: 12" SOLID SURFACE
COLOR: CARBON CONCRETE
INSTALL: MONOLITHIC
LOCATION: CONCESSION/SCENE SHOP

MISCELLANEOUS

TEXTILE
TEX-1: MFG: FILZFELT
TYPE: 1/8" 100% WOOL DESIGN FELT
COLOR: 170 ASCHÉ
LOCATION: L118 CORRIDOR

TEX-2: MFG: FILZFELT
TYPE: 1/8" 100% WOOL DESIGN FELT
COLOR: 423 HELLGRAU
LOCATION: L118 CORRIDOR

TEX-3: MFG: KM FABRICS
TYPE: 100% IFR POLYESTER
PATTERN: CHARISMA
COLOR: 1118 NAVY
LOCATION: AUDITORIUM CURTIAN

CORNER GUARDS
CG-1: MFG: ACROVYN
TYPE: VA SERIES - FULL HEIGHT
CORNER GUARD
COLOR: TO MATCH ADJACENT PAINT
LOCATION: TBD - TO BE SELECTED BY
ARCHITECT

WALL PROTECTION
WP-1: MFG: P3 TECH
TYPE: ADVANCED WALL PROTECTION
PATTERN: SHARA STONE
COLOR: MORROCAN SLATE
INSTALL: TBD - TO BE SELECTED BY
ARCHITECT

AUDITORIUM SEATING
TEX-4: MFG: CULP CONTRACT
TYPE: AUDITORIUM SEATING FABRIC
PATTERN: ARCHETYPÉ
COLOR: ADMIRAL
BACKING: TBD, ARCHITECT TO APPROVE
LOCATION: AUDITORIUM SEATS

PL-3: MFG: NEVAMAR
TYPE: PLASTIC LAMINATE
COLOR: S6054T WROT IRON
INSTALL: MONOLITHIC
LOCATION: AISLE PANEL

RAILING
RF-1: MFG: HOLLANDAR
TYPE: GLASS
COLOR: TBD
LOCATION: GRAND STAIR

ACOUSTICAL:
AP-1: MFG: KINETICS
TYPE: NOISE CONTROL
PATTERN: 4'X96" ACOUSTICAL DIFFUSER
COLOR: HIGH TONES
INSTALL: TO BE PAINTED PT.4
LOCATION: REF. ELEVATION FOR DIRECTION
AUDITORIUM BACK WALL

AP-2: MFG: AUTEX
TYPE: 1" QUIETSPACE PANEL FACE WITH
VERIFACE VELOUR FINISH
COLOR: CITRUS
LOCATION: K107 POOL

AP-3 : MFG: AUTEX
TYPE: 1" QUIETSPACE PANEL FACE WITH
VERIFACE VELOUR FINISH
COLOR: MYST
LOCATION: K107 POOL

AP-4 : MFG: AUTEX
TYPE: 1" QUIETSPACE PANEL FACE WITH
VERIFACE VELOUR FINISH
COLOR: KOLA
LOCATION: K107 POOL


GLASS WALL
GW-1: MFG: CLARUS
TYPE: WALL/WALL WALL-MOUNTED
GLASS BOARD
COLOR: CBC-824
LOCATION: MAIN LOBBY



REVISEIONS:	#	Date	Desc.
	7	06/09/22	BID PKG. #2 ADD. #7

BID PACKAGE #2 - 100% CONSTRUCTION DOCUMENTS
PROJECT: #211107
DATE: 05.20.2022
DRAWN BY: MC

INTERIOR
FINISH LEGEND



GENERAL NOTES - FINISH PLAN

1. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSIDERED THAT THE INSTALLER AND/OR FINISHER HAS INSPECTED AND ACCEPTED THE SUBSTRATE RECEIVING THE NEW WORK. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, UNKNOWN CONDITIONS OR UNSATISFACTORY SUBSTRATE ONCE THE FINISH WORK HAS PROCEEDED.
2. WHERE WALLS ARE INDICATED TO RECEIVE PAINT FINISH, PAINT ALL PRIMED GRILLES, FIRE EXTINGUISHER CABINETS, AND OTHER ITEMS EMBEDDED IN WALL CONSTRUCTION TO MATCH SURFACE ON WHICH THEY OCCUR UNLESS NOTED OTHERWISE.
3. ALIGN FLOOR TRANSITION AT CENTER OF DOORWAY, TYP.
4. WINDOW STOODLS TO BE SS-3.
5. REFERENCE ELEVATIONS AND FINISH LEGEND FOR CUSTOM GRAPHIC WALL COVERING.
6. PROVIDE DRYWALL REVEAL JOINT WHERE DRYWALL MEETS DISSIMILAR MATERIALS.
7. PROVIDE SCHLUTER EDGE WHERE TILE MEETS DISSIMILAR MATERIALS.
8. PAINT EXPOSED STEEL COLUMNS PT-1.
9. PAINT HM DOOR FRAMES AND RELATED EXPOSED LINTELS PT-4 UNLESS NOTED OTHERWISE.
10. PAINT EXTERIOR HM DOOR PANELS PT-4 UNLESS NOTED OTHERWISE.
11. PAINT INTERIOR HM DOOR PANELS PT-2 UNLESS NOTED OTHERWISE.
12. GRIND DOWN THE EDGE OF TERRAZZO WHERE IT MEETS DISSIMILAR FLOORING.
13. ALL PAINT INSIDE RESTROOMS AND CONCESSION TO BE EPOXY BASED PAINT.
14. PROVIDE TERRAZZO WALL BASE ADJACENT TO TERRAZZO FLOOR.
15. WITHIN AUDITORIUM PAINT ALL WALL FACES ABOVE 33'-6" AFF PT-5.

FINISH PLAN NOTES

- 1 CORRIDOR FEATURE WALL - REF. ELEVATIONS FOR MORE DETAILS
- 2 WALL COVERING (WC-1) AT THIS LOCATION - REF. FINISH LEGEND
- 3 ACoustical DIFFUSER (AP-1) AT THIS LOCATION - REF. FINISH LEGEND
- 4 WALL TILE (WT-SWT-4) AT THIS LOCATION - REF. FINISH LEGEND
- 5 ACCENT PAINT (PT-2) AT THIS LOCATION - REFER TO FINISH LEGEND
- 6 ACCENT PAINT (PT-4) AT THIS LOCATION - REFER TO FINISH LEGEND
- 7 WALL PROTECTION (WP-1) AT THIS LOCATION - REF. FINISH LEGEND
- 8 EXISTING MATERIALS TO REMAIN - CLEAN SURFACES
- 9 WALL FACE TO BE PAINTED (PT-1A) - REF. FINISH LEGEND
- 10 WALL FACE TO BE PAINTED (PT-1B) - REF. FINISH LEGEND
- 11 WALL FACE TO BE PAINTED (PT-1C) - REF. FINISH LEGEND
- 12 BACK PAINTED WALL MOUNTED GLASS (GW-1) - REF. TO FINISH LEGEND
- 13 BALCONY WATERFALL SOLID SURFACE WALL CAP (SS-3) AT THIS LOCATION - REFER TO FINISH LEGEND
- 14 BALCONY WATERFALL SOLID SURFACE WALL CAP (SS-2) AT THIS LOCATION - REFER TO FINISH LEGEND
- 15 WALL PAINT (PT-2) AT THIS LOCATION - REF. FINISH LEGEND
- 16 TV ALCOVES TO BE PAINTED (PT-4) - REF. FINISH LEGEND AND ELEVATIONS FOR MORE INFORMATION
- 17 PLYWOOD ON BAR GRADING. REF. R-SERIES FOR ADDITIONAL INFORMATION
- 18 SOLID SURFACE WALL CAP (SS-1) AT THIS LOCATION - REFER TO FINISH LEGEND
- 19 PAINT ALL WALLS IN POOL (PT-1) NOT COVERED BY FINISH PLAN NOTES - REFER TO FINISH LEGEND (ALTERNATE BID)

1 INTERIOR FINISH PLAN - FIRST FLOOR - UNIT L
SCALE: 3/32" = 1'-0" REF. 3 / A142




REVISIONS:		
#	Date	Desc.
7	06/09/22	BID PKG. #2 ADD. #7

BID PACKAGE #2 - 100%
CONSTRUCTION DOCUMENTS
PROJECT: #21107
DATE: 05.20.2022
DRAWN BY: MC



INTERIOR
FINISH PLAN -
FIRST FLOOR -
UNIT L

A721L




1. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND/OR FINISHER HAS INSPECTED AND ACCEPTED THE SUBSTRATE RECEIVING THE NEW WORK. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY UNACCEPTED, UNKNOWING CONDITIONS OR UNSATISFACTORY SUBSTRATE TO WHICH THE FINISH WORK HAS PROCEEDED.
2. WHERE WALLS ARE INDICATED TO RECEIVE PAINT, PAINT ALL PRIMED GRILLS, FIRE EXTINGUISHER CABINETS, AND OTHER ITEMS EMBEDDED IN WALL CONSTRUCTION TO MATCH SURFACE OF ADJACENT WALLS AND FINISH THEREOVER.
3. ALIGN FLOOR TRANSITION AT CORNER OF DOORWAY, TYP.
4. WOOD STUOLS TO BE 56-3/4".
5. PROVIDE FINISH LEGEND FOR CUSTOM GRAPHIC WALL COVERING.
6. PROVIDE DRYWALL REVEAL JUNGLE WHERE DRYWALL MEETS DISSIMILAR MATERIALS.
7. PROVIDE SLUTTER EDGE WHERE TILE MEETS DISSIMILAR MATERIALS.
8. PAINT EXPOSED SCHED 40 STUDS, JOISTS, LATHES, AND TRUSSES.
9. PAINT HM DOOR FRAMES AND RELATED EXPOSED LINTELS PT-4 UNLESS NOTED OTHERWISE.
10. PAINT EXTERIOR HM DOOR PANELS PT-4 UNLESS NOTED OTHERWISE.
11. PAINT INTERIOR HM DOOR PANELS PT-2 UNLESS NOTED OTHERWISE.
12. GRIND DOWN THE EDGE OF TERRAZZO WHERE IT MEETS DISSIMILAR FLOORING.
13. ALL PAINT INSIDE RESTROOMS AND CONCESSIONS TO BE EPOXY BASED PAINT.
14. PROVIDE TERRAZZO TO MATCH EXISTING TERRAZZO.
15. WITHIN AUDITORIUM PAINT ALL WALL FACES ABOVE 3'-6" AFF-PT 4.

1	CORRIDOR FEATURE WALL - REF. ELEVATIONS FOR MORE DETAILS
2	WALL COVERING (WC-1) AT THIS LOCATION - REF. FINISH LEGEND
4	ACOUSTICAL DIVIDER (AP-1) AT THIS LOCATION - REF. FINISH LEGEND
5	WALL TILE (WT-5/4-1) AT THIS LOCATION - REF. FINISH LEGEND
6	ACCENT PAINT (PT-2) AT THIS LOCATION - REFER TO FINISH LEGEND
8	ACCENT PAINT (PT-4) AT THIS LOCATION - REFER TO FINISH LEGEND
10	WALL PROTECTION (WP-1) AT THIS LOCATION - REF. FINISH LEGEND
11	EXISTING MATERIALS TO REMAIN - CLEAN SURFACES
12	WALL FACE TO BE PAINTED (PT-1A) - REF. FINISH LEGEND
13	WALL FACE TO BE PAINTED (PT-1B) - REF. FINISH LEGEND
14	WALL FACE TO BE PAINTED (PT-1C) - REF. FINISH LEGEND
15	BACK PAINTED WALL MOUNTED GLASS (GV-1) - REF. TO FINISH LEGEND
16	BALCONY WATERFALL SOLID SURFACE WALL CAP (SS-3) AT THIS LOCATION - REFER TO FINISH LEGEND
17	BALCONY WATERFALL SOLID SURFACE WALL CAP (SS-2) AT THIS LOCATION - REFER TO FINISH LEGEND
18	WALL PAINT (PT-2) AT THIS LOCATION - REF. FINISH LEGEND
19	WALL ALCOVES TO BE PAINTED (PT-4) - REF. FINISH LEGEND AND ELEVATIONS FOR MORE INFORMATION
20	PLYWOOD ON BAR GRADINGS, REF. S-SERIES FOR ADDITIONAL INFORMATION
22	SOLID SURFACE SILL CAP (SS-3) AT THIS LOCATION - REFER TO FINISH LEGEND
23	WALLS THAT ALL WALLS NOT COVERED BY FINISH PLAN NOTES - REFER TO FINISH LEGEND (ALTERNATE BID)




1

SCALE: 3/32" = 1'-0" REF. 1 / A201




○ PLAN NOTES

1. DIFFUSER TO APPEAR CONTINUOUS. BLANK OFF UNUSED SECTIONS.
2. DIFFUSER SLOTS TO HAVE OPPOSED THROW. BALANCING CONTRACTOR TO BALANCE DIFFUSER TO ENSURE COMPLETE COVERAGE OF THE SPACE.
3. BOTTOM OF FAN SHALL BE FULLY ABOVE EXISTING SUPPLY DIFFUSERS. MAINTAIN ALL REQUIRED CLEARANCES AND SPACING PER MANUFACTURER.
4. REPLACE UPPER GRILLE WITH 36" X 84" GRILLE EXTENDING OPENING DOWN AS REQUIRED. GRILLE TO MATCH EXISTING APPEARANCE. BALANCE GRILLE TO MATCH TOTAL OF TWO EXISTING GRILLES.
5. HYLIS FAN CONTROLLER. COORDINATE WITH DIV 26. CONFIRM LOCATION WITH OWNER.
6. FAN TO SHUT DOWN UPON ACTIVATION OF FIRE ALARM OR SPRINKLER SYSTEM.
7. CABLE OPERATED BALANCE DAMPER.
8. SIDE WALL DISPLACEMENT DIFFUSER AT 0' 0" A.F.F. DIFFUSER TO APPEAR CONTINUOUS AND FOLLOW THE CURVE OF THE WALL. VERIFY SECTION LENGTHS AS REQUIRED. TRIM DIFFUSERS AND SEND A RETURN AS REQUIRED TO MAINTAIN CONTINUOUS APPEARANCE AT CHANGES IN FLOOR SLOPE.
9. 84" X 20" SUPPLY DUCTWORK UP TO AHU-1 ON ROOF. TRANSITION AS REQUIRED.
10. 60" X 22" SUPPLY DUCTWORK UP TO AHU-2 ON ROOF. TRANSITION AS REQUIRED.
11. 50" X 20" RETURN DUCTWORK UP TO AHU-2 ON ROOF. TRANSITION AS REQUIRED.
12. 44" X 18" SUPPLY DUCTWORK UP TO AHU-3 ON ROOF. TRANSITION AS REQUIRED.
13. 60" X 10" RETURN DUCTWORK UP TO AHU-3 ON ROOF. TRANSITION AS REQUIRED.
14. 14" X 14" EXHAUST UP TO EF-2 ON ROOF. TRANSITION AS REQUIRED.
15. 14" X 14" EXHAUST UP TO EF-2 ON ROOF. TRANSITION AS REQUIRED.
16. UNDERGROUND DUCTWORK SHALL TRANSITION TO STAINLESS STEEL AT THE FLOOR SLAB. SEAL TRANSITION WATER TIGHT. TRANSITION AS REQUIRED FOR CONNECTION TO ROUND FLOOR DISPLACEMENT DIFFUSER.



1 MECHANICAL DUCTWORK PLAN - FIRST FLOOR - UNIT L
SCALE: 3/32" = 1'-0"




- PLAN NOTES**
1. COVER RETURN AIR OPENING WITH 1/2" MESH HARDWARE CLOTH. REFER TO ROOF PLAN FOR CONTINUATION.
 2. DIFFUSE AIR EDGE OF CLOUD TO BE FIELD CUT TO LENGTH AS REQUIRED. TOUCH UP PAINT TO MATCH DIFFUSER COLOR.
 3. SHEET METAL PLENUM.
 4. BUILDING DIFFERENTIAL PRESSURE SENSOR ABOVE CEILING.
 5. BUILDING DIFFERENTIAL PRESSURE SENSOR ABOVE CATWALK.
 6. 8" X 8" EXHAUST UP TO EF-3 ON ROOF. TRANSITION AS REQUIRED.
 7. 20" X 20" EXHAUST UP TO EF-1 ON ROOF. TRANSITION AS REQUIRED.

REVISIONS:	DATE	BY	DESCRIPTION
1	08/09/22	BM	BID PKG. #2 ADD. #7

BID PACKAGE #2 - 100%
CONSTRUCTION DOCUMENTS
PROJECT: #21107
DATE: 05/20/2022
DRAWN BY: BMW

MECHANICAL
DUCTWORK
PLAN - SECOND
FLOOR - UNIT L

M102L



PLAN NOTES


- CONDENSATE DRAIN DOWN IN CHASE. CONNECT TO SANITARY WITH AIR GAP FITTING.
- CONDENSATE DRAIN DOWN TO MSP BASIN.
- REFRIGERANT PIPING UP TO SECOND FLOOR. PIPE SIZING AND SPECIALTIES BY MANUFACTURER.
- AVERAGE THERMOSTATS IN VESTIBULE TO CONTROL RADIANT FLOOR AND CUH-3.
- CONDENSATE DRAIN DOWN TO MSP BASIN.

REVISIONS:		
#	DATE	DESCRIPTION
7	06.09.22	BID PKG. #2 ADD. #7

BID PACKAGE #2 - 100%
CONSTRUCTION DOCUMENTS
PROJECT: #21107
DATE: 05.20.2022
DRAWN BY: BMW

MECHANICAL
PIPING PLAN -
FIRST FLOOR -
UNIT L


M201L



1 MECHANICAL PIPING PLAN - FIRST FLOOR - UNIT L
SCALE: 3/32" = 1'-0"

PLT DATE/TIME: 05/20/2022 11:16:38 AM



PLOT DATE/TIME: 05/20/2022 11:10:39 AM




PLAN NOTES

1. REFRIGERANT PIPE SIZING AND SPECIALTIES BY MANUFACTURER.
2. REFRIGERANT PIPE DOWN TO MS-1.
3. REFRIGERANT PIPE DOWN TO MS-2.

1 MECHANICAL ROOF PLAN - UNIT L
SCALE: 3/32" = 1'-0"





PLOT DATE/TIME: 6/5/2022 11:15:49 AM




1 ENLARGED MECHANICAL ROOM PLAN
SCALE: 1/4" = 1'-0"

PLAN NOTES

1. NEW 8" 3-WAY CONTROL VALVE, 1,500 GPM.
2. NEW VFDs MOUNTED ON EXISTING UNSTRUT.
3. FLUE GAS OUTLET UP THROUGH ROOF. SIZE, ROUTING, AND TERMINATION PER MANUFACTURERS RECOMMENDATION.
4. COMBUSTION AIR INTAKE UP THROUGH ROOF. SIZE, ROUTING, AND TERMINATION PER MANUFACTURERS RECOMMENDATION.
5. MAINTAIN MINIMUM WORKING CLEARANCE OF 48" FROM FACE OF ELECTRICAL PANEL.
6. BOILER TO BE MOUNTED ON EXISTING HOUSE KEEPING PAD. EXTEND PAD AS REQUIRED.



GREENFIELD CENTRAL HIGH SCHOOL
AUDITORIUM RENOVATION & ADDITION
810 N BROADWAY ST.
GREENFIELD, IN 46140



REVISIONS:	
#	DESC.
7	06.08.22 BID PKG. #2 ADD. #7


BID PACKAGE #2 - 100%
CONSTRUCTION DOCUMENTS
PROJECT: #21107
DATE: 05.20.2022
DRAWN BY: BMW

ENLARGED
MECHANICAL
PLANS

M401


LANCER+BEEBE, LLC
ARCHITECTURE | PLANNING | INTERIORS
220 N. COLLEGE AVE
INDIANAPOLIS, IN
46202

HEAPY
PROJECT NO. 2021-07128




NOTES

- CONICAL SPIN-IN BRANCH TAP FITTING, STRAIGHT SIDE, INTEGRAL INSULATION GUARD SLEEVE REQUIRED FOR TAP FITTING TO MAIN SUPPLY DUCT WITH INTERNAL INSULATION.
- ROUND SHEET METAL BRANCH DUCT, SAME SIZE AS AIR TERMINAL UNIT INLET SIZE UNLESS NOTED OTHERWISE.
- INSULATED FLEXIBLE DUCT, MAXIMUM LENGTH OF 3 FT. MINIMUM LENGTH OF 4 IN. STRETCH FLEXIBLE DUCT TO 90% OF FULLY EXTENDED LENGTH.
- AIR TERMINAL UNIT.
- MINIMUM FOUR HANGER RODS FOR UNIT (CORNER POINTS), ATTACH TO STRUCTURE.
- TRANSITION WHEN REQUIRED.
- MINIMUM STRAIGHT LENGTH OF DUCT SHALL BE TERMINAL UNIT MANUFACTURER'S REQUIRED LENGTH, BUT AT LEAST 3 TIMES UNIT INLET DIAMETER.
- DUCT HANGER, ATTACH TO STRUCTURE.
- DUCT SHALL BE FULL SIZE OF UNIT OUTLET UNLESS NOTED OTHERWISE ON FLOOR PLANS.
- REHEAT COIL WHEN SPECIFIED. REFER TO COIL DETAIL.



NOTES


- SQUARE, ROUND ADAPTER IF DIFFUSER NECK IS SQUARE. CONNECT ADAPTOR TO DIFFUSER. SEAL TO AIR DEVICE. SEAL CLASS A. INSULATE ADAPTOR AND EXPOSED BACKSIDE SURFACES OF AIR DEVICE.
- INSULATED FLEXIBLE DUCT SAME DIAMETER AS BRANCH DUCT (7). 3 FT. MAXIMUM TOTAL LENGTH PER AIR DEVICE. STRETCH FLEXIBLE DUCT TO AT LEAST 90% OF FULLY EXTENDED LENGTH.
- SPIN-IN BRANCH TAP FITTING, STRAIGHT SIDE WITH MANUAL DAMPER. DAMPER SHAFT IN HORIZONTAL. INTEGRAL INSULATION GUARD SLEEVE REQUIRED FOR TAP FITTING TO MAIN DUCT WITH INTERNAL INSULATION, AND EXTENDED DAMPER SHAFT AND HANDLE WITH STAND-OFF TO ACCOMMODATE EXTERNAL INSULATION.
- DUCT STRAP HANGER. ATTACH TO STRUCTURE.
- STRAP HANGER REQUIRED IF LENGTH OF FLEXIBLE DUCT IS LONGER THAN 2 FT.
- MINIMUM CENTERLINE RADIUS EQUAL TO DUCT DIAMETER.
- ROUND SHEET METAL BRANCH DUCT, SAME SIZE AS DIFFUSER INLET UNLESS NOTED OTHERWISE.
- FLEXIBLE DUCT ELBOW SUPPORT, INSTALLED WITH NYLON BANDING PER MANUFACTURER'S INSTRUCTIONS.
- A RADIUS SHEET METAL ELBOW MAY BE USED IN LIEU OF A FLEXIBLE ELBOW SUPPORT WHEN CONNECTED DIRECTLY TO AIR DEVICE.
- CEILING T-BAR SUPPORT (FOR LAY-IN APPLICATIONS). COORDINATE AND VERIFY T-BAR TYPE FOR COMPATIBILITY WITH DIFFUSER.



NOTES

- SHEET METAL PLENUM, FULL SIZE OF GRILLE NECK, MINIMUM 4" TALLER THAN DUCT ROUND SIZE, WITH SAME INTERNAL OR EXTERNAL INSULATION AS RETURN OR EXHAUST DUCT, CONNECT TO GRILLE. SEAL PLENUM AND CONNECTION TO GRILLE. SEAL CLASS A.
- FLEXIBLE DUCT, SAME DIAMETER AS BRANCH DUCT (7). 3 FT. MAXIMUM TOTAL LENGTH PER AIR DEVICE. STRETCH FLEXIBLE DUCT TO AT LEAST 90% OF FULLY EXTENDED LENGTH.
- SPIN-IN BRANCH TAP FITTING, STRAIGHT SIDE WITH MANUAL DAMPER. DAMPER SHAFT IN HORIZONTAL. INTEGRAL INSULATION GUARD SLEEVE REQUIRED FOR TAP FITTING TO MAIN DUCT WITH INTERNAL INSULATION. EXTENDED DAMPER SHAFT AND HANDLE WITH STAND-OFF REQUIRED FOR EXTERNALLY INSULATED DUCTWORK.
- SPIN-IN TAP FITTING SIMILAR TO (3) EXCEPT NO DAMPER.
- DUCT STRAP HANGER, ATTACH TO STRUCTURE.
- STRAP HANGER REQUIRED IF LENGTH OF FLEXIBLE DUCT IS LONGER THAN 2 FT.
- ROUND SHEET METAL BRANCH DUCT, SIZE AS INDICATED IN ADJACENT SCHEDULE UNLESS NOTED OTHERWISE ON PLANS.
- CEILING T-BAR SUPPORT (FOR LAY-IN APPLICATIONS). COORDINATE AND VERIFY T-BAR TYPE FOR COMPATIBILITY WITH GRILLE.

BRANCH CFM	RD. DUCT SIZE
0 TO 80 CFM	6"D
81 TO 120 CFM	7"D
121 TO 200 CFM	8"D
201 TO 400 CFM	10"D
401 TO 700 CFM	12"D
701 TO 1000 CFM	14"D



NOTES

- SHEET METAL PLENUM, FULL SIZE OF GRILLE NECK, MINIMUM 6" TALL WITH SAME INTERNAL OR EXTERNAL INSULATION AS RETURN OR EXHAUST DUCT. CONNECT TO GRILLE. SEAL PLENUM AND CONNECTION TO GRILLE. SEAL CLASS A.
- FLEXIBLE DUCT, SAME DIAMETER AS BRANCH DUCT (7). 3 FT. MAXIMUM TOTAL LENGTH PER AIR DEVICE. STRETCH FLEXIBLE DUCT TO AT LEAST 90% OF FULLY EXTENDED LENGTH.
- SPIN-IN BRANCH TAP FITTING, STRAIGHT SIDE WITH MANUAL DAMPER. DAMPER SHAFT IN HORIZONTAL. INTEGRAL INSULATION GUARD SLEEVE REQUIRED FOR TAP FITTING TO MAIN DUCT WITH INTERNAL INSULATION. EXTENDED DAMPER SHAFT AND HANDLE WITH STAND-OFF REQUIRED FOR EXTERNALLY INSULATED DUCTWORK.
- SPIN-IN TAP FITTING SIMILAR TO (3) EXCEPT NO DAMPER.
- DUCT STRAP HANGER, ATTACH TO STRUCTURE.
- STRAP HANGER REQUIRED IF LENGTH OF FLEXIBLE DUCT IS LONGER THAN 2 FT.
- ROUND SHEET METAL BRANCH DUCT, SIZE AS INDICATED IN ADJACENT SCHEDULE UNLESS NOTED OTHERWISE ON PLANS.
- CEILING T-BAR SUPPORT (FOR LAY-IN APPLICATIONS). COORDINATE AND VERIFY T-BAR TYPE FOR COMPATIBILITY WITH GRILLE.
- MINIMUM CENTERLINE RADIUS EQUAL TO DUCT DIAMETER.
- FLEXIBLE DUCT ELBOW SUPPORT, INSTALLED WITH NYLON BANDING PER MANUFACTURER'S INSTRUCTIONS.
- A RADIUS SHEET METAL ELBOW MAY BE USED IN LIEU OF A FLEXIBLE ELBOW SUPPORT WHEN CONNECTED DIRECTLY TO AIR DEVICE.

BRANCH CFM	RD. DUCT SIZE
0 TO 80 CFM	6"D
81 TO 120 CFM	7"D
121 TO 200 CFM	8"D
201 TO 400 CFM	10"D
401 TO 700 CFM	12"D
701 TO 1000 CFM	14"D

1 AIR TERMINAL UNIT DUCT CONNECTION

SCALE: NONE

2 CEILING DIFFUSER DUCT CONNECTION


SCALE: NONE

3 RETURN/EXHAUST GRILLE DUCT CONNECTION

SCALE: NONE

4 RETURN/EXHAUST GRILLE DUCT CONNECTION


SCALE: NONE



AIR SPLIT DUCT TAKE-OFF
PLAN VIEW

BRANCH DUCT TAKE-OFF
PLAN VIEW


THE BRANCH DUCT TAKE-OFF MAY BE USED FOR UP TO 15% OF THE MAIN DUCT CFM, AND UP TO 40% WHEN THE MAIN DUCT VELOCITY IS 1000 FPM OR LESS. THE AIR SPLIT DUCT TAKE-OFF SHALL BE USED IN ALL OTHER CASES.




TYPICAL DUCTWORK
TRANSITION WITH EQUIPMENT
MOUNTED IN DUCT PLAN OR
SIDE VIEW

TYPICAL DUCTWORK
TRANSITION PLAN OR SIDE
VIEW

NOTE:
A. UNLESS OTHERWISE INDICATED ON PLANS, MAXIMUM ANGLES SHOWN SHALL APPLY.
B. TRANSITION ANGLES IN AND OUT OF FANS SHALL BE 50% OF THOSE SHOWN ABOVE.



AIR DEVICE SIZE	DUCT SIZE
12x12	12x10
24x12	12x12
24x24	24x12



NOTES

- LOCATE STRAINER WITH BLOW-DOWN VALVE AND HOSE CONNECTION AT LOW POINT OF COIL PIPING.
- PIPE REDUCER IF REQUIRED.
- PIPE REDUCER/INCREASER IF COIL CONNECTION SIZE DIFFERS FROM AUTO CONTROL VALVE SIZE.
- PIPING SAME SIZE AS AUTO CONTROL VALVE OR COIL CONNECTION, WHICHEVER IS LARGER.
- 6" MINIMUM LENGTH INCLUDES ANY REQUIRED ELBOWS AND OFFSETS. PIPING INSULATION FROM COIL TO UNION SHALL INCLUDE SEALED VAPOR BARRIER.
- MAXIMUM DISTANCE FROM SUPPLY AND RETURN SHUT-OFF VALVES TO COIL IS 48".
- FACTORY ASSEMBLED PIPING PACKAGE (OPTIONAL).
- LINE SIZE START-UP FLUSHING BYPASS.

GENERAL NOTES

- ALL PIPING SHALL BE FULL SIZE OF MAIN RUN-OUT PIPING UNLESS NOTED OTHERWISE.
- REFER TO AIR TERMINAL UNIT SCHEDULE FOR AUTOMATIC CONTROL VALVE SIZE.
- REFER TO SPECIFICATIONS FOR DEVICES NOT TO BE INSULATED. INSULATED DEVICES SHALL INCLUDE EXTENDED NECKS, SHAFTS, ETC., SO THEY ARE ACCESSIBLE ABOVE THE INSULATION.

5 SUPPLY DUCTWORK BRANCH TAKE-OFFS

SCALE: NONE

6 DUCTWORK TRANSITIONS


SCALE: NONE

7 RETURN AIR SOUND BOOT

SCALE: NONE

8 AIR TERMINAL UNIT / DUCT REHEAT COIL

SCALE: NONE



9 AIR TERMINAL UNIT / DUCT REHEAT COIL


SCALE: NONE

NOTES

- LOCATE STRAINER WITH BLOW-DOWN VALVE AND HOSE CONNECTION AT LOW POINT OF COIL PIPING.
- PIPE REDUCER IF REQUIRED.
- PIPE REDUCER/INCREASER IF COIL CONNECTION SIZE DIFFERS FROM AUTO CONTROL VALVE SIZE.
- PIPING SAME SIZE AS AUTO CONTROL VALVE OR COIL CONNECTION, WHICHEVER IS LARGER.
- 6" MINIMUM LENGTH INCLUDES ANY REQUIRED ELBOWS AND OFFSETS. PIPING INSULATION FROM COIL TO UNION SHALL INCLUDE SEALED VAPOR BARRIER.
- MAXIMUM DISTANCE FROM SUPPLY AND RETURN SHUT-OFF VALVES TO COIL IS 48".
- UNION OR SCREWED VALVE FITTING.
- TRUE "T" FITTING (NOT A PORT OFF AN ACCESSORY).
- FACTORY ASSEMBLED PIPING PACKAGE (OPTIONAL).
- LINE SIZE START-UP FLUSHING BYPASS.

GENERAL NOTES

- ALL PIPING SHALL BE FULL SIZE OF MAIN RUN-OUT PIPING UNLESS NOTED OTHERWISE.
- REFER TO AIR TERMINAL UNIT SCHEDULE FOR AUTOMATIC CONTROL VALVE SIZE. VERIFY VALVE PORTING AND CONNECT PIPING TO PROPER PORTS, PER MANUFACTURER'S RECOMMENDATIONS.
- REFER TO SPECIFICATIONS FOR DEVICES NOT TO BE INSULATED. INSULATED DEVICES SHALL INCLUDE EXTENDED NECKS, SHAFTS, ETC., SO THEY ARE ACCESSIBLE ABOVE THE INSULATION.




10 FAN MOUNTING CURB

SCALE: NONE

NOTES

- 12" HIGH INSULATED STEEL CURB.
- PROVIDE PRESSURE TREATED RIGID WOOD BLOCK FRAME SAME THICKNESS AS ROOF INSULATION. BOLT TO CONCRETE ROOF DECK.
- SHEET METAL SCREW.
- CONCRETE ROOF DECK OPENING. COORDINATE REQUIRED OPENING SIZE.




11 ROOFTOP UNIT DRAIN PIPING

SCALE: NONE

NOTES

- DRAIN PIPE SAME SIZE AS UNIT DRAIN PAN CONNECTION.
- UNIT ROOF CURB. VERIFY REQUIRED HEIGHT FOR DRAIN PIPE AND TRAP INSTALLATION. PROVIDE CURB OF ADEQUATE HEIGHT TO ATTAIN REQUIRED DIMENSION.
- TEE WITH CLEANOUT PLUG.
- 1" CENTERLINE - TO - CENTERLINE DIMENSION NOT LESS THAN SUPPLY FAN T.S.P. (INCH W.G.) + 12 INCH.
- CENTERLINE - TO - CENTERLINE DIMENSION NOT LESS THAN SUPPLY FAN T.S.P. (INCH W.G.) + 1 INCH.
- CENTERLINE - TO - CENTERLINE DIMENSION SHALL BE 50% OF DIMENSION FOUND IN (6) ABOVE.
- CENTERLINE - TO - CENTERLINE DIMENSION SHALL BE 50% OF DIMENSION FOUND IN (6) ABOVE.
- SPLASH BLOCK.




NOTES

- SLOT DIFFUSER ASSEMBLY AND PLENUM WITH SAME INTERNAL OR EXTERNAL INSULATION AS MAIN SUPPLY DUCT. CONNECT PLENUM TO DIFFUSER. SEAL PLENUM TO DIFFUSER. SEAL CLASS A. INSULATE BACKSIDE SURFACES OF DIFFUSER.
- INSULATED FLEXIBLE DUCT SAME DIAMETER AS BRANCH DUCT (7). 5 FT. MAXIMUM TOTAL LENGTH PER AIR DEVICE. STRETCH FLEXIBLE DUCT TO AT LEAST 90% OF FULLY EXTENDED LENGTH.
- SPIN-IN BRANCH TAP FITTING, STRAIGHT SIDE WITH MANUAL DAMPER. DAMPER SHAFT IN HORIZONTAL. INTEGRAL INSULATION GUARD SLEEVE REQUIRED FOR TAP FITTING TO MAIN DUCT WITH INTERNAL INSULATION, AND EXTENDED DAMPER SHAFT AND HANDLE WITH STAND-OFF TO ACCOMMODATE EXTERNAL INSULATION.
- SPIN-IN TAP FITTING SIMILAR TO (3) EXCEPT NO DAMPER.
- DUCT STRAP HANGER, ATTACH TO STRUCTURE.
- STRAP HANGER REQUIRED IF LENGTH OF FLEXIBLE DUCT IS LONGER THAN 4 FT.
- ROUND SHEET METAL BRANCH DUCT, SAME SIZE AS DIFFUSER INLET UNLESS NOTED OTHERWISE.
- CEILING T-BAR SUPPORT (FOR LAY-IN APPLICATIONS). COORDINATE AND VERIFY T-BAR TYPE FOR COMPATIBILITY WITH DIFFUSER.


12 SLOT DIFFUSER DUCT CONNECTION

SCALE: NONE



13 RADIANT FLOOR SLAB TEMPERATURE SENSOR1

SCALE: NONE




14 RADIANT FLOOR PIPING1

SCALE: NONE

GENERAL NOTES

- ALL PIPING SHALL BE FULL SIZE OF MAIN RUN-OUT PIPING UNLESS NOTED OTHERWISE.
- ALL COMPONENTS SHOWN SHALL BE WITHIN MANIFOLD CLOSET AND FURNISHED BY THE MANUFACTURER AND INSTALLED BY THE MECHANICAL CONTRACTOR.
- 120V ELECTRICAL OUTLET IS PROVIDED. REFER TO ELECTRICAL PLANS FOR DETAILS. ALL INTERNAL 24 VAC WIRING SHALL BE FURNISHED BY MANUFACTURER AND INSTALLED BY THE MECHANICAL CONTRACTOR.

- EXACT NUMBER OF PEX RUN/OUTS NOT SHOWN. REFER TO RADIANT FLOOR HEATING SYSTEMS SCHEDULE FOR FURTHER INFORMATION.
- PIPE REDUCER IF REQUIRED.
- PIPE REDUCER/INCREASER IF MANIFOLD CONNECTION SIZE DIFFERS FROM AUTO CONTROL VALVE SIZE.
- PIPING SAME SIZE AS AUTO CONTROL VALVE OR MANIFOLD CONNECTION, WHICHEVER IS LARGER.
- 18" BRAIDED BRONZE HOSE. INSULATE FIRST 6" NEXT TO MANIFOLD.
- INSULATE PIPING UP TO SHUT-OFF VALVE.
- RADIANT FLOOR PUMP. REFER TO PUMP SCHEDULE.




15 PIPE MOUNTED PUMP

SCALE: NONE


NOTES

- PUMP WITH FLANGED CONNECTIONS.
- STRAP HANGER.
- PRESSURE GAUGE WITH INTERCONNECTING PIPING AND VALVES.
- BALANCING VALVE, SIZED FOR 3 TO 5 FT. HD. W/PO AT FULL PUMP GPM. PROVIDE REDUCERS IN AND OUT FOR PUMPS FITTED WITH AN ADJUSTABLE FREQUENCY MOTOR CONTROLLER. LEAVE THE BALANCING VALVE FULL OPEN.
- REDUCER WHEN PUMP CONNECTION SIZE DIFFERS FROM PIPE SIZE.
- LEAVE SPACE TO ALLOW MOTOR TO BE PULLED.
- DRAIN VALVE WITH HOSE CONNECTION.



16 EXHAUST OR RETURN BRANCH DUCTWORK

SCALE: NONE




- NOTES**
1. PIPE REDUCER IF COIL CONNECTION SIZE DIFFERS FROM PIPE SIZE.
 2. MAXIMUM DISTANCE FROM SHUT-OFF VALVE TO COIL IS 48".
 3. FACTORY ASSEMBLED PIPING PACKAGE (OPTIONAL).
 4. LINE SIZE START-UP/FLUSHING BYPASS.

GENERAL NOTES

- ALL PIPING SHALL BE FULL SIZE OF MAIN RUN-OUT PIPING UNLESS NOTED OTHERWISE.
- REFER TO EQUIPMENT SCHEDULE FOR AUTOMATIC CONTROL VALVE SIZE.
- REFER TO SPECIFICATIONS FOR DEVICES NOT TO BE INSULATED. INSULATED DEVICES SHALL INCLUDE EXTENDED NECKS, SHAFTS, ETC. SO THEY ARE ACCESSIBLE ABOVE THE INSULATION.

4 CABINET UNIT HEATER PIPING-HEATING COIL

SCALE: NONE




- NOTES**
1. AUTOMATIC TWO-PORT CONTROL VALVE. NORMALLY OPEN THRU COIL.
 2. 0.5" DRAIN VALVE.
 3. PIPE REDUCER IF COIL CONNECTION DIFFERS FROM PIPE SIZE.

GENERAL NOTES

- ALL PIPING SHALL BE FULL SIZE OF MAIN RUN-OUT PIPING UNLESS NOTED OTHERWISE.
- REFER TO AIR HANDLING UNIT SCHEDULE FOR AUTOMATIC CONTROL VALVE SIZE.

3 A.H. UNIT 2 AND 3 HOT WATER COIL

SCALE: NONE




- NOTES**
1. AUTOMATIC TWO-PORT CONTROL VALVE. NORMALLY CLOSED THRU COIL.
 2. 0.5" DRAIN VALVE.
 3. PIPE REDUCER IF COIL CONNECTION DIFFERS FROM PIPE SIZE.
 4. DRAIN PAN.
 5. DRAIN PIPE. SAME SIZE AS PAN CONNECTION, WITH DEEP SEAL TRAP. REFER TO CONDENSATE DRAIN PIPING DETAIL.

GENERAL NOTES

- ALL PIPING SHALL BE FULL SIZE OF MAIN RUN-OUT PIPING UNLESS NOTED OTHERWISE.
- REFER TO AIR HANDLING UNIT SCHEDULE FOR AUTOMATIC CONTROL VALVE SIZE.


2 A.H. UNIT 2 AND 3 CHILLED WATER COIL

SCALE: NONE



1 UNDERFLOOR DUCT BACK FILL DETAIL


SCALE: NONE



- NOTES**
1. BASE MOUNTED END SUCTION CENTRIFUGAL PUMP WITH FLANGED PIPE CONNECTIONS.
 2. 4" CONCRETE HOUSEKEEPING PAD.
 3. SUCTION DIFFUSER WITH INTEGRAL FINE MESH START-UP STRAINER AND ADJUSTABLE SUPPORT. REMOVE MESH AFTER PIPING IS CLEANED.
 4. SPHERICAL FLEXIBLE PIPE CONNECTOR.
 5. PRESSURE GAUGE WITH INTERCONNECTING PIPING AND VALVES.
 6. PIPE REDUCER WHEN PIPE SIZE DIFFERS FROM PUMP CONNECTION SIZE.
 7. SPRING HANGER. 3 SPRING HANGERS REQUIRED WITHIN 50 LF OF PUMP.
 8. BALANCING VALVE. SIZED FOR 3 TO 5 FT. HD. WPD AT FULL PUMP GPM. PROVIDE REDUCERS IN AND OUT. FOR PUMPS FITTED WITH AN ADJUSTABLE FREQUENCY MOTOR CONTROLLER LEAVE THE BALANCING VALVE FULL OPEN.
 9. SHUT-OFF, CHECK AND BALANCING VALVES MAY BE COMBINED INTO A SINGLE TRIPLE DUTY VALVE (OPTIONAL).

7 BASE MOUNTED PUMP - END SUCTION


SCALE: NONE



- NOTES**
1. BOILER. REFER TO EQUIPMENT SCHEDULE.
 2. 75" DRAIN VALVE WITH HOSE THREAD FITTING.
 3. REDUCER IF BOILER CONNECTION SIZE DIFFERS FROM PIPE SIZE.
 4. PRESSURE GAUGE WITH INTERCONNECTING PIPING AND VALVES.
 5. ONE OR MORE SAFETY RELIEF VALVES. PIPE DISCHARGE(S) TO SPILL ON FLOOR NEXT TO BOILER.
 6. 4" CONCRETE HOUSEKEEPING PAD.
 7. FULL SIZE DRAIN VALVE.
 8. PRIMARY BOILER PUMP PHWP-3.
 9. STAINLESS STEEL SECONDARY HX CONDENSATE DRAIN. PIPE TO FLOOR DRAIN THRU A NEUTRALIZING BASIN. DISCHARGE TO DRAIN PER PLUMBING CODE.
 10. STAINLESS STEEL OVERFLOW DRAIN LINE TO SPILL ONTO FLOOR NEXT TO FLOOR DRAIN.
 11. LINE SIZE MANUAL BALANCING VALVE. LEAVE WIDE-OPEN UNLESS REQUIRED TO BALANCE PRIMARY PUMP. VALVE MAY BE DELETED IF PRIMARY BOILER PUMP IS PROVIDED WITH AN ELECTRONICALLY COMMUTATED MOTOR WITH MANUAL SPEED ADJUSTMENT.

6 BOILER DETAIL

SCALE: NONE



- NOTES**
1. PIPE REDUCER IF COIL CONNECTION SIZE DIFFERS FROM PIPE SIZE.
 2. 0.5" DRAIN VALVE.
 3. MAXIMUM DISTANCE FROM SHUT-OFF VALVES TO COIL IS 48".
 4. LINE SIZE 2-POSITION AUTOMATIC ISOLATION VALVE FOR SEASONAL SHUT-OFF.
 5. FACTORY ASSEMBLED PIPING PACKAGE (OPTIONAL).

GENERAL NOTES


- REFER TO SPECIFICATIONS FOR DEVICES NOT TO BE INSULATED. INSULATED DEVICES SHALL INCLUDE EXTENDED NECKS, SHAFTS, ETC. SO THEY ARE ACCESSIBLE ABOVE THE INSULATION.

5 PROPELLER UNIT HEATER

SCALE: NONE


GENERAL NOTES

- FIRE DAMPERS SHALL BE UL LABELED.
- INSTALLATION OF FIRE DAMPERS AND ACCESSORIES SHALL CONFORM TO NFPA 90A, SMACNA AND MANUFACTURER'S INSTRUCTIONS.
- DETAILS SHOW INSTALLATION OF FIRE DAMPER IN WALL. DAMPER INSTALLATION IN FLOOR SIMILAR. COORDINATE REQUIRED ACCESS LOCATIONS.
- INSULATE RETAINING ANGLES FOR SYSTEMS REQUIRED TO BE INSULATED.




11 FIRE DAMPER AT AIR DEVICE - WALL

SCALE: NONE



10 FIRE DAMPER TYPE "B"

SCALE: NONE



9 FIRE DAMPER TYPE "A"


SCALE: NONE

NOTES

- FIRE DAMPER, FOLDED BLADE CURTAIN TYPE. EXCEPT AS NOTED, VERTICAL MOUNT, GRAVITY DROP, HORIZONTAL MOUNT, SPRING LOADED TO CLOSE. REFER TO SPECS FOR VELOCITY LIMITATIONS OF EACH TYPE. REFER TO DRAWINGS FOR STATIC OR DYNAMIC REQUIREMENTS.
 - TYPE "A" - BLADES STORED IN AIR STREAM. RECTANGULAR, ROUND OR OVAL DUCT CONNECTION.
 - TYPE "B" - BLADES STORED OUT OF AIR STREAM. RECTANGULAR, ROUND OR OVAL DUCT CONNECTION.
 - TYPE "C" - HIGH VELOCITY TYPE. BLADES STORED OUT OF AIR STREAM. RECTANGULAR, ROUND OR OVAL DUCT CONNECTION.
 - TYPE "D" - HIGH VELOCITY CENTER PIVOTED MULTIBLADE. RECTANGULAR, ROUND OR OVAL DUCT CONNECTION.
 - TYPE "E" - HORIZONTAL, CEILING RADIATION TYPE.
 - TYPE "AA", "BB", "CC", "DD" - SAME AS "A", "B", "C", "D", EXCEPT RATED FOR 3HRS.
- SHEET METAL WALL SLEEVE. SAME MATERIAL AS DUCT (EXCEPT GALVANIZED SHEET METAL FOR FIBERGLASS DUCT). SHEET METAL GAUGE PER SMACNA. USE EXTENDED HEAVY GAUGE SLEEVES WHEN INSTALLED CONDITION REQUIRED.
- DUCT/SLEEVE CONNECTION. BREAKAWAY TYPE SHOWN. CONNECTION MAY BE RIGID TYPE IF ALLOWED BY CODE AUTHORITY.
- RETAINING ANGLE ALL FOUR SIDES. GAUGE PER SMACNA. 1" MINIMUM OVERLAP OF WALL OPENING. LONGER LEG MAY BE REQUIRED TO ATTAIN REQUIRED OVERLAP. BOLT, SCREW OR TACK WELD TO WALL SLEEVE. SPACING OF FASTENERS PER SMACNA.
- DUCT ACCESS PANEL OR DOOR. REFER TO SPECIFICATIONS.
- CEILING ACCESS PANEL IF CEILING IS NOT ACCESSIBLE.

8 FIRE DAMPER NOTES

SCALE: NONE




- NOTES**
1. AUTOMATIC TWO-PORT CONTROL VALVE. NORMALLY OPEN THRU COIL.
 2. 0.5" DRAIN VALVE.
 3. PIPE REDUCER IF COIL CONNECTION DIFFERS FROM PIPE SIZE.
 4. LEAVE WIDE OPEN UNLESS NEEDED TO EVENLY DISTRIBUTE FLOW THRU COILS.

GENERAL NOTES

- ALL PIPING SHALL BE FULL SIZE OF MAIN RUN-OUT PIPING UNLESS NOTED OTHERWISE. BRANCH PIPING TO EACH COIL ONE SIZE SMALLER THAN MAIN RUN-OUT PIPING, BUT NO SMALLER THAN COIL CONNECTION SIZE.
- REFER TO AIR HANDLING UNIT SCHEDULE FOR AUTOMATIC CONTROL VALVE SIZE.

13 A.H. UNIT 1 HOT WATER COILS

SCALE: NONE




- NOTES**
1. AUTOMATIC TWO-PORT CONTROL VALVE. NORMALLY CLOSED THRU COIL.
 2. 0.5" DRAIN VALVE.
 3. PIPE REDUCER IF COIL CONNECTION DIFFERS FROM PIPE SIZE.
 4. DRAIN PAN.
 5. DRAIN PIPE. SAME SIZE AS PAN CONNECTION, WITH DEEP SEAL TRAP. REFER TO CONDENSATE DRAIN PIPING DETAIL.
 6. LEAVE WIDE OPEN UNLESS NEEDED TO EVENLY DISTRIBUTE FLOW THRU COILS.

GENERAL NOTES


- ALL PIPING SHALL BE FULL SIZE OF MAIN RUN-OUT PIPING UNLESS NOTED OTHERWISE. BRANCH PIPING TO EACH COIL ONE SIZE SMALLER THAN MAIN RUN-OUT PIPING, BUT NO SMALLER THAN COIL CONNECTION SIZE.
- REFER TO AIR HANDLING UNIT SCHEDULE FOR AUTOMATIC CONTROL VALVE SIZE.

12 A.H. UNIT 1 CHILLED WATER COILS


SCALE: NONE



1 AHU-1 ELEVATION
SCALE: NONE



2 AHU-2 ELEVATION
SCALE: NONE




3 AHU-3 ELEVATION
SCALE: NONE

REVISIONS:	#	DATE	DESCRIPTION
	1	08/08/22	BID PKG. #2 ADD. #7

BID PACKAGE #2 - 100% CONSTRUCTION DOCUMENTS
PROJECT: #21107
DATE: 05.20.2022
DRAWN BY: BMW

MECHANICAL
DETAILS

M503



SCALE: NONE

EF-1 AND EF-2 POINTS LIST

GENERAL NOTES:

A. THE FOLLOWING LIST SHALL BE THE MINIMUM POINTS REQUIRED OF THE DIRECT DIGITAL CONTROL SYSTEM (BUILDING AUTOMATION SYSTEM). IT IS NOT THE INTENT TO SHOW ALL REQUIRED POINTS. IF OR WHEN ADDITIONAL POINTS ARE REQUIRED TO ACCOMPLISH THE SEQUENCES OF CONTROL SPECIFIED, THOSE POINTS SHALL ALSO BE PROVIDED.

NOTES:

1. CURRENT SENSOR.

POINT NO.	EF-1	EF-2	EF-3	EF-4				
POINT NAME	FAN ON/OFF	FAN STATUS	EXHAUST AIR DAMPER	EXHAUST AIR DAMPER FEEDBACK				
TYPE	BO	BI	AO	AI				
ALARM		ON FAULT		ON MISMATCH				
NOTES		1						

[illegible]

3.8 AIR HANDLING UNIT AHU-1

- [illegible]


HEATING SET POINT THE SEQUENCE WILL REVERSE IN ORDER. DURING THE COOLING MODE, THE SUPPLY FAN SHALL RAMP UP FROM MINIMUM TO THE DESIGN MAXIMUM CFM WHEN THE ECONOMIZER IS ACTIVE BEFORE THE COOLING VALVE OPENS. IF THE ECONOMIZER IS NOT ACTIVE THE COOLING VALVE WILL LEAD BY ENABLING THE COOLING SUPPLY AIR RESET SCHEDULE. WHEN THE COOLING SUPPLY AIR TEMPERATURE HAS REACHED ITS MINIMUM SUPPLY AIR TEMPERATURE THE FAN SPEED SHALL BE RAMPED UPWARD UNTIL THE ROOM TEMPERATURE SET POINT HAS BEEN REACHED OR 100% SPEED AS REACHED. ON A FALL OF THE ROOM TEMPERATURE THE SEQUENCE HAS REVERSE IN ORDER.

1. RETURN FAN SYSTEM CONTROL
2. RETURN FAN SPEED IS ADJUSTED BY AN ARRAY OF 2 FANS AND ASSOCIATED 2 VFD'S (1 FAN PER VFD). REFER TO 20.25 14 ADJUSTABLE FREQUENCY MOTOR CONTROLLERS FOR VFD REQUIREMENTS.
3. A MANUAL "HAND-OFF" SWITCH ON THE FACE OF EACH VFD WHICH SELECT MODE OF OPERATION WHEN THE SELECTOR SWITCH IS INDEXED TO THE "OFF" POSITION. THE ASSOCIATED VFD WILL STOP WHEN THE SELECTOR SWITCH IS INDEXED TO THE "OFF" POSITION AND ALL SAFETIES ARE NORMAL. THE ASSOCIATED FAN SYSTEM SHALL START AND RUN CONTINUOUSLY WHEN THE SELECTOR SWITCH IS INDEXED TO THE "AUTO" POSITION AND ALL SAFETIES ARE NORMAL. THE BAS SHALL START AND STOP THE ASSOCIATED FAN SYSTEM.
4. THE MANUAL "HAND-OFF" SWITCH ON THE FACE OF EACH VFD SHALL SELECT CONTROL SIGNAL SOURCE FOR MOTOR SPEED WHEN THE MOTOR IS ENABLED AND IS INDEXED TO THE "MANUAL" POSITION. THE MANUAL SPEED ADJUSTOR OF THE VFD SHALL PROVIDE THE CONTROL SIGNAL FOR MOTOR SPEED. WHEN THE MOTOR IS ENABLED AND IS INDEXED TO THE "AUTO" POSITION, THE BAS SHALL PROVIDE A PROPORTIONAL PLUS INTEGRAL CONTROL SIGNAL TO THE VFD TO ADJUST THE MOTOR SPEED TO MAINTAIN SETPOINT.
4. RETURN FAN SYSTEM SPEED CONTROL - THE VARIABLE SPEED DRIVES ON THE RETURN FAN SYSTEM SHALL BE MODULATED BY A PLENUM-MOUNTED STATIC PRESSURE SENSOR LOCATED IN THE RETURN FAN DUCTWORK PLenum AND A PROPORTIONAL PLUS INTEGRAL CONTROL SIGNAL SHALL PROVIDE A MANUAL THRU THE VFD TO ADJUST THE MOTOR SPEED TO MAINTAIN SETPOINT.
5. N. SUPPLY AIR TEMPERATURE SET POINT AND RESET
- IF THE AIR HANDLING UNIT COMPONENTS SHALL BE SEQUENCED TO PROVIDE A SUPPLY AIR TEMPERATURE OF 55 DEGS F DURING "WARM-UP" CYCLES, AND 56 DEGS F DURING "COOLING" CYCLES, AND 57 DEGS F DURING "MODE" - THE SUPPLY AIR TEMPERATURE SET POINT SHALL BE 56 DEGS F EXCEPT REACTIVE AS FOLLOWS:
- A. SUPPLY AIR TEMPERATURE RESET BASED ON ZONE TEMPERATURE: PULL ALL ZONES ASSOCIATED WITH THIS AIR HANDLING UNIT EVERY 15 MINUTES AND THE ZONE FURTHEST FROM ITS COOLING SETPOINT SHALL COVER. AS THE FAN ZONE'S COOLING DEVIATION FROM ITS COOLING SETPOINT DECREASES, THE SUPPLY AIR TEMPERATURE SHALL INCREASE. AS THE FAN ZONE'S COOLING DEVIATION FROM ITS COOLING SETPOINT INCREASES, THE SUPPLY AIR SET POINT SHALL RESET TO THE UPPER LIMIT OF 60 DEG F. AUTOMATICALLY DETECT THOSE ZONES THAT MAY BE EXCESSIVELY DRIVING THE RESET AND INCREASE THE SUPPLY AIR TEMPERATURE SET POINT TO 57 DEGS F. THE SUPPLY AIR TEMPERATURE SHALL BE 56 DEGS F FOR ALL OTHER ZONES.
- IF RETURN AIR RELATIVE HUMIDITY RISES ABOVE 55 PERCENT RH IN THE RESET SCHEDULE, THE RESET SHALL BE DEACTIVATED. AFTER 60 MINUTES, RE-ACTIVATE RESET SCHEDULE IF BUILDING RH FALLS BELOW 55 PERCENT. PROVIDE RETURN Duct RH SENSOR FOR MONITORING AND RESET CONTROL.
6. PREHEAT CONTROL
1. HOT WATER PREHEAT COIL - IF THE AHU FAN SYSTEM IS 'ON' AND CHILLED WATER VALVE IS CLOSED AND ECONOMIZER IS 'OFF' AND THE AHU SUPPLY AIR TEMPERATURE FALLS 2 DEGREES BELOW SETPOINT, THE HOT WATER PREHEAT COIL CONTROL VALVE SHALL MODULATE TO MAINTAIN THE SUPPLY AIR AT 2 DEGREES ABOVE SETPOINT. THE SETPOINT SHALL BE 55 DEGS F. THE HOT WATER PREHEAT COIL VALVE SHALL MODULATE TO MAINTAIN THE SUPPLY AIR AT 2 DEGREES ABOVE SETPOINT. THE SETPOINT SHALL BE 55 DEGS F.
2. CHILLED WATER PREHEAT COIL - IF THE AHU FAN SYSTEM IS 'ON' AND THE ECONOMIZER IS ACTIVE AND AT 100 PERCENT (OUTSIDE AIR DAMPERS FULL OPEN) AND THE AHU SUPPLY AIR TEMPERATURE IS ABOVE SET POINT, MODULATE THE CHILLED WATER VALVE OPEN TO MAINTAIN THE SUPPLY AIR SET POINT. IF THE AHU FAN SYSTEM IS 'OFF' AND THE ECONOMIZER IS ACTIVE AND AT 100 PERCENT (OUTSIDE AIR DAMPERS FULL OPEN) AND THE AHU SUPPLY AIR TEMPERATURE IS ABOVE SET POINT, MODULATE THE HOT WATER PREHEAT COILS TO MAINTAIN THE SUPPLY AIR SET POINT. THE CHILLED WATER VALVE SHALL BE CLOSED ANY TIME THE AHU FAN SYSTEM IS 'OFF' FOR ANY REASON.
3. ZONE HOT WATER PREHEAT COILS - HOT WATER CONTROL VALVES WILL MODULATE TO MAINTAIN SPACE TEMPERATURE WITH A MINIMUM SUPPLY TEMPERATURE OF 120 DEGS F (EXCEEDS MAXIMUM AVAILABLE TEMPERATURE ADJUSTABLE).
7. AIR FILTER MONITORING
1. THE BAS SYSTEM SHALL MONITOR THE DIFFERENTIAL PRESSURE ACROSS EACH FILTER BANK. WHEN THE FILTER BANK PRESSURE DROP EXCEEDS THE BAS SPECIFIED FILTER LOAD LIMIT (GENERATE AN ALARM TO THE BAS).

Professional Engineer Seal for Ehren E. Lohrmann, State of Indiana, No. PE10911293, dated 10/1/2012.

ATC DIAGRAMS

M602

[illegible][illegible]

OFF FULL OPEN, RESET THE SUPPLY CURT TARGET PRESSURE SETPOINT DOWNWARD 0.5 TO 1.0, EVERY 10 MINUTES UNTIL AT LEAST ONE VAV BOX DAMPER IS 85 PERCENT FULL OPEN. MAY BOX DAMPERS WILL BE 100 PERCENT FULL OPEN. REVERSE THE SEQUENCE: RESET THE STATIC SETPOINT TO 0.85 PERCENT FULL OPEN, THEN CLOSE DAMPERS AS NEARLY AS POSSIBLE TO 0.5 FULL OPEN. REVERSE THE SEQUENCE: RESET THE STATIC SETPOINT TO 0.5 PERCENT FULL OPEN, THEN CLOSE DAMPERS AS NEARLY AS POSSIBLE TO 0.25 PERCENT FULL OPEN. THE SUPPLY CURT TARGET PRESSURE SHALL BE 1.20 W.C. AUTOMATICALLY DETECT THOSE ZONES THAT MAY BE EXCESSIVELY DURING THE RESET LOGIC AND GENERATE AN ALARM TO THE SYSTEM OPERATOR. REACTIVELY ALLOW OPERATOR REMOVAL OF ZONES) FROM THE RESET ALGORITHM.

TURN FAN SYSTEM CONTROL ON.

THE RETURN FAN SYSTEM CONSISTS OF AN ARRAY OF 2 FANS AND ASSOCIATED 2 SPEEDS (1 FAN PER FLOOR). REFER TO 23.05.4 ADJUSTABLE FREQUENCY MOTOR CONTROL.

MANUAL "HAND-AUTO" SWITCH ON THE FACE OF EACH VAV UNIT SELECTS MODE OF OPERATION WHEN THE SELECTOR SWITCH IS INDEXED TO THE "OFF" POSITION, THE ASSOCIATED FAN SYSTEM SHALL STOP. WHEN THE SELECTOR SWITCH IS INDEXED TO THE "ON" POSITION AND ALL PASSENGER AND ALL SERVICE ARE NORMAL, THE FAN SYSTEM SHALL BE AUTOMATICALLY STARTED. WHEN THE SELECTOR SWITCH IS INDEXED TO THE "AUTO" POSITION AND ALL PASSENGER AND ALL SERVICE ARE NORMAL, THE BAS SHALL START AND STOP THE ASSOCIATED FAN SYSTEM.

MANUAL "MANUAL-AUTO" SWITCH CONTROL PAD FEATURE (ON THE FACE OF EACH VAV UNIT) SHALL PROVIDE CONTROL SIGNAL SOURCE FOR MOTOR SPEED. WHEN THE SELECTOR SWITCH IS INDEXED TO THE "OFF" POSITION, THE MANUAL SPEED ADJUSTOR OF THE BAS SHALL PROVIDE THE CONTROL SIGNAL FOR MOTOR SPEED. WHEN THE MOTOR IS ENABLED AND IS INDEXED TO THE "AUTO" POSITION, THE BAS SHALL PROVIDE A PROPORTIONAL PLUS INTEGRAL CONTROL SIGNAL TO MODULATE MOTOR SPEED TO MAINTAIN SETPOINT.

THE RETURN FAN SYSTEM SHALL BE AUTOMATICALLY DRIVEN ON THE RETURN FAN SYSTEM SHALL BE MODULATED BY A PLENUM-MOUNTED STATIC PRESSURE SENSOR LOCATED IN THE RETURN FAN DISCHARGE PLENUM, AND A PROPORTIONAL PLUS INTEGRAL CONTROL SHALL PROVIDE A SIGNAL THRU THE BAS TO THE SUPPLY AIR TEMPERATURE SETPOINT TO MAINTAIN A DISCHARGE AIR PLENUM SETPOINT OF 10.5 DEG F. (ADJUSTABLE).

PPLY AIR TEMPERATURE SETPOINT CONTROL AND RESET:

THE AIR HANDLING UNIT COMPONENTS SHALL BE SEQUENCED TO PROVIDE A SUPPLY AIR TEMPERATURE SETPOINT OF 10.5 DEG F. DURING "WARM-UP" CYCLES, AND 5.0 DEG F. DURING "COOLING" CYCLES. THE SEQUENCE OF THE SUPPLY AIR TEMPERATURE SETPOINT SHALL BE AS FOLLOWS:

A. SUPPLY AIR TEMPERATURE RESET BASED ON ZONE TEMPERATURE: PULL ALL ZONES ASSOCIATED WITH THIS AIR HANDLING UNIT EVERY 15 MINUTES AND THE ZONE FURTHEST FROM ITS COOLING SETPOINT SHALL GOVERN, AS THE WORST-CASE ZONE DEVIATION FROM ITS COOLING SETPOINT DECREASES, THE ZONE FURTHEST FROM ITS COOLING SETPOINT SHALL GOVERN. THE SUPPLY AIR TEMPERATURE SETPOINT SHALL BE ADJUSTED TO 10.5 DEG F. DURING "WARM-UP" CYCLES. THE SUPPLY AIR TEMPERATURE SETPOINT SHALL BE RESET TO THE UPPER LIMIT OF 60.0 DEG F. AUTOMATICALLY DETECT THOSE ZONES THAT MAY BE EXCESSIVELY DURING THE RESET LOGIC AND GENERATE AN ALARM TO THE SYSTEM OPERATOR. REACTIVELY ALLOW OPERATOR REMOVAL OF ZONES) FROM THE RESET ALGORITHM.

THE SUPPLY AIR TEMPERATURE SETPOINT SHALL BE RESET TO THE UPPER LIMIT OF 60.0 DEG F. AUTOMATICALLY DETECT THOSE ZONES THAT MAY BE EXCESSIVELY DURING THE RESET LOGIC AND GENERATE AN ALARM TO THE SYSTEM OPERATOR. REACTIVELY ALLOW OPERATOR REMOVAL OF ZONES) FROM THE RESET ALGORITHM.

SCHEDULE #1 BUILDING RUL FALLS BELOW 55 PERCENT. PROVIDE RETURN DUCT RH SENSOR FOR MONITORING AND RESET CONTROL.

DEHAT COOLING RUL:


IF THE AHU FAN SYSTEM IS "ON" AND CHILLED WATER VALVE IS CLOSED AND ECONOMIZER IS "OFF" AND THE AHU SUPPLY AIR TEMPERATURE FALLS 2 DEGREES BELOW SETPOINT, THE HOT WATER PREHEAT COIL CONTROL VALVE SHALL MODULATE TO MAINTAIN THE SUPPLY AIR AT 2 DEGREES BELOW SETPOINT. WHEN THE AHU FAN SYSTEM IS "OFF" UNDER NORMAL OPERATION, A TEMPERATURE SENSOR IN THE COIL LEAVING WATER VALVE SHALL BE USED TO MAINTAIN THE 55 DEG F COIL LEAVING WATER SETPOINT, IF THE UNIT SHUTS DOWN ON FREEZE/STAT THE VALVE SHALL GO FULL OPEN TO THE COIL.

CHILLED WATER VALVE CONTROL:

CHILLED WATER COIL - IF THE AHU FAN SYSTEM IS "ON" AND THE ECONOMIZER IS ACTIVE AND AT 100 PERCENT (SHUTS AIR DAMPERS FULL OPEN) AND THE AHU SUPPLY AIR TEMPERATURE IS ABOVE SET POINT, MODULATE THE CHILLED WATER VALVE OPEN TO MAINTAIN THE SUPPLY AIR SET POINT. IF THE AHU FAN SYSTEM IS "OFF" UNDER NORMAL OPERATION, THE CHILLED WATER VALVE SHALL BE CLOSED ANY TIME THE AHU FAN SYSTEM IS "OFF" FOR ANY REASON.

FILTER MONITORING

THE SYSTEM SHALL MONITOR THE DIFFERENTIAL PRESSURE ACROSS EACH FILTER BANK. WHEN THE FILTER BANK PRESSURE DROP EXCEEDS THE MANUFACTURER'S FILTER LOAD LIMIT GENERATE AN ALARM TO THE BAS.



A. AIR HANDLING UNIT AHU-3

A.1. SYSTEM DESCRIPTION: THE AIR HANDLING SYSTEM SHALL CONSIST OF A SUPPLY FAN WITH VFD AND AIRFLOW MEASURING STATIONS, RETURN FAN WITH VFD AND AIRFLOW MEASURING STATIONS, MIXING BOX WITH RETURN AIR DAMPERS AND OUTSIDE AIR DAMPERS, RELIEF AIR DAMPERS, PREFILTERS, FINAL FILTERS, PREHEAT COIL, COOLING COIL, AND REHEAT COIL. REFER TO THE DRAWINGS FOR DETAILS.

B. SYSTEM EMISSIONS AND CONDITIONS:

1. REFER TO PARAGRAPH 3.1 FOR DEFINITIONS OF "OCCUPIED," "UNOCCUPIED," "MORNING WARM UP," AND "OVERMODE" MODES.

2. THE "OCCUPIED" MODE OPERATION FOR THIS AIR HANDLING SYSTEM SHALL BE AS DEFINED IN PARAGRAPH 3.1. VERIFY AND COORDINATE TIME OF DAY SCHEDULING WITH OWNER'S SCHEDULE. THE "TEMPERATURE CONTROLS" SHALL FUNCTION AS SPECIFIED. REFER TO BELOW FOR "UNOCCUPIED" MODE AND "OVERMODE" MODE.

3. WHEN A ZONE THERMOSTAT OVERRIDE BUTTON IS ENERGIZED, THE AIR HANDLING SYSTEM SHALL BE ENABLED TO RUN IN THE "OCCUPIED" MODE FOR THE DURATION OF THE OVERRIDE.

4. PROVIDE START-STOP INTERLOCK BETWEEN SUPPLY AND RETURN FANS. SCHEDULE EXHAUST FANS EF-1 AND EF-2 TO RUN WHEN THE AHU IS IN THE "OCCUPIED" NIGHT SETPOINT HEATING MODE.

C. "UNOCCUPIED" NIGHT SETPOINT HEATING MODE:

1. WHEN THE AIR HANDLING UNIT IS IN THE "UNOCCUPIED" MODE AND ANY ZONE TEMPERATURE FALLS 3 DEGREES BELOW THE ZONE "UNOCCUPIED" HEATING SETPOINT (REFER TO PARAGRAPH 3.3 ABOVE), THE AIR HANDLING UNIT SYSTEM SHALL OPEN, EXCEPT THAT THE OUTSIDE AIR DAMPERS SHALL REMAIN CLOSED AND THE INTERLOCKED EXHAUST FANS SHALL REMAIN CLOSED. WHEN ALL ZONE TEMPERATURES ARE AT OR ABOVE THEIR ZONE "UNOCCUPIED" HEATING SETPOINT, THE AIR HANDLING UNIT SHALL SHUT DOWN AND GO INTO A FULL STOP MODE.

2. "UNOCCUPIED" NIGHT SETPOINT COOL-DOWN MODE:

1. WHEN THE AIR HANDLING UNIT IS IN THE "UNOCCUPIED" MODE AND ANY ZONE TEMPERATURE RISES 3 DEGREES ABOVE THE ZONE "UNOCCUPIED" COOLING SETPOINT, REFER TO PARAGRAPH 3.3 ABOVE, THE AIR HANDLING UNIT SHALL OPEN, EXCEPT THAT THE OUTSIDE AIR DAMPERS SHALL REMAIN CLOSED, EXCEPT THAT AND THE INTERLOCKED GENERAL EXHAUST FANS SHALL REMAIN OPEN. PROVIDE WALL MOUNTED BURNER SENSOR AS SHOWN ON DRAWINGS.

2. DURING COOL-DOWN, OUTSIDE AIR SHALL BE USED FOR COOLING FIRST UNLESS THE ECONOMIZER IS LOCKED OUT. IF THE ECONOMIZER IS INACTIVE, THE ASSOCIATED RELIEF SHALL REMAIN OPEN, AND OUTSIDE AIR DAMPERS SHALL REMAIN CLOSED, AND CALLED WATER SYSTEM SHALL BE MADE AVAILABLE. WHEN ALL ZONE TEMPERATURES ARE AT OR BELOW THEIR ZONE "UNOCCUPIED" COOLING SETPOINT THE AIR HANDLING SYSTEM SHALL CYCLE OFF.

D. ADAPTIVE OPTIMAL START

1. THE START PROGRAM SHALL START THE UNIT IN ADVANCE OF THE SCHEDULED "OCCUPIED" TIME TO ENSURE PROPER SPACE TEMPERATURES AT OCCUPANCY TIME. REFER TO PARAGRAPH 3.2 ABOVE. THE CONTROL LEARNING ALGORITHM AT A MINIMUM SHALL BE A FUNCTION OF THE DIFFERENCE BETWEEN ZONE TEMPERATURES AND OCCUPIED SET POINTS AND THE AMOUNT OF TIME PRIOR TO SCHEDULED OCCUPANCY. THE ALGORITHM SHALL ADJUST START TIMES BASED ON PAST HISTORIES AND TIMES TO OBTAIN OCCUPIED SETPOINTS AT SIMILAR OUTSIDE AIR TEMPERATURES.

2. DURING OPTIMAL START, THE OUTSIDE AIR DAMPERS SHALL BE USED TO PREHEAT THE RETURN AIR DAMPERS FULL OPEN, RELIEF DAMPERS FULL CLOSED, AND ASSOCIATED GENERAL EXHAUST FANS OFF. HOT WATER SHALL BE MADE AVAILABLE. THIS MODE SHALL CONTINUE UNTIL THE EXTERIOR ZONES (ONLY) REACH THEIR "OCCUPIED" HEATING SETPOINTS. IF THE SYSTEM IS STILL IN ITS WARMUP CYCLE 30 MINUTES AFTER THE EXTERIOR ZONES REACH OCCUPIED SETPOINTS, THE ECONOMIZER SHALL BE POSITIONED TO MINIMUM AND THE RESPECTIVE EXHAUST FANS SHALL BE ENABLED. ECONOMIZER DAMPER CONTROL SHALL BE DELAYED TWO MINUTES DURING START-UP TO PREVENT CABINET HEAT FROM FALSE LOADING THE SYSTEM.

3. DURING OPTIMAL START, THE OUTSIDE AIR DAMPERS SHALL BE USED TO PRECOOL THE RETURN AIR DAMPERS FULL OPEN, RELIEF DAMPERS FULL OPEN, ECONOMIZER IS INACTIVE, THE ASSOCIATED RELIEF AND OUTSIDE AIR DAMPERS SHALL REMAIN CLOSED, AND CHILLED WATER SYSTEM SHALL BE MADE AVAILABLE. THIS MODE SHALL CONTINUE UNTIL ALL ZONES REACH THEIR "OCCUPIED" COOLING SETPOINTS. IF THE SYSTEM IS STILL IN ITS COOL-DOWN CYCLE 30 MINUTES AFTER THE SCHEDULED START TIME, AND THE COOL-DOWN CYCLE AND ALARM HAS BEEN DEACTIVATED, THE SYSTEM SHALL BE POSITIONED TO COOLING SETPOINT. WHEN THE COOL-DOWN CYCLE ENDS, THE ECONOMIZER DAMPERS SHALL BE POSITIONED TO MINIMUM AND THE RESPECTIVE EXHAUST FANS SHALL BE ENABLED.

F. SAFETIES:

THE FOLLOWING SAFETIES SHALL BE PROVIDED TO STOP THE AIR HANDLING UNIT SYSTEM AND POSITION ASSOCIATED CONTROL DEVICES TO THEIR "SAFE" POSITION: 1. OUTSIDE AND RELIEF DAMPERS CLOSED, RETURN DAMPERS OPEN, HEATING VALVES OPEN AND HUMIDIFIER VALVES CLOSED. SAFETIES SHALL BE WIRED INTO THE FAN STARTER CIRCUIT SUCH THAT THE SAFETY SHALL FUNCTION WHEN THE STARTER SELECTOR SWITCH IS IN THE HAND ON OR AUTO POSITION, AND WHEN EITHER OF THE FOLLOWING OCCURS:

A. LOW TEMPERATURE LIMIT CUTOFF "FREEZE/STATS" AUTO RESET TYPE WITH REMOTE MANUAL RESET. SELECTOR SWITCH IS PROVIDED AND INSTALLED ON THE LEAVING AIR FACE OF THE FIRST COIL, IN THE AIR STREAM (UNLESS OTHERWISE NOTED) AND SHALL STOP THE AIR HANDLING UNIT SYSTEM IF A LOW TEMPERATURE BELOW 38 DEG F IS DETECTED. REFER TO DETAILED INSTALLATION REQUIREMENTS IN 23.02.95 INSTRUMENTATION AND CONTROL DEVICES FOR HVAC.

UNIT SMOKE DETECTORS—UPON SENSING SMOKE OR PRODUCTS OF COMBUSTION THE AIR HANDLING SYSTEM SHALL BE DISABLED. SMOKE DETECTORS SHALL BE PROVIDED PER DIVISION 28 UNLESS OTHERWISE NOTED. INSTALLED IN THE RETURN DUCT SYSTEM AND WIRED TO THE FAN SAFETY CIRCUITS TO STOP THE FAN. THE FAN SHALL BE STOPPED IMMEDIATELY UPON SMOKE DETECTION. REVIEW THE DRAWINGS FOR DETECTOR LOCATIONS AND COORDINATE THEIR INSTALLATION.

3. SUPPLY DUCT HIGH STATIC PRESSURE OUTGO—PROVIDE A MANUALLY RESET TYPE DUCT STATIC PRESSURE SWITCH, SET AT THE MAXIMUM WORKING STATIC PRESSURE OF THE SUPPLY DUCT. THE SWITCH SHALL BE INSTALLED IN THE SUPPLY DUCT DOWNSTREAM OF THE FAN, AS SHOWN IN SECTION 20.04.00.

4. RETURN DUCT HIGH NEGATIVE PRESSURE OUTGO—PROVIDE A MANUAL RESET TYPE DUCT STATIC PRESSURE SWITCH, SET AT THE MAXIMUM NEGATIVE WORKING PRESSURE OF THE RETURN DUCT, TO STOP THE FAN SYSTEM. SUPPLY RETURN EXHAUST ON A FALL IN DUCT STATIC BELOW SETPOINT.

5. RETURN AIR DAMPER—THE RETURN AIR DAMPER SHALL BE INSTALLED IN THE RETURN AIR DUCT, AS SHOWN IN SECTION 20.04.00, SET AT THE MAXIMUM NEGATIVE WORKING PRESSURE OF THE DUCT, TO STOP THE AHU FAN SYSTEM ON A FALL IN DUCT STATIC BELOW SETPOINT.

MINIMUM OUTSIDE AIR CONTROL

1. PROVIDE A MANUAL OPERATION OF OUTSIDE AIR, RELIEF AIR AND RETURN AIR DAMPERS (ECONOMIZER DAMPERS) TO PROVIDE MINIMUM OUTSIDE AIR FOR VENTILATION. THE PHRASE "MINIMUM IN THE SEQUENCES OF OPERATION SHALL INCLUDE THIS PARAGRAPH."

PERCENTUAL ENTHALPY ECONOMIZER CONTROL

1. DURING "OCCUPIED" MODE OR "COOL-DOWN" MODE, OUTSIDE AIR TEMPERATURE AND HUMIDITY, AND RETURN AIR TEMPERATURE AND HUMIDITY SHALL BE MONITORED TO DETERMINE IF THE ENTHALPY OF THE OUTSIDE AIR IS LESS THAN THE ENTHALPHY OF THE RETURN AIR. THE ECONOMIZER SHALL BE ENABLED WHEN THE OUTSIDE AIR ENTHALPY IS HIGHER THAN THE RETURN AIR ENTHALPY, OR WHEN THE OUTSIDE AIR TEMPERATURE IS GREATER THAN 75°F. IF THE ECONOMIZER SHALL BE DISABLED.

2. DURING "OCCUPIED" MODE, OUTSIDE AIR SHALL BE PROVIDED. THE RETURN AIR DAMPERS SHALL OPEN FULLY AND RETURN AIR DAMPERS SHALL REMAIN CLOSED. THIS CONDITION IS THE NORMAL POSITION AND SHALL BE MAINTAINED DURING THE "OCCUPIED" MODE EXCEPT DURING THE "ECONOMIZER" CYCLE. DURING THE "ECONOMIZER" CYCLE, THE AMOUNT OF OUTSIDE AIR AND RELIEF AIR SHALL BE INCREASED AS REQUIRED TO MAINTAIN THE ROOM TEMPERATURE AND HUMIDITY AT THE DESIGN SETPOINT. THE ECONOMIZER SHALL BE ADJUSTED TO PREVENT THE RETURN AIR DAMPERS FROM OPENING OF THE OUTSIDE AIR DAMPERS. IF THE MIXED AIR TEMPERATURE FALLS BELOW 55°F FOR 10 MINUTES AND THE OUTSIDE AIR DAMPERS ARE AT MINIMUM POSITION, ECONOMIZER SHALL BE CONSIDERED "INACTIVE." ALL CONTROL SEVENTS SHALL BE FULLY ADJUSTABLE TO MEET JOB CONDITIONS.

3. THE ECONOMIZER MODE SHALL BE AVOIDED TWO MINUTES DURING START-UP TO PREVENT CABINET HEAT FROM FLOOD LOADING THE SYSTEM.

4. MINIMUM AIR DAMPER CONTROL

1. WHEN THE SUPPLY AIR FAN IS OFF FOR ANY REASON OR THE UNIT IS OPERATING IN THE "UNOCCUPIED" MODE, WARM-UP MODE, OR COOL-DOWN MODE, THE OUTSIDE AIR DAMPERS SHALL BE CLOSED UNLESS ECONOMIZER IS ENABLED.

2. RETURN AIR DAMPER CONTROL

1. THE RETURN AIR DAMPER SHALL MODULATE INVERSELY TO THE OUTDOOR AIR FLOW WHEN THE ECONOMIZER MODE IS ENABLED. WHEN THE ECONOMIZER MODE IS DISABLED THE RETURN DAMPER SHALL BE FULLY OPEN. PROVIDE INTERLOCK SO THAT THE RETURN AIR DAMPERS AND OUTSIDE AIR DAMPERS CANNOT BE OPENED AT THE SAME TIME. UNDER NORMAL OPERATION, SUPPLY AIR OR EXHAUST OUTSIDE AIR SHALL BE OPENED.

2. RELIEF AIR AIR DAMPER CONTROL

1. THE RELIEF AIR AIR DAMPER ON THE AIR HANDLING UNIT IN THE ECONOMIZER SECTION DOWNSTREAM OF THE RETURN AIR DAMPER SHALL BE OPPOSED BLADE TYPE. IT SHALL BE CONTROLLED BY THE SAME LINE UNDER NORMAL OPERATION, SUPPLY AIR OR EXHAUST OUTSIDE AIR SHALL BE OPENED.

2. PRESSURE OF ± 0.05 "W.C." AT THAT LOCATION. REFERRED TO OUTDOORS. REFER TO DRAWINGS FOR SENSOR LOCATION.

PRV/FAN SYSTEM CONTROL

1. THE SYSTEMS OF AN ARRAY OF 2 FANS AND ASSOCIATED 2 VFD'S (1 FAN PER VFD). REFER TO 20.5 14 ADJUSTABLE FREQUENCY MOTOR CONTROLS FOR VFD REQUIREMENTS.

2. A MANUAL "HAND-OFF-AUTOMATIC" SWITCH ON THE FACE OF EACH VFD SHALL SELECT MODE OF OPERATION. WHEN THE SELECTOR SWITCH IS INDEXED TO THE "OFF" POSITION, THE MOTOR SHALL BE STOPPED IMMEDIATELY. WHEN THE SELECTOR SWITCH IS INDEXED TO THE "ON" POSITION, ALL SAFESIES ARE NORMALLY SET. WHEN THE SELECTOR SWITCH IS INDEXED TO THE "MANUAL" POSITION, THE FAN SHALL BE MODULATED. WHEN THE SELECTOR SWITCH IS INDEXED TO THE "ASSOCIATED FAN SYSTEM" SHALL START AND RUN CONTINUOUSLY WHEN THE SELECTOR SWITCH IS INDEXED TO THE "AUTO" POSITION AND ALL SAFESIES ARE NORMAL. THE BAS SHALL START AND STOP THE ASSOCIATED FAN SYSTEM.

3. A MANUAL "MANUAL-AUTOMATIC" SWITCH CONTROL FAN FEATURE ON THE FACE OF EACH VFD SHALL SELECT CONTROL. SIGNAL, SOURCE FOR MOTOR SPEED. WHEN THE SELECTOR SWITCH IS INDEXED TO THE "MANUAL" POSITION, MANUAL SPEED ADJUSTOR OF THE VFD SHALL PROVIDE THE CONTROL SIGNAL FOR MOTOR SPEED. WHEN THE MOTOR IS ENABLED AND IS INDEXED TO THE "AUTO" POSITION, THE BAS SHALL PROVIDE A PROPORTIONAL PLUS INTEGRAL CONTROL SIGNAL TO MODULATE MOTOR SPEED TO MAINTAIN THE SUPPLY AIR STATIC PRESSURE SETPOINT.

4. FAN SPEED MINIMUM SHALL BE MAINTAINED AT ALL TIMES. THE FAN SPEED MINIMUM SHALL BE BALANCED TO MAINTAIN THE FAN SYSTEM AT 50% OF THE DESIGN MAXIMUM COOLING CFM. WHEN THE SYSTEM IS OPERATING IN THE HEATING-COOLING DEAD BAND THE FAN SPEED SHALL BE AT MINIMUM. DURING THE HEATING MODE, THE FAN SHALL REMAIN AT MINIMUM SPEED UNTIL THE HEATING RESETH HAS REACHED ITS MAXIMUM SETPOINT. DURING THE COOLING MODE, THE FAN SHALL BE MAINTAINED AT MINIMUM SPEED UNTIL THE COOLING RESETH HAS REACHED ITS MAXIMUM SETPOINT. PER MINUTE UNTIL THE ROOM HEATING SET POINT IS SATISFIED OR 100% SPEED AS REACHED. AS THE ROOM TEMPERATURE RISES ABOVE THE

HEATING SET POINT THE SEQUENCE WILL REVERSE IN ORDER DURING THE COOLING MODE. THE SUPPLY FAN SHALL RAMP UP FROM MINIMUM TO THE DESIGN MAXIMUM CFM WHEN THE ECONOMIZER IS ACTIVE BEFORE THE COOLING VALVE OPENS. IF THE ECONOMIZER IS NOT ACTIVE THE COOLING VALVE WILL LEAD TO BURNER SHUT DOWN. WHEN THE COOLING VALVE OPENS, THE SUPPLY FAN SHALL RAMP UP TO THE DESIGN MAXIMUM CFM. WHEN THE COOLING VALVE CLOSURE, THE FAN SPEED SHALL BE RAMPED UP UNTIL THE ROOM TEMPERATURE SET POINT HAS BEEN REACHED OR 100% SPEED AS REACHED. ON A FALL OF THE ROOM TEMPERATURE SET POINT THE SEQUENCE HAS REVERSE IN ORDER.

M. RETURN FAN SYSTEM CONTROL

1. THE RETURN FAN SYSTEM CONSISTS OF AN ARRAY OF 2 FANS AND ASSOCIATED 2 VFD'S (1 PER FAN). REFER TO 2305 14 ADJUSTABLE FREQUENCY MOTOR CONTROLLERS FOR VFD REQUIREMENTS.
2. THE RETURN FAN SYSTEM OPERATES ON THE FACE OF EACH VFD SHALL SELECT MODE OPERATION WHEN THE SELECTOR SWITCH IS INDEXED TO THE 'ON' POSITION. THE ASSOCIATED FAN SYSTEM SHALL STOP WHEN THE SELECTOR SWITCH IS INDEXED TO THE 'ON' POSITION AND ALL SAFETIES ARE NORMAL. THE ASSOCIATED FAN SYSTEM SHALL START AND RUN CONTINUOUSLY WHEN THE SELECTOR SWITCH IS INDEXED TO THE 'AUTO' POSITION AND ALL SAFETIES ARE NORMAL.
3. A MANUAL 'MANUAL-AUTO' SWITCH (CONTROL PAD FEATURE) ON THE FACE OF EACH VFD SHALL SELECT CONTROL. SIGNAL SOURCE FOR MOTOR SPEED WHEN THE RETURN IS ENABLED AND IS INDEXED TO THE 'MANUAL' POSITION. THE MANUAL SPEED ADJUSTOR OF THE VFD SHALL PROVIDE THE CONTROL SIGNAL FOR THE MOTOR SPEED. WHEN THE SWITCH IS INDEXED TO THE 'AUTO' POSITION, THE BAS SHALL PROVIDE A PROPORTIONAL PLUS INTEGRAL CONTROL SIGNAL TO MODULATE MOTOR SPEED TO MAINTAIN SETPOINT.
4. THE RETURN FAN SYSTEM SPEED CONTROL - THE VARIABLE SPEED DRIVES ON THE RETURN FAN SYSTEM SHALL BE MODULATED BY A PLENUM MODULATED STATIC PRESSURE CONTROL. THE CONTROL LOGIC SHALL BE SUCH THAT THE PLENUM MODULATOR SHALL PROVIDE A PROPORTIONAL PLUS INTEGRAL CONTROL SIGNAL TO THE BAS TO MODULATE THE RETURN FAN SYSTEM VFD SPEEDS TO MAINTAIN A DISCHARGE AIR PLENUM SET POINT OF +0.15 "W.C. (ADJUSTABLE).

N. SUPPLY AIR TEMPERATURE SET POINT AND RESET

THE SUPPLY AIR TEMPERATURE SET POINT SHALL BE SEQUENCED TO PROVIDE A SUPPLY AIR TEMPERATURE OF 55 DEG (DURING "WARM-UP" CYCLES, AND 53 DEG DURING "COOL DOWN CYCLES DURING "OCCUPIED" MODE. THE SUPPLY AIR TEMPERATURE SET POINT SHALL BE 53 DEG EXCEPT AS FOLLOWS

- A. SUPPLY AIR TEMPERATURE RESET BASED ON ZONE TEMPERATURE: POLL ALL ZONES ASSOCIATED WITH THIS AIR HANDLING UNIT EVERY 15 MINUTES AND DETERMINE THE "HIGHEST" FROM THE ZONE TEMPERATURES. THE SUPPLY AIR TEMPERATURE SET POINT SHALL BE 53 DEGS FOR ZONES WITH A TEMPERATURE DISCHARGE AIR SHALL BE RESET UPWARDS TOWARD 60 DEGS IF ALL ZONES ARE IN HEATING AND/OR IN DEAD BAND. THE SUPPLY AIR SET POINT SHALL BE RESET TO THE UPPER LIMIT OF 60 DEGS IF AUTOMATICALLY DETECT THOSE ZONES THAT MAY BE EXCESSIVELY DRIVING THE RESET LOGIC. GENERATE AN ALARM TO THE SYSTEM WHEN THE SUPPLY AIR TEMPERATURE SET POINT IS RESET TO 60 DEGS. THE RESET LOGIC SHALL BE SCHEDULED TO REACTIVATE RESET SCHEDULE IF BUILDING RH FALLS BELOW 55 PERCENT. PROVIDE RETURN DUTY RH SENSOR FOR MONITORING AND RESET CONTROL.

O. PREHEAT COIL CONTROL

1. HOT WATER COIL - IF THE AHU FAN SYSTEM IS 'ON' AND CHILLED WATER VALVE IS CLOSED AND ECONOMIZER IS 'OFF' AND THE AHU SUPPLY AIR TEMPERATURE FALLS 2 DEGREES BELOW SETPOINT, THE 'HOT WATER PREHEAT COIL CONTROL VALVE' SHALL MODULATE TO MAINTAIN THE SUPPLY AIR AT 2 DEGREES BELOW SETPOINT. WHEN THE AHU FAN SYSTEM IS 'OFF' UNDER NORMAL OPERATION, A TEMPERATURE SENSOR ON THE COIL LEAVING WATER SHALL CLOSE THE HOT WATER VALVE TO MAINTAIN TO 55°F COIL LEAVING WATER TEMPERATURE. IF THE UNIT SHUTS DOWN ON FREEZE/STAG THE VALVE SHALL GO FULL OPEN TO THE COIL.

P. COOLING COIL CONTROL

1. HOT WATER COIL - IF THE AHU FAN SYSTEM IS 'ON' AND THE ECONOMIZER IS ACTIVE AND AT 100 PERCENT 'OUTSIDE AIR DAMPERS FULL OPEN' AND THE AHU SUPPLY AIR TEMPERATURE IS ABOVE SET POINT, MODULATE THE CHILLED WATER VALVE OPEN TO MAINTAIN THE SUPPLY AIR SET POINT. IF THE AHU FAN SYSTEM IS 'ON' AND THE ECONOMIZER IS NOT ACTIVE AND THE AHU SUPPLY AIR TEMPERATURE IS ABOVE SET POINT, MODULATE THE CHILLED WATER VALVE TO MAINTAIN THE SUPPLY AIR SET POINT. IF THE AHU FAN SYSTEM IS 'OFF' FOR ANY REASON, THE CHILLED WATER VALVE SHALL BE CLOSED.
2. REHEAT COIL CONTROL - HOT WATER CONTROL VALVE SHALL MODULATE TO MAINTAIN SPACE TEMPERATURE.

R. AIR FILTER MONITORING

THE BAS SYSTEM SHALL MONITOR THE DIFFERENTIAL PRESSURE ACROSS EACH FILTER BANK. WHEN THE FILTER BANK PRESSURE DROP EXCEEDS THE MANUFACTURER'S FILTER LOAD LIMIT, GENERATE AN ALARM TO THE BAS.