

February 26, 2024

DISTRICT WIDE - TRI-CREEK ELEMENTARY SCHOOLS' FINISHES AND LOWELL MIDDLE SCHOOL MEDIA CENTER RENOVATION Lowell, IN 46356

TO: ALL BIDDERS OF RECORD

This Addendum forms a part of and modifies the Bidding Requirements, Contract Forms, Contract Conditions, the Specifications, and the Drawings dated February 9, 2024 by Gibraltar Design. Acknowledge receipt of the Addendum in the space provided on the Bid Form. Failure to do so may subject the Bidder to disqualification.

This Addendum consists of Pages ADD 1-1 and attached Addendum No. 1 from Gibraltar Design dated February 22, 2024 and consisting of 3 pages and 34 drawings.

A. <u>SPECIFICATION SECTION 0 32 00 - SCHEDULES AND REPORTS</u>

1. Replace:

Guideline Schedule with that attached revised Guideline Schedule


Original	Activity Name	Start	Finish						2024					
Duration				oruary	March 26 04 1 18 25	April	May	June		August	September		November	
Тг	i Creek District Wide Elementary & Middle	26-Feb-24	30-May-25								2020001120			
-	Project Administration	26-Feb-24	30-May-25											
	-		-)haaa								
	Bid Phase	26-Feb-24	14-Mar-24	4	1 1	Phase								
	Bid Opening	12-Mar-24	12-Mar-24	_										
	Awards	22-Mar-24	22-Mar-24			vards	Dreesed							
	Notice to Proceed	25-Mar-24	25-Mar-24	_	× N	otice to	Proceed	- O In	441-					
	Procure Submittals	25-Mar-24	03-May-24	-		7 01-			tais					
	Start Construction	15-Apr-24	15-Apr-24	-		× Sta	art Constru	1	00 000 4	0				
	End 2023-2024 School Year	31-May-24	31-May-24	-				End 20	23-2024	School Year				
	Begin 2024-2025 School Year	14-Aug-24	14-Aug-24					-+		× Beć	jin 2024-20	025 Schoo	l year	
	Substantial Completion		21-Mar-25	-										
	Punchlist		18-Apr-25	_										
	Final Completion		30-May-25									1		
	Lowell Middle School	03-Jun-24	08-Jan-25										1	
	Classroom Renovations	11-Jun-24	13-Aug-24							Cla	ssroom R	enovations	5	
	Unit C	20-Jun-24	02-Aug-24				- <u>1</u>			📫 Unit C				
	Demo	20-Jun-24	28-Jun-24	-					Demo					-
	Paint	20-Jun-24 01-Jul-24	20-Jul-24 12-Jul-24	-						aint				
		15-Jul-24	23-Jul-24	-						V Ceilings				
	Ceilings	15-Jui-24	23-JUI-24							Ŭ				
	Flooring	24-Jul-24	02-Aug-24							🖵 Floorin	ġ			
	Unit D	11-Jun-24	12-Jul-24						- U	nit D				
		44 km 04	40 km 04	_					Jomo					
	Demo		19-Jun-24	-					Paint				1 1 1	
	Paint		27-Jun-24	-				1	v raint ∕⊐ Ceili	inge				
	Ceilings		05-Jul-24	-						ooring				
	Flooring	08-Jul-24 01-Jul-24	12-Jul-24				· .			Uni	t F			
	Unit E		13-Aug-24	_						_				
	Demo	01-Jul-24	09-Jul-24	_					De De					
	Paint	10-Jul-24	23-Jul-24	_						Paint				
	Ceilings	24-Jul-24	01-Auq-24	_					4	Ceiling				
	Flooring		13-Auq-24							Floo				
	LGI & Stairwells	10-Jul-24	24-Jul-24							LGI & Stai	rwells			
	Demo	10-Jul-24	11-Jul-24						🖉 De	emo				
	Spray Insulation	12-Jul-24	15-Jul-24						1	Spray Insulat	1		 	-
	Gypsum Board	16-Jul-24	17-Jul-24							Gypsum Bo	ard			
	Paint	18-Jul-24	22-Jul-24							7 Paint		, , ,		
	Acoustical Wall Panels	23-Jul-24	24-Jul-24						2	Acoustica	l Wall Pan	els		
	Media Center	03-Jun-24	08-Jan-25					4						
	Demo	03-Jun-24	10-Jun-24					🟧 Den	no					
	Relocate Media Shelving & Casework		03-Jun-24					Reloc	ate Medi	a Shelving 8	Casewor	ĸ		1
	Lighting		17-Jun-24						ighting					-
	Mechanical		17-Jun-24	T			1 1 1		lechanic	al		 	1	
	Paint		26-Jun-24						7 Paint					
	Ceilinas		10-Jul-24					4	Ce	ilings				
	Flooring	11-Jul-24	17-Jul-24				1 1 1 1			Flooring		1 1 1 1		
	Set Media Shelving & Casework	18-Jul-24	22-Jul-24							7 Set Media	Shelving &	& Casewoi	ĸ	
	Acoustical Wall Panels	18-Jul-24	24-Jul-24	Ι						Acoustica	I Wall Pan	els		
	Markerboards	18-Jul-24	22-Jul-24							7 Markerboa	rds			
	Folding Wall Partitions	02-Jan-25												
											1			

✓ Actual Work
▲ ✓ Remaining Work

Critical Remaining Work

MilestoneSummary

222100.05 Tri Creek District Wide Elementary Middle School Renovations Schedule Update 26-Feb-24 1 of 5



Driginal Activity Name Duration	Start	Finish	2024 uary March April May June July August September October 2 2 1 26 04 1 18 25 01 0 15 22 2 06 13 2 27 03 10 1 24 01 0 15 22 2 05 12 19 2 02 09 1 23 30 0 14 21 28	November December January February Mar 0 11 18 2 02 09 1 23 30 06 1 20 27 0 10 17 2 03 10
Lake Prairie Elementary School	03-Jun-24	08-Jan-25		Lake Prairie Elemen
Unit A	05-Jul-24	08-Jan-25		🗖 Unit A
Demo	08-Aug-24	14-Aug-24	Demo 🗠	
Hand Drvers (Alternate)	15-Aua-24	21-Aua-24	🖾 Hand Dryers (Alternate)
Paint		02-Sep-24	△—> Paint	
Counter Tops (Alternate)		09-Sep-24	Counter Tops (Al	ternate)
Toilet Partitions	03-Sep-24	-	Toilet Partitions	
Cornerquards		09-Sep-24		
LVT	10-Sep-24	16-Sep-24		
Carpet	10-Sep-24	19-Sep-24	Carpet	
Tile	10-Sep-24	16-Sep-24		
Gym	05-Jul-24	08-Jan-25		Gym
Demo	05-Jul-24	11-Jul-24	Demo 🖾	
Relocate Bleachers	12-Jul-24	16-Jul-24	A Relocate Bleachers	
Paint & Wall Coating	17-Jul-24	24-Jul-24	A Paint & Wall Coating	
Acoustical Wall Panels	25-Jul-24	31-Jul-24	Acoustical Wall Panels	
Basketball Equipment (Alternate)	02-Jan-25			Basketball Equipme
Reception Area	23-Dec-24	08-Jan-25		Reception Area
Demo	23-Dec-24	24-Dec-24		Demo
Painting		30-Dec-24		Arr Painting
Reception Desk	31-Dec-24			A Reception Desk
Electric	31-Dec-24			▲ Electric
Counter Tops (Alternate)	31-Dec-24			Counter Tops (Altern
Flooring	02-Jan-25	08-Jan-25		△ Flooring
Media Center	12-Jul-24	25-Jul-24	Media Center	
Relocate Media Shelving	12-Jul-24	12-Jul-24	Relocate Media Shelving	
Demo	15-Jul-24	17-Jul-24	⊿ Demo	
Paint	18-Jul-24	22-Jul-24	AV Paint	
Flooring	23-Jul-24	25-Jul-24	✓ Flooring	
Unit B	18-Jul-24	05-Sep-24	Company Contraction Contraction	
	18-Jul-24	24-Jul-24	△ Demo	
Hand Drvers (Alternate)	25-Jul-24	31-Jul-24	Arrow Hand Dryers (Alternate)	
Paint Bathroom Partitions		12-Aug-24 19-Aug-24	△ Paint △ Bathroom Partitions	
Paint Lockers		19-Aug-24 19-Aug-24	△ Datiloon Partitions	
Cornerguards		19-Aug-24 19-Aug-24	△ Cornerguards	
		26-Aug-24		
Carpet		29-Aug-24	Carpet	
Tile		26-Aug-24	△ Tile	
Counter Tops (Alternate)		05-Sep-24	Counter Tops (Alte	rnate)
Unit C	28-Jun-24	19-Sep-24	□ Unit C	
Demo	25-Jul-24	07-Auq-24	Demo	
Hand Dryers (Alternate)		14-Aug-24	Hand Dryers (Alternate)	
Paint		26-Auq-24	Paint Paint	
Paint Lockers		02-Sep-24	A Paint Lockers	
Bathroom Partitions	27-Aug-24	02-Sep-24	Bathroom Partition	S
 ▲ Actual Work ▲ Milestone ▲ Remaining Work ▲ Summary ▲ Critical Remaining Work 		222	00.05 Tri Creek District Wide Elementary Middle School Renovations Schedule Update 26-Feb-24 2 of 5	

					025		
October November	December	January	February	March	April	May	
30 0 14 21 28 0 11 18 2	02[09] 1[23]		7 0 10 17 2 Prairie Ele	ementary	School	28 0 12 19 2	02 09 16 2 30
		💶 Unit A					
		+					
rs (Alternate)							
		1 1 1					
ter Tops (Alternate)							
Partitions							
erguards							
T							
arpet							
e : :		1					
		🛋 Gym					
anels		1					
		✓ Baske	thall Fou	inmont (A	ltornato)		
	· · · · · · · · · · · · · · · · · · ·		tion Area			L	
		-					
		Demo					
		Painting					
		Reception Reception					
		\sim Counter \sim		(Iternate)			
		Floori		atomatoj			
		1 1 1					
		1 1 1					
		, , ,				 	
		1 1 1					
		1					
		1					
rnate)							
inaco)							
artitions							
rs							
ds							
		; 					
ar Tana (Altarnata)							
er Tops (Alternate)							
nit C							
		1					
(Alternate)		<u>1</u>					
ockers							
om Partitions		1 1 1					
ovations				SKILL	MAN,		
				an			
					NDD -		

Original	Activity Name Start	Finish			2024		
Original Duration			pruary March Apri		June July August September October November	December January	February
	Tile 03-Su	ep-24 16-Sep-24			103 10 1 24 01 0 15 22 2 05 17 19 2 02 09 1 23 30 0 14 21 28 0 11 18 2 ΔΞΞΣ Tile		
		ep-24 10-Sep-24					
		ep-24 12-Sep-2			Carpet		
		ep-24 19-Sep-2			△ Counter Tops (Altern	ate)	
		· ·					
	Student Dining 28-Ju	un-24 25-Jul-24			Student Dining		
	Demo 28-Ju	un-24 04-Jul-24			A⊐ Demo		
	Paint 05-Ju	ul-24 11-Jul-24			A Paint		
	LVT 12-Ju	ul-24 18-Jul-24					
	Acoustical Wall Panels 19-Ju	ul-24 25-Jul-24			Acoustical Wall Panels		
	Exterior 03-Ju	un-24 05-Jul-24			Exterior		
		un-24 05-Jul-24			✓ Paint		
			i i				
	Oak Hill Elementary School 03-Ju	un-24 14-Jan-2					Hill Elem
	Unit A 14-Ju	un-24 23-Jul-24			Concernation of the second sec		
	Demo 14-Ju	un-24 20-Jun-24			∠ Demo		
		un-24 27-Jun-24			Hand Dryers (Alternate)		
		un-24 09-Jul-24			A Paint		
		ul-24 19-Jul-24			Carpet		
	LVT 10-Ju				LVT .		
	Toilet Partitions 10-Ju				▲ Toilet Partitions		
	Counter Tops (Alternate) 17-Ju				Counter Tops (Alternate)		
		un-24 14-Jan-2				🗅 Unit B	в
			i		~		
		un-24 31-Dec-24				Gym & St	udent Di
		un-24 07-Jun-24					
	Electrical 10-Ju	un-24 14-Jun-24			A Electrical		
	Paint & Wall Coating 10-Ju	un-24 21-Jun-24			A Paint & Wall Coating		
	Gym Flooring 24-Ju	un-24 05-Jul-24			Gym Flooring		
	Toilet Partitions and Accessories 08-Ju	ul-24 10-Jul-24			Toilet Partitions and Accessories		
	LVT 08-Ju	ul-24 12-Jul-24			AV LVT		
	Athletic Equipment 08-Ju				AV Athletic Equipment		1
	Acoustical Wall Panels 11-Ju				Acoustical Wall Panels		
		ec-24 31-Dec-2				A Basketbal	II Equipn
		ec-24 14-Jan-2				Rece	ption Are
	Demo 23-D	ec-24 24-Dec-24	1			Demo	
		ec-24 27-Dec-24				Metal Stud	Framing
		ec-24 27-Dec-24				🖉 Counter To	ons (Alter
	Reception Desk 25-D	ec-24 27-Dec-24	•			Reception I	
	Mechanical 30-D	ec-24 01-Jan-2	5			A Mechanic	
	Electrical 30-D	ec-24 01-Jan-2	5			Electrical	
	Drywall and Tape 02-Ja	an-25 06-Jan-2	5			🖾 Drywall	and Tap
	Paint 07-Ja	an-25 09-Jan-2	;			A Paint	
		an-25 14-Jan-2	5			∆⊽ Ceilin	ngs
		un-24 09-Aug-2			△ Unit C		
	Demo 21-Ju	un-24 27-Jun-24			Demo		
		un-24 04-Jul-24			🖾 Calming Room Walls		
		un-24 04-Jul-24			A Hand Dryers (Alternate)		
	Paint 05-Ju				A Paint		
		41 <u>2</u> -7 10-001-24					i
	Actual Work	2:	22100.05 Tri Creek D	istrict Wide	Elementary Middle School Renovations		
	Remaining Work				-		
	Critical Remaining Work			Schedule	Update 26-Feb-24		
	~				3 of 5		0
·							

		-				2025		-		
October 30 0 14 21 2	November 8 0 11 18 2	December	January 30 06 1 20 27	February 7 0 10 17 2	March 03 10 17 2	A 311071	oril 1 21 2	May 28 0 12	/ 191-21	June ly 02 09 16 2 30
)		<u>_</u>					<u> </u>			
		±	 	L				L		
bet		1 1 1								
ounter Top	s (Alterna	ate)		1						-
-	-					 				
						1				
		1		1						
		 # 								
						1 1 1				
els				1						-
0.0		1				1 1 1				
		1	Oak	Hill Elem	entary Sc	hool				
		1 1		1 1 1						1
		' ' 								
ata)		1		1						
ate)										
			💶 🗅 Unit	В						
			Gym & S	Student D	ining					
					ning					
		1				 				
						 				-
essories										
		1 1 1		1		 				
		1 1 1				1 1 1				
			7 Pookoth	oll Equipr	nont					
			Basketba	eption Ar						
		1								
			Demo							
		∠	Metal Stu	d Framin	9					
			Counter T	ops (Alte	rnate)	1 1 1				
		1		1	, , ,	 				
			Reception	n Desk						
			V Mechani	ical				•		
			Electrica							
			🖾 Drywa		be	1 1 1				1 1 1
		1 1 1	A Paint							
		 	AV Ceil	ings		 				
		· · · · · · · · · · · · · · · · · · ·								
						1				
		, , ,								
		1 1 1								
										1
vations										
					SKILL	MAN				
					ап		1			

riginal	Activity Name	Start	Finish		2024			
uration				oruary March April 12 1 26 04 1 18 25 01 0 15 22	May June July August September October 2 06 13 2 27 03 10 1 24 01 0 15 22 2 05 12 19 2 02 09 1 23 30 0 14 21 2	November Decembe		February
	Carpet	17-Jul-24	26-Jul-24					
	LVT	17-Jul-24	23-Jul-24					
	Doors and Hardware	29-Jul-24	02-Auq-24		Doors and Hardware			
	Counter Tops (Alternate)	29-Jul-24	02-Aug-24		△ Counter Tops (Alternate)			
	Toilet Partitions		09-Aug-24		Toilet Partitions			
	Media Center	10-Jun-24	21-Jun-24		Media Center			
	Relocate Media Shelving	10 <u>-</u> lup_24	10-Jun-24		☑ Relocate Media Shelving			
	Demo		13-Jun-24		⊿ Demo			
	Paint		18-Jun-24		∆⊽ Paint			
	Flooring		21-Jun-24		⊿ Flooring			
-	Fhree Creeks Elementary School		14-Jan-25				Three	Creeks
	Unit A	11-Jun-24	23-Jul-24		Commence Unit A			
	Demo		20-Jun-24		Arr Hand Dryers (Alternate)			
	Hand Drvers (Alternate)		27-Jun-24		\sim Paint \sim Paint			
-	Paint	28-Jun-24						
	Carpet	10-Jul-24	19-Jul-24					
-	LVT	10-Jul-24	16-Jul-24		$\Delta \nabla$ LV I $\Delta \nabla$ Toilet Partitions			
-	Toilet Partitions	10-Jul-24	16-Jul-24					
	Counter Tops (Alternate)	17-Jul-24	23-Jul-24		Counter Tops (Alternate)			
	Unit B	03-Jun-24	14-Jan-25				🗖 Unit E	3
	Gym & Student Dining	03-Jun-24	03-Jan-25	·	<u> </u>		📫 Gym & S	tudent D
	Demo	02 lum 24	07-Jun-24		∆⊽ Demo			1
	Paint & Wall Coating		26-Jun-24		Paint & Wall Coating			
		27-Jun-24			Athletic Equipment			
	Athletic Equipment				Toilet Partitions and Accessories			1
	Toilet Partitions and Accessories	27-Jun-24						
	LVT Acoustical Wall Panels	27-Jun-24 04-Jul-24	03-Jul-24 10-Jul-24		Acoustical Wall Panels			
	Basketball Backboards (Alternate)	30-Dec-24	03-Jan-25				△ Basketba	all Backb
	Reception Area		14-Jan-25				Rece	ption Are
	Demo		24-Dec-24				Demo	Francisco
	Metal Stud Framing		27-Dec-24				Metal Stud	-
	Counter Tops (Alternate)		27-Dec-24				Counter To	
	Reception Desk		27-Dec-24			Ζ	Reception	
	Mechanical		01-Jan-25				Mechanic	al
	Electrical		01-Jan-25		ļ			
	Drvwall and Tape		06-Jan-25				A Drywall	and Tap
	Paint	07-Jan-25	09-Jan-25					
	Ceilings	10-Jan-25	14-Jan-25				AV Ceilin	ngs
	Unit C	10-Jun-24	09-Aug-24		Caracteria Contracteria Contrac			
	Demo	21-Jun-24	27-Jun-24		△ ▼ Demo			
	Hand Dryers (Alternate)	28-Jun-24			Arr Hand Dryers (Alternate)			
	Paint	05-Jul-24	16-Jul-24		A Paint			
	Toilet Partitions	17-Jul-24	23-Jul-24		▲ Toilet Partitions			
	Carpet	24-Jul-24	02-Aug-24	1				
	LVT	24-Jul-24	30-Jul-24					
	Doors and Hardware		09-Aug-24		△ Doors and Hardware			
	Counter Tops (Alternate)		09-Aug-24		Counter Tops (Alternate)			
Δ	 ✓ Actual Work ✓ Remaining Work ✓ Termaining Work 		222		rict Wide Elementary Middle School Renovations chedule Update 26-Feb-24	· · · ·		
	Critical Remaining Work			Ŭ	•			
					4 of 5			<

						2025				
October 30 0 14 21 2	November 3 0 11 18 2	December 02 09 1 23	January 30 06 1 20 21	February 7 0 10 17 2	March	Apr 2 31 07 1	1 1 21 2	May 8 0 12 19 2	June 02 09 16	ly 2 30
are										
ternate) S										
				e Creeks	Elomon	ton So	haal			
				e Cieens	Liemen	liary SC				
									1	
nate)										
; , , , , , , , , , , , , , , , , , , ,		1	📥 Unit	В						
 			🗖 Gym &	Student I	Dinina				 	
			- j							
									1	
sories										
									1 1 1	
			△ Baskett	ball Backl	poards (/	Alterna	te)			
		_		eption Ar	ea				1	
			Demo							
		Δ	Metal Stu	d Framin	9					
			Counter T	ops (Alte	rnate)				1	
			 Reception Mechanic 	i Desk Ical					1	
			🖾 Drywa	ll and Tap	e					
									1	
			∆⊽ Ceil	ings						
1 1 1									1 1 1	
									i i i	
dware									1	
Alternate)										
vations										
vali0115					SKIL	LMAN				
					In	- IN				
							>			

O	Original Activity Name Start	Finish	2024 2025
Du	Duration		pruary March April May June July August September October November December January February March April May June I
			12 1 26 04 1 18 25 01 0 15 22 2 06 13 2 27 03 10 1 24 01 0 15 22 2 06 12 19 2 02 09 1 23 30 0 14 21 28 0 11 18 2 02 09 1 23 30 06 1 20 27 0 10 17 2 31 07 1 21 28 0 12 19 2 02 09 16 2 3
	Media Center 10-J	un-24 21-Jun-24	And Media Center
	Relocate Media Shelving 10-J	un-24 10-Jun-24	
	Demo 11-J	un-24 13-Jun-24	
	Paint 14-J	un-24 18-Jun-24	AV Paint
		un-24 21-Jun-24	

222100.05 Tri Creek District Wide Elementary Middle School Renovations Schedule Update 26-Feb-24 5 of 5





ADDENDUM ONE

Addendum One (AD.01) to the drawings and specifications prepared by Gibraltar Design for District Wide – Tri Creek Elementary Schools' Finishes, and Lowell Middle School Media Center Renovation for Tri-Creek School Corporation, Lowell, Indiana.

All Contractors bidding on this project shall read all of the items covered below and shall comply with all of the requirements as set forth, including any necessary refinements or additions generated by this Addendum and required by the intent of the original contract documents. All Contractors shall acknowledge on their bid form that they have received this Addendum and include the appropriate content of same within their bid proposal.

DRAWINGS – Lowell Middle School

1. Sheet AD104.MS

- A. Refer to revised full size drawing, included in this Addendum, for the following revisions:
 - 1. Add notes to remove flooring in SGIs and office adjacent to Media Center.

2. Sheets AD108.MS, AD109.MS, AD110.MS

- A. Refer to revised full size drawings, included in this Addendum, for the following revisions:
 - 1. Remove duplicate room numbers and add note to remove flooring in Humanities D205.

3. Sheet A-104.MS

- A. Refer to revised full size drawings, included in this Addendum, for the following revisions:
 - 1. Modify sizes of acoustical ceiling clouds.

4. Sheet A-750.MS

- A. Refer to revised full size drawing, included in this Addendum, for the following revisions:
 - 1. Add clarification on reused/relocated media shelving and revise Elevation 7 to match plan.

5. Sheet A-760.MS

- A. Refer to revised full size drawing, included in this Addendum, for the following revisions:
 - 1. Clarification of keynotes.
- 6. Sheets A-804.MS, A-805.MS, A-808.MS, A-809.MS, A-810.MS
 - A. Refer to revised full size drawings, included in this Addendum, for the following revisions:
 - 1. Remove all instances of Note 1 (no finishes) in rooms receiving new ceiling pads.

7. Sheet A-820.MS

- A. Refer to revised full size drawing, included in this Addendum, for the following revisions:
 - 1. Modify sizes and product information for acoustical ceiling clouds and add custom paint information.



8. Sheet A-860.MS

- A. Refer to revised full size drawing, included in this Addendum, for the following revisions:
 - 1. Add legend for clarification between existing and new markerboards, casework and media shelving.

9. Sheet A-861.MS

- A. Refer to revised full size drawing, included in this Addendum, for the following revisions:
 - 1. Add legend for clarification between existing and new markerboards, casework and media shelving.
 - 2. Modify LGI elevations for further clarification.

10. Sheet A-904.MS

- A. Refer to revised full size drawing, included in this Addendum, for the following revisions:
 - 1. Modify sizes and types of acoustical ceiling clouds.

DRAWINGS – Lake Prairie Elementary School

11. Sheets AD-101.LP, AD-102.LP

- A. Refer to revised full size drawings, included in this Addendum, for the following revisions:
 - 1. Flooring demo changes.

12. Sheets A-101.LP

- A. Refer to revised full size drawing, included in this Addendum, for the following revisions:
 - 1. Modifications to reception desk.
 - 2. Modifications to casework.

13. Sheets A-701.LP

- A. Refer to revised full size drawings, included in this Addendum, for the following revisions:
 - 1. Modifications to reception layout.
 - 2. Modification to casework.

14. Sheet A-760.LP

- A. Refer to revised full size drawing, included in this Addendum, for the following revisions:
 - 1. Modifications to casework.
 - 2. Modifications to reception desk.

15. Sheets A-801.LP, A-802.LP, A-803.LP

- A. Refer to revised full size drawings, included in this Addendum, for the following revisions:
 - 1. Room finish modifications.



DRAWINGS – Oak Hill Elementary School

16. Sheets AD-101.OH, AD-102.OH, AD-103.OH

- A. Refer to revised full size drawings, included in this Addendum, for the following revisions:
 - 1. VCT floor graphic to remain.
 - 2. Door to be removed.

17. Sheets A-101.OH

A. Refer to revised full size drawings, included in this Addendum, for the following revisions:1. VCT floor graphic to remain.

18. Sheets A-801.OH

- A. Refer to revised full size drawings, included in this Addendum, for the following revisions:
 - 1. VCT floor graphic to remain.
 - 2. Room finish modifications.

DRAWINGS – Three Creeks Elementary School

19. Sheets AD-101.TC, AD-102.TC, AD-103.TC

- A. Refer to revised full size drawings, included in this Addendum, for the following revisions:
 - 1. VCT floor graphic to remain.

20. Sheets A-101.TC

- A. Refer to revised full size drawings, included in this Addendum, for the following revisions:
 - 1. VCT floor graphic to remain.


21. Sheets A-801.TC


- A. Refer to revised full size drawings, included in this Addendum, for the following revisions:
 - 1. VCT floor graphic to remain.
 - 2. Room finish modifications.

Pages 1 through 3, inclusive, and Thirty-Four (34) Full-Size Drawings, constitute the total makeup of **Addendum One**.



Y:\23-107 Tri-Creek SC – Lowell MS Media Center Improvements\Specs\ADDENDUM ONE\AD01.docx







GENERAL DEMOLITION NOTES:

- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS.
- B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS SHEET.
- C. CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
- E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.
- F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION. VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL. REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS.
- G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER.
- H. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE).
- I. WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE PUBLIC.
- J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER OWNERS' DIRECTION, UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEMS ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED.
- K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR, OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES.
- L. EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE CENTER EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW FINISHES.
- N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, AND ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED. PATCH OPENINGS AND/OR SURFACES AS REQUIRED TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT OF ITEMS TO REMOVED.
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING. WHERE APPLICABLE, TOOTH NEW MASONRY INTO EXISTING MASONRY.
- P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION.
- Q. MASONRY WALLS TO BE REMOVED SHALL BE REMOVED TO A POINT 2" MINIMUM BELOW THE EXISTING FLOOR SLAB UNLESS SETTING ON A SLAB OR SPECIFICALLY NOTED OTHERWISE. PATCH WITH NEW CONCRETE TO BE FLUSH WITH THE EXISTING FLOOR SLAB.
- R. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO THEIR SCOPE OF WORK.
- S. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF SITE.
- T. REFER TO THE STRUCTURAL, MECHANICAL, PLUMBING, ELECTRICAL AND TECHNOLOGY DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK.
- U. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING, ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE.
- V. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER TO SPECIFICATIONS AND DRAWINGS FOR REQUIREMENTS AND SPECIAL CONDITIONS.
- W. WHERE APPLICABLE SALVAGE EXISTING MASONRY (FACE BRICK, GLAZED CMU, FACING TILE) AS REQUIRED FOR PATCHING AND INFILL IN RENOVATED AREAS WHERE INDICATED. DISCARD UNUSED PORTION OFF SITE.
- X. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW CEILING PADS.

DEMOLITION PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.) 1 REMOVE EXISTING FLOOR FINISHES AND WALL BASE IN ITS ENTIRETY, PREP DRAWN BY
- 2 REMOVE EXISTING FLOOR FINISHES, WALL FINISHES AND WALL BASE IN ITS CHECKED BY
- ENTIRETY, PREP FOR NEW FINISHES.
- 3 REMOVE EXISTING ACOUSTIC CEILING PADS. CLEAN GRID AND PREP TO RECEIVE NEW ACOUSTIC PADS.
- 4 REMOVE ACOUSTICAL BOARD CEILING, GRID AND SUSPENSION SYSTEM SALVAGE FOR REUSE IN ITS ENTIRETY. PREP TO RECEIVE NEW GRID AND ACOUSTICAL CEILING. REFER TO REFLECTED CEILING PLANS FOR COORDINATION W/ EXISTING CONDITIONS WHERE PRESENT.
- 5 REMOVE METAL STUD WALL IN ITS ENTIRETY. PATCH AND REPAIR ADJACENT ---- FLOOR AND WALL TO ACCEPT NEW FINISHES.
- 6 REMOVE PORTION OF CMU WALL FOR NEW DOOR, REFER TO FLOOR PLANS. MARK DATE ISSUED FOR 7 CAREFULLY REMOVE AND SALVAGE SECTION OF EXISTING CASEWORK FOR REUSE ELSEWHERE IN MEDIA CENTER. PATCH AND REPAIR WALL TO ACCEPT
- NEW FINISHES.
- 8 REMOVE CASEWORK AND SHELVING IN ITS ENTIRETY. PATCH FLOOR AND WALL TO RECEIVE NEW FINISHES.
- 9 CAREFULLY REMOVE AND SALVAGE MEDIA SHELVING FOR REUSE ELSEWHERE IN MEDIA CENTER
- 10 REMOVE EXISTING MILLWORK SYSTEM IN ITS ENTIRETY. PATCH AND REPAIR FLOOR TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR ADDITIONAL INFO.
- 11 REMOVE MARKERBOARD/ TACKBOARD/ CHALKBOARD IN ITS ENTIRETY, PREP WALL FOR NEW FINISHES 12 EXISTING DOOR TO BE REMOVED. HOLLOW METAL FRAME TO REMAIN.
- MODIFY AND PREP EXISTING FRAME TO RECEIVE NEW DOOR HARDWARE AND TO RETURN TO LIKE NEW CONDITIONS. 13 REMOVE PORTION OF CMU WALL FOR NEW WINDOW, REFER TO FLOOR
- PLANS. 14 CAREFULLY REMOVE GYPSUM BOARD FROM UNDERSIDE OF STAIRS
- COMPLETE TO EXPOSE TREADS, PREP AREA TO RECEIVE NEW GYPSUM BOARD IN SAME PLACE. 15 REMOVE TV ASSEMBLY COMPLETE. PATCH AND REPAIR WALL TO RECEIVE NEW FINISHES.
- 16 REMOVE ALL WALL MOUNTED ACOUSTICAL PANELS IN THEIR ENTIRETY. PATCH AND REPAIR WALL TO RETURN TO LIKE NEW CONDITIONS REFER TO A-860 AND A-861 FOR INSTALLATION OF NEW ACOUSTICAL WALL PANELS.





GENERAL DEMOLITION NOTES:

- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS.
- B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS SHEET.
- C. CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
- E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.
- F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION. VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL. REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS.
- G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER.
- H. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE).
- I. WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE PUBLIC.
- J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER OWNERS' DIRECTION. UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEMS ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED.
- K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR, OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES.
- . EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE CENTER EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECEIVE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW


FINISHES.


OF ITEMS TO REMOVED.

- N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, AND ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED, PATCH OPENINGS AND/OR SURFACES AS REQUIRED TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING. WHERE APPLICABLE, TOOTH NEW MASONRY INTO EXISTING MASONRY.
- P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION.
- Q. MASONRY WALLS TO BE REMOVED SHALL BE REMOVED TO A POINT 2" MINIMUM BELOW THE EXISTING FLOOR SLAB UNLESS SETTING ON A SLAB OR SPECIFICALLY NOTED OTHERWISE. PATCH WITH NEW CONCRETE TO BE FLUSH WITH THE EXISTING FLOOR SLAB.
- R. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO THEIR SCOPE OF WORK.
- S. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF SITE.
- T. REFER TO THE STRUCTURAL, MECHANICAL, PLUMBING, ELECTRICAL AND TECHNOLOGY DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK.
- U. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING, ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE.
- V. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER TO SPECIFICATIONS AND DRAWINGS FOR REQUIREMENTS AND SPECIAL CONDITIONS.
- W. WHERE APPLICABLE SALVAGE EXISTING MASONRY (FACE BRICK, GLAZED CMU, FACING TILE) AS REQUIRED FOR PATCHING AND INFILL IN RENOVATED AREAS WHERE INDICATED. DISCARD UNUSED PORTION OFF SITE.
- X. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW CEILING PADS.

DEMOLITION PLAN NOTES: (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)

- 1 REMOVE EXISTING FLOOR FINISHES AND WALL BASE IN ITS ENTIRETY, PREP DRAWN BY
- FOR NEW FINISHES. 2 REMOVE EXISTING FLOOR FINISHES, WALL FINISHES AND WALL BASE IN ITS CHECKED BY
- ENTIRETY, PREP FOR NEW FINISHES. 3 REMOVE EXISTING ACOUSTIC CEILING PADS. CLEAN GRID AND PREP TO RECEIVE NEW ACOUSTIC PADS.
- 4 REMOVE ACOUSTICAL BOARD CEILING, GRID AND SUSPENSION SYSTEM
- SALVAGE FOR REUSE IN ITS ENTIRETY. PREP TO RECEIVE NEW GRID AND ACOUSTICAL CEILING. REFER TO REFLECTED CEILING PLANS FOR COORDINATION W/ EXISTING CONDITIONS WHERE PRESENT.
- 5 REMOVE METAL STUD WALL IN ITS ENTIRETY. PATCH AND REPAIR ADJACENT
- 6 REMOVE PORTION OF CMU WALL FOR NEW DOOR, REFER TO FLOOR PLANS. MARK DATE ISSUED FOR 7 CAREFULLY REMOVE AND SALVAGE SECTION OF EXISTING CASEWORK FOR AD-0102/22/24 ADDENDUM 1 REUSE ELSEWHERE IN MEDIA CENTER. PATCH AND REPAIR WALL TO ACCEPT
- NEW FINISHES.
- 8 REMOVE CASEWORK AND SHELVING IN ITS ENTIRETY. PATCH FLOOR AND WALL TO RECEIVE NEW FINISHES.
- 9 CAREFULLY REMOVE AND SALVAGE MEDIA SHELVING FOR REUSE ELSEWHERE IN MEDIA CENTER
- 10 REMOVE EXISTING MILLWORK SYSTEM IN ITS ENTIRETY. PATCH AND REPAIR FLOOR TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR ADDITIONAL INFO.
- 11 REMOVE MARKERBOARD/ TACKBOARD/ CHALKBOARD IN ITS ENTIRETY, PREP WALL FOR NEW FINISHES
- 12 EXISTING DOOR TO BE REMOVED. HOLLOW METAL FRAME TO REMAIN. MODIFY AND PREP EXISTING FRAME TO RECEIVE NEW DOOR HARDWARE AND TO RETURN TO LIKE NEW CONDITIONS. 13 REMOVE PORTION OF CMU WALL FOR NEW WINDOW, REFER TO FLOOR
- PLANS. 14 CAREFULLY REMOVE GYPSUM BOARD FROM UNDERSIDE OF STAIRS
- COMPLETE TO EXPOSE TREADS, PREP AREA TO RECEIVE NEW GYPSUM BOARD IN SAME PLACE. 15 REMOVE TV ASSEMBLY COMPLETE. PATCH AND REPAIR WALL TO RECEIVE
- NEW FINISHES. 16 REMOVE ALL WALL MOUNTED ACOUSTICAL PANELS IN THEIR ENTIRETY. PATCH AND REPAIR WALL TO RETURN TO LIKE NEW CONDITIONS REFER TO A-860 AND A-861 FOR INSTALLATION OF NEW ACOUSTICAL WALL PANELS.





GENERAL DEMOLITION NOTES:


- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS.
- B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS SHEET.
- C. CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
- E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.
- F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION. VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL. REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS.
- G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER.
- H. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE).
- I. WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE PUBLIC.
- J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER OWNERS' DIRECTION. UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEM: ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED.
- K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR, OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES.
- L. EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE CENTER EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW


FINISHES.


- N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, AND ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED, PATCH OPENINGS AND/OR SURFACES AS REQUIRED TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT OF ITEMS TO REMOVED.
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING. WHERE APPLICABLE, TOOTH NEW MASONRY INTO EXISTING MASONRY.
- P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION.
- Q. MASONRY WALLS TO BE REMOVED SHALL BE REMOVED TO A POINT 2" MINIMUM BELOW THE EXISTING FLOOR SLAB UNLESS SETTING ON A SLAB OR SPECIFICALLY NOTED OTHERWISE. PATCH WITH NEW CONCRETE TO BE FLUSH WITH THE EXISTING FLOOR SLAB.
- R. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO THEIR SCOPE OF WORK.
- S. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF SITE.
- T. REFER TO THE STRUCTURAL, MECHANICAL, PLUMBING, ELECTRICAL AND TECHNOLOGY DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK.
- U. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING, ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE.
- V. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER TO SPECIFICATIONS AND DRAWINGS FOR REQUIREMENTS AND SPECIAL CONDITIONS.
- W. WHERE APPLICABLE SALVAGE EXISTING MASONRY (FACE BRICK, GLAZED CMU, FACING TILE) AS REQUIRED FOR PATCHING AND INFILL IN RENOVATED AREAS WHERE INDICATED. DISCARD UNUSED PORTION OFF SITE.
- X. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW CEILING PADS.

DEMOLITION PLAN NOTES: (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)

- 1 REMOVE EXISTING FLOOR FINISHES AND WALL BASE IN ITS ENTIRETY, PREP DRAWN BY
- FOR NEW FINISHES. 2 REMOVE EXISTING FLOOR FINISHES, WALL FINISHES AND WALL BASE IN ITS CHECKED BY
- ENTIRETY, PREP FOR NEW FINISHES. 3 REMOVE EXISTING ACOUSTIC CEILING PADS. CLEAN GRID AND PREP TO RECEIVE NEW ACOUSTIC PADS.
- 4 REMOVE ACOUSTICAL BOARD CEILING, GRID AND SUSPENSION SYSTEM SALVAGE FOR REUSE IN ITS ENTIRETY. PREP TO RECEIVE NEW GRID AND ACOUSTICAL CEILING. REFER TO REFLECTED CEILING PLANS FOR
- COORDINATION W/ EXISTING CONDITIONS WHERE PRESENT.
- 5 REMOVE METAL STUD WALL IN ITS ENTIRETY. PATCH AND REPAIR ADJACENT FLOOR AND WALL TO ACCEPT NEW FINISHES.
- 7 CAREFULLY REMOVE AND SALVAGE SECTION OF EXISTING CASEWORK FOR AD-0102/22/24 ADDENDUM 1 REUSE ELSEWHERE IN MEDIA CENTER. PATCH AND REPAIR WALL TO ACCEPT
- NEW FINISHES. 8 REMOVE CASEWORK AND SHELVING IN ITS ENTIRETY. PATCH FLOOR AND
- WALL TO RECEIVE NEW FINISHES.
- 9 CAREFULLY REMOVE AND SALVAGE MEDIA SHELVING FOR REUSE ELSEWHERE IN MEDIA CENTER
- 10 REMOVE EXISTING MILLWORK SYSTEM IN ITS ENTIRETY. PATCH AND REPAIR FLOOR TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR ADDITIONAL INFO.
- 11 REMOVE MARKERBOARD/ TACKBOARD/ CHALKBOARD IN ITS ENTIRETY, PREP WALL FOR NEW FINISHES
- 12 EXISTING DOOR TO BE REMOVED. HOLLOW METAL FRAME TO REMAIN. MODIFY AND PREP EXISTING FRAME TO RECEIVE NEW DOOR HARDWARE AND TO RETURN TO LIKE NEW CONDITIONS. 13 REMOVE PORTION OF CMU WALL FOR NEW WINDOW, REFER TO FLOOR
- PLANS.
- 14 CAREFULLY REMOVE GYPSUM BOARD FROM UNDERSIDE OF STAIRS COMPLETE TO EXPOSE TREADS, PREP AREA TO RECEIVE NEW GYPSUM BOARD IN SAME PLACE. 15 REMOVE TV ASSEMBLY COMPLETE. PATCH AND REPAIR WALL TO RECEIVE
- NEW FINISHES. 16 REMOVE ALL WALL MOUNTED ACOUSTICAL PANELS IN THEIR ENTIRETY. PATCH AND REPAIR WALL TO RETURN TO LIKE NEW CONDITIONS REFER TO A-860 AND A-861 FOR INSTALLATION OF NEW ACOUSTICAL WALL PANELS.







LAST SAVED MS MEDIA CE AM -OWELL GS\05 4 1 1 8 Thursday, 2/22/2024 - 10:4 Y:\23-107 TRI-CREEK SC -IMPROVEMENTS\23-107 DRAWI ARCH\AD110-MS.DWG

UNIT "E" ARCHITECTURAL SECOND FLOOR DEMOLITION PLAN

GENERAL DEMOLITION NOTES:

- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS.
- B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS SHEET.
- C. CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
- E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.
- F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION. VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL. REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS.
- G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER.
- H. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE).
- I. WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE PUBLIC.
- J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER OWNERS' DIRECTION, UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEMS ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED.
- K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR, OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES.
- L. EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE CENTER EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECEIVE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW FINISHES.
- N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, AND ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED, PATCH OPENINGS AND/OR SURFACES AS REQUIRED TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING. WHERE APPLICABLE, TOOTH NEW MASONRY INTO EXISTING MASONRY.


OF ITEMS TO REMOVED.


- P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION.
- Q. MASONRY WALLS TO BE REMOVED SHALL BE REMOVED TO A POINT 2" MINIMUM BELOW THE EXISTING FLOOR SLAB UNLESS SETTING ON A SLAB OR SPECIFICALLY NOTED OTHERWISE. PATCH WITH NEW CONCRETE TO BE FLUSH WITH THE EXISTING FLOOR SLAB.
- R. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO THEIR SCOPE OF WORK.
- S. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF SITE. T. REFER TO THE STRUCTURAL, MECHANICAL, PLUMBING, ELECTRICAL AND
- TECHNOLOGY DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK.
- U. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING, ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE.
- V. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER TO SPECIFICATIONS AND DRAWINGS FOR REQUIREMENTS AND SPECIAL CONDITIONS.
- W. WHERE APPLICABLE SALVAGE EXISTING MASONRY (FACE BRICK, GLAZED CMU, FACING TILE) AS REQUIRED FOR PATCHING AND INFILL IN RENOVATED AREAS WHERE INDICATED. DISCARD UNUSED PORTION OFF SITE.
- X. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW CEILING PADS.

DEMOLITION PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.) 1 REMOVE EXISTING FLOOR FINISHES AND WALL BASE IN ITS ENTIRETY, PREP DRAWN BY
- FOR NEW FINISHES. 2 REMOVE EXISTING FLOOR FINISHES, WALL FINISHES AND WALL BASE IN ITS CHECKED BY
- ENTIRETY, PREP FOR NEW FINISHES. 3 REMOVE EXISTING ACOUSTIC CEILING PADS. CLEAN GRID AND PREP TO RECEIVE NEW ACOUSTIC PADS.
- 4 REMOVE ACOUSTICAL BOARD CEILING, GRID AND SUSPENSION SYSTEM SALVAGE FOR REUSE IN ITS ENTIRETY. PREP TO RECEIVE NEW GRID AND ACOUSTICAL CEILING. REFER TO REFLECTED CEILING PLANS FOR
- COORDINATION W/ EXISTING CONDITIONS WHERE PRESENT. 5 REMOVE METAL STUD WALL IN ITS ENTIRETY. PATCH AND REPAIR ADJACENT
- 6 REMOVE PORTION OF CMU WALL FOR NEW DOOR, REFER TO FLOOR PLANS. MARK DATE ISSUED FOR
- 7 CAREFULLY REMOVE AND SALVAGE SECTION OF EXISTING CASEWORK FOR AD-0102/22/24 ADDENDUM 1 REUSE ELSEWHERE IN MEDIA CENTER. PATCH AND REPAIR WALL TO ACCEPT NEW FINISHES.
- 8 REMOVE CASEWORK AND SHELVING IN ITS ENTIRETY. PATCH FLOOR AND
- ---- WALL TO RECEIVE NEW FINISHES. 9 CAREFULLY REMOVE AND SALVAGE MEDIA SHELVING FOR REUSE ELSEWHERE
- 10 REMOVE EXISTING MILLWORK SYSTEM IN ITS ENTIRETY. PATCH AND REPAIR FLOOR TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR ADDITIONAL
- INFO. 11 REMOVE MARKERBOARD/ TACKBOARD/ CHALKBOARD IN ITS ENTIRETY, PREP WALL FOR NEW FINISHES
- 12 EXISTING DOOR TO BE REMOVED. HOLLOW METAL FRAME TO REMAIN. MODIFY AND PREP EXISTING FRAME TO RECEIVE NEW DOOR HARDWARE AND TO RETURN TO LIKE NEW CONDITIONS.
- 13 REMOVE PORTION OF CMU WALL FOR NEW WINDOW, REFER TO FLOOR PLANS.
- 14 CAREFULLY REMOVE GYPSUM BOARD FROM UNDERSIDE OF STAIRS COMPLETE TO EXPOSE TREADS, PREP AREA TO RECEIVE NEW GYPSUM BOARD IN SAME PLACE.
- [15] REMOVE TV ASSEMBLY COMPLETE. PATCH AND REPAIR WALL TO RECEIVE NEW FINISHES. 16 REMOVE ALL WALL MOUNTED ACOUSTICAL PANELS IN THEIR ENTIRETY. PATCH AND REPAIR WALL TO RETURN TO LIKE NEW CONDITIONS REFER TO
- A-860 AND A-861 FOR INSTALLATION OF NEW ACOUSTICAL WALL PANELS.







Thursday, 2/22/2024 - 10:49 AM - LAST SAVED BY:AS Y:\23-107 TRI-CREEK SC -LOWELL MS MEDIA CENTER IMPROVEMENTS\23-107 DRAWINGS\05 ARCH\A-104-MS.DWG

GENERAL PLAN NOTES:

- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS. B. PLAN DIMENSIONS TO MASONRY WALLS ARE TO FACE OF ROUGH MASONRY.
- PLAN DIMENSIONS TO STUD WALLS ARE TO FACE OF FINISHED GYPSUM BOARD OR PLASTER. PLAN DIMENSIONS TO STUD WALLS WITH CERAMIC TILE FINISH ARE TO THE FACE OF TILE BACKER BOARD.
- C. ALL CMU WALLS THAT DO NOT LAY OUT IN FULL OR HALF LENGTHS SHOULD BE BALANCED SO AS NOT TO HAVE ANY PIECES LESS THAN 4" IN SIZE EXPOSED TO VIEW.
- D. THE BASE FIRST FLOOR ELEVATION INDICATED FOR THE PROJECT IS 100'-0". REFER TO SITE PLAN FOR CORRELATION TO USGS DATUM.
- E. HINGE SIDE OF DOOR JAMB AT CMU WALLS SHALL BE LOCATED 8" MINIMUM FROM ADJACENT WALL AND HINGE SIDE OF DOOR JAMB AT GYPSUM BOARD WALLS SHALL BE LOCATED 4" MINIMUM FROM ADJACENT WALL UNLESS NOTED OTHERWISE.
- F. PROVIDE WOOD BLOCKING (OR METAL STRAPPING WHERE APPLICABLE) AS REQUIRED WITHIN METAL STUD WALLS FOR WALL MOUNTED ITEMS.
- G. REFER TO LIFE SAFETY PLANS REGARDING FIRE RATED WALL LOCATIONS AND OTHER CODE INFORMATION.
- H. REFER TO FINISH PLANS FOR LOCATION AND EXTENT OF FINISHED FLOOR AND WALL MATERIAL.
- I. REFER TO DEMOLITION SHEETS FOR ADDITIONAL PATCHING AND REPAIR WORK.


PLAN LEGEND:


 \bigcirc INDICATES WALL TYPES REFER TO G-301 FOR WALL THICKNESS, HEIGHT, AND COMPOSITION.


PLAN NOTES:


(ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.) (1) RELOCATED CASEWORK, REFER TO DEMO AND EQUIPMENT PLANS.


- 2) NEW MILLWORK, REFER TO EQUIPMENT PLANS.
- 3 MANUAL FOLDING PARTITION, COORDINATE WITH MFGR FOR FINAL DIMENSIONS. (4) NEW DECORATIVE 1/2 HEIGHT WALL CONSTRUCTION WITH 3/4" STAINED OAK CAP WITH 1/2" OVERHANG ALL AROUND. WALL TO TERMINATE 1" BELOW TRIM OF ADJACENT WALL. REFER TO A-860 AND A-861 FOR ADDITIONAL INFO.
- 5 NEW ACOUSTICAL BAFFLES ABOVE, REFER TO REFLECTED CEILING PLANS FOR ADDITIONAL INFO.
- 6 SPRAY INSULATION TO FILL UNDERSIDE OF TREADS COMPLETE, THEN INSTALL NEW GYPSUM BOARD CEILING TO RETURN TO LIKE NEW CONDITIONS.

















GENERAL FINISH PLAN NOTES:

A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION.B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING


- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
 C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE
- FINISH WORK HAS PROCEEDED. D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD.
 F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING
- MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION.
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES.
 H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED ON THE FLOOR PATTERN PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED TYPE/COLOR WITH ARCHITECT.
- J. ALL FLOOR FINISH TRANSITIONS AT DOORS SHALL BE CENTERED UNDER DOOR UNLESS NOTED UTHERWISE.K. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A
- INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMOM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803.
 L. PAINT ALL SIDES OF NEW DOOR FRAMES TO MATCH EXISTING, P4, UNLESS
- NOTED OTHERWISE.M. EXPOSED SURFACES OF DUCTWORK TO BE PAINTED TO MATCH ADJACENT
- SURFACES UNLESS NOTED OTHERWISE. N. EXISTING BRICK TO REMAIN, DO NOT PAINT.


FINISH SYMBOL LEGEND:

P1	
C1	FLOOR FINISH
B1	BASE FINISH
	MISC FINISH INFORMATION
\uparrow	FLOOR TRANSITION STRIP AS REQUIRED

--- INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS, REFER TO REFLECTED CEILING PLANS.

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN) AD-01 (1) NO NEW FINISHES THIS ROOM. EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES. (2) WALLCOVERING, WC2
- 3 NEW ACOUSTICAL WALL PANELS, THIS ROOM, REFER TO A-860 SERIES SHEETS
- (4) EXPOSED STRUCTURE AND HVAC, THIS ROOM, TO RECEIVE NO PAINT. EXISTING FINISH TO REMAIN.





UNIT "E" FIRST FLOOR FINISH PLAN SCALE: 1/8" = 1'-0"

GENERAL FINISH PLAN NOTES:

A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION.B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING


- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
 C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE
- ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE FINISH WORK HAS PROCEEDED. D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS
- AND MATERIALS FOR ALL FINISHES. E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING
- PER MANUFACTURER'S RECOMMENDED METHOD. F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION.
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES.
 H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED ON THE FLOOR PATTERN PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED TYPE/COLOR WITH ARCHITECT.
- J. ALL FLOOR FINISH TRANSITIONS AT DOORS SHALL BE CENTERED UNDER DOOR UNLESS NOTED UTHERWISE.K. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW
- INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803.L. PAINT ALL SIDES OF NEW DOOR FRAMES TO MATCH EXISTING, P4, UNLESS
- NOTED OTHERWISE.M. EXPOSED SURFACES OF DUCTWORK TO BE PAINTED TO MATCH ADJACENT
- SURFACES UNLESS NOTED OTHERWISE. N. EXISTING BRICK TO REMAIN, DO NOT PAINT.


FINISH SYMBOL LEGEND:

P1	
C1	FLOOR FINISH
B1	BASE FINISH
	MISC FINISH INFORMATION
-	OR TRANSITION STRIP AS REQUIRED

INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS, REFER TO REFLECTED CEILING PLANS.

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN) AD-01 1 NO NEW FINISHES THIS ROOM. EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES. 2 WALLCOVERING, WC2
- 3 NEW ACOUSTICAL WALL PANELS, THIS ROOM, REFER TO A-860 SERIES SHEETS
- (4) EXPOSED STRUCTURE AND HVAC, THIS ROOM, TO RECEIVE NO PAINT. EXISTING FINISH TO REMAIN.






GENERAL FINISH PLAN NOTES:

A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING


- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION. C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE
- ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE FINISH WORK HAS PROCEEDED. D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS
- AND MATERIALS FOR ALL FINISHES. E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN $10^{\circ}-0$ " WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING
- PER MANUFACTURER'S RECOMMENDED METHOD. F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION.
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES. H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH
- ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED. I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED
- ON THE FLOOR PATTERN PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED TYPE/COLOR WITH ARCHITECT. J. ALL FLOOR FINISH TRANSITIONS AT DOORS SHALL BE CENTERED UNDER
- DOOR UNLESS NOTED UTHERWISE. K. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX
- OF 450 MAXIMUM, PER IBC SECTION 803. L. PAINT ALL SIDES OF NEW DOOR FRAMES TO MATCH EXISTING, P4, UNLESS NOTED OTHERWISE.
- M. EXPOSED SURFACES OF DUCTWORK TO BE PAINTED TO MATCH ADJACENT SURFACES UNLESS NOTED OTHERWISE.
- N. EXISTING BRICK TO REMAIN, DO NOT PAINT.


FINISH SYMBOL LEGEND



INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS, REFER TO REFLECTED CEILING PLANS.

- AD-01 (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN) 1 NO NEW FINISHES THIS ROOM. EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES. 2 WALLCOVERING, WC2
- (3) NEW ACOUSTICAL WALL PANELS, THIS ROOM, REFER TO A-860 SERIES SHEETS
- 4 EXPOSED STRUCTURE AND HVAC, THIS ROOM, TO RECEIVE NO PAINT. EXISTING FINISH TO REMAIN.





GENERAL FINISH PLAN NOTES


A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING

- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
 C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE FINISH WORK HAS PROCEEDED.
- D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD.
 F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING
- MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION. G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES.
- H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED ON THE FLOOR PATTERN PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED TYPE/COLOR WITH ARCHITECT.
- J. ALL FLOOR FINISH TRANSITIONS AT DOORS SHALL BE CENTERED UNDER DOOR UNLESS NOTED UTHERWISE.K. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM. WITH
- INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803. L. PAINT ALL SIDES OF NEW DOOR FRAMES TO MATCH EXISTING, P4, UNLESS
- M. EXPOSED SURFACES OF DUCTWORK TO BE PAINTED TO MATCH ADJACENT
 SUBFACES UNUESS NOTED OTUGDWIGE
- SURFACES UNLESS NOTED OTHERWISE. N. EXISTING BRICK TO REMAIN, DO NOT PAINT.

FINISH SYMBOL LEGEND:

P1 C1 B1	
_X _	FLOOR TRANSITION STRIP AS REQUIRED
\bigwedge	INDICATES DIRECTION OF MATERIAL GRAIN
	INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS, REFER TO REFLECTED CEILING PLANS.

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN) (1) NO NEW FINISHES THIS ROOM. EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES. (2) WALLCOVERING, WC2 (3) NEW ACOUSTICAL WALL PANELS, THIS ROOM, REFER TO A-860 SERIES
- (4) EXPOSED STRUCTURE AND HVAC. THIS ROOM TO RECEIVE NO PA
- (4) EXPOSED STRUCTURE AND HVAC, THIS ROOM, TO RECEIVE NO PAINT. EXISTING FINISH TO REMAIN.





GENERAL FINISH PLAN NOTES:

A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION.B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING


- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
 C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE
- FINISH WORK HAS PROCEEDED. D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD.
 F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING
- MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION.
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES.
 H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED ON THE FLOOR PATTERN PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED TYPE/COLOR WITH ARCHITECT.
 J. ALL FLOOR FINISH TRANSITIONS AT DOORS SHALL BE CENTERED UNDER
- DOOR UNLESS NOTED UTHERWISE.K. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A
- FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803.L. PAINT ALL SIDES OF NEW DOOR FRAMES TO MATCH EXISTING, P4, UNLESS
- NOTED OTHERWISE. M. EXPOSED SURFACES OF DUCTWORK TO BE PAINTED TO MATCH ADJACENT
- SURFACES UNLESS NOTED OTHERWISE. N. EXISTING BRICK TO REMAIN, DO NOT PAINT.

FINISH SYMBOL LEGEND:

	7
P1 –	WALL FINISH
C1 _	FLOOR FINISH
B1 _	BASE FINISH
	MISC FINISH INFORMATION
\uparrow	R TRANSITION STRIP AS REQUIRED


INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS, REFER TO REFLECTED CEILING PLANS.


- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN) (1) NO NEW FINISHES THIS ROOM. EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES. (2) WALLCOVERING, WC2
- 3 NEW ACOUSTICAL WALL PANELS, THIS ROOM, REFER TO A-860 SERIES SHEETS
- (4) EXPOSED STRUCTURE AND HVAC, THIS ROOM, TO RECEIVE NO PAINT. EXISTING FINISH TO REMAIN.




F Wednesday, 2/21/2024 - 1:46 PM - LAST SAVED BY:A' Y:\23-107 TRI-CREEK SC -LOWELL MS MEDIA CENTER IMPROVEMENTS\23-107 DRAWINGS\05 ARCH\A-820-MS.DWG

SURFACE	MARK	DESCRIPTION	MANUFACTURER	PATTERN/FINISH	NUMBER/COLOR	SIZE	COMMENTS
EILING MATERIAL						04" \/ 49"	
	ACT1	ACOUSTICAL CEILING	USG	RADAR 2410	WHITE	24" X 48"	
~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~				RADAR HIGH NRG 22122			<u> </u>
	ACC1	ACOUSTIC. CEILING CLOUI		ZINTRA CLOUD SQUARE	PEBBLE (PB)	108" X 108"	
	ACC2	ACOUSTIC. CEILING CLOUI		ZINTRA CLOUD SQUARE	SLATE (SL)	108 X 108"	
	ACC3	ACOUSTIC. CEILING CLOUI	MDC	ZINTRA CLOUD SQUARE	PEBBLE (PB)	48" X 48"	
	ACC4	ACOUSTIC. CEILING CLOUI		ZINTRA CLOUD SQUARE	SLATE (SL)	48" X 48"	
	P3	PAINT	SHERWIN WILLIAMS		SW 7007 CEILING BRIGHT WHITE		
NALL BASE		i			-		
	B1	VINYL BASE	TARKETT		BURNT UMBER 63	4" COVE	
	<u></u>						
LOOR MATERIALS	İ	İ	1				
	C1	CARPET TILE	TARKETT	APPLAUSE III 02803	FIREWORKS 28515	24" X 24"	INSTALL: MONOLITHIC
	C2	CARPET TILE	TARKETT	VISUAL PATH 11684	BE COURTEOUS 20504	24" X 24"	INSTALL: VERTICAL ASHLAR
	LVT1	LUXURY VINYL TILE	TARKETT	EVEN PLANE – CEMENT	MEDIUM GRAY 8704	50CM X 50CM	INSTALL: QUARTER TURN
NALL MATERIALS		i	+	i	1		
	P1	PAINT	SHERWIN WILLIAMS		SW 7029 AGREEABLE GRAY		_
	P2	PAINT	SHERWIN WILLIAMS		CUSTOM		SEE NOTE 1
	P3	SEE CEILING MATERIALS		Į			
	P4	PAINT	SHERWIN WILLIAMS		CUSTOM		SEE NOTE 2
	WC1	WALL COVERING	MOMENTUM	ON TRACK	DESTINATION SG3094		
	FW-AWP1	ACOUSTICAL PANEL	MAYER FABRICS	EQUAL	OPAL EQ394		
	FW-AWP2	ACOUSTICAL PANEL	MAYER FABRICS	EQUAL	GREY MIX EQ238		
	FW-AWP3	ACOUSTICAL PANEL	MAYER FABRICS	EQUAL	CLARENT ACCENT EQ418		
	AR-AWP1	ACOUSTICAL PANEL	SHERWIN WILLIAMS	TECTUM	CRUSHED ICE SW7637		
	AR-AWP2	ACOUSTICAL PANEL	SHERWIN WILLIAMS	TECTUM	SW 7017 DORIAN GRAY		
	AR-AWP3	ACOUSTICAL PANEL	SHERWIN WILLIAMS	TECTUM	SW 7585 SUN DRIED TOMATO		+
		I	<u>I</u>	1		1	
CASEWORK AND N							
			WILSONADT		DIVED CHEDDY 7077		
	PL1	PLASTIC LAMINATE	WILSONART	38 FINE VELVET TEXTURE	RIVER CHERRY 7937		
	PL2	PLASTIC LAMINATE	WILSONART	38 FINE VELVET TEXTURE	OILED SOAPSTONE 4882		
	PL3	PLASTIC LAMINATE			WHITE ESSENCE		
	PL4	PLASTIC LAMINATE	WILSONART	60 MATTE	TUNGSTEN EV 4814		
	PL5	PLASTIC LAMINATE		l			
	CC1			l	NEUTRAL AGGREGATE		
	SS1	SOLID SURFACE	CORIAN		INEUTRAL AUGREGATE		<b>I</b>
	•						
MISCELLANEOUS	TRIM1	METAL TRIM	SCHLUTER	RONDEC	SATIN ANODIZED ALUMINUM		
		WOOD DOOR STAIN		WHITE OAK CLEAR STAIN	SATIN ANODIZED ALUMINUM		
		WOOD DOUR STAIN		WHITE VAN GLEAR STAIN			
TR = FXISTING T							
		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~					
. CUSTOM COLOR T	U MATCH EXIS	STING PAINT IN CLASSROOM	15. 5				
			5				
ICI 1793 DAMASK		70 04 400	<				
CCE COLORANT	0Z	32 64 128	\langle				
B1-BLACK		5 – –	\langle				
R2-MAROON	- 1	1 –)				
V/ DEED AALD	_	8 1 1)				
Y3-DEEP GOLD			5				
		STING DOOK FRAMES.	5				
2. CUSTOM COLOR TO	O MAICH EXIS						
2. CUSTOM COLOR TO			\$				
2. CUSTOM COLOR TO	BROWN		$\left\{ \right\}$				
2. CUSTOM COLOR TO ICI 1721 TURRET CCE COLORANT		32 64 128					
2. CUSTOM COLOR TO ICI 1721 TURRET CCE COLORANT B1-BLACK	BROWN	32 64 128 21 1 1					
2. CUSTOM COLOR TO ICI 1721 TURRET CCE COLORANT	BROWN 0Z 2	32 64 128					





52 54 52 54 52 54 52 54 53 53 52 54 52
R NORTH ELEVATION 1 1 A-860



6'-6"	6'-6"
(55)	55
56	57

	<mark>-2'-10"</mark>	^{8"} 3'-11" ⁸	⁶ 4'-0" ⁸	³ " <u>3'-3</u> "8	["] _3'_3"_8	"3'3"	-2" 4'-3"
2,-6"	55	55	55	55	55	55	- 14 (55)
2,-6"	57	57	56	57	(56)	57	L
		= = = = = = = = = = = = = = = = = = =	= = = = = = = = 4'-8"	(18)	===== 	====== 4'-2"	= = = = = = = = = = = = = = = = = = =
8'-1"	20	 			:		8

GENERAL INTERIOR ELEVATION NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE FLOOR PATTER PLANS, EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
- . PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALI SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL B ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE
- FINISH WORK HAS PROCEEDED. D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- F. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803.

INTERIOR ELEVATION LEGEND:

----- EXISTING OR RELOCATED COMPONENTS, REFER TO FLOOR AND EQUIPMENT PLANS.

----- NEW COMPONENTS, REFER TO FLOOR AND EQUIPMENT PLANS.


AD-01 **INTERIOR ELEVATION NOTES:**

- (1) DOOR. __AD_01 |
- 2) WINDOW ~~~~~~ (3) EXISTING HVAC LOUVERS. CLEAN EXISTING GRILLES AND PAINT, P1.
- (4) EXISTING RAILING.
- (5) RELOCATED CASEWORK, REFER TO EQUIPMENT PLAN.
- (6) RELOCATED AND/OR REINSTALLED MEDIA SHELVING, REFER TO EQUIPMEN PLAN.
- (7) NEW MILLWORK, REFER TO EQUIPMENT PLAN.
- (9) TELEVISION, REFER TO EQUIPMENT PLAN.
- (10) EXISTING PA SYSTEM SPEAKER.
- (11) EXISTING SECURITY CAMERA/DEVICE. (12) EXISTING EXIT SIGN.
- 13) EXISTING PLUMBING PIPE.
- (14) EXPOSED CEILING STRUCTURE.
- 15) EXISTING HVAC
- (16) LINE OF EXISTING STAIR BEHIND WALL.
- (17) LINE OF SECOND FLOOR FINISHED FLOOR.
- (18) CUT ACOUSTICAL WALL PANEL TO FIT AROUND PLUMBING PIPE, HVAC, HVAC LOUVERS, AND STRUCTURE AS NEEDED. VERIFY EXISTING CONDITIONS.
- (19) 3/4" stained oak cap with 1/2" overhang. Refer to detail 1/G-301 ALIGN TOP OF CAP WITH BOTTOM OF EXISTING OAK TRIM. (20) EXISTING CASEWORK. AD-01

June 1 **INTERIOR ELEVATION NEW FINISH** NOTES:

- (50) PAINT, P2
- (51) WALLCOVERING, WC1
- (52) ACOUSTICAL WALL PANEL, FW-AWP1
- (53) ACOUSTICAL WALL PANEL, FW-AWP2
- (54) ACOUSTICAL WALL PANEL, FW-AWP3
- 55) ACOUSTICAL WALL PANEL, AR-AWP1. CENTER BETWEEN ADJACENT WALLS, JOISTS, AND/OR BEAMS. FIELD VERIFY DIMENSIONS.
- 56) ACOUSTICAL WALL PANEL, AR-AWP2. ALIGN WITH ABOVE ACOUSTICAL WALL PANELS. FIELD VERIFY DIMENSIONS.
- 57) ACOUSTICAL WALL PANEL, AR-AWP3. ALIGN WITH ABOVE ACOUSTICAL WALL
- PANELS. FIELD VERIFY DIMENSIONS.
- 58) VINYL WALL BASE, B1





GENERAL REFLECTED CEILING PLAN NOTES:


- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO GI SERIES SHEETS.
- B. THE ARCHITECTURAL REFLECTED CEILING PLAN GOVERN THE LAYOUT OF ALL CEILING ELEMENTS AND PENETRATIONS.
- C. BULKHEAD FRAMING SHALL BE ATTACHED TO STRUCTURAL SUPPORTS AND NOT THE ROOF DECK.
- D. REFER TO FLOOR PLANS FOR WALL TYPES
- E. REFER TO ELECTRICAL DRAWINGS FOR ADDITIONAL CEILING MOUNTED
- ELECTRICAL ITEMS.
- F. REFER TO TECHNOLOGY DRAWINGS FOR ADDITIONAL CEILING MOUNTED TECHNOLOGY ITEMS.
- G. REFER TO MECHANICAL DRAWINGS FOR LOCATION OF CEILING DIFFUSERS, RETURN AIR GRILLS, AND CEILING CABINET HEATERS.
- H. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW CEILING PADS.


REFLECTED CEILING PLAN LEGEND:


2'-0" x 4'-0" ACST. BD. CEILING SEE ROOM FINISH SCHEDULE 2'-0" x 4'-0" EXISTING GRID TO REMAIN, REPLACE ACOUSTICAL PADS, REFER TO NOTES/ SPEC		2x4 LIGHT FIXTURE SUPPLY AIR DIFFUSER RETURN, EXHAUST, AND TRANSFER AIR GRILLE
$2^{\circ}-0^{\circ} \times 4^{\circ}-0^{\circ}$ EXISTING TO REMAIN REFER TO NOTES WHERE APPLICABLE	OS	OCCUPANCY SENSOR


REFLECTED CEILING PLAN NOTES: (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.


- 1 MODIFY EXISTING CEILING GRID AND SUSPENSION SYSTEM TO RECEIVE NEW GRID AND NEW CONSTRUCTION ADJACENT. REPLACE EXISTING PADS WITH NEW THROUGHOUT. WHERE APPLICABLE, MODIFY TO ACCOMMODATE NEW MECHANICAL, ELECTRICAL, TECHNOLOGY, AND FIRE PROTECTION ABOVE AND AT CEILING,
- 2 EXISTING LAY-IN CEILING GRID AND SUSPENSION SYSTEM TO REMAIN. REPLACE EXISTING CEILING PADS THIS ROOM WITH NEW THROUGHOUT. WHERE APPLICABLE, MODIFY TO ACCOMMODATE NEW MECHANICAL, ELECTRICAL, TECHNOLOGY, AND FIRE PROTECTION ABOVE AND AT CEI
- (3) NEW ACOUSTICAL CEILING GRID, PADS AND SUSPENSION SYSTEM. (4) REPLACE EXISTING LIGHTS WITH NEW. REFER TO ELECTRICAL FOR
- ADDITIONAL INFO. 5 MODIFY EXISTING CEILING GRID AND SUSPENSION SYSTEM TO RECEIVE NEW CONSTRUCTION ADJACENT. REPLACE EXISTING PADS WITH NEW THROUGHOUT. WHERE APPLICABLE, MODIFY TO ACCOMMODATE NEW MECHANICAL, ELECTRICAL, TECHNOLOGY, AND FIRE PROTECTION ABOVE AND AT CEILING.
- 6 EXISTING CEILING PADS THIS ROOM TO BE REPLACED WITH SPECIALTY ACOUSTICAL CEILING PADS, REFER TO SPECS.
- (7) MOVABLE PARTITION SLOT SUPPORTED FROM EXISTING STRUCTURE ABOVE. 8 NEW ACOUSTICAL BAFFLES TO BE SUSPENDED FROM EXISTING STRUCTURE ABOVE BY HANGER BOLTS. MODIFY ACOUSTICAL PADS AS NEEDED TO ACCOMMODATE CABLES. REFER TO SPECS.














GENERAL PLAN NOTES:

- LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS. B. PLAN DIMENSIONS TO MASONRY WALLS ARE TO FACE OF ROUGH MASONRY.
- REQUIRED WITHIN METAL STUD WALLS FOR WALL MOUNTED ITEMS. REFER TO DEMOLITION SHEETS FOR ADDITIONAL PATCHING AND REPAIR WORK.
- E. REFER TO FINISH PLANS FOR INTERIOR ELEVATIONS, LOCATION AND EXTENT
- F. REFER TO EQUIPMENT PLANS FOR CASEWORK, DISPLAY BOARDS, LOCKERS, AND OTHER ADDITIONAL TYPICAL EQUIPMENT NOTES AND INFORMATION.
- G. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROOM PLANS AND TOILET ACCESSORIES.









PLASTIC LAMINATE


VERTICAL BLOCKING ------4" VINYL BASE, B1 ------







		PLASTI	C LA	MINATE CASEWORK SCHEDULE
	MARK	CATALOG NUMBER	WIDTH	DESCRIPTION
	B1 B2	10129 10315		24"D X 29"H 2 DOORS, ADJUSTABLE SELF.LOCKABLE 24"D X 29"H 2 FILE DRAWERS, LOCKABLE
		GENER	ALN	NOTES (APPLIES TO PLASTIC LAMINATE CASEWORK)
		"A-800" SE ADDITIONAL	RIES D	
		INDUSTRIES, ONLY. SEE	INC (I SPECIF	PURPOSES ONLY, MODEL NUMBERS ARE TAKEN FROM STEVENS UNLESS NOTED OTHERWISE) AND ARE FOR CABINET REQUIREMENTS ICATIONS FOR CABINET CONSTRUCTION METHODS. AND CASEWORK DIMENSIONS WITH CASEWORK MANUFACTURER.
	D.	ALL COUNT BACKSPLASI	ERTOPS	TO BE PLASTIC LAMINATE WITH 4" HIGH PLASTIC LAMINATE OR ENDSPASH AT ALL LOCATIONS WHERE COUNTERTOP MEETS E (UNLESS NOTED OTHERWISE).
		PROVIDE 3N	IM PVC	E CONLESS NOTED OTHERWISE). E EDGE ON ALL PLASTIC LAMINATED COUNTERTOPS AND BACKSPLAS H TOE SPACE ON ALL BASE AND FULL HEIGHT CABINETS.
	G.			EWORK SURFACES TO BE PLASTIC LAMINATE FINISHED, INCLUDING DF CABINETRY (UNLESS NOTED OTHERWISE).
5		PROVIDE CO	NTINUC	EWORK ENDS SHALL BE FINISHED TO MATCH CASEWORK FRONTS. DUS PLASTIC LAMINATE SLOPED TOPS ON ALL WALL AND FULL HEI G OTHERWISE NOTED).
		FILLER PAN TO MAKE C	ELS, TR ASEWOF	RIM, AND MOLDING PROVIDED SHALL BE CONTINUOUS AS NECESSAI RK CONTINUOUS TO ADJACENT PARTITION, CEILING, AND/OR BULKH ACTURER / INSTALLER SHALL PROVIDE ALL FILLERS AND SCRIBES
				COMPLETE AND FINISHED CASEWORK INSTALLATION. N ALL CABINET DRAWERS AND DOORS, KEYED ALIKE BY ROOM.
				BINETS SHALL BE ALIGNED. REQUIRES SHIMMING, PROVIDE ONLY APPROVED METAL SHIMS.
$\begin{array}{c c c c c c c c c c c c c c c c c c c $		PROVIDE JC	INT SE	N FRONT OF A PIPE CHASE SHALL HAVE REMOVABLE BACKS.
ATION CABINETS: PL COUNTERTOP: PL 1/4"=1'-0" A-131 2		PROVIDE 4"	HIGH	R CASEWORK. VINYL COVE BASE AT ALL TOE SPACE AREAS AND AT EXPOSED IDES OF CABINETS ADJACENT TO TOE SPACES. BY FLOORING
	Q.		ELECTRI	ICAL DRAWINGS AND SCHEDULES FOR DEVICE TYPES, HEIGHTS AND
	R.	REFER TO I		NG DRAWINGS AND SCHEDULES FOR FIXTURE TYPES AND LOCATION NG DRAWINGS FOR PLUMBING CONNECTIONS.
				LING AND PATCHING OF CASEWORK AND COUNTERTOPS AS REQUIN OF PIPING OR CONDUIT SHALL BE BY CASEWORK MANUFACTURER
		INSTALLER.	'G" SEF	RIES SHEETS FOR MOUNTING HEIGHTS OF EQUIPMENT AND
				${\sf S}$ (applies to plastic laminate casework)
		LINE OF FI		
	$\begin{pmatrix} 2 \\ 3 \end{pmatrix}$	FLOORING	INSTALL	
		25"D COUN	ITERTOF	
	5	NOTED OTH		
	MILL	VORK (GEN	ERAL NOTES
				(A-820) FOR FINISH INFORMATION. REFERENCE WRITTEN FOR ADDITIONAL INFORMATION.
				MOLDING PROVIDED SHALL BE CONTINUOUS AS NECESSARY TO M ADJACENT PARTITION, CEILING, AND/OR BULKHEAD.
				S SHIMMING. ONLY APPROVED METAL SHIMS SHALL BE USED.
				AT ALL TOE SPACE AREAS AND AT EXPOSED SURFACES AND SIDE TOE SPACES. BY FLOORING CONTRACTOR.
	E. FIELD VE			
	G. ALL EXPO	OSED SURFA		WINGS AND SCHEDULES FOR DEVICE TYPES, HEIGHTS, AND LOCATI D BE PLASTIC LAMINATE FINISHED, INCLUDING OPEN INTERIORS OF
	CABINETR	Ϋ́.		HALL BE ALIGNED.
				D BE FINISHED.
	J. ALL CABI	NETS TO BE	LOCK	ABLE, KEY ALIKE BY ROOM.
	K. ALL PLAS	STIC LAMINA	E COU	INTERTOPS TO HAVE 3MM PVC EDGE.
		_		








- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE
- ÍSSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS
- . ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO
- INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING












GENERAL FINISH PLAN NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING
- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE
- FINISH WORK HAS PROCEEDED. D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD.
- F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION.
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES.
- H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED ON PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED TYPE/COLOR WITH ARCHITECT.
- PAINT ALL NEW DOOR FRAMES TO MATCH EXISTING (BRONZE COLOR, P8) ALL SIDES UNLESS NOTED OTHERWISE. PAINT EXISTING DOOR FRAMES IN ADMIN AREA TO MATCH EXISTING (BRONZE COLOR, P8). K. UNLESS NOTED OTHERWISE, PAINT GYPSUM BOARD AND OR PLASTER CE
- AND BULKHEADS SHERWIN WILLIAMS SW7007. . EXISTING FABRIC WRAPPED TACKABLE WALLS, TACKABLE PANELS, MARKERBOARDS, TACKBOARDS OR SIGNAGE SHALL REMAIN. M. OWNER HAS FINAL CONFIRMATION TO COVER PAINTED MURALS WITH NEW

PAINT. VERIFY WITH OWNER.	
~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	·····
FINISH SYMBOL LEGEND:	AD-01




FLOOR TRANSITION STRIP AS REQUIRED


INDICATES DIRECTION OF FLOOR MATERIAL GRAIN

## FINISH PLAN NOTES:

(ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)

- (1) NO NEW FINISHES THIS ROOM, EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES. (2) WALL AND FLOOR TILE, REFER TO FINISH LEGEND AND ELEVATION ON
- SHEET 4/A-862
- (3) PAINT, P3 AND P4. SEE FINISH LEGEND AND ELEVATION ON SHEET A-862.
- (4) paint bulkhead, slanted wall, and/or light cove, p6
- 5) EXISTING FRAMED WALL GRAPHIC TO REMAIN.
- (6) LOCKERS, PAINT, P5.
- 7) EXISTING WALL MURAL TO REMAIN
- 8) PAINT, P2. (9) EXISTING BRICK TO REMAIN. NO NEW FINISH TO BE APPLIED.
- 10) ROLLED CARPET ON MEDIA STEPS, C4
- 1) WALL COATING, W2
- 12) CARPET, C5.
- (13) CARPET C3 ENDS HERE.
- (14) LVT, LVT2
- (15) ALTERNATE: PLASTIC LAMINATE COUNTERTOP PL4






SCALE: 1/8" = 1'-0"


## **GENERAL DEMOLITION NOTES**

- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS.
- B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS SHEET.
- C. CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
- E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.
- F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION. VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL. REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS.
- G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER. H. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS
- REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE). I. WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION
- AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE PUBLIC. J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER
- OWNERS' DIRECTION, UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEMS ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED.
- K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES
- EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECEIVE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW FINISHES.
- N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED, PATCH OPENINGS AND/OR SURFACES AS REQUIRE TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT OF ITEMS TO REMOVED.
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING. P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE
- FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION. Q. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF
- DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO THEIR SCOPE OF WORK. R. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF
- SITE S. REFER TO THE STRUCTURAL, MECHANICAL, PLUMBING, ELECTRICAL AND TECHNOLOGY DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK.
- T. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING, ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE.
- U. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER TO SPECIFICATIONS AND DRAWINGS FOR REQUIREMENTS AND SPECIAL CONDITIONS.
- V. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW CEILING PADS.

## **DEMOLITION PLAN NOTES:**

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)
- 1 REMOVE TOILET AND URINAL PARTITIONS IN THEIR ENTIRETY. PREP FLOOR AND WALLS TO RECEIVE NEW HARDWARE AND PARTITIONS IN SAME LOCATION. SEE ARCHITECTURAL PLAN
- 2 REMOVE RECEPTION DESK IN ITS ENTIRETY. PREP AREA TO RECEIVE NEW FINISHES AND NEW RECEPTION COUNTER.
- 3 REMOVE EXISTING CARPET FLOORING AND VINYL WALL BASE SYSTEMS IN ITS ENTIRETY INCLUDING ALL MASTICS. PREPARE ALL SURFACES FOR NEW FINISHES.
- REMOVE EXISTING VCT AND VINYL WALL BASE SYSTEMS IN ITS ENTIRETY  ${igsquirt}$  INCLUDING ALL MASTICS. ADHESIVES AND SEALERS. PREPARE ALL SURFACES FOR NEW FINISHES.
- 5 REMOVE CERAMIC OR PORCELAIN TILE FLOORING AND WALL SYSTEM IN ITS - ENTIRETY, PREPARE, FLOOR AND WALL FOR NEW FINISHES.
- 6 REMOVE EXISTING DOOR, FRAME AND HARDWARE SYSTEM IN ITS ENTIRETY.
- <u>______</u> 7 REMOVE WALL COVERING IN ITS ENTIRETY. PREPARE WALL FOR NEW / FINISHES.
- REMOVE EXISTING BASKETBALL BACKSTOPS AND SUPPORTS COMPLETE ALLOW NEW SUPPORTS AND BACKSTOPS. WHERE APPLICABLE, PREP EXISTING STRUCTURE TO BE RETROFITTED FOR NEW BASKETBALL BACKSTOPS AND SUPPORTS
- 9 REMOVE ACOUSTICAL BOARD CEILING, GRID AND SUSPENSION SYSTEM IN ITS ENTIRETY. PREP REMAINING GRID FOR NEW CONSTRUCTION. REFER TO 2/A-102 FOR COORDINATION W/ EXISTING CONDITIONS WHERE PRESENT.
- REMOVE EXISTING SAFETY WALL PADDING, PATCH AND SMOOTH OUT WALL TO ACCEPT NEW.
- REMOVE EXISTING VINYL WALLCOVERING ON FOLDING PARTITION DOOR. ____ PREPARE FOR NEW.
- MEDIA CENTER SHELVING TO BE MOVED AND STORED/PROTECTED, THEN EINSTALLED AFTER CARPET IS REPLACED.
- 13 REMOVE METAL STUDS AND GYPSUM BOARD STUD WALL IN ITS ENTIRETY. 13 REMOVE METAL STUDS AND GYPSUM BOARD STUD WALL IN ITS ENTIRETY. PATCH AND REPAIR ADJACENT FLOOR AND WALL AS REQUIRED TO ACCEPT NEW FINISHES.
- NEW FINISHES. 14 CAREFULLY REMOVE AND STORE EXISTING PLUMBING FIXTURE, THEN REPLACE IN SAME POSITION AFTER NEW FINISHES ARE COMPLETED ON WALLS/ FLOORS ADJACENT. REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
- 15 REMOVE BASE CABINETS, COUNTERTOP, AND WALL CABINETS WHERE PRESENT COMPLETE. PATCH AND REPAIR FLOOR AND WALLS AS REQUIRED TO RECEIVE NEW FINISHES.
- 16 EXISTING WOOD GYM FLOOR TO BE SANDED PER SPECS. REMOVE EXISTING VINYL WALL BASE THIS ROOM COMPLETE, PREP FOR NEW BASE. REFER TO FINISH PLANS AND STRIPING PLAN FOR NEW CONSTRUCTION.
- 17 EXISTING BLEACHERS WITH UNDERSLUNG SCOREBOARD CONTROLS TO BE DISCONNECTED FROM POWER THEN CAREFULLY REMOVED, STORED AND PROTECTED FOR SANDING GYM FLOOR. THEN, REPLACE BLEACHERS IN SAME POSITION AFTER NEW FINISHES ARE PLACED.
- 18 EXISTING VOLLEYBALL SLEEVE LOCATION- CAREFULLY REMOVE FOR SANDING GYM FLOOR THEN REPLACE IN SAME LOCATION.
- 19 WHERE APPLICABLE, EXISTING THRESHOLD TRANSITION PLATE AND HARDWARE TO BE CAREFULLY REMOVED FOR SANDING GYM FLOOR, THEN REPLACED IN SAME POSITION.
- 20 WHERE PRESENT, REMOVE EXISTING FLOOR BOXES, PATCH AND REPAIR FLOOR AS NEEDED TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR ADDITIONAL INFO.
- 21 REMOVE PLUMBING FIXTURES IN THEIR ENTIRETY. CUT AND CAP LINE BELOW WALL OR FLOOR SURFACE. UNLESS NOTED OTHERWISE ON PLUMBING DRAWINGS, REMOVE ALL ACCESSORIES AND WALL AND FLOOR FINISHES. PATCH AND REPAIR FLOOR AND/OR WALL AS REQUIRED TO ACCEPT NEW FINISHES. SEE ELECTRICAL FOR MORE INFORMATION.
- 22 EXISTING DOOR AND FRAME TO BE REMOVED. PREP FOR NEW. 23 REMOVE EXISTING ACOUSTIC PADS. CLEAN GRID AND PREP TO RECEIVE
- NEW ACOUSTIC PADS. 24 ALTERNATE: CAREFULLY REMOVE EXISTING PLASTIC LAMINATE COUNTERTOPS IN THEIR ENTIRETY. SECURE AND STORE SINK AND FAUCET ASSEMBLY TO BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING DRAWINGS FOR PLAN
- ADDUTIONAL INFO 25 CUT AND REMOVE EXISTING VCT TILE 4" FROM THE OUTER MOST FLOOR GRAPHIC LINE. FLOOR GRAPHIC TO REMAIN AND PROTECTED.






## GENERAL DEMOLITION NOTES


- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS.
  B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS SHEET.
- CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
  E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE
- TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION. VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL.
- REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS. G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL
- DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER.H. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS
- REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE). WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION
- AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE PUBLIC. J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER
- OWNERS' DIRECTION, UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEMS ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED. K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING
- CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR, OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES
- .. EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECEIVE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW FINISHES.
   N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, A
- ADJACENT WALLS ON BOENLADS AND REMOVED, PAICH FLOORS, CEILINGS, AN ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED, PATCH OPENINGS AND/OR SURFACES AS REQUIRE TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT OF ITEM: TO REMOVED.
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING.
  P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE
- FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION. 2. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO
- THEIR SCOPE OF WORK. R. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF
- SITE. S. REFER TO THE STRUCTURAL, MECHANICAL, PLUMBING, ELECTRICAL AND TECHNOLOGY DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK. T. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING,
- ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE. U. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER TO SPECIFICATIONS AND DRAWINGS FOR REQUIREMENTS AND SPECIAL
- CONDITIONS. V. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW

### CEILING PADS. DEMOLITION PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)
- 1
   REMOVE TOILET AND URINAL PARTITIONS IN THEIR ENTIRETY. PREP FLOOR AND WALLS TO RECEIVE NEW HARDWARE AND PARTITIONS IN SAME LOCATION. SEE ARCHITECTURAL PLAN
- 2
   REMOVE RECEPTION DESK IN ITS ENTIRETY. PREP AREA TO RECEIVE NEW FINISHES AND NEW RECEPTION COUNTER.

   3
   REMOVE EXISTING CARPET FLOORING AND VINYL WALL BASE SYSTEMS IN RECEPTION COUNTER.
- ITS ENTIRETY INCLUDING ALL MASTICS. PREPARE ALL SURFACES FOR NEW FINISHES. REMOVE EXISTING VCT AND VINYL WALL BASE SYSTEMS IN ITS ENTIRETY
- INCLUDING ALL MASTICS. ADHESIVES AND SEALERS. PREPARE ALL SURFACES FOR NEW FINISHES.
   REMOVE CERAMIC OR PORCELAIN TILE FLOORING AND WALL SYSTEM IN ITS
- ENTIRETY, PREPARE FLOOR AND WALL FOR NEW FINISHES
- 6 REMOVE EXISTING DOOR, FRAME AND HARDWARE SYSTEM IN ITS ENTIRETY. 7 REMOVE WALL COVERING IN ITS ENTIRETY. PREPARE WALL FOR NEW 7 REMOVE WALL COVERING IN ITS ENTIRETY. PREPARE WALL FOR NEW 7 REMOVE WALL COVERING IN ITS ENTIRETY. PREPARE WALL FOR NEW
- FINISHES.
- ALLOW NEW SUPPORTS AND BACKSTOPS. WHERE APPLICABLE, PREP EXISTING STRUCTURE TO BE RETROFITTED FOR NEW BASKETBALL BACKSTOPS AND SUPPORTS REMOVE ACOUSTICAL BOARD CEILING, GRID AND SUSPENSION SYSTEM IN
- ITS ENTIRETY. PREP REMAINING GRID FOR NEW CONSTRUCTION. REFER TO 2/A-102 FOR COORDINATION W/ EXISTING CONDITIONS WHERE PRESENT.
- CLASSROON C-130
  REMOVE EXISTING SAFETY WALL PADDING, PATCH AND SMOOTH OUT WALL TO ACCEPT NEW.
  - IIREMOVE EXISTING VINYL WALLCOVERING ON FOLDING PARTITION DOOR.PREPARE FOR NEW.MEDIA CENTER SHELVING TO BE MOVED AND STORED/PROTECTED, THEN
  - REINSTALLED AFTER CARPET IS REPLACED.
  - PATCH AND REPAIR ADJACENT FLOOR AND WALL AS REQUIRED TO ACCEPT NEW FINISHES.
  - 14 CAREFULLY REMOVE AND STORE EXISTING PLUMBING FIXTURE, THEN REPLACE IN SAME POSITION AFTER NEW FINISHES ARE COMPLETED ON WALLS/ FLOORS ADJACENT. REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
  - 15 REMOVE BASE CABINETS, COUNTERTOP, AND WALL CABINETS WHERE PRESENT COMPLETE. PATCH AND REPAIR FLOOR AND WALLS AS REQUIRED TO RECEIVE NEW FINISHES.
  - EXISTING WOOD GYM FLOOR TO BE SANDED PER SPECS. REMOVE EXISTING VINYL WALL BASE THIS ROOM COMPLETE, PREP FOR NEW BASE. REFER TO FINISH PLANS AND STRIPING PLAN FOR NEW CONSTRUCTION.
     EXISTING BLEACHERS WITH UNDERSLUNG SCOREBOARD CONTROLS TO BE
  - DISCONNECTED FROM POWER THEN CAREFULLY REMOVED, STORED AND PROTECTED FOR SANDING GYM FLOOR. THEN, REPLACE BLEACHERS IN SAME POSITION AFTER NEW FINISHES ARE PLACED.
  - 18 EXISTING VOLLEYBALL SLEEVE LOCATION CAREFULLY REMOVE FOR SANDING GYM FLOOR THEN REPLACE IN SAME LOCATION.
  - 19 WHERE APPLICABLE, EXISTING THRESHOLD TRANSITION PLATE AND HARDWARE TO BE CAREFULLY REMOVED FOR SANDING GYM FLOOR, THEN REPLACED IN SAME POSITION.
  - 20 WHERE PRESENT, REMOVE EXISTING FLOOR BOXES, PATCH AND REPAIR FLOOR AS NEEDED TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR ADDITIONAL INFO.
  - 21 REMOVE PLUMBING FIXTURES IN THEIR ENTIRETY. CUT AND CAP LINE BELOW WALL OR FLOOR SURFACE. UNLESS NOTED OTHERWISE ON PLUMBING DRAWINGS, REMOVE ALL ACCESSORIES AND WALL AND FLOOR FINISHES. PATCH AND REPAIR FLOOR AND/OR WALL AS REQUIRED TO ACCEPT NEW FINISHES. SEE ELECTRICAL FOR MORE INFORMATION.
    22 EXISTING DOOR AND FRAME TO BE REMOVED. PREP FOR NEW.
  - 23 REMOVE EXISTING ACOUSTIC PADS. CLEAN GRID AND PREP TO RECEIVE
  - NEW ACOUSTIC PADS. 24 ALTERNATE: CAREFULLY REMOVE EXISTING PLASTIC LAMINATE COUNTERTOPS IN THEIR ENTIRETY. SECURE AND STORE SINK AND FAUCET ASSEMBLY TO BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING DRAWINGS FOR ADDITIONAL INFO
  - ADDITIONAL INFO 25 CUT AND REMOVE EXISTING VCT TILE 4" FROM THE OUTER MOST FLOOR GRAPHIC LINE. FLOOR GRAPHIC TO REMAIN AND PROTECTED.





## GENERAL DEMOLITION NOTES

- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS.B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS
- RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS SHEET.
- C. CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
- E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.
- F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION. VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL. REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS.
- G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER.
- H. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE).
- I. WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE PUBLIC.
   J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER
- OWNERS' DIRECTION, UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEMS ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED.
- K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR, OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES
- L. EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECEIVE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW FINISHES.
- N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, AN ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED, PATCH OPENINGS AND/OR SURFACES AS REQUIRE TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT OF ITEM TO REMOVED.
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING.
  P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE
- FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION. Q. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF
- DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO THEIR SCOPE OF WORK. R. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF
- SITE. S. REFER TO THE STRUCTURAL, MECHANICAL, PLUMBING, ELECTRICAL AND TECHNOLOGY DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK.
- T. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING, ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE.
   U. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER
- DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. RE TO SPECIFICATIONS AND DRAWINGS FOR REQUIREMENTS AND SPECIAL CONDITIONS.
   V. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES
- (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW CEILING PADS.

## DEMOLITION PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)

   I
   REMOVE TOILET AND URINAL PARTITIONS IN THEIR ENTIRETY. PREP FLOOR AND WALLS TO RECEIVE NEW HARDWARE AND PARTITIONS IN SAME
- LOCATION. SEE ARCHITECTURAL PLAN


   2
   REMOVE RECEPTION DESK IN ITS ENTIRETY. PREP AREA TO RECEIVE NEW


   FINISHES AND NEW RECEPTION COUNTER.
- FINISHES AND NEW RECEPTION COUNTER.

   3
   REMOVE EXISTING CARPET FLOORING AND VINYL WALL BASE SYSTEMS IN

   ITS ENTIRETY INCLUDING ALL MASTICS. PREPARE ALL SURFACES FOR NEW
- FINISHES. A REMOVE EXISTING VCT AND VINYL WALL BASE SYSTEMS IN ITS ENTIRETY
- INCLUDING ALL MASTICS. ADHESIVES AND SEALERS. PREPARE ALL SURFACES FOR NEW FINISHES.
   REMOVE CERAMIC OR PORCELAIN TILE FLOORING AND WALL SYSTEM IN ITS
- 5 ENTIRETY, PREPARE ELOOR AND WALL FOR NEW FINISHES
- 6 REMOVE EXISTING DOOR, FRAME AND HARDWARE SYSTEM IN ITS ENTIRETY. Email info@GibraltarDesign.com Phone 317.580.5777 Fax 317.
- 7 REMOVE WALL COVERING IN ITS ENTIRETY. PREPARE WALL FOR NEW FINISHES. AD-01
- 8 REMOVE EXISTING BASKETBALL BACKSTOPS AND SUPPORTS COMPLETE ALLOW NEW SUPPORTS AND BACKSTOPS. WHERE APPLICABLE, PREP EXISTING STRUCTURE TO BE RETROFITTED FOR NEW BASKETBALL BACKSTOPS AND SUPPORTS
- 9 REMOVE ACOUSTICAL BOARD CEILING, GRID AND SUSPENSION SYSTEM IN ITS ENTIRETY. PREP REMAINING GRID FOR NEW CONSTRUCTION. REFER TO 2/A-102 FOR COORDINATION W/ EXISTING CONDITIONS WHERE PRESENT.
- 10 REMOVE EXISTING SAFETY WALL PADDING, PATCH AND SMOOTH OUT WALL TO ACCEPT NEW.
- 11 REMOVE EXISTING VINYL WALLCOVERING ON FOLDING PARTITION DOOR. PREPARE FOR NEW.
- 12 MEDIA CENTER SHELVING TO BE MOVED AND STORED/PROTECTED, THEN REINSTALLED AFTER CARPET IS REPLACED.
- 13
   REMOVE METAL STUDS AND GYPSUM BOARD STUD WALL IN ITS ENTIRETY.

   PATCH AND REPAIR ADJACENT FLOOR AND WALL AS REQUIRED TO ACCEPT NEW FINISHES.
- 14 CAREFULLY REMOVE AND STORE EXISTING PLUMBING FIXTURE, THEN REPLACE IN SAME POSITION AFTER NEW FINISHES ARE COMPLETED ON WALLS/ FLOORS ADJACENT. REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
- 15 REMOVE BASE CABINETS, COUNTERTOP, AND WALL CABINETS WHERE PRESENT COMPLETE. PATCH AND REPAIR FLOOR AND WALLS AS REQUIRED TO RECEIVE NEW FINISHES.
- 16 EXISTING WOOD GYM FLOOR TO BE SANDED PER SPECS. REMOVE EXISTING VINYL WALL BASE THIS ROOM COMPLETE, PREP FOR NEW BASE. REFER TO FINISH PLANS AND STRIPING PLAN FOR NEW CONSTRUCTION.
- 17 EXISTING BLEACHERS WITH UNDERSLUNG SCOREBOARD CONTROLS TO BE DISCONNECTED FROM POWER THEN CAREFULLY REMOVED, STORED AND PROTECTED FOR SANDING GYM FLOOR. THEN, REPLACE BLEACHERS IN SAME POSITION AFTER NEW FINISHES ARE PLACED.
- 18 EXISTING VOLLEYBALL SLEEVE LOCATION- CAREFULLY REMOVE FOR SANDING GYM FLOOR THEN REPLACE IN SAME LOCATION.
- 19 WHERE APPLICABLE, EXISTING THRESHOLD TRANSITION PLATE AND HARDWARE TO BE CAREFULLY REMOVED FOR SANDING GYM FLOOR, THEN REPLACED IN SAME POSITION.
- 20 WHERE PRESENT, REMOVE EXISTING FLOOR BOXES, PATCH AND REPAIR FLOOR AS NEEDED TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR ADDITIONAL INFO.
- 21 REMOVE PLUMBING FIXTURES IN THEIR ENTIRETY. CUT AND CAP LINE BELOW WALL OR FLOOR SURFACE. UNLESS NOTED OTHERWISE ON PLUMBING DRAWINGS, REMOVE ALL ACCESSORIES AND WALL AND FLOOR FINISHES. PATCH AND REPAIR FLOOR AND/OR WALL AS REQUIRED TO ACCEPT NEW FINISHES. SEE ELECTRICAL FOR MORE INFORMATION.
- 22 EXISTING DOOR AND FRAME TO BE REMOVED. PREP FOR NEW. 23 REMOVE EXISTING ACOUSTIC PADS. CLEAN GRID AND PREP TO RECEIVE
- NEW ACOUSTIC PADS. ALTERNATE: CAREFULLY REMOVE EXISTING PLASTIC LAMINATE COUNTERTOPS IN THEIR ENTIRETY. SECURE AND STORE SINK AND FAUCET ASSEMBLY TO
- IN THEIR ENTIRETY. SECURE AND STORE SINK AND FAUCET ASSEMBLY TO BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING DRAWINGS FOR ADDITIONAL INFO 25 CUT AND REMOVE EXISTING VCT TILE 4" FROM THE OUTER MOST FLOOR
- GRAPHIC LINE. FLOOR GRAPHIC TO REMAIN AND PROTECTED.





## **GENERAL PLAN NOTES:**


- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS.B. PLAN DIMENSIONS TO MASONRY WALLS ARE TO FACE OF ROUGH MASONRY. PLAN DIMENSIONS TO STUD WALLS ARE TO FACE OF FINISHED GYPSUM
- BOARD OR PLASTER. PLAN DIMENSIONS TO STUD WALLS WITH CERAMIC TILE FINISH ARE TO THE FACE OF TILE BACKER BOARD.
- C. PROVIDE WOOD BLOCKING (OR METAL STRAPPING WHERE APPLICABLE) AS REQUIRED WITHIN METAL STUD WALLS FOR WALL MOUNTED ITEMS.
- D. REFER TO DEMOLITION SHEETS FOR ADDITIONAL PATCHING AND REPAIR WORK.
- E. REFER TO FINISH PLANS FOR INTERIOR ELEVATIONS, LOCATION AND EXTENT OF FINISHED FLOOR AND WALL MATERIAL
- F. REFER TO EQUIPMENT PLANS FOR CASEWORK, DISPLAY BOARDS, LOCKERS, AND OTHER ADDITIONAL TYPICAL EQUIPMENT NOTES AND INFORMATION.
   G. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROOM
- PLANS AND TOILET ACCESSORIES.
- PLAN LEGEND:


INDICATES WALL TYPES REFER TO G-301 FOR WALL THICKNESS, HEIGHT, AND COMPOSITION.

# PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)
- INSTALL NEW MOTORIZED FORWARD BASKETBALL BACKSTOP AND SUPPORT FRAMING IN SAME LOCATION AS EXISTING. ADJUSTABLE HEIGHT. WHERE APPLICABLE, RETROFIT NEW SUPPORT FRAMING TO UTILIZE EXISTING IN-PLACE BEAMS.
   NEW RECEPTION COUNTER, SEE EQUIPMENT AND FINISH DRAWINGS.
- (3) NEW SAFETY WALL PADS, REFER TO 1/A-501
- (4) INSTALL NEW TOILET PARTITIONS AND URINAL PARTITIONS IN SAME LOCATION AS EXISTING. INSTALL NEW HARDWARE TO PARTITIONS. OWNER TO PROVIDED AND INSTALLED ACCESSORIES.
- (5) NEW FLOOR AND WALL TILE, SEE TRANSITION DETAILS ON 3/A-501, FINISH LEGEND AND ELEVATION 7/A-860
- (6) REFINISH EXISTING WOOD FLOOR, COURT MARKINGS AND EQUIPMENT PER SPEC, REFER TO GYMNASIUM COURT MARKING PLAN ON SHEET A/840.
- (7) EXISTING DRINKING FOUNTAINS TO BE REINSTALLED IN SAME LOCATION.
- REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
- (8) PARTITION DOOR TO RECEIVE NEW WALLCOVERING, SEE FINISH LEGEND.
- (9) REINSTALL EXISTING BLEACHERS IN SAME POSITION AFTER NEW FINISHES ARE PLACED.
- (10) ALTERNATE: INSTALL NEW ELECTRIC HAND DRYERS.
- (1) INSTALL NEW 3/4" FIRE RATED PLYWOOD ON ALL WALLS, FULL HEIGHT SEE DETAIL 2/A-501

 ALTERNATE: INSTALL NEW PLASTIC LAMINATE COUNTERTOP ON ALL EXISTING CASEWORK COUNTERS. PROVIDE A 4" BACK/SIDE SPLASH.
 INFILL EXISTING DOOR OPENING WITH NEW METAL STUD AND GYPSUM TO MATCH EXISTING ADJACENT WALL CONSTRUCTION.






UNIT "A" FIRST FLOOR FINISH PLAN SCALE: 1/8" = 1'-0"

NORTH

## GENERAL FINISH PLAN NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING
- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION. C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE
- FINISH WORK HAS PROCEEDED. D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS
- AND MATERIALS FOR ALL FINISHES. E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD.
- F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION.
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES. H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER
- CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED. I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED
- ON PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED TYPE/COLOR WITH ARCHITECT. J. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW
- INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803. K. PAINT NEW DOOR FRAMES TO MATCH EXISTING (CREAM COLOR, P8) - ALL
- SIDES UNLESS NOTED OTHERWISE. PAINT EXISTING DOOR FRAMES IN ADMIN AREA TO MATCH EXISTING (CREAM COLOR, P8). L. UNLESS NOTED OTHERWISE, PAINT GYPSUM BOARD AND OR PLASTER CEIL
- AND BULKHEADS SHERWIN WILLIAMS SW7007. M. EXISTING FABRIC WRAPPED TACKABLE WALLS, TACKABLE PANELS,
- MARKERBOARDS, TACKBOARDS OR SIGNAGE SHALL REMAIN.

## FINISH SYMBOL LEGEND:





INDICATES DIRECTION OF FLOOR MATERIAL GRAIN

## FINISH PLAN NOTES:

(ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)


- (1) NO NEW FINISHES THIS ROOM, EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES.
- (2) WALL AND FLOOR TILE, REFER TO FINISH LEGEND AND ELEVATION ON SHEET 4/A-861
- (3) PAINT, P3 AND P4. REFER TO FINISH LEGEND AND ELEVATION ON SHEET 5/A-861.
- (4) SAFETY CUSHION, SC. SEE DETAIL 1/A-501
- (5) GRAPHIC WALLCOVERING, GWC1
- (6) PAINT, P2
- (7) PAINT BULKHEAD, SLANTED WALL AND/OR LIGHT COVE, P6
- 8) EXISTING BRICK TO REMAIN
- 9) ROLLED CARPET ON MEDIA AND MUSIC STEPS, C4.
- 10) CARPET, C5.
- 11) CARPET, C3 END HERE.
- 12) PADDED WALL, SEE DETAIL 2/A-501
- (13) ALTERNATE: PLASTIC LAMINATE COUNTERS, PL4 (14) EXISTING VCT PATTERN TO REMAIN.)
- AD-01








**GENERAL DEMOLITION NOTES** 





# **GENERAL DEMOLITION NOTES**

- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS. B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS
- RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS SHEET. C. CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF
- CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
- E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.
- F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION. VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL. REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS.
- G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER. H. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS
- REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE). I. WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION
- AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE PUBLIC. J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER
- OWNERS' DIRECTION, UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEMS ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED.
- K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES
- L. EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECEIVE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW FINISHES.
- N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED, PATCH OPENINGS AND/OR SURFACES AS REQUIRE TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT OF ITEM TO REMOVED.
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING.
- P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION. Q. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF
- DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO THEIR SCOPE OF WORK. R. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE
- BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF SITE S. REFER TO THE, MECHANICAL, PLUMBING, AND ELECTRICAL DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK.
- T. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING, ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE.
- U. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER TO SPECIFICATIONS AND DRAWINGS FOR REQUIREMENTS AND SPECIAL CONDITIONS.
- V. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW CEILING PADS.


# **DEMOLITION PLAN NOTES:**

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.) 1 REMOVE TOILET AND URINAL PARTITIONS IN THEIR ENTIRETY. PREP FLOOR AND WALLS FOR NEW PARTITIONS AND NEW HARDWARE IN SAME LOCATION. SEE ARCHITECTURAL PLAN.
- 2 REMOVE RECEPTION DESK IN ITS ENTIRETY. PREP AREA TO RECEIVE NEW FINISHES AND RECEPTION COUNTER.
- 3 REMOVE EXISTING CARPET FLOORING AND VINYL WALL BASE SYSTEMS IN ITS ENTIRETY INCLUDING ALL MASTICS. PREPARE ALL SURFACES FOR NEW
- FINISHES. 4 REMOVE EXISTING VCT AND VINYL WALL BASE SYSTEMS IN ITS ENTIRETY  $\stackrel{ au}{\longrightarrow}$  INCLUDING ALL MASTICS. ADHESIVES AND SEALERS. PREPARE ALL SURFACES FOR NEW FINISHES.
- 5 REMOVE CERAMIC OR PORCELAIN TILE FLOORING AND WALL TILE SYSTEM □ ITS ENTIRETY. PREPARE FLOOR AND WALL FOR NEW FINISHES.
- 6 REMOVE METAL STUDS AND GYPSUM BOARD WALL IN ITS ENTIRETY. PATCH AND REPAIR ADJACENT FLOOR AND WALL AS REQUIRED TO ACCEPT NEW

FINISHES. SALVAGE OWNER METAL CABINET FOR REUSE. REMOVE EXISTING DOOR, FRAME AND HARDWARE SYSTEM IN ITS ENTIRETY.

- REMOVE EXISTING VINYL WALLCOVERING ON FOLDING PARTITION DOOR. PREPARE FOR NEW. CAFETERIA SIDE ONLY. 9 REMOVE ACOUSTICAL BOARD CEILING, GRID AND SUSPENSION SYSTEM IN ITS ENTIRETY. PREP REMAINING GRID FOR NEW CONSTRUCTION. REFER TO 2/A-102 FOR COORDINATION W/ EXISTING CONDITIONS WHERE PRESENT.
- 10 MEDIA CENTER SHELVING TO BE MOVED AND STORED/PROTECTED, THEN REINSTALLED AFTER CARPET IS REPLACED.
- 11 REMOVE EXISTING REVOLVING CUBBIE CASEWORK IN ITS ENTIRETY. PREPARE ALL SURFACES FOR NEW FINISHES.
- 12 REMOVE CABINETS, COUNTERTOP, AND WALL CABINETS WHERE PRESENT COMPLETE. PATCH AND REPAIR FLOOR AND WALLS AS REQUIRED TO RECEIVE NEW FINISHES.
- 13 CAREFULLY REMOVE AND STORE EXISTING PLUMBING FIXTURE, THEN REPLACE IN SAME POSITION AFTER NEW FINISHES ARE COMPLETED ON WALLS/ FLOORS ADJACENT. REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
- 14 WHERE PRESENT, REMOVE EXISTING FLOOR BOXES, PATCH AND REPAIR FLOOR AS NEEDED TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR AD-1 2/22/24 ADDENDUM #1 ADDITIONAL INFO.
- [15] REMOVE EXISTING ACOUSTIC PADS. CLEAN GRID AND PREP TO RECEIVE NEW ACOUSTIC PADS.
- [16] ALTERNATE: CAREFULLY REMOVE EXISTING PLASTIC LAMINATE COUNTERTOPS IN THEIR ENTIRETY. SECURE AND STORE SINK AND FAUCET ASSEMBLY TO BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING DRAWINGS FOR ADDITIONAL INFO.
- CUT AND REMOVE EXISTING VCT TILE 4" FROM THE OUTER MOST FLOOR GRAPHIC LINE. FLOOR GRAPHIC TO REMAIN AND PROTECTED.
- 18 REMOVE EXISTING PLASTIC LAMINATE BASE AND WALL CABINETS IN THEIR ENTIRETY. SECURE AND STORE SINK AND FAUCET ASSEMBLY TO BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING DRAWINGS FOR ADDITIONAL INFO.





## **GENERAL PLAN NOTES:**


- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS. B. PLAN DIMENSIONS TO MASONRY WALLS ARE TO FACE OF ROUGH MASONRY.
- PLAN DIMENSIONS TO STUD WALLS ARE TO FACE OF FINISHED GYPSUM BOARD OR PLASTER. PLAN DIMENSIONS TO STUD WALLS WITH CERAMIC TILE FINISH ARE TO THE FACE OF TILE BACKER BOARD. C. PROVIDE WOOD BLOCKING (OR METAL STRAPPING WHERE APPLICABLE) AS
- REQUIRED WITHIN METAL STUD WALLS FOR WALL MOUNTED ITEMS.
- D. REFER TO DEMOLITION SHEETS FOR ADDITIONAL PATCHING AND REPAIR WORK. E. REFER TO FINISH PLANS FOR INTERIOR ELEVATIONS, LOCATION AND EXTENT
- OF FINISHED FLOOR AND WALL MATERIAL F. REFER TO EQUIPMENT PLANS FOR CASEWORK, DISPLAY BOARDS, LOCKERS,
- AND OTHER ADDITIONAL TYPICAL EQUIPMENT NOTES AND INFORMATION. G. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROOM PLANS AND TOILET ACCESSORIES.


# PLAN LEGEND:

INDICATES WALL TYPES REFER TO G-301 FOR WALL THICKNESS, HEIGHT, AND COMPOSITION.

# PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.) (1) ALTERNATE: INSTALL NEW ELECTRIC HAND DRYERS.
- (2) NEW RECEPTION COUNTER, SEE EQUIPMENT AND FINISH DRAWINGS.
- $\overline{(3)}$  NOT USED.
- 4 INSTALL NEW TOILET PARTITIONS AND URINAL PARTITIONS IN SAME LOCATION AS EXISTING. INSTALL NEW HARDWARE TO PARTITIONS. OWNER TO PROVIDE AND INSTALLED ACCESSORIES.
- 5 NEW FLOOR AND WALL TILE, SEE TRANSITION DETAILS ON A/820, FINISH LEGEND.
- (6) casework and/or millwork, refer to equipment plans
- 7 EXISTING DRINKING FOUNTAINS TO BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
- 8 ALTERNATE: INSTALL NEW PLASTIC LAMINATE COUNTERTOP ON ALL EXISTING CASEWORK COUNTERS. PROVIDE A 4" BACK/SIDE SPLASH.
- (9) CUBICLE CURTAIN AND TRACK (1'-0" RADIUS AT CORNER). SEE DETAIL
- ON SHEET A-820 (10) INFILL EXISTING DOOR OPENING WITH NEW METAL STUD AND GYPSUM TO MATCH EXISTING ADJACENT WALL CONSTRUCTION.








- B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
- C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE FINISH WORK HAS PROCEEDED.
- D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD.
- F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION.
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES. H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER
- CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED. I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED
- ON PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED DISTRICT WIDE -J. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW
- INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803. K. PAINT NEW DOOR FRAMES TO MATCH EXISTING (CREAM COLOR, P8) - ALL
- SIDES UNLESS NOTED OTHERWISE. PAINT EXISTING DOOR FRAMES IN ADMIN AREA TO MATCH EXISTING (CREAM COLOR, P8).
- L. UNLESS NOTED OTHERWISE, PAINT GYPSUM BOARD AND OR PLASTER CEIL AND BULKHEADS SHERWIN WILLIAMS SW7007. M. EXISTING FABRIC WRAPPED TACKABLE WALLS, TACKABLE PANELS,
- MARKERBOARDS, TACKBOARDS OR SIGNAGE SHALL REMAIN.

# FINISH SYMBOL LEGEND:



INDICATES DIRECTION OF FLOOR MATERIAL GRAIN

# FINISH PLAN NOTES:

(ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)

- (1) NO NEW FINISHES THIS ROOM, EXCLUDING DOOR FRAMES CONNECTED TO
- OTHER ROOMS THAT RECEIVE NEW FINISHES. 2 WALL AND FLOOR TILE, REFER TO FINISH LEGEND AND ELEVATION ON SHEET 4/A-861
- 3 PAINT, P3 AND P4. REFER TO FINISH LEGEND AND ELEVATION ON SHEET 5/A-861.
- (4) SAFETY CUSHION, SC. SEE DETAIL 1/A-501
- 5 GRAPHIC WALLCOVERING, GWC1
- (6) PAINT, P2
- (7) PAINT BULKHEAD, SLANTED WALL AND/OR LIGHT COVE, P6
- 8) EXISTING BRICK TO REMAIN
- 9) ROLLED CARPET ON MEDIA AND MUSIC STEPS, C4.
- 10) CARPET, C5.
- 11) CARPET, C3 END HERE.
- 12) PADDED WALL, SEE DETAIL 2/A-501
- (13) ALTERNATE: PLASTIC LAMINATE COUNTERS, PL4 (14) EXISTING VCT PATTERN TO REMAIN.)
- AD-01

