

March 11, 2024

DISTRICT WIDE - TRI-CREEK ELEMENTARY SCHOOLS' FINISHES AND LOWELL MIDDLE SCHOOL MEDIA CENTER RENOVATION Lowell, IN 46356

TO: ALL BIDDERS OF RECORD

This Addendum forms a part of and modifies the Bidding Requirements, Contract Forms, Contract Conditions, the Specifications, and the Drawings dated February 9, 2024 by Gibraltar Design. Acknowledge receipt of the Addendum in the space provided on the Bid Form. Failure to do so may subject the Bidder to disqualification.

This Addendum consists of Pages ADD 3-1 through ADD 3-2 and attached Addendum No. 3 from Gibraltar Design dated March 8, 2024 and consisting of 4 pages, Specification Sections 09 12 00 - Acoustical Spray, 09 91 00 - Painting, 10 21 23 - Cubicle Curtains and Tracks, 11 19 90 - Wall Padding, and 59 drawings.

A. <u>SPECIFICATION SECTION 00 00 20 - TABLE OF CONTENTS</u>

1. Add:

Specification Section 09 12 00 - Acoustical Spray Specification Section 10 21 23 - Cubicle Curtains and Tracks Specification Section 11 19 90 - Wall Padding

B. SPECIFICATION SECTION 00 31 00 - BID FORM

1. Replace:

Specification Section 00 31 00 - Bid Form with the attached revised section

C. <u>SPECIFICATION SECTION 01 12 00 - MULTIPLE CONTRACT SUMMARY</u>

A. BID CATEGORY NO. 01 - GENERAL TRADES

1. Add:

Specification Section 10 21 23 - Cubicle Curtains and Tracks Specification Section 11 19 90 - Wall Padding

B. BID CATEGORY NO. 02 - METAL STUDS/DRYWALL/ACOUSTICS

1. **Add:**

Specification Section 09 12 00 - Acoustical Spray

2. Add:

Clarification No. 5:

The **Bid Category No. 2 Contractor** shall be responsible to clean existing ceiling grid as indicated on the Contract Documents.

D. SPECIFICATION SECTION 01 23 00 - ALTERNATES

1. Replace:

Specification Section 01 23 00 - Alternates with the attached revised section

CONTRACTOR'S BID FOR PUBLIC WORKS FORM NO. 96

Format (Revised 2013) (Amended for TCSC)

DISTRICT WIDE - TRI-CREEK ELEMENTARY SCHOOL'S FINISHES AND LOWELL MIDDLE SCHOOL MEDIA CENTER RENOVATION

Tri-Creek School Corporation

Lowell, IN

PART I

(To be completed for all bids. Please type or print)

	Date (month, day, year):
BIDDER (Firm)	
Address	P.O. Box
City/State/Zip	
Telephone Number:	Email Address:
Person to contact regarding this Bid_	
Pursuant to notices given, the undersigned complete the public works project of:	gned offers to furnish labor and/or materials necessary to
Insert C	Category No. (s) and Name(s)
Middle School Media Center Renova	<i>te - Tri-Creek Elementary School's Finishes & Lowell</i> <i>tion</i> , in accordance with Plans and Specifications prepared <i>leridian St., Ste. 300, Indianapolis, IN</i> 46260, as follows:
BASE BID	

For the sum of

(Sum in words)

DOLLARS (\$_____

_)

(Sum in figures)

The undersigned acknowledges receipt of the following Addenda: Receipt of Addenda No. (s)

PROPOSAL TIME

Bidder agrees that this Bid shall remain in force for a period of sixty (60) consecutive calendar days from the due date, and Bids may be accepted or rejected during this period. Bids not accepted within said sixty (60) consecutive calendar days shall be deemed rejected.

Attended pre-bid conference	YES	NO
Has visited the jobsite	YES	NO

The Bidder has reviewed the Guideline Schedule in Section 01 32 00 and the intent Of the schedule can be met.

YES _____ NO _____

The Bidder has included their Written Drug Testing Plan that covers all employees of the bidder who will perform work on the public work project and meets or exceeds the requirements set in IC 4-13-18-5 or IC 4-13-18-6.

YES _____ NO____

The Skillman Corporation's diversity initiative is to create a program to encourage, assist and measure the active participation of Minority- Owned, Women-Owned, Veteran – Owned and Disabled Individual-Owned Businesses. The Program is to ensure that MWVDBEs are provided full and equal opportunity to participate in all Skillman Corporation's Projects.

Bidder has included:	DBE: YES	%	NO
	MBE: YES	%	NO
	WBE: YES	%	NO
	VBE: YES	%	NO

The undersigned further agrees to furnish a bond or certified check with this Bid for an amount specified in the Notice to Bidders. If Alternate Bids apply, submit a proposal for each in accordance with the Plans and Specifications.

If additional units of material included in the contract are needed, the cost of units must be the same as that shown in the original contract if accepted by the governmental unit. If the bid is to be awarded on a unit basis, the itemization of the units shall be shown on a separate attachment.

The contractor and his subcontractors, if any, shall not discriminate against or intimidate any employee, or applicant for employment, to be employed in the performance of this contract, with respect to any matter directly or indirectly related to employment because of race, religion, color, sex, national origin, or ancestry. Breach of this covenant may be regarded as a material breach of the contract.

CERTIFICATION OF USE OF UNITED STATES STEEL PRODUCTS (if applicable)

I, the undersigned bidder, or agent as a contractor on a public works project, understand my statutory obligation to use steel products made in the United States (I.C. 5-16-8-2). I hereby certify that I and all subcontractors employed by me for this project will use U.S. steel on this project if awarded. I understand that violations hereunder may result in forfeiture of contractual payments.

ALTERNATE BIDS

A blank entry or an entry of "No Bid", "N/A", or similar entry on any Alternate will cause the bid to be rejected as non-responsive only if that Alternate is selected. If no change in the bid amount is required, indicate "No Change".

<u>MARK "ADD" OR "DEDUCT" FOR EACH ALTERNATE</u>

<u>Alternate Bid No. 1 – Counter Tops</u>		
Change the Base Bid the sum of(sum in words)	DOLLARS (\$) (sum in figures)	ADD DEDUCT
Alternate Bid No. 2 – Electric Hand Dryers		
Change the Base Bid the sum of(sum in words)	DOLLARS (\$) (sum in figures)	ADD DEDUCT
<u>Alternate Bid No. 3 – Carpet Manufacturer</u>		
Change the Base Bid the sum of(sum in words)	DOLLARS (\$) (sum in figures)	ADD DEDUCT

Alternate Bid No. 4 – Basketball Backstops and Supports

Change the Base Bid the sum of(sum in words)		
	DOLLARS (\$(sum in figures	ADD _) DEDUCT \$)
<u>Alternate Bid No. 5 – Marker Boards</u>		
Change the Base Bid the sum of(sum in words)		
	DOLLARS (\$ (sum in figures	ADD _) DEDUCT

PART II

(For projects of \$150,000 or more – IC 36-1-12-4)

These statements to be submitted under oath by each bidder with and as a part of his bid. (Attach additional pages for each section as needed.)

SECTION I EXPERIENCE QUESTIONNAIRE

1. What public works projects has your organization completed for the period of one (1) year prior to the date of the current bid?

Contract Amount	Class of Work	Completion Date	Name and Address of Owner

2. What public works projects are now in the process of construction by your organization?

Contract Amount	Class of Work	Completion Date	Name and Address of Owner

3. Have you ever failed to complete any work awarded to you?______If so, where, and why?

4. List references from private firms for which you have performed work.

SECTION II PLAN AND EQUIPMENT QUESTIONNAIRE

1. Explain your plan or layout for performing proposed Work. (Examples could include a narrative of when you could begin, complete the project, number of workers, etc. and any other information which you believe would enable the governmental unit to consider your bid.)

2. Please list the names and addresses of all subcontractors (i.e. persons or firms outside your own firm who have performed part of the work) that you have used on public works projects during the past five (5) years along with a brief description of the work done by each subcontractor.

3. If you intend to sublet any portion of the work, state the name, and addresses of each subcontractor, equipment to be used by the subcontractor, and whether you will require a bond. However, if you are unable to currently provide a listing, please understand a listing must be provided prior to contract approval. Until the completion of the proposed project, you are under a continuing obligation to immediately notify the governmental unit in the event that you subsequently determine that you will use a subcontractor on the proposed project.

4. What equipment do you have available to use for the proposed Project? Any equipment used by subcontractors may also be required to be listed by the governmental unit.

5. Have you into contracts or received offers for all materials which substantiate the prices used in preparing your proposal? If not, please explain the rationale used which corroborate the process listed.

SECTION III CONTRACTOR'S FINANCIAL STATEMENT

Attachment of Bidder's financial statement is mandatory. Any Bid submitted without said financial statement as required by statute shall thereby be rendered invalid. The financial statement provided hereunder to the governing body awarding the Contract must be specific enough in detail so that said governing body can make a proper determination of the Bidder's capability for completing the Project if awarded.

SECTION IV CONTRACTOR NON-COLLUSION AFFIDAVIT

The undersigned Bidder or agent, being duly sworn on oath, says that he has not, nor has any other member, representative, or agent of the firm, company, corporation or partnership represented by him, entered into any combination, collusion or agreement with any person relative to the price to be bid by anyone at such letting nor to prevent any person from bidding nor to induce anyone to refrain from bidding, and that this Bid is made without reference to any other bid and without any agreement, understanding or combination with any other person in reference to such bidding.

He further says that no person or persons, firms, or corporations has, have, or will receive directly or indirectly, any rebate, fee, gift, commission, or thing of value on account of such contract.

SECTION V OATH AND AFFIRMATION

I HEREBY AFFIRM UNDER THE PENALTIES OF PERJURY THAT THE FACTS AND INFORMATION CONTAINED IN THE FOREGOING BID FOR PUBLIC WORKS ARE TRUE AND CORRECT

Dated at	this	day of	, 20
			(Name of Organization)
	Ву		
			(Title of Person Signing)
	ACKNO	WLEDGEMI	
STATE OF)	
COUNTY OF) SS:		
Before me, a Notary Pub		eared the abov	ve-named
Swore that the statement	s contained in the fo		iment are true and correct.
			day of
(Title)			
(The)	Notore Dublic		
	Notary Public		
My Commission Expires	3:		
County of Residence:			
	END OF S	SECTION 00	31 00

SECTION 01 23 00 - ALTERNATES

PART 1 - GENERAL

1.01 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including amended General Conditions and other Division 1 Specification Sections, apply to work of this Section.

1.02 PURPOSE

A. The Bids for the Alternates described herein are required in order for the Owner to obtain information necessary for the proper consideration of the Project in its entirety.

1.03 ALTERNATES

A. Definitions: Alternates are defined as alternate products, materials, equipment, installations, or systems for the Work, which may, at Owner's option and under terms established by Instructions to Bidders, be selected and recorded in the Owner-Contractor Agreement to either supplement or displace corresponding basic requirements of Contract Documents. Alternates may or may not substantially change scope and general character of the Work; and must not be confused with "allowances", "unit prices", "change orders", "substitutions", and other similar provisions.

1.04 SCHEDULE OF ALTERNATES

- A. <u>ALTERNATE NO. 1: State the cost to provide new plastic laminate countertops at all Elementary Schools. See manufacturer and color noted in finish schedule.</u> <u>Remove the existing fixed casework plastic laminate countertops throughout.</u> Base Bid: Existing countertops to remain.
- B. <u>ALTERNATE NO. 2: For all three Elementary Schools, state the cost to provide</u> new electric hand dryers as noted in the Construction Documents. Remove existing paper towel dispensers in large student restrooms. **Base Bid:** Leave existing paper towel dispensers in place.
- C. <u>ALTERNATE NO. 3: State the cost to provide carpet manufactured by Tarkett if</u> <u>not already included in your base bid.</u>
- D. <u>ALTERNATE NO. 4: Regarding Three Creeks and Lake Prairie Elementary</u> Schools, state the cost to provide new basketball back stops and supports as indicated in the Construction Documents. **Base Bid:** Leave existing in place.

E. <u>ALTERNATE NO. 5: Regarding all three Elementary Schools, state the cost to</u> remove existing chalkboards/tackboards and provide new markerboards as indicated in the Construction Documents. **Base Bid:** Leave existing in place.

PART 2 - PRODUCTS, PART 3 - EXECUTION (Not Used)

END OF SECTION 01 23 00



ADDENDUM THREE

Addendum Three (AD.03) to the drawings and specifications prepared by Gibraltar Design for District Wide – Tri Creek Elementary Schools' Finishes, and Lowell Middle School Media Center Renovation for Tri-Creek School Corporation, Lowell, Indiana.

All Contractors bidding on this project shall read all of the items covered below and shall comply with all of the requirements as set forth, including any necessary refinements or additions generated by this Addendum, Addendum #1, Addendum #2, and required by the intent of the original contract documents. All Contractors shall acknowledge on their bid form that they have received this Addendum, Addendum One and Addendum Two, and include the appropriate content of same within their bid proposal.

SPECIFICATIONS

1. Specification Section 00 01 10 Table of Contents

- A. Add Section 09 12 00, Acoustical Spray, to the Table of Contents, Division 9.
- B. Add Section 10 21 23, Cubicle Curtains and Tracks, to the Table of Contents, Division 10.
- C. Add Section 11 19 90, Wall Padding, to the Table of Contents, Division 11..
- 2. Specification Section 09 12 00 Acoustical Spray
 - A. Add Specification Section 09 12 00, Acoustical Spray, included in this Addendum, to the Project Manual.
- 3. Specification Section 09 91 00 Painting
 - A. Replace Specification Section 09 91 00, Painting, with Specification Section 09 91 00 included in this Addendum.
 - 1. Note: Addition of EIFS Paints and Existing Metal Locker Painting.

4. Specification Section 10 11 00 Markerboards and Corkboards

- A. Delete Paragraph 2.2.G. in its entirety.
- B. Add new Paragraph 2.3.A.3. as follows:
- C. "3. Markings: Provide factory applied chalkboard and markerboard markings fused to finished writing surface. Verify color of markings.

a. Staff Lines: Five bar staff markings with lines spaced 1 inch on center and 5 inches between staffs.

1) Size: Refer to Drawings.

2) Location: Lake Prairie ES Music Room #A-137, Oak Hill ES Music Room #A-120, and Three Creeks ES Music Room #A-118."

5. Specification Section 10 21 23 Cubicle Curtains and Tracks

A. Add Specification Section 10 21 23, Cubicle Curtains and Tracks, included in this Addendum, to the Project Manual.



6. Specification Section 11 19 90 Wall Padding

A. Add Specification Section 11 19 90, Wall Padding, included in this Addendum, to the Project Manual.

DRAWINGS – General

1. Sheet G-301

A. Refer to revised full-size drawing, included in this Addendum for revisions to markerboard mounting height elevation.

DRAWINGS – Lowell Middle School

2. Sheet AD104-MS

- A. Refer to revised full-size drawing, included in this Addendum for clarification of Demo notes.
- 3. Sheet A-804-MS, A-805-MS, A-808.MS A-809-MS, A-810-MS
 - A. Refer to revised full-size drawings, included in this Addendum for the following revisions:
 - 1. Addition of note for painted door frames.
 - 2. Additional rooms requiring carpet.

4. Sheet A-820-MS

A. Refer to revised full-size drawing, included in this Addendum for clarifications of plastic laminate.

5. Sheet A-860-MS, A-861-MS

A. Refer to revised full-size drawings, included in this Addendum for clarifications of paint locations.

6. Sheet A-904-MS

A. Refer to revised full-size drawing, included in this Addendum for clarification of plan notes.

DRAWINGS – Lake Prairie Elementary School

7. Sheet AD-101-LP, AD-102-LP, AD-103-LP

- A. Refer to revised full-size drawing, included in this Addendum for the following revision:
 - 1. Addition of Alternate note and locations to remove existing chalk boards.

8. Sheet A-101-LP, A-102-LP, A-103-LP

- A. Refer to revised full-size drawing, included in this Addendum for the following revisions:
 - 1. Addition of Alternate note and locations to install new Markerboard.



9. Sheet A-701-LP, A-702-LP, A-703-LP

- A. Refer to revised full-size drawings, included in this Addendum for the following revisions:
 - 1. Addition of Alternate note and locations to install new Markerboard.

10. Sheet A-760-LP

A. Refer to revised full-size drawing, included in this Addendum for modifications to reception counter.

11. Sheet A-801-LP, A-802-LP, A-803-LP

A. Refer to revised full-size drawings, included in this Addendum for miscellaneous modifications to Finish Plan.

12. Sheet A-820-LP

A. Refer to revised full-size drawing, included in this Addendum for additional finish information.

13. Sheet A-861-LP, A-862-LP

A. Refer to revised full-size drawings, included in this Addendum for clarifications of finishes.

DRAWINGS – Oak Hill Elementary School

14. Sheet AD-101-OH, AD-102-OH, AD-103-OH

- A. Refer to revised full-size drawings, included in this Addendum for the following revisions:
 - 1. Addition of Alternate note and locations to remove existing chalk boards.

15. Sheet A-101-OH, A-102-OH, A-103-OH

- A. Refer to revised full-size drawings, included in this Addendum for the following revisions:
 - 1. Addition of Alternate note and locations to install new chalk boards.

16. Sheet A-701-OH, A-702-OH, A-703-OH

- A. Refer to revised full-size drawings, included in this Addendum for the following revisions:
 - 1. Addition of Alternate note and locations to install new chalk boards.

17. Sheet A-760-OH

A. Refer to revised full-size drawing, included in this Addendum for modifications to reception counter.

18. Sheet A-801-OH, A-802-OH, A-803-OH

A. Refer to revised full-size drawings, included in this Addendum for miscellaneous modifications to finish plan.

19. Sheet A-820-OH

A. Refer to revised full-size drawing, included in this Addendum for additional finish information.

20. Sheet A-860-OH, A-861-OH

A. Refer to revised full-size drawings, included in this Addendum for clarification of elevation notes and finishes.



DRAWINGS – Three Creeks Elementary School

21. Sheet AD-101-TC, AD-102-TC, AD-103-TC

- A. Refer to revised full-size drawings, included in this Addendum for the following revisions:
 - 1. Addition of Alternate note and locations to remove existing chalk boards.

22. Sheet A-101-TC, A-102-TC, A-103-TC

- A. Refer to revised full-size drawings, included in this Addendum for the following revisions:
 - 1. Addition of Alternate note and locations to install new chalk boards.

23. Sheet A-701-TC, A-702-TC, A-703-TC

- A. Refer to revised full-size drawings, included in this Addendum for the following revisions:
 - 1. Addition of Alternate note and locations to install new chalk boards.

24. Sheet A-760-TC

A. Refer to revised full-size drawing, included in this Addendum for modifications to reception counter.

25. Sheet A-801.TC, A-802.TC, A-803.TC

A. Refer to revised full-size drawings, included in this Addendum for miscellaneous modifications to finish plan.

26. Sheet A-820.TC

A. Refer to revised full-size drawing, included in this Addendum for additional finish information.

27. Sheet A-860-TC, A-861.TC

A. Refer to revised full-size drawing, included in this Addendum for clarification of finishes.

Pages 1 through 4, inclusive, Specification Sections 09 12 00, 09 91 00, 10 21 23 and 11 19 90; and Fifty-Nine (59) Full-Size Drawings, constitute the total makeup of **Addendum Three**.



Y:\23-107 Tri-Creek SC – Lowell MS Media Center Improvements\Specs\ADDENDUM THREE\AD03.docx



SECTION 09 12 00 ACOUSTICAL SPRAY

1 General

1.1 Section Includes

A. Acoustical Spray system.

1.2 Regulatory Requirements

A. Conform to applicable code for fire rated assemblies.

1.3 Environmental Requirements

- A. Do not apply acoustical spray when ambient temperature is less than 50 degrees F.
- B. Maintain minimum ambient temperature of 50 degrees F during and after installation of acoustical spray.

1.4 Delivery, Storage, And Handling

- A. Deliver products to site under provisions of Division 1.
- B. Store and protect products under provisions of Division 1.
- C. Deliver and store manufactured materials in original packages plainly marked with manufacturer's brand name.
- D. Materials in broken containers or in packages showing water marks or other evidence of damage will be rejected.

2 Products

2.1 Acoustical Plaster

- A. Acceptable Manufacturers:
 - 1. Cafco/Isolatek International, Stanhope, New Jersey; Sound-Shield 40.
 - 2. International Cellulose Coproation, Houston Texas; K-13.
- B. Spray-on acoustical finish: Minimum Rated Class A per ASYM E84.
- C. Thickness: 1-1/2 inch.
- D. Color: to be selected by Owner.
- E. Application: Refer to Drawings.



3 Execution

3.1 Inspection

- A. Verify that site conditions are ready to receive work.
- B. Beginning of installation means acceptance of substrate and existing surfaces.
- C. Verify surfaces to receive spay insulation to determine if priming/sealing is required to insure bonding and/or to prevent discoloration caused by migratory stains.

3.2 Preparation

- A. Provide masking, drop cloths or other satisfactory coverings for materials/surfaces that are not to receive insulation to protect from over-spray.
- B. Coordinate installation of the sprayed cellulose fiber with work of other trades.
- C. Prime surfaces as required by manufacturer's instructions or as determined by examination.

3.3 Installation

- A. Install spray applied insulation according to manufacturer's recommendations.
- B. Install to thickness indicated.
- C. Cure insulation with continuous natural or mechanical ventilation.
- D. Remove and dispose of over-spray.

END OF SECTION



SECTION 09 91 00 PAINTING

1 General

1.1 Section Includes

- A. Surface preparation and painting.
- B. Surface finish schedule.

1.2 Related Sections

- A. Section 05 12 00 Structural Steel: Shop primed items.
- B. Section 05 21 00 Steel Joists: Shop primed items.
- C. Section 05 31 23 Steel Roof Deck: Shop primed items.
- D. Section 05 50 00 Miscellaneous Metals: Shop primed items.
- E. Section 06 20 00 Finish Carpentry: Finish carpentry items and millwork to be field finished.
- F. Section 08 11 13 Standard Steel Doors and Frames: Shop primed items.
- G. Section 09 72 16 Fabric Wall Covering.
- H. Section 08 91 00 Aluminum Wall Louvers: Wall louvers and aluminum roof penthouses.
- I. Section 22 05 53 and Section 23 05 53 Mechanical Identification: Stenciling and identification of mechanical items.
- J. Section 26 05 30 Conduit.
- K. Section 26 05 36 Surface Raceways.
- L. Section 26 05 53 Electrical Identification

1.3 References

- A. SSPC-SP-1 Solvent Cleaning.
- B. SSPC-SP-2 Hand Tool Cleaning.
- C. SSPC-SP-3 Power Tool Cleaning.



1.4 Submittals

- A. Submit one paint color sample of each color to be used as noted on the Drawings.
 - 1. Where color is not specified, submit samples under provisions of Division 1.
- B. Submit one 8 inch by 10 inch and four 4 inch by 5 inch stain samples of each color to be used as noted on the Drawings.
 - 1. Where color is not specified, submit samples under provisions of Division 1.
- C. Provide product data on all finishing products.
 - 1. Provide physical properties of each product to be used on the project, including the following.
 - a. Weight per gallon.
 - b. Solids by weight.
 - c. Solids by volume.
 - d. V.O.C. as supplied.
- D. Schedule of surfaces and products, applicable to project.
- E. Submit manufacturer's application instructions under provisions of Division 1.
- F. Submit documentation indicating installer is an EPA Lead-Safe Certified Firm.

1.5 Quality Assurance

A. Installer Qualifications: An experienced firm who is Lead-Safe Certified through the Environmental Protection Agency (EPA).

1.6 Field Samples

- A. Provide field sample panel of each color selected, 4 feet long by 4 feet wide, illustrating color, texture, and finish.
- B. Locate where directed.
- C. Accepted samples may remain as part of the work at the discretion of the Architect.

1.7 Delivery, Storage, And Handling

- A. Deliver products to site under provisions of Division 1.
- B. Store and protect products under provisions of Division 1.
- C. Deliver products to site in sealed and labeled containers, inspect to verify acceptance.



- D. Container labeling to include manufacturer's name, type of paint, brand name, brand code, coverage, surface preparation, drying time, cleanup, color designation, and instructions for mixing and reducing.
- E. Store paint materials at minimum ambient temperature of 45 degrees F and a maximum of 90 degrees F, in well ventilated area, unless required otherwise by manufacturer's instructions.
- F. Take precautionary measures to prevent fire hazards and spontaneous combustion.

1.8 Environmental Requirements

- A. Provide continuous ventilation and heating facilities to maintain surface and ambient temperatures above 50 degrees F for twenty-four (24) hours before, during, and forty-eight (48) hours after application of finishes, unless required otherwise by manufacturer's instructions.
- B. Do not apply exterior coatings during rain or snow, or when relative humidity is above 50 percent, unless required otherwise by manufacturer's instructions.
- C. Minimum Application Temperatures for Latex Paints: 50 degrees F for exterior, unless required otherwise by manufacturer's instructions.
- D. Minimum Application Temperature for Varnish Finishes: 65 degrees F for interior or exterior, unless required otherwise by manufacturer's instructions.
- E. Provide lighting level of 80 foot-candles measured mid-height at substrate surface.

2 Products

2.1 Paint - Acceptable Manufacturers

- A. Benjamin Moore & Company, Montvale, New Jersey (Moore).
- B. PPG Architectural Finishes, Inc., Pittsburgh, Pennsylvania (PPG).
- C. Porter Paints, Louisville, Kentucky (Porter).
- D. The Sherwin-Williams Company, Cleveland, Ohio (S-W).
- E. Or as specifically noted in the Schedule.

2.2 Materials

- A. Coatings: Ready mixed, except field catalyzed coatings.
 - 1. Process pigments to a soft paste consistency, capable of being readily and uniformly dispersed to a homogeneous coating.
- B. Coatings: Good flow and brushing properties; capable of drying or curing free of streaks or sags.



C. Accessory Materials: Linseed oil, shellac, turpentine, paint thinners, and other materials not specifically indicated but required to achieve the finishes specified, of commercial quality.

2.3 Finishes

- A. Refer to schedule at end of Section for surface finish schedule.
- B. Colors will be selected by the Architect and Owner.
 - 1. See Drawings.
 - 2. Paint ceilings white, unless noted otherwise. The underside of gypsum board bulkheads shall be painted the same color as the vertical surface of the bulkhead.

3 Execution

3.1 Inspection

- A. Verify that surfaces and substrate conditions are ready to receive work as instructed by the product manufacturer.
- B. Examine surfaces scheduled to be finished prior to commencement of work.
 - 1. Report any condition that may potentially affect proper application.
- C. Beginning of installation means acceptance of substrate and existing surfaces.

3.2 Preparation - General

- A. Provide all scaffolding and staging required for work in this Section.
 - 1. Coordinate locations to eliminate interference with work of others.
- B. Remove electrical plates, hardware, light fixture trim, clocks, speakers, and fittings prior to preparing surfaces or finishing.
- C. Correct minor defects and clean surfaces which affect work of this Section.
- D. Shellac and seal marks which may bleed through surface finishes.

3.3 Surface Preparation - New Surfaces

- A. Shop Primed Steel Surfaces: Sand and scrape to remove loose primer and rust.
 - 1. Feather edges to make touch-up patches inconspicuous.
 - 2. Clean surfaces with solvent.
 - 3. Prime bare steel surfaces.



- B. Galvanized Surfaces: Remove surface contamination and oils and wash with solvent.
 - 1. Apply coat of etching primer.
- C. Concrete and Unit Masonry Surfaces: Remove dirt, loose mortar, scale, salt or alkali powder, and other foreign matter.
 - 1. Remove oil and grease with a solution of tri-sodium phosphate; rinse well and allow to dry.
 - 2. Remove stains caused by weathering of corroding metals with a solution of sodium metasilicate after thoroughly wetting with water.
 - 3. Allow to dry.
- D. Gypsum Board Surfaces: Latex fill minor defects.
 - 1. Spot prime defects after repair.
- E. Interior Wood Scheduled to Receive Transparent Finish: Remove loose dust, dirt, grit, and foreign matter.
 - 1. Set nails and screws.
 - 2. Fill nail and screw holes, cracks, and blemishes after staining with filler to match color of wood or stain.
 - 3. Sand smooth.
- F. Wood and Metal Doors: Apply one coat of paint to glazing stops and rabbets prior to glazing.
- G. Impervious Surfaces: Remove mildew by scrubbing with solution of tri-sodium phosphate and bleach.
 - 1. Rinse with clean water and allow surface to dry.

3.4 Surface Preparation - Existing Surfaces

- A. Existing Painted Ferrous Metal Surfaces: Solvent clean all surfaces in accordance with SSPC-SP-1.
 - 1. Clean rusted surfaces in accordance with SSPC-SP-2 or SSPC-SP-3.
 - 2. Spot prime as required.
 - 3. Finish as specified for new work.
- B. Existing Gloss Surfaces to Receive Wall Coating: Sand or etch gloss surfaces prior to application of base coat.
- C. Removal and Protection of Existing Lead Paint: In accordance with guidelines published by the Environmental Protection Agency (EPA).



1. Locations: Kindergarten and First Grade Classrooms.

3.5 Protection

- A. Protect elements surrounding the work of this Section from damage or disfiguration.
- B. Repair damage to other surfaces caused by work of this Section.
- C. Furnish drop cloths, shields, and protective methods to prevent spray or droppings from disfiguring other surfaces.
- D. Remove empty paint containers from site.

3.6 Application

- A. Paint and finish all new interior and exterior general construction items; heating, air conditioning, and ventilating items; plumbing installations; and electrical items which will be exposed in the final work, except as noted below.
 - 1. Surfaces Not to be Painted:
 - a. Sprinkler heads.
 - b. Identification plates and tags.
 - c. Factory finished equipment, unless specifically noted to be field finished.
 - d. Stainless steel, copper, and bronze, unless specifically noted to be painted.
 - e. Anodized aluminum.
 - f. Concrete floors, unless specifically noted to be painted.
 - g. Exterior concrete.
 - h. Door hardware, except closers and removable mullions that are not aluminum or plated.
 - i. Glass.
 - j. Plated finishes.
 - k. Concealed surfaces, unless specifically noted to be painted.
 - I. Walls in Boiler Room and Mechanical Equipment Rooms, unless specifically noted to be painted, and except for touch up in existing painted areas.
- B. Apply products in accordance with manufacturer's instructions.
- C. Do not apply finishes to surfaces that are not dry.



- D. Apply each coat to uniform finish.
- E. Apply each coat of paint slightly darker than preceding coat unless otherwise approved.
- F. Sand lightly between coats to achieve required finish.
- G. Allow applied coat to dry before next coat is applied.
- H. Apply paint by the brush method, as recommended by the manufacturer and as approved by the Architect.
 - 1. Apply final coat to concrete, masonry, and smooth finished wall and ceiling surfaces with roller.
 - 2. Apply paint to exposed ceiling surfaces and in inaccessible areas by spraying.
 - 3. Do not use spray application on other areas without written approval of Architect.
- I. Draw lines of demarcation between different shades or colors to eliminate blurred edges.
- J. Back-prime all surfaces of interior and exterior wood blocking and woodwork, except pressure treated wood and wood framing, with one coat of aluminum paint.
- K. Prime back surfaces of interior woodwork scheduled to receive stain or varnish finish with gloss varnish reduced 25 percent with mineral spirits.
- L. Where clear finishes are required, tint fillers to match wood.
 - 1. Work fillers into the grain before set.
 - 2. Wipe excess from surface.
- M. Coat steel items that come in contact with aluminum items with a field coat of bituminous paint.
- N. Paint Piping and Coverings in Boiler Room and Mechanical Equipment Rooms only.
 - 1. See Section 22 05 53 and Section 23 05 53, Mechanical Identification, for required colors.
 - a. Paint new piping and coverings only to match existing.
- O. Paint exposed conduit and surface raceways in with wall.
- P. Paint coverings of boiler and breeching light gray.
- Q. Paint walls behind metal enclosures with one coat primer and one finish coat prior to installation of metal enclosures.



- R. In existing areas where work is required, paint the entire room or area to give the appearance, as nearly as possible, of a new room.
 - 1. Paint existing painted ceilings to remain in those areas.
- S. Paint any damaged surfaces or new surfaces in existing areas where new work is required.
 - 1. Paint as scheduled; or touch up damaged areas, paint entire wall, or paint to a stopping point as approved by the Architect.
- T. Paint all new and existing exposed ceiling construction, including joists, structural members, metal deck or deck forms and all new and existing exposed conduit, surface raceways, pipes, pipe covering, and ductwork in these ceiling areas.
 - 1. Paint walls, if exposed in these areas, from the underside of deck down to a point level with lowest point of roof structure.
- U. Seal, stain, and varnish concealed and semi-concealed surfaces of millwork items.
 - 1. Seal internal surfaces of millwork items with two coats of shellac.
 - 2. Brush apply only.

3.7 Finishing Mechanical And Electrical Equipment

- A. Paint shop primed equipment.
- B. Touch up marred or damaged shop prefinished items.
- C. Remove unfinished louvers, grilles, covers, and access panels on mechanical and electrical components and paint separately.
- D. Replace identification markings on mechanical or electrical equipment when painted accidentally.
- E. Paint interior surfaces of air ducts, and convector and heating cabinets that are visible through grilles and louvers with one coat of flat black paint, to limit of sight line.
 - 1. Paint dampers exposed behind louvers, grilles, and convector and heating cabinets to match face panels.
- F. Paint exposed conduit, surface raceways, and electrical equipment occurring in finished areas.
- G. Paint both sides and all edges of plywood backboards for electrical and telephone equipment with one coat of light to medium gray paint before installation of equipment.
- H. Reinstall electrical plates, hardware, light fixture trim, clocks, speakers, and fittings removed prior to finishing.



- I. Paint all equipment located on roofs, including aluminum exhaust fans, gravity relief vents, appliance exhausts, and all equipment, unless factory finish is acceptable to Architect.
 - 1. Do not paint aluminum roof penthouses.
- J. Refer to Section 22 05 53, 23 05 53, and Section 26 05 53 for schedule of color coding and identification banding of equipment, ductwork, piping, conduit, and surface raceways.

3.8 Cleaning

- A. As work proceeds, promptly remove paint where spilled, splashed, or spattered.
- B. During progress of work maintain premises free of unnecessary accumulation of tools, equipment, surplus materials, and debris.
- C. Collect cotton waste, cloths, and material which may constitute a fire hazard, place in closed metal containers, and remove daily from site.

3.9 Schedule - Shop Primed Items For Site Finishing

- A. Miscellaneous Metals (Section 05 50 00): Various items.
- B. Standard Steel Doors and Frames (Section 08 11 13): Metal doors, frames, and accessories.

3.10 Schedule - Interior Surfaces - New

Α.

 Wood - Transparent Finish - Millwork; perimeter trim at wainscots; wood trim. Basis-of-Design Product:
 S-W
 Filler coat tinted to shade of stain (for open grained wood only). Sherwood Natural Filler, D70T1.
 Apply stain of selected shade, Wood Classics 250 VOC Interior Stain A49 Series. Three coats varnish, satin, Wood Classics WB Polyurethane, A68 Series. Sand between each coat.

Β.

Concret	te Masonry Units - Wall Coating (Solid Color) - Basis-of-Design Product:
S-W	One coat block filler, sand lightly, Heavy Duty Block Filler, B42W46.
	Two coats solid color two-component acrylic epoxy paint, semi-gloss, SW Pro
	Industrial Zero VOC Waterborne Catalyzed Epoxy B73-300 Series.

C.

Steel - Pi	rimed - Basis-of-Design Product:
S-W	Touch-up with original primer.
	Two coats ProMar 200 Zero VOC Interior Latex Flat B30-2600 Series.



D.

Steel - St	nop Primed – Exposed construction areas. Basis-of-Design Product:
S-W	Clean surfaces of rust, scale and contaminants. Roughen glossy surfaces.
	Touch-up with same material as shop coat or with compatible primer.
	One coat flat black waterborne low VOC acrylic dryfall, S-W Waterborne SW
	Low VOC Waterborne Acrylic Dryfall B42 Series.

Ε.

Metal De	oors and Frames. Basis-of-Design Product:
S-W	Touch-up with original primer.
	Two coats ProMar 200 Interior Waterbased Acrylic B34-8251 series.

F.

Steel – Galvanized – Including ductwork, conduit, and surface raceways in exposed	
construction areas. Basis-of-Design Product:	
S-W	One coat Self cross linking acrylic primer, SW Pro Industrial Pro-Cryl Universal
	Water Based Primer B66-310 Series.
	One coat ProMar 200 Zero VOC Interior Latex Flat BB30-2600 Series.

G.

Gypsum Board - Paint. Basis-of-Design Product:	
S-W	Gypsum Board: One coat latex primer sealer, ProMar 200 Zero Voc Interior Latex
	Primer B28.
	Two Coats ProMar 200 Zero VOC Interior Latex EgShel B20-2600 Series
11	

Η.

Gypsum Board - Wall Coating. Basis-of-Design Product:	
S-W	One coat latex primer, ProMar 200 Zero VOC Interior Latex Primer.
	Two coats solid color two-component acrylic epoxy paint, ProIndustrial Zero
	VOC Waterborne Catalyzed Epoxy B73-300 Series.

3.11 Schedule – Exterior Surfaces – Existing

Α.

Existing Exterior Insulation and Finish System	
	Thoroughly Clean existing surfaces to be finished.
S-W	One coat Latex Acrylic Primer, SW Exterior Latex Primer B42 Series.
	Two coats Acrylic Latex Satin, A-100 Exterior Latex Satin A8 Series.



3.12 Schedule - Interior Surfaces - Existing

Α.

Concrete Masonry Units - Painted. Basis-of-Design Product:	
S-W	Two coats ProMar 200 Zero VOC Interior Latex Eg-Shel B20-2600 Series.

Β.

Steel - All existing interior ferrous metal, including but not limited to columns and lintels.	
Basis-of-Design Product:	
S-W Two coats ProMar 200 Zero VOC Interior Latex Flat B30-2600 Series.	

C.

Metal D	Metal Doors and Frames. Basis-of-Design Product:	
S-W	Two coats ProMar 200 Interior Waterbased Acrylic Semi-Gloss B35-8251 Series.	

D.

Gypsum Board. Basis-of-Design Product:	
S-W	Two coats ProMar 200 Zero VOC Interior Latex EgShel B20W2600 Series.

E.

Concrete Masonry Units - Wall Coating (Solid Color) Basis-of-Design Product:	
S-W	Two coats solid color two-component Acrylic epoxy paint. ProIndustrial Zero
	VOC Waterborne Catalyzed Epoxy B73-300 Series.

F.

Electrost	Electrostatic Paint Finish - Existing corridor lockers; existing metal enclosures.	
	Clean and sand existing surfaces to be finished.	
	Apply two component epoxy coating using Ransburg electrostatic catalyzed process, installed in strict accordance with the manufacturer's	
	specifications.	
	Do not refinish interior surfaces of corridor lockers.	
S-W	Pro Industrial High Performance Epoxy, B67W00200/B67V00200 Series.	

END OF SECTION



SECTION 10 21 23 CUBICLE CURTAINS AND TRACKS

1 General

1.1 Section Includes

- A. Overhead suspended surface mounted metal curtain track and guides.
- B. Curtains.

1.2 Submittals

- A. Submit shop drawings under provisions of Division 1.
 - 1. Submit shop drawings indicating a reflected ceiling plan view of curtain track, hangers and suspension points, attachment details, schedule of curtain sizes.

1.3 Regulatory Requirements

A. Conform to applicable code for flame spread requirements for curtain fabric.

1.4 Delivery, Storage, And Handling

- A. Deliver products to site under provisions of Division 1.
- B. Store and protect products under provisions of Division 1.

2 Products

2.1 Cubicle Curtains And Tracks - Acceptable Manufacturers

- A. General Cubicle Company, Telford, Pennsylvania.
- B. Imperial Fastener Company, Pompano Beach, Florida.
- C. InPro Corporation, Muskego, Wisconsin.
- D. A. R. Nelson Company, Inc., Long Island City, New York.
- E. Watrous, Division of Lansbrie Corp., Northbrook, Illinois.

2.2 Track Materials

- A. Track: Extruded aluminum sections, one piece per cubicle track run.
- B. Track Ends: Positive stop to fit track extrusion.
- C. Carriers: SliderRoller to accurately fit track, designed to eliminate bind when curtain is pulled, and fitted to curtain to prevent accidental curtain removal.



D. Escutcheons: Aluminum.

2.3 Curtain Materials

- A. Curtain: Architex, Refer to Finish Legend.
- B. Open Mesh Cloth: Open weave to permit air circulation, flameproof material, same color as curtain.

2.4 Finishing

- A. Exposed Aluminum Surfaces: Clear anodized finish.
- B. Curtain: Color as selected by the Architect. See Finish Legend.

2.5 Fabrication

- A. Fabricate track bend with minimum 8 12 inch radius, without deforming track section, or impeding movement of carriers.
- B. Manufacture curtains of one piece, sized 10 percent wider than track length.
- C. Terminate curtain 15 inches from the floor.
- D. Curtain heading of triple thickness 2 inches wide, with grommetted holes for carriers 6 inches on center, double fold bottom hem 2 inches wide.
 - 1. Lockstitch seams in two rows.
 - 2. Turn seam edges and lockstitch.
- E. Include open mesh cloth at top 20 inches of curtain for room air circulation.

3 Execution

3.1 Examination

- A. Verify that surfaces are ready to receive work.
- B. Verify field measurements.
- C. Beginning of installation means installer accepts existing surfaces and conditions.

3.2 Installation

- A. Install above ceiling track supports.
- B. Install curtain track secure and rigid, true to ceiling line.
- C. Install end cap and stop device.
- D. Mount track at 7'-4" above the floor.



E. Install curtains on carriers ensuring smooth operation.

3.3 Schedule

A. Location: Three Creeks & Oak Hill ES.

END OF SECTION



SECTION 11 19 90 WALL PADDING

1 General

1.1 Work Included

A. Provide wall padding in Oak Hill Elementary School, Calm Rooms C-147 nd C-151.

1.2 References

- A. ASTM D412 Vulcanized Rubber and Thermoplastic Rubbers and Thermoplastic Elastomers.
- B. ASTM D471 Rubber Property Effects of Liquids.
- C. ASTM D2240 Rubber Property Durometer Hardness.
- D. ASTM E84 Surface Burning Characteristics of Building Materials.
- E. MIL I-631 Insulation, Electrical, Synthetic-Resin Composition, Nonrigid.

1.3 Submittals

- A. Shop drawings indicating dimensions, termination and change-of-plane details, method of attachment, and finishes.
- B. Product data.
- C. Samples.

2 Products

2.1 Wall Padding - Approved Manufacturer

- A. Marathon Engineering Corporation, Mountain Ranch, California; Gold Medal Resilient Wall Padding.
- B. Padded Surfaces by B & E, Indianapolis, Indiana.

2.2 Materials

- A. A resilient resinous composition designed as a surfacing material which has no extraneous plasticizers or softening agents which are not integrally and completely bonded in the internal chemical structure; scuff resistant, long lasting, self adhering to properly prepared substrate when poured on site.
 - 1. Thickness: 1 inch.
 - 2. Color: Tan.




- 3. Finish: Smooth.
- B. Bond Coat: Provided by manufacturer to ensure compatibility with subsurface.
- C. Technical Data: Sheets of resilient resinous plastic, containing fire retardant additives intended for use as floor and wall padding; meeting or exceeding the following tests at standard ASTM Class A conditions.
 - 1. Flame Spread Classification: ASTM E84; 23.
 - 2. Smoke Density: ASTM E84; 178.
 - 3. Fuel Contribution: ASTM E84; 20.
 - 4. Hardness Range: ASTM D2240; 45-50 Shore A-2, typical.
 - 5. Weight: Approximately 4 pounds per square foot at 1 inch thickness.
 - 6. Oil Resistance: ASTM D471; less than 5 percent volume swell.
 - 7. Moisture Absorption: 1 percent by weight, typical.
 - 8. Compression Properties: 1 inch nominal thickness; compressive strength, psi at 10 percent deflection-6.00; psi at 50 percent deflection-110.6.
 - 9. Fungus Resistance: MIL I-631; Completely resistant, 0, 0, 0.
 - 10. Elongation at Break: ASTM D412; 150 percent, typical.


3 Execution

3.1 Installation

- A. Install in prefabricated sheets with a nominal thickness of 1 inch.
- B. Apply to 7/16 inch OSB panel provided by this Contractor.
- C. Leave a gap of not less than 1/8 inch between panels on walls.
- D. Install wall padding from floor to ceiling.
- E. Field fill seams and anchor openings.
 - 1. Sand prior to final application of wall padding coating.
- F. Treat doors same as walls.
- G. Floor: Provide 7/16 inch OSB anchored to floor, covered with 1/2 inch thick field poured resilient material.
 - 1. Provide field applied hard formula at exposed edges.

END OF SECTION





GENERAL PARTITION NOTES:

A. REFER TO LIFE SAFETY PLANS FOR RATED WALL LOCATIONS THAT EXTEND TO DECK ABOVE.

- B. PARTITION SYMBOLS APPEAR ON LARGEST SCALE FLOOR PLAN PROVIDED FOR AREA.
- C. REFER TO FINISH PLANS FOR WALL FINISH AND BASE INFORMATION.
- D. PROVIDE WATER RESISTANT GYPSUM BOARD ON WALLS WITH OPERABLE PLUMBING FIXTURES AND WITHIN 4 FEET OF DRINKING FOUNTAINS/WATER COOLERS UNLESS NOTED OTHERWISE.
- E. ALL WALLS THAT ARE NOT INDICATED TO EXTEND TO THE UNDERSIDE OF DECK ABOVE SHELL EXTEND TO 4" MINIMUM ABOVE FINISHED CEILING UNLESS NOTED OTHERWISE.
- F. PROVIDE LATERAL BRACING FOR PARTITIONS WHICH EXTEND ABOVE CEILING. G. PROVIDE SPECIFIED TILE BACKER BOARD AT ALL WALLS SCHEDULED TO RECEIVE
- CERAMIC TILE.
- H. STEEL STUD FRAMING SHALL BE ATTACHED/BRACED TO STRUCTURAL FRAMING AND NO TO ROOF DECK.
- I. ISOLATE NON-LOAD-BEARING STUD FRAMING FROM BUILDING STRUCTURE TO PREVENT TRANSFER OF VERTICAL LOADS WHILE PROVIDING LATERAL SUPPORT AS SPECIFIED.
- J. PACK DECK FLUTE VOIDS AT NON-RATED WALLS WITH MINERAL WOOL. FILL DECK FLUTE VOIDS AT RATED WALLS WITH FIRESTOPPING. REFER TO PROJECT MANUAL.
- K. PROVIDE FIRE RESISTIVE RATED GYPSUM WALL BOARD AT ALL RATED ASSEMBLIES TO MEET ASSEMBLY REQUIREMENTS.
- L. PROVIDE FIRE RESISTIVE JOINT SYSTEMS EQUAL TO WALL RATING AT ALL PENETRATIONS AND AT HEAD/FLOOR INTERSECTIONS WITH RATED ASSEMBLIES. M. PROVIDE ACOUSTICAL INSULATION AT INTERIOR WALLS NOTED TO RECEIVE BLANKET
- INSULATION. N. PROVIDE ACOUSTICAL SEALANT AT WALL SILL, HEAD, PENETRATIONS, AND ADDITIONAL
- SPECIFIED SOUND ATTENUATION COMPONENTS AT SOUND RATED WALLS. 0. STUD SPACING 16" O.C. UNLESS NOTED OTHERWISE.
- P. PROVIDE MOLD/MOISTURE RESISTANT, ABUSE RESISTANT GYPSUM BOARD ADJACENT TO DRINKING FOUNTAINS/BOTTLE FILLERS.

PARTITION TYPES

G = -301

Q. PROVIDE ABUSE RESISTANT GYPSUM BOARD WHERE INDICATED ON DRAWINGS.

SCALE: 3/4" = 1'-0"

G	ENERAL PROJECT NOTES:
(AP	PLY TO ENTIRE DRAWING SET)
Α.	ALL CONTRACTORS SHALL CHECK ENTIRE SET OF CONTRACT DOCUMENTS FOR THE EXTENT OF WORK.
В.	EACH TRADE SHALL VERIFY ALL DIMENSIONS AND CLEARANCES AND AL FIELD CONDITIONS BEFORE STARTING CONSTRUCTION. COMMENCEMENT CONSTITUTES ACCEPTANCE OF CONDITIONS. SHOULD DIFFERENT CONDIT ENCOUNTERED, CONTACT THE ARCHITECT BEFORE PROCEEDING WITH WO
C.	EACH TRADE SHALL COORDINATE WITH THE APPROPRIATE CONTRACTOR(VERIFY SIZE AND LOCATION OF ALL RECESSES, CHASES, PADS, & OPE REQUIRED FOR MECHANICAL, ELECTRICAL AND OTHER EQUIPMENT.
D.	EACH TRADE SHALL COORDINATE WITH THE APPROPRIATE CONTRACTOR(VERIFY LOCATION, HEIGHT, AND DEPTH OF BULKHEADS PRIOR TO BULK CONSTRUCTION.
Ε.	THE BOTTOM OF ALL CONVECTOR FAN COIL, AND UNIT HEATER RECESS BE INSTALLED A MINIMUM OF 6" AND A MAXIMUM OF 12" ABOVE FLOO PLACE MASONRY LINTELS AT UNCUT COURSING HEIGHT. COORDINATE O WITH APPROPRIATE CONTRACTOR(S).
F.	FLOOR ELEVATIONS, GRADES, DIMENSIONS, CLEARANCES, AND CONDITIO

- UNSTRUCTION INDICATED ON THESE DRAWINGS SHALL BE FIELD Y ALL CONTRACTOR(S). REPORT CONFLICTS OR DISCREPANCIES TO THE FOR RESOLUTION PRIOR TO STARTING WORK. VERIFIED ARCHITEC EQUIPMENT OR MATERIALS NOT MARKED OR INDICATED AS EXISTING SHALL BE FURNISHED BY THE APPROPRIATE CONTRACTOR.
- E GENERAL CONTRACTOR IS RESPONSIBLE FOR ALL CUTTING INDICATED ON THE CHITECTURAL DRAWINGS RELATED TO INSTALLATION OR REMOVAL OF WORK OF E MECHANICAL AND ELECTRICAL TRADES. ALL REQUIRED CUTTING MAY NOT B' OWN. ANY ADDITIONAL CUTTING AND PATCHING REQUIRED, WHICH IS NOT DICATED ON THE ARCHITECTURAL DRAWINGS, SHALL BE THE RESPONSIBILITY OF E TRADE REQUIRING THE ACCESS, AS PROVIDED FOR IN THE SPECIFICATIONS.
- ICAL ITEMS (SUCH AS SINKS, TOILETS, PANELS, ETC.) MAY DEMOLITION ON SEVERAL DRAWINGS INCLUDING 3. REMOVAL OF THESE ITEMS SHALL BE BY THE
- , ANCHORS _ SHALL F / ITEMS T

SYMBOL LEGEND:		
REFERENCE NUMBER	R ELEVATION NUMBER (SEE SHEET A8.01)	
99		

(AE99		<u>U-999</u>	ROOM NUMBER	EU-999 ROOM NUMBER
\smile	SHEET NUMBER			NUMBER
		R	UNIT ADDITIONAL	
99 AE99		ÚA 999	DOOR NUMBER	$\nabla \nabla$
	SHEET NUMBER			
\sim		R 9	WINDOW NUMBER	
4E99		99	PLAN NOTE	\langle / \rangle
	SHEET NUMBER	99	DEMOLITION NOTE	UNIT BREAK

MATERIAL INDICATIONS:

IN GENERAL, THE MATERIAL INDICATIONS SHOWN BELOW ARE TYPICAL.
HOWEVER, ALL MATERIAL INDICATIONS PRESENTED HERE MAY NOT BE USED
ON THIS PARTICULAR PROJECT. THESE SYMBOLS TYPICALLY INDICATE THE
MATERIALS WHEN SECTIONED THROUGH ON PLANS, DETAILS AND WALL
SECTIONS.

	FACE BRICK	SOLID SURFACE	LIGHTWEIGHT BLOCK		TERRAZ
	CONCRETE	EIFS	CONCRETE BLOCK	N	MARBLE
	WOOD BLOCKING	BLANKET INSULATION	PLASTER OR GYPSUM BOARD		
0 0 0 0 0 0 0 0 0	CUT STONE	FINISH WOOD	RIGID INSULATION		

LINE SYMBOLOGY

STONE

IN GENERAL THE FOLLOWING LINE SYMBOLOGY CONVENTIONS APPLY TO THE ENTIRE SET OF DRAWINGS FOR THIS PROJECT, EXISTING, AND DEMOLITION SYMBOLOGY APPLY TO ADDITION AND RENOVATION PROJECTS ONLY.

- "SCREENED" BACKGROUND LINES (LIGHT GRAY LINES) INDICATE EXISTING CONSTRUCTION WALLS, PIPES, LIGHTS, ETC.
- HEAVY DASHED LINES INDICATE DEMOLITION ITEMS ON DEMOLITION DRAWINGS. DEMOLITION DRAWINGS ALSO INDICATE DEMOLITION WORK WITH "LIGHT" DASHED LINES WHEN DEMOLITION WORK IS NOT SPECIFICALLY RELATED TO THE CURRENT SHEET. (FOR EXAMPLE: WALLS BEING REMOVED APPEAR AS HEAVY DASHED LINES ON THE ARCHITECTURAL PLANS AND APPEAR AS LIGHT DASHED LINES ON HVAC, LIGHTING. FTC. PLANS.) -----

LIGHTING, ETC. PLANS.)


- PLAN EXAMPLES: EXISTING WALL EXISTING WALL TO BE REMOVED
- NEW SOUNDPROOF WALL NEW STUD WALL


NEW CMU WALL


ARCHITECTURAL ABBREVIATIONS:

THE ARCHITECTURAL ABBREVIATIONS LISTED BELOW ARE TYPICAL. HOWEVER ALL ABBREVIATIONS PRESENTED HERE HAVE NOT BEEN USED ON THIS PARTICULAR PROJECT. SEE ROOM FINISH SCHEDULE LEGENDS FOR ADDITIONAL ABBREVIATIONS USED ONLY ON THE ROOM FINISH SCHEDULE.


CAB CCER CFOI CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC	ACOUSTICAL ABOVE FINISHED FLOOR ALUMINUM ALTERNATE ANODIZED ARCHITECTURAL BOARD BLOCK BULKHEAD CABINET CHALKBOARD CEMENT CERAMIC CONTRACTOR FURNISHED OWNER INSTALLED CENTERLINE CEILING CONTROL JOINT CLASSROOM CONCRETE CONFERENCE CONFERENCE CONFERENCE CONFERENCE CONFERENCE CONFERENCE CONFERENCE CONFERENCE CONFERENCE CONFERENCE CONFERENCE CONFERENCE CONFERENCE CONFERENCE CONFERENCE CONFERENCE CONFERENCE CONFERENCE CONTINUOUS CORKBOARD CASEWORK CERAMIC TILE DEGREE DEMOLITION DRINKING FOUNTAIN DIAMETER DOWN EXTERIOR INSULATION AND FINISH SYSTEM ELECTRICAL EQUAL EQUIPMENT ELECTRIC WATER COOLER EXISTING EXPANSION JOINT EXTERIOR FLOOR DRAIN	MARB MB MAS MAX MCCH MIN MISC MO MR MTD MTL NA NTS OC OFCI OFOI OFVI OFF ORD PERE	GAGE GALVANIZED GYPSUM HOLLOW METAL HORIZONTAL INSIDE DIAMETER INSULATED, OR INSULATION INTERIOR JANITOR KEENE'S CEMENT PLASTER LAVATORY LIGHTWEIGHT MARBLE MARKERBOARD MASONRY MAXIMUM MISC STEEL CHANNEL MECHANICAL MINIMUM MISC STEEL CHANNEL MINIMUM MISC STEEL CHANNEL MINIMUM MISC STEEL CHANNEL MINIMUM MISC STEEL CHANNEL MINIMUM MISC STEEL CHANNEL MINIMUM MISC STEEL CHANNEL MINIMUM MISC STEEL CHANNEL MINIMUM MINIMUM MISC STEEL CHANNEL MINIMUM MINI	STD STD STD STD STD STD STD STD STD STD	RUBBER E ROOF CON ROOF DRA REINFORCI REINFORCI REVISION ROUGH OF ROUGH OF SQUARE F SIMILAR SMOOTH SPECIFICAT SQUARE SSTAINLESS STAINLESS STAINLESS STEEL AND STEEL M- STEEL STF TUBE STAINLESS STEEL AND STEEL M- STEEL STF UNSTEEL STF TUBE STAINLESS STORAGE SYNTHETIC SYSTEM TELEPHONI TERRAZZO TYPICAL UNFINISHE VINYL BAS VINYL CON TILE VENEER VENTICAL VENDOR F VENDOR IN VENDOR IN VINYL WAL COVERING WITH
EXT FD FE FEC FRP FWC	FLOOR DRAIN FIRE EXTINGUISHER FIRE EXTINGUISHER CABINET FIBERGLASS REINFORCED PANEL FABRIC WALL	PERF PL PLAM PLAS PORC PRCST PTN			COVERING
	COVERING	QT QTY	QUANTITY		












GENERAL DEMOLITION NOTES


- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO GI SERIES SHEETS.
- B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS SHEET.
- C. CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
- E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.
- F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL. REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS.
- G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER. H. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS
- REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE). I. WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION
- AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE PUBLIC. J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER
- OWNERS' DIRECTION, UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEMS ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED. K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING
- CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES
- EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECEIVE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW FINISHES.
- N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED, PATCH OPENINGS AND/OR SURFACES AS REQUIRE TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT OF ITEMS TO REMOVED.
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING. WHERE APPLICABLE, TOOTH NEW MASONRY INTO EXISTING MASONRY.
- P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION. Q. MASONRY WALLS TO BE REMOVED SHALL BE REMOVED TO A POINT 2" MINIMUM BELOW THE EXISTING FLOOR SLAB UNLESS SETTING ON A SLAB OR
- SPECIFICALLY NOTED OTHERWISE. PATCH WITH NEW CONCRETE TO BE FLUSH WITH THE EXISTING FLOOR SLAB. R. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO
- THEIR SCOPE OF WORK. S. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE
- BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF SITE. T. REFER TO THE STRUCTURAL, MECHANICAL, PLUMBING, ELECTRICAL AND
- TECHNOLOGY DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK.
- U. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING, ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE. V. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER
- TO SPECIFICATIONS AND DRAWINGS FOR REQUIREMENTS AND SPECIAL CONDITIONS. W. WHERE APPLICABLE SALVAGE EXISTING MASONRY (FACE BRICK, GLAZED CMU,
- FACING TILE) AS REQUIRED FOR PATCHING AND INFILL IN RENOVATED AREAS WHERE INDICATED. DISCARD UNUSED PORTION OFF SITE. **DEMOLITION PLAN NOTES:**

(ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)


- 1 REMOVE TOILET AND URINAL PARTITIONS IN THEIR ENTIRETY. PREP FLOOR AND WALLS FOR NEW PARTITIONS AND NEW HARDWARE IN SAME LOCATIONS SEE ARCHITECTURAL PLAN.
- 2 REMOVE RECEPTION DESK IN ITS ENTIRETY. PREP AREA TO RECEIVE NEW FINISHES AND NEW RECEPTION COUNTER.
- 3 REMOVE EXISTING CARPET FLOORING AND VINYL WALL BASE SYSTEMS IN ITS ENTIRETY INCLUDING ALL MASTICS. PREPARE ALL SURFACES FOR NEW FINISHES.
- REMOVE EXISTING VCT AND VINYL WALL BASE SYSTEMS IN ITS ENTIRETY INCLUDING ALL MASTICS. ADHESIVES AND SEALERS. PREPARE ALL SURFACES
- FOR NEW FINISHES. 5 REMOVE CERAMIC WALL TILE AND PORCELAIN FLOOR TILE SYSTEM IN ITS ENTIRETY INCLUDING ALL MASTICS AND GROUT. PREPARE FLOOR AND WALL PROJECT FOR NEW FINISHES.
- 6 REMOVE CASEWORK IN ITS ENTIRETY. PATCH AND REPAIR WALL AND FLOOR AS REQUIRED TO ACCEPT NEW FINISHES. ALTERNATE: REMOVE EXISTING CHALKBOARD ONLY. PREP WALL FOR NEW ┘ MARKERBOARD.
- 8 REMOVE EXISTING BEACHERS IN ITS ENTIRETY. PATCH AND REPAIR WALL $\stackrel{\smile}{\rightharpoonup}$ as required to accept new bleachers.
- 9 REMOVE EXISTING CORNER GUARDS IN ITS ENTIRETY. PATCH AND REPAIR WALL AS REQUIRED TO ACCEPT NEW. REMOVE EXISTING CAFE AWNING ABOVE CAFETERIA ENTRANCE. PATCH AND
- REPAIR WALL AS REQUIRED TO ACCEPT NEW FINISHES. 11 WHERE PRESENT, REMOVE EXISTING FLOOR BOXES, PATCH AND REPAIR FLOOR AS NEEDED TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR THE CONCEPTS, DESIGNS, PLANS, DETAILS, ETC, SHOWN ON
- ADDITIONAL INFO. 12 CAREFULLY REMOVE EXISTING DRINKING FOUNTAINS. SECURE AND STORE
- FROM WALL. REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
- 13 MEDIA CENTER SHELVING TO BE MOVED AND STORED/PROTECTED, THEN REINSTALLED AFTER CARPET AND WALL BASE IS REPLACED.
- 14 ALTERNATE: CAREFULLY REMOVE EXISTING PLASTIC LAMINATE COUNTERTOPS IN THEIR ENTIRETY. SECURE AND STORE SINK AND FAUCET ASSEMBLY TO AD-03 3/7/24 ADDENDUM 3 BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING DRAWINGS FOR ADDITIONAL INFO.
- 15 ALTERNATE: REMOVE EXISTING BASKETBALL BACKSTOP AND SUPPORTS COMPLETE TO ALLOW NEW SUPPORTS AND BACKSTOPS. WHERE APPLICABLE PREP EXISTING STRUCTURE TO BE RETROFITTED FOR NEW BASKETBALL BACKSTOPS AND SUPPORTS.
- 16 ALTERNATE: REMOVE EXISTING BASKETBALL BACKSTOP AND SUPPORTS COMPLETE TO ALLOW NEW SUPPORTS AND BACKSTOPS. WHERE APPLICABLE PREP WALL FOR NEW SUPPORTS.








- LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS. B. PLAN DIMENSIONS TO MASONRY WALLS ARE TO FACE OF ROUGH MASONRY.
- C. PROVIDE WOOD BLOCKING (OR METAL STRAPPING WHERE APPLICABLE) AS
- REQUIRED WITHIN METAL STUD WALLS FOR WALL MOUNTED ITEMS. REFER TO DEMOLITION SHEETS FOR ADDITIONAL PATCHING AND REPAIR WORK.
- E. REFER TO FINISH PLANS FOR INTERIOR ELEVATIONS, LOCATION AND EXTENT
- F. REFER TO EQUIPMENT PLANS FOR CASEWORK, DISPLAY BOARDS, LOCKERS, AND OTHER ADDITIONAL TYPICAL EQUIPMENT NOTES AND INFORMATION.
- G. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROOM







GENERAL PLAN NOTES:

- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS. B. PLAN DIMENSIONS TO MASONRY WALLS ARE TO FACE OF ROUGH MASONRY. PLAN DIMENSIONS TO STUD WALLS ARE TO FACE OF FINISHED GYPSUM BOARD OR PLASTER. PLAN DIMENSIONS TO STUD WALLS WITH CERAMIC TILE FINISH ARE TO THE FACE OF TILE BACKER BOARD.
- C. PROVIDE WOOD BLOCKING (OR METAL STRAPPING WHERE APPLICABLE) AS REQUIRED WITHIN METAL STUD WALLS FOR WALL MOUNTED ITEMS.
- D. REFER TO DEMOLITION SHEETS FOR ADDITIONAL PATCHING AND REPAIR WORK. E. REFER TO FINISH PLANS FOR INTERIOR ELEVATIONS, LOCATION AND EXTENT
- OF FINISHED FLOOR AND WALL MATERIAL F. REFER TO EQUIPMENT PLANS FOR CASEWORK, DISPLAY BOARDS, LOCKERS,
- AND OTHER ADDITIONAL TYPICAL EQUIPMENT NOTES AND INFORMATION.
- G. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROOM PLANS AND TOILET ACCESSORIES.


PLAN LEGEND:


PLAN NOTES:


(ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)

- 1 INSTALL NEW MANUAL BLEACHERS, SAME NUMBER OF SEATS AND ROWS AS THE EXISTING. 24" SEAT MINIMUM, MOUNTED TO WALL. (2) BLEACHERS FULLY EXTENDED.
- (3) CASEWORK AND/OR MILLWORK (TYPICAL), REFER TO EQUIPMENT PLANS.
- 4 INSTALL NEW TOILET AND URINAL PARTITIONS IN SAME LOCATION AS EXISTING. INSTALL NEW HARDWARE. OWNER PROVIDED AND INSTALL NEW ACCESSORIES TO PARTITIONS.
- (5) NEW FLOOR AND WALL TILE, SEE TRANSITION DETAILS ON A/820, FIN
- LEGEND AND ELEVATION 4/A-862 (6) EXISTING LOCKERS, FACE ONLY, TO BE ELECTROSTATIC PAINTED. SEE FINISH LEGEND.
- (7) NOT USED
- (8) EXISTING DRINKING FOUNTAINS TO BE REINSTALLED IN SAME LOCATION REFER TO PLUMBING DRAWINGS FOR MORE INFO.
- 9 ALTERNATE: INSTALL NEW PLASTIC LAMINATE COUNTERTOP ON ALL EXISTING CASEWORK COUNTERS. PROVIDE A 4" BACK/SIDE SPLASH.
- (10) ALTERNATE: INSTALL NEW ELECTRIC HAND DRYERS. REFER TO ELECTRICAL DRAWINGS FOR MORE INFO.
- 11) ALTERNATE: INSTALL NEW MOTORIZED FORWARD BASKETBALL BACKSTOP AND SUPPORT FRAMING IN SAME LOCATION AS EXISTING. ADJUSTABLE HEIGHT. WHERE APPLICABLE, RETROFIT NEW SUPPORT FRAMING TO UTIL EXISTING IN-PLACE BEAMS.
- (12) ALTERNATE: INSTALL NEW BASKETBALL BACKSTOP AND WALL SUPPORT FRAMING IN SAME LOCATION AS EXISTING. ADJUSTABLE HEIGHT. WHERE APPLICABLE,
- (13) ALTERNATE: INSTALL NEW MARKERBOARD. SEE EQUIPMENT PLAN AND SPECIFICATIONS.


AD-03

















GENERAL EQUIPMENT PLAN NOTES:

- A. REFER TO SPECIFICATIONS AND FINISH LEGEND FOR ADDITIONAL INFORMATION.
- B. FIELD VERIFY ALL DIMENSIONS.
- C. CASEWORK AND/OR MILLWORK INSTALLER TO COORDINATE ELECTRICAL AND PLUMBING WORK. REFER TO ELECTRICAL DRAWINGS AND SCHEDULES FOR ELECTRICAL DEVICE TYPES, HEIGHTS, AND LOCATIONS.
- D. REFER TO G SERIES DRAWINGS FOR MOUNTING HEIGHTS. E. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROOM
- PLANS AND TOILET ROOM ACCESSORIES. F. NIGHTLOCK DOOR SECURITY DEVICE PROVIDED BY OWNER, INSTALLED BY
- CONTRACTOR. CONTRACTOR TO COORDINATE LOCATIONS AND INSTALLATION WITH OWNER.

EQUIPMENT PLAN LEGEND:

- A-760 DRAWING FOR ELEVATIONS AND DETAILS. ------ INDICATES ITEMS TO BE PART OF LOOSE EQUIPMENT PACKAGE BY OWNER. (NOT INCLUDED IN CONSTRUCTION CONTRACT). ---- INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS (NOT
- INCLUDED IN CONSTRUCTION CONTRACTS).
- (CG) INDICATES CORNER GUARD. (MB) INDICATES 4' HIGH MARKERBOARD LENGTH AS INDICATES, REFER TO MOUNTING HEIGHT DRAWINGS.
 - AD-03


EQUIPMENT PLAN NOTES: (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)


- (1) NEW BLEACHERS, FULLY EXTENDED.
- (2) NEW MANUAL BLEACHERS, SEE FINISH LEGEND.
- $\overline{(3)}$ NOT USED
- (4) NEW TOILET AND URINAL PARTITIONS. OWNER PROVIDED AND INSTALLED ACCESSORIES, SEE FINISH LEGEND.
- (5) ALTERNATE: MOTORIZED FORWARD FOLDING BASKETBALL BACKSTOP SUPPORTS AND BASKETBALL BACKSTOP AND HOOP.
- (6) ALTERNATE: WALL HUNG BASKETBALL BACKSTOP SUPPORTS AND BASKETBALL BACKSTOP AND HOOP.

OWNER FURNISHED EQUIPMENT

PLAN NOTES:

(50) LOOSE FURNITURE, BY OWNER, INDICATED ON PLAN FOR ROOM LAYOUT (51) COMPUTER/MONITOR, BY OWNER





			2X BLOCKING AS
AD-03			
		\rightarrow	~~~~~
A-760 SS		PL3	DRK TRIM DE CORNER PL3-
} PL1	PL1 / FILE FILE PL1 PL1 FILE FILE PL1 V V V V V V V V V V V V V V V V V V V		^{2,-} 6,
	7'-8" 13'-10"		
	ELEVATION SCALE: $3/8" = 1'-0"$ 4		ELEVAT SCALE: 3/8


PLASTIC LAMINATE

VERTICAL BLOCKING ------

4" VINYL BASE, B1 ------


SOLID SURFACE TRANSACTION-TOP WITH EASED EDGE


Wednesday, 3/6/2024 - 9:52 AM - LAST SA Y:\23-117 TRI-CREEK SC -LAKE PRAIRIE ES IMPROVEMENTS\23-117 DRAWINGS\05 ARCH\A-760-LP.DWG




2'-8"


		PLASTI	C LAMINA	ATE CASEWORK SCHEDULE	
	MARK	NUMBER	WIDTH	DESCRIPTION	
	B1 B2	10129 10315		29"H 2 DOORS, ADJUSTABLE SELF.LOCKABLE 29"H 2 FILE DRAWERS, LOCKABLE	
		GENEF	RAL NOTE	${\sf S}$ (applies to plastic laminate casework)	
		"A-800" SE		NS FOR CASEWORK LOCATIONS AND FINISH LEGE 5 FOR FINISH INFORMATION. REFER TO SPECIFICA	
	В.	FOR SCHED	ULING PURPOSE , INC (UNLESS	ES ONLY, MODEL NUMBERS ARE TAKEN FROM S NOTED OTHERWISE) AND ARE FOR CABINET REQ FOR CABINET CONSTRUCTION METHODS.	
	D.	ALL COUNT BACKSPLAS	ERTOPS TO BE H AND/OR END	SEWORK DIMENSIONS WITH CASEWORK MANUFACT PLASTIC LAMINATE WITH 4" HIGH PLASTIC LAMIN SPASH AT ALL LOCATIONS WHERE COUNTERTOP SS NOTED OTHERWISE).	IATE
	E. F.	PROVIDE 3 PROVIDE A	MM PVC EDGE (4" HIGH TOE S	ON ALL PLASTIC LAMINATED COUNTERTOPS AND SPACE ON ALL BASE AND FULL HEIGHT CABINETS	S.
		OPEN INTER	RIORS OF CABIN	SURFACES TO BE PLASTIC LAMINATE FINISHED, II IETRY (UNLESS NOTED OTHERWISE). ENDS SHALL BE FINISHED TO MATCH CASEWORK	
5		CABINETS (UNLESS OTHER	STIC LAMINATE SLOPED TOPS ON ALL WALL AND WISE NOTED). MOLDING PROVIDED SHALL BE CONTINUOUS AS	
		TO MAKE C CASEWORK REQUIRED I	CASEWORK CONT MANUFACTURER FOR A COMPLET	INUOUS TO ADJACENT PARTITION, CEILING, AND/ / INSTALLER SHALL PROVIDE ALL FILLERS AND E AND FINISHED CASEWORK INSTALLATION.	OR BULKH SCRIBES
	L.	ALL ADJOIN	IING CABINETS S	ABINET DRAWERS AND DOORS, KEYED ALIKE BY SHALL BE ALIGNED. ES SHIMMING, PROVIDE ONLY APPROVED METAL	
$\begin{bmatrix} B2 \\ B2 \\ 3'-0'' \\ 3'-0'' \\ 3'-0'' \\ 3'-0'' \\ 3'-0'' \\ 1'-6'' $	N. O.	CABINETS L PROVIDE JO	OCATED IN FRC	NT OF A PIPE CHASE SHALL HAVE REMOVABLE T ALL JUNCTIONS OF CASEWORK / COUNTERTOP	BACKS.
ELEVATION SCALE: 1/4"=1'-0" ROOM: A-131 CADINETS. FLT COUNTERTOP: PL3 2 2	Ρ.	PROVIDE 4'	' HIGH VINYL C	OVE BASE AT ALL TOE SPACE AREAS AND AT EX CABINETS ADJACENT TO TOE SPACES. BY FLOO	
AD-03	Q.	REFER TO LOCATIONS.		WINGS AND SCHEDULES FOR DEVICE TYPES, HE	
	S.	REFER TO ALL CUTTIN	PLUMBING DRAW	/INGS AND SCHEDULES FOR FIXTURE TYPES AND /INGS FOR PLUMBING CONNECTIONS. D PATCHING OF CASEWORK AND COUNTERTOPS	AS REQUIF
	т.	INSTALLER.	"G" SERIES SHE	NG OR CONDUIT SHALL BE BY CASEWORK MANU TETS FOR MOUNTING HEIGHTS OF EQUIPMENT AN	
				LIES TO PLASTIC LAMINATE CASEWORK)	
			INISHED FLOOR PACE WITH VINYI	- BASE BY	
		FLOORING FINISHED E	INSTALLER BACK/END PANE	L	
		BACKSPLAS NOTED OTH	NTERTOP WITH 4 SH AND SIDESPL HERWISE		
<u>-</u>			GENERAL		
	SPECIFICA	ATIONS AND	PLANS FOR Á	FOR FINISH INFORMATION. REFERENCE WRITTEN DDITIONAL INFORMATION. G PROVIDED SHALL BE CONTINUOUS AS NECESS	
RS	MILLWORK	CONTINUO	OUS TO ADJACEN	ING. ONLY APPROVED METAL SHIMS SHALL BE	
				TOE SPACE AREAS AND AT EXPOSED SURFACES ACES. BY FLOORING CONTRACTOR.	S AND SID
	E. FIELD VE			ND SCHEDULES FOR DEVICE TYPES, HEIGHTS, A	ND LOCATI
B1	CABINETR	Ϋ́.		ASTIC LAMINATE FINISHED, INCLUDING OPEN INT	ERIORS OF
			NETS SHALL BE ARE TO BE FII		
				EY ALIKE BY ROOM. PS TO HAVE 3MM PVC EDGE.	
]
					-
			_		
			$\begin{pmatrix} 4 \end{pmatrix}$		
GROMM	1ET -				
4'-7"		<u> </u>			










- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE
- D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS
- E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING
- F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING









GENERAL FINISH PLAN NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING
- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE
- FINISH WORK HAS PROCEEDED. . PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD.
- F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION.
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES. H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS
- OTHERWISE NOTED. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED ON PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED
- TYPE/COLOR WITH ARCHITECT. PAINT ALL NEW DOOR FRAMES TO MATCH EXISTING (BRONZE COLOR, P8)
- ALL SIDES UNLESS NOTED OTHERWISE. PAINT EXISTING DOOR FRAMES IN ADMIN AREA TO MATCH EXISTING (BRONZE COLOR, P8). K. UNLESS NOTED OTHERWISE, PAINT GYPSUM BOARD AND OR PLASTER CE
- AND BULKHEADS SHERWIN WILLIAMS SW7007. L. EXISTING FABRIC WRAPPED TACKABLE WALLS, TACKABLE PANELS,
- MARKERBOARDS, TACKBOARDS OR SIGNAGE SHALL REMAIN. M. OWNER HAS FINAL CONFIRMATION TO COVER PAINTED MURALS WITH NEW PAINT. VERIFY WITH OWNER.

FINISH SYMBOL LEGEND

P1 _	
C1	-FLOOR FINISH
B1	-BASE FINISH


FLOOR TRANSITION STRIP AS REQUIRED

INDICATES DIRECTION OF FLOOR MATERIAL GRAIN

FINISH PLAN NOTES:

(ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)

- (1) NO NEW FINISHES THIS ROOM, EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES.
- (2) WALL AND FLOOR TILE, REFER TO FINISH LEGEND AND ELEVATION ON SHEET 4/A-862
- (3) PAINT, P3 AND P4. SEE FINISH LEGEND AND ELEVATION ON SHEET A-862.
- (4) paint bulkhead, slanted wall, and/or light cove, p6
- (5) EXISTING FRAMED WALL GRAPHIC TO REMAIN.
- (6) LOCKERS, PAINT, P5.
- 7) EXISTING WALL MURAL TO REMAIN
- 8) PAINT, P2.
- (9) EXISTING BRICK TO REMAIN. NO NEW FINISH TO BE APPLIED. 10) ROLLED CARPET ON MEDIA STEPS, C4
- 1) WALL COATING, W2
- 12) CARPET, C5.
- (13) CARPET C3 ENDS HERE.
- (14) LVT, LVT2
- (15) ALTERNATE: PLASTIC LAMINATE COUNTERTOP PL4








	SURFACE	MARK	DESCRIPTION	MANUFACTURER	PATTERN/FINISH	NUMBER/COLOR	SIZE	COMMENTS
L,	WALL BASE							
		B1	WALL BASE	TARKETT		BURNT UMBER 63	4" COVE	
F		B2	WALL BASE	TARKETT		BURNT UMBER 63	6" MILLWORK	
Ļ								
		TB1	TILE BASE	DALTILE	UNGLAZED MOSAICS	STORM GRAY SPECKLED A22	5" BUILT-UP COVE	
l -								
ľ	FLOOR MATERIAL	_ 5 C1a	CARPET TILE	TARKETT	SQUAREUP II 11549	ELECTRICITY 71604	24" X 24"	INSTALL: VERTICAL ASHLAR
	C1	C1b	CARPET TILE	MANNINGTON	HUB	CUSTOM COLOR	24" X 24"	INSTALL: VERTICAL ASHLAR
F		C2a	CARPET TILE	TARKETT	CREATE BALANCE 11770	FORWARD 32809	24" X 24"	INSTALL: VERTICAL ASHLAR
	C2	C2b	CARPET TILE	MANNINGTON	CIRCUIT	VIDEO DECODER 14403	24" X 24"	INSTALL: VERTICAL ASHLAR
Г	C3	C3a	CARPET TILE	TARKETT	ABRASIVE ACTION II 02578	WINTER GRAY 19103	24" X 24"	INSTALL: MONOLITHIC
F		C3b	CARPET TILE	MANNINGTON	FORCE	STATIC 34365	18" X 36"	INSTALL: MONOLITHIC
	C4	C4a	ROLLED CARPET		CREATE BALANCE 11770	FORWARD 32809	1260" X 72"	
		C4b C5a	ROLLED CARPET CARPET TILE	MANNINGTON TARKETT	CIRCUIT FABRICATE 11498	VIDEO DECODER 14403 BASE GREY 36201	150" 24" X 24"	 INSTALL: VERTICAL ASHLAR
	C5	C5h				EDGGX 13354		INSTALL: VERTICAL ASHLAR
· · · ·		C6	CARPET TILE	TARKETT	GABARDINE 11511	BEDSTONE 77204	24" X 24"	INSTALL: VERTICAL ASHLAR
		\rightarrow		ϕ		+		
F	LVT1	LVT1a	LUXURY VINYL TILE	TARKETT	ENTWINE	OXFORD 10383	36" X 9"	
L	LVI 1	LVT1b	LUXURY VINYL TILE	MANNINGTON	CRISSCROSS	FLASH AL101	36" X 6"	
	LVT2	LVT2a	LUXURY VINYL TILE	TARKETT	ENTWINE	SHADOWSTITCH 10380	36" X 9"	
F		LVT2b	LUXURY VINYL TILE	MANNINGTON	CRISSCROSS	POP ALC401	36" X 6"	
F		FT1						
F			MOSAIC FLOOR TILE	AMERICAN OLEAN	UNGLAZED MOSAICS	STROM GRAY SPECKLED A22	2" X 2"	
-								<u> </u>
-	WALL MATERIAL	1						
-		P1	PAINT	SHERWIN WILLIAMS	<u> </u>	SW 7029 AGREEABLE GRAY SW 7017 DORIAN GRAY		
-		P2 P3	PAINT PAINT	SHERWIN WILLIAMS SHERWIN WILLIAMS	 	CUSTOM		 SEE NOTE 1
-		P4	PAINT	SHERWIN WILLIAMS		CUSTOM		SEE NOTE 2
_		P5	PAINT	SHERWIN WILLIAMS		CUSTOM		SEE NOTE 3
		P6	PAINT	SHERWIN WILLIAMS		SW 7004 SNOWBOUND		
-		P7 P8	PAINT PAINT	SHERWIN WILLIAMS SHERWIN WILLIAMS		SW 7757 HIGH REFLECTIVE WHITE CUSTOM		 SEE NOTE 4
-		FO		SHERWIN WILLIAMS				SEL NOTE 4
-		W1	WALLCOATING	SHERWIN WILLIAMS		SW 7029 AGREEABLE GRAY		
		W2	WALLCOATING	SHERWIN WILLIAMS		SW 7017 DORIAN GRAY		
_		WT1	CERAMIC WALL TILE	AMERICAN OLEAN	COLOR STORY WALL	ICE WHITE 0025	4" X 12"	
_		WT2	CERAMIC WALL TILE	AMERICAN OLEAN	COLOR STORY WALL	STABLE 0053	4" X 12"	
-		WT3	CERAMIC WALL TILE	AMERICAN OLEAN	COLOR STORY WALL	DEPENDABLE 0053	4" X 12"	
F		WT4	CERAMIC WALL TILE	AMERICAN OLEAN	COLOR STORY WALL	STORM GRAY 40	4" X 12"	
F		AR-AWP1	ACOUSTICAL PANEL		ТЕСТИМ	SW 7017 DORIAN GRAY		
-		AR-AWP2	ACOUSTICAL PANEL		ТЕСТИМ	CUSTOM		SEE NOTE 1
-		AR-AWP3	ACOUSTICAL PANEL		ТЕСТИМ	CUSTOM		SEE NOTE 2
-								
1	CASEWORK AND	MILLWORK						
		PL1	PLASTIC LAMINATE	WILSONART	12 SOFTGRAIN	UPTOWN WALNUT 7917		
Ľ		PL2	PLASTIC LAMINATE	WILSONART	31 TRACELESS	CHARCOAL VELVET 15504		
F		PL3	PLASTIC LAMINATE	WILSONART	38 FINE VELVET TEXTURE	ORGANIC COTTON 4945		
┝		PL4	PLASTIC LAMINATE	WILSONART	60 MATTE	CANYON ZEPHYR 4842		
⊢		<u></u>						
F		SS1	SOLID SURFACE	CORIAN		PLATINUM		
F								
F	MISCELLANEOUS	6						
- F		CG1	CORNER GUARD	[
F		TP1	TOLIET PARTITION	ASI	ORANGE PEEL	GRAY 9200		
F		TRIM1	METAL TRIM	SCHLUTER	RONDEC	SATIN ANODIZED ALUMINUM		
F		BL1	BLEACHER SEAT	HUSSEY SEATING		GREY 050		
F								<u> </u>
F								
-	ETR = EXISTING							
	1. CUSTOM COLOF	R TO MATCH S	CHOOL COLOR BLUE. HEX	#204E9E, TO BE VERIFIED IEX #F59923, TO BE VERIF DITION.	WITH OWNER.			
	Z. CUSIUM COLOH	N IU MAICH S	NUTIOUL CULUK UKANGE, H	ILA #FJYYZS, IU BE VERH	TED WITH OWNER.			
	3. CUSTOM COLO	R TO MATCH L	OCKER COLOR IN NEW AD.	DITION.		DUCT. INSTALL ONE DIE LOT IN A ROOM.		


VINYL TRIM —	VINYL COMPOSITION
	/ TILE
	<u>/</u>
	FLOOR LINE
CARPET TO	VINYL
DIVIDER	
STRIP	
	/ PORCELAIN TILE
PROVIDE TAPERED	
FLOOR LEVELER AS	∽ FLOOR LINE
REQUIRED FOR TOP OF CARPET TO BE FLUSH	
WITH TOP OF TILE	
CARPET TO PO	KUELAIN IILE

FLOOR TRANSITION DETAILS SCALE: 6'' = 1'-0''











GYMNASIUM SOUTH ELEVATION \A−861/ GENERAL INTERIOR ELEVATION NOTES:


- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE FLOOR PATTER PLANS, EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
- C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE SSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE FINISH WORK HAS PROCEEDED.
- D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- F. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803.


INTERIOR ELEVATION NOTES: (ALL ELEVATION NOTES MAY NOT BE INDICATED ON THIS PLAN)


- 1) EXISTING DOOR.
- 2) EXISTING WINDOW. 3) EXISTING HVAC LOUVER.
- (4) EXISTING FIRE EXTINGUISHER CABINET.
- 5) BLEACHERS, REFER TO EQUIPMENT PLANS.
- (6) EXISTING LOCKERS, PAINT, P5
- 7) ALTERNATE: NEW BASKETBALL BACKSTOP AND SUPPORT, REFER TO EQUIPMENT PLANS.
- (8) EXISTING SAFETY CUSHION WAINSCOT.
- 9) EXISTING SCOREBOARD.
- 10) EXISTING EXPOSED STRUCTURE AND ROOF DECK.
- 11) EXISTING HVAC.
- 12) EXISTING EXIT SIGN. 13) EXISTING MARKERBOARD/TACKBOARD.
- (14) EXISTING STAGE.
- (15) EXISTING SPEAKERS.
- (16) EXISTING DISPLAY CASE.


INTERIOR ELEVATION FINISH NOTES: (ALL ELEVATION NOTES MAY NOT BE INDICATED ON THIS PLAN)

- (50) PAINT, P1
- (51) PAINT, P2
- (52) PAINT, P3
- (53) PAINT, P4 (54) NOT USED
- (55) PAINT, P6
- (56) WALLCOATING, W1
- (57) WALLCOATING, W2
- (58) PAINT, P7
- (59) NOT USED
- (60) EXISTING WALL COVERING TO REMAIN. (61) WALL BASE, B1
- (62) WALL BASE, B2
- (63) ACOUSTICAL WALL PANEL AR-AWP1
- (64) ACOUSTICAL WALL PANEL AR-AWP2
- (65) ACOUSTICAL WALL PANEL AR-AWP3
- (66) SCHLUTER TRIM, OUTSIDE CORNER OR END OF TILE RUN










A-862

Thursday, 3/7/2024 - 5:15 PM - LAST SAVI Y:\23-117 TRI-CREEK SC - LAKE PRAIRIE ES IMPROVEMENTS\23-117 DRAWINGS\05 ARCH\A-862-LP.DWG




CLASSROOM ENTRANCE (TYPICAL) SCALE: 1/4" = 1'-0"


57


53 4"





(52)













A-862









WT1 AMERICAN OLEAN

ICE WHITE 0025 (4X12)

WT2 AMERICAN OLEAN

DEPENDABLE 0053 (4X12)

WT4 AMERICAN OLEAN

STABLE 0055 (4X12)

🕅 WT3 AMERICAN OLEAN

□ STORM GRAY 0040 (4X12)

(54) NOT USED

(55) PAINT, P6 (56) WALLCOATING, W1

- 63) ACOUSTICAL WALL PANEL AR-AWP1 (64) ACOUSTICAL WALL PANEL AR-AWP2
- (65) ACOUSTICAL WALL PANEL AR-AWP3
- (66) SCHLUTER TRIM, OUTSIDE CORNER OR END OF TILE RUN

GENERAL INTERIOR ELEVATION NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE FLOOR PATTER PLANS, EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
- C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE FINISH WORK HAS PROCEEDED.
- D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS
- AND MATERIALS FOR ALL FINISHES. E. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- F. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803.

INTERIOR ELEVATION NOTES: (ALL ELEVATION NOTES MAY NOT BE INDICATED ON THIS PLAN)

(1) EXISTING DOOR.

2) EXISTING WINDOW.

- 3) EXISTING HVAC LOUVER.
- (4) EXISTING FIRE EXTINGUISHER CABINET.
- 5) BLEACHERS, REFER TO EQUIPMENT PLANS.


- (6) EXISTING LOCKERS, PAINT, P5 7) ALTERNATE: NEW BASKETBALL BACKSTOP AND SUPPORT, REFER TO
- EQUIPMENT PLANS.
- (8) EXISTING SAFETY CUSHION WAINSCOT.
- 9) EXISTING SCOREBOARD.
- 10) EXISTING EXPOSED STRUCTURE AND ROOF DECK.
- 11) EXISTING HVAC.
- 12) EXISTING EXIT SIGN. 13) EXISTING MARKERBOARD/TACKBOARD.
- (14) EXISTING STAGE.
- (15) EXISTING SPEAKERS.
- (16) EXISTING DISPLAY CASE.

INTERIOR ELEVATION FINISH NOTES: (ALL ELEVATION NOTES MAY NOT BE INDICATED ON THIS PLAN)

- (50) PAINT, P1
- (51) PAINT, P2
- (52) PAINT, P3
- (53) PAINT, P4

- (57) WALLCOATING, W2
- (58) PAINT, P7
- (59) NOT USED
- (60) EXISTING WALL COVERING TO REMAIN.
- (61) WALL BASE, B1
- 62) WALL BASE, B2







GENERAL DEMOLITION NOTES: A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL

- LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS. B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS
- RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS SHEET.
- C. CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
- E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.
- F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION. VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL. REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS.
- G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER.
- H. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE).
- I. WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE PUBLIC.
- J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER OWNERS' DIRECTION, UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEMS ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED.
- K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR, OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES.
- .. EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE CENTER EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW FINISHES.
- N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, AND ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED, PATCH OPENINGS AND/OR SURFACES AS REQUIRED TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT OF ITEMS TO REMOVED.
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING. WHERE APPLICABLE, TOOTH NEW MASONRY INTO EXISTING MASONRY.
- P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION.
- Q. MASONRY WALLS TO BE REMOVED SHALL BE REMOVED TO A POINT 2" MINIMUM BELOW THE EXISTING FLOOR SLAB UNLESS SETTING ON A SLAB OR SPECIFICALLY NOTED OTHERWISE. PATCH WITH NEW CONCRETE TO BE FLUSH WITH THE EXISTING FLOOR SLAB.
- R. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO THEIR SCOPE OF WORK.
- S. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF SITE.
- T. REFER TO THE STRUCTURAL, MECHANICAL, PLUMBING, ELECTRICAL AND TECHNOLOGY DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK.
- U. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING, ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE. V. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER
- TO SPECIFICATIONS AND DRAWINGS FOR REQUIREMENTS AND SPECIAL CONDITIONS.
- W. WHERE APPLICABLE SALVAGE EXISTING MASONRY (FACE BRICK, GLAZED CMU, FACING TILE) AS REQUIRED FOR PATCHING AND INFILL IN RENOVATED AREAS WHERE INDICATED. DISCARD UNUSED PORTION OFF SITE.
- X. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW CEILING PADS.

DEMOLITION PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.) 1 | REMOVE EXISTING FLOOR FINISHES AND WALL BASE IN ITS ENTIRETY, PREP | DRAWN BY 7 FOR NEW FINISHES. 2 REMOVE EXISTING WALL COVERING IN ITS ENTIRETY INCLUDING MASTICS, ADHESIVES, AND SEALERS. PREPARE WALL FOR NEW FINISHES.
- 3 REMOVE EXISTING ACOUSTIC CEILING PADS. CLEAN GRID AND PREP TO RECEIVE NEW ACOUSTIC PADS.
- 4 REMOVE ACOUSTICAL BOARD CEILING, GRID AND SUSPENSION SYSTEM SALVAGE FOR REUSE IN ITS ENTIRETY. PREP TO RECEIVE NEW GRID AND ACOUSTICAL CEILING. REFER TO REFLECTED CEILING PLANS FOR COORDINATION W/ EXISTING CONDITIONS WHERE PRESENT.
- 5 REMOVE METAL STUD WALL IN ITS ENTIRETY. PATCH AND REPAIR ADJACENT
- 7 CAREFULLY REMOVE AND SALVAGE SECTION OF EXISTING CASEWORK FOR
- NEW FINISHES.
- 8 REMOVE CASEWORK AND SHELVING IN ITS ENTIRETY. PATCH FLOOR AND WALL TO RECEIVE NEW FINISHES.
- 9 CAREFULLY REMOVE AND SALVAGE MEDIA SHELVING FOR REUSE ELSEWHERE IN MEDIA CENTER
- 10 REMOVE EXISTING MILLWORK SYSTEM IN ITS ENTIRETY. PATCH AND REPAIR FLOOR TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR ADDITIONAL INFO.
- 11 REMOVE MARKERBOARD/ TACKBOARD/ CHALKBOARD IN ITS ENTIRETY, PREP WALL FOR NEW FINISHES 12 EXISTING DOOR TO BE REMOVED. HOLLOW METAL FRAME TO REMAIN.
- MODIFY AND PREP EXISTING FRAME TO RECEIVE NEW DOOR HARDWARE AND TO RETURN TO LIKE NEW CONDITIONS. 13 REMOVE PORTION OF CMU WALL FOR NEW WINDOW, REFER TO FLOOR
- PLANS. 14 CAREFULLY REMOVE GYPSUM BOARD FROM UNDERSIDE OF STAIRS COMPLETE TO EXPOSE TREADS, PREP AREA TO RECEIVE NEW GYPSUM
- BOARD IN SAME PLACE. 15 REMOVE TV ASSEMBLY COMPLETE. PATCH AND REPAIR WALL TO RECEIVE NEW FINISHES.
- 16 REMOVE ALL WALL MOUNTED ACOUSTICAL PANELS IN THEIR ENTIRETY. $^{-\!-\!-}$ patch and repair wall to return to like new conditions refer to A-860 AND A-861 FOR INSTALLATION OF NEW ACOUSTICAL WALL PANELS.
- 17 EXISTING MARKERBOARD/ TACKBOARD TO REMAIN. 18 CAREFULLY REMOVE AND SALVAGE MARKERBOARD / TACKBOARD FOR REUSE UNIT "D" ARCHITECTURAL
- IN SAME LOCATION. PATCH AND REPAIR WALL TO RECEIVE NEW FINISHES. 19 CAREFULLY REMOVE AND SALVAGE TV ASSEMBLY FOR REUSE IN SAME
- LOCATION. PATCH AND REPAIR WALL TO RECEIVE NEW FINISHES.





GENERAL FINISH PLAN NOTES:

A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING

- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION. C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE
- FINISH WORK HAS PROCEEDED. D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN $10^{\circ}-0$ " WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD. F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING
- MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION. G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES.
- H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED ON THE FLOOR PATTERN PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED TYPE/COLOR WITH ARCHITECT.
- J. ALL FLOOR FINISH TRANSITIONS AT DOORS SHALL BE CENTERED UNDER DOOR UNLESS NOTED UTHERWISE. K. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A
- FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803. L. PAINT ALL SIDES OF NEW DOOR FRAMES TO MATCH EXISTING, P4, UNLESS
- NOTED OTHERWISE. M. EXPOSED SURFACES OF DUCTWORK TO BE PAINTED TO MATCH ADJACENT SURFACES UNLESS NOTED OTHERWISE.
- N. EXISTING BRICK TO REMAIN, DO NOT PAINT.

FINISH SYMBOL LEGEND:

P.	1 _		SH		
C	1	-FLOOR FIN	NSH		
B	1 _	-BASE FINI	SH		
		-MISC FINIS	SH INFO	DRM	ATION
-X	FLOOR	TRANSITION	STRIP	AS	REQUIRED
\wedge					


INDICATES DIRECTION OF MATERIAL GRAIN


INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS, REFER TO REFLECTED CEILING PLANS.

FINISH PLAN NOTES:


(ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)

- 1 NO NEW FINISHES THIS ROOM. EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES. 2) WALLCOVERING, WC2
- (3) NEW ACOUSTICAL WALL PANELS, THIS ROOM, REFER TO A-860 SERIES SHEETS
- (4) EXPOSED STRUCTURE AND HVAC, THIS ROOM, TO RECEIVE NO PAINT. EXISTING FINISH TO REMAIN. (5) PAINT DOOR FRAME, P4
- 6 COORDINATE CARPET INSTALLATION WITH PHASE 1. AD-03





UNIT "E" FIRST FLOOR FINISH PLAN SCALE: 1/8" = 1'-0"



GENERAL FINISH PLAN NOTES:

A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING

- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION. C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE
- FINISH WORK HAS PROCEEDED. D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD.
- F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION.
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES. H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED ON THE FLOOR PATTERN PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED TYPE/COLOR WITH ARCHITECT.
- J. ALL FLOOR FINISH TRANSITIONS AT DOORS SHALL BE CENTERED UNDER DOOR UNLESS NOTED UTHERWISE. K. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW
- INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803.
- L. PAINT ALL SIDES OF NEW DOOR FRAMES TO MATCH EXISTING, P4, UNLESS NOTED OTHERWISE. M. EXPOSED SURFACES OF DUCTWORK TO BE PAINTED TO MATCH ADJACENT
- SURFACES UNLESS NOTED OTHERWISE. N. EXISTING BRICK TO REMAIN, DO NOT PAINT.

FINISH SYMBOL LEGEND:


P1 —	
C1	-FLOOR FINISH
B1 —	—BASE FINISH


INDICATES DIRECTION OF MATERIAL GRAIN

INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS, REFER TO REFLECTED CEILING PLANS.

FINISH PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)
- 1 NO NEW FINISHES THIS ROOM. EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES. (2) WALLCOVERING, WC2
- $(\overline{3})$ NEW ACOUSTICAL WALL PANELS, THIS ROOM, REFER TO A-860 SERIES SHEETS
- 4 EXPOSED STRUCTURE AND HVAC, THIS ROOM, TO RECEIVE NO PAINT. EXISTING FINISH TO REMAIN. 5 PAINT DOOR FRAME, P4
- 6 COORDINATE CARPET INSTALLATION WITH PHASE 1. AD-03






GENERAL FINISH PLAN NOTES:

A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING

- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION. C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE
- FINISH WORK HAS PROCEEDED. D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD. F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING
- MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION.
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES. H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED ON THE FLOOR PATTERN PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED TYPE/COLOR WITH ARCHITECT.
- J. ALL FLOOR FINISH TRANSITIONS AT DOORS SHALL BE CENTERED UNDER DOOR UNLESS NOTED UTHERWISE. K. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A
- FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803. L. PAINT ALL SIDES OF NEW DOOR FRAMES TO MATCH EXISTING, P4, UNLESS
- NOTED OTHERWISE. M. EXPOSED SURFACES OF DUCTWORK TO BE PAINTED TO MATCH ADJACENT
- SURFACES UNLESS NOTED OTHERWISE. N. EXISTING BRICK TO REMAIN, DO NOT PAINT.

FINISH SYMBOL LEGEND





INDICATES DIRECTION OF MATERIAL GRAIN

INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS, REFER TO REFLECTED CEILING PLANS.

FINISH PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)
- 1 NO NEW FINISHES THIS ROOM. EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES. 2) WALLCOVERING, WC2
- (3) NEW ACOUSTICAL WALL PANELS, THIS ROOM, REFER TO A-860 SERIES SHEETS
- 4 EXPOSED STRUCTURE AND HVAC, THIS ROOM, TO RECEIVE NO PAINT. EXISTING FINISH TO REMAIN. 5 PAINT DOOR FRAME, P4
- (6) COORDINATE CARPET INSTALLATION WITH PHASE 1.) AD-03





GENERAL FINISH PLAN NOTES

A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING

- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION. C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ÍSSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE
- FINISH WORK HAS PROCEEDED. D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN $10^{\circ}-0$ " WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD. F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING
- MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION. G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES.
- H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED ON THE FLOOR PATTERN PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED TYPE/COLOR WITH ARCHITECT.
- J. ALL FLOOR FINISH TRANSITIONS AT DOORS SHALL BE CENTERED UNDER DOOR UNLESS NOTED UTHERWISE. K. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX
- OF 450 MAXIMUM, PER IBC SECTION 803. L. PAINT ALL SIDES OF NEW DOOR FRAMES TO MATCH EXISTING, P4, UNLESS
- NOTED OTHERWISE. M. EXPOSED SURFACES OF DUCTWORK TO BE PAINTED TO MATCH ADJACENT SURFACES UNLESS NOTED OTHERWISE.
- N. EXISTING BRICK TO REMAIN, DO NOT PAINT.

FINISH SYMBOL LEGEND:


P	1 -	-WALL	FINIS	SH		
С	1 _	-FLOOF	r fin	ISH		
B	1 -	—BASE	FINIS	SH		
·		-MISC	FINIS	SH INFO) RM/	ATION
_X _	FLOOR	TRANSI	TION	STRIP	AS	REQUIRED
\uparrow						


INDICATES DIRECTION OF MATERIAL GRAIN

INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS, REFER TO REFLECTED CEILING PLANS.

FINISH PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)
- 1 NO NEW FINISHES THIS ROOM. EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES. (2) WALLCOVERING, WC2
- (3) NEW ACOUSTICAL WALL PANELS, THIS ROOM, REFER TO A-860 SERIES SHEETS
- 4 EXPOSED STRUCTURE AND HVAC, THIS ROOM, TO RECEIVE NO PAINT. EXISTING FINISH TO REMAIN. 5 PAINT DOOR FRAME, P4
- 6 COORDINATE CARPET INSTALLATION WITH PHASE 1. AD-03





GENERAL FINISH PLAN NOTES:

A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING

- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION. C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE
- FINISH WORK HAS PROCEEDED. D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN $10^{\circ}-0^{\circ}$ WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD. F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING
- MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION.
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES. H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED ON THE FLOOR PATTERN PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED TYPE/COLOR WITH ARCHITECT.
- J. ALL FLOOR FINISH TRANSITIONS AT DOORS SHALL BE CENTERED UNDER DOOR UNLESS NOTED UTHERWISE. K. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A
- FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803. L. PAINT ALL SIDES OF NEW DOOR FRAMES TO MATCH EXISTING, P4, UNLESS
- NOTED OTHERWISE. M. EXPOSED SURFACES OF DUCTWORK TO BE PAINTED TO MATCH ADJACENT
- SURFACES UNLESS NOTED OTHERWISE. N. EXISTING BRICK TO REMAIN, DO NOT PAINT.

FINISH SYMBOL LEGEND:

P1	1 -	-WALL	FINIS	SН		
C1	1	-FLOO	r fin	ISH		
B1	1 _	—BASE	FINIS	SH		
		-MISC	FINIS	H INFO	DRM	ATION
-X -	FLOOR	TRANS	ITION	STRIP	AS	REQUIRED


INDICATES DIRECTION OF MATERIAL GRAIN

INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS, REFER TO REFLECTED CEILING PLANS.

FINISH PLAN NOTES:

(ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)


- 1 NO NEW FINISHES THIS ROOM. EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES. (2) WALLCOVERING, WC2
- (3) NEW ACOUSTICAL WALL PANELS, THIS ROOM, REFER TO A-860 SERIES SHEETS
- (4) EXPOSED STRUCTURE AND HVAC, THIS ROOM, TO RECEIVE NO PAINT. EXISTING FINISH TO REMAIN. (5) PAINT DOOR FRAME, P4
- 6 COORDINATE CARPET INSTALLATION WITH PHASE 1. AD-03




Tuesday, 3/5/2024 - 12:03 PM - LAST SAVED BY:ASCOTT Y:\23-107 TRI-CREEK SC -LOWELL MS MEDIA CENTER IMPROVEMENTS\23-107 DRAWINGS\05 ARCH\A-820-MS.DWG

SURFACE	MARK	DESCRIPTION	MANUFACTURER	PATTERN/FINISH	NUMBER/COLOR	SIZE	COMMENTS
EILING MATERI	ALS						
	ACT1	ACOUSTICAL CEILING	USG	RADAR 2410	WHITE	24" X 48"	
	ACT2	ACOUSTICAL CEILING	USG	RADAR HIGH NRC 22122	WHITE	24" X 48"	
	ACC1	ACOUSTIC. CEILING CLOUD	MDC	ZINTRA CLOUD SQUARE	PEBBLE (PB)	108"X 108"	
	ACC2	ACOUSTIC. CEILING CLOUD	MDC	ZINTRA CLOUD SQUARE	SLATE (SL)	108 X 108"	
	ACC3	ACOUSTIC. CEILING CLOUD	MDC	ZINTRA CLOUD SQUARE	PEBBLE (PB)	48" X 48"	
	ACC4	ACOUSTIC. CEILING CLOUD	MDC	ZINTRA CLOUD SQUARE	SLATE (SL)	48" X 48"	
	P3	PAINT	SHERWIN WILLIAMS		SW 7007 CEILING BRIGHT WHITE		
	•	•					
VALL BASE							
	B1	VINYL BASE	TARKETT		BURNT UMBER 63	4" COVE	
LOOR MATERIA	LS						
	C1	CARPET TILE	TARKETT	APPLAUSE III 02803	FIREWORKS 28515	24" X 24"	INSTALL: MONOLITHIC
	C2	CARPET TILE	TARKETT	VISUAL PATH 11684	BE COURTEOUS 20504	24" X 24"	INSTALL: VERTICAL ASHLAR
	LVT1	LUXURY VINYL TILE	TARKETT	EVEN PLANE – CEMENT	MEDIUM GRAY 8704	50CM X 50CM	INSTALL: QUARTER TURN
	•					•	
VALL MATERIAL	_S						
	P1	PAINT	SHERWIN WILLIAMS		SW 7029 AGREEABLE GRAY		
	P2	PAINT	SHERWIN WILLIAMS		CUSTOM		SEE NOTE 1
	P3	SEE CEILING MATERIALS					
	P4	PAINT	SHERWIN WILLIAMS		CUSTOM		SEE NOTE 2
	WC1	WALL COVERING	MOMENTUM	ON TRACK	DESTINATION SG3094		
	FW-AWP1	ACOUSTICAL PANEL	MAYER FABRICS	EQUAL	OPAL EQ394		
	FW-AWP1	ACOUSTICAL PANEL	MAYER FABRICS	EQUAL	GREY MIX EQ238		
	FW-AWP3	ACOUSTICAL PANEL	MAYER FABRICS	EQUAL	CLARENT ACCENT EQ418		
	AR-AWP1	ACOUSTICAL PANEL	SHERWIN WILLIAMS	ТЕСТИМ	CRUSHED ICE SW7637		
	AR-AWP2	ACOUSTICAL PANEL	SHERWIN WILLIAMS	ТЕСТИМ	SW 7017 DORIAN GRAY		
	AR-AWP3	ACOUSTICAL PANEL	SHERWIN WILLIAMS	ТЕСТИМ	SW 7585 SUN DRIED TOMATO		
ASEWORK AND							
\mathbf{v} \mathbf{v} \mathbf{v} \mathbf{v} $\mathbf{\nabla}$ $\mathbf{\nabla}$	PL1 V V	PLASTIC [®] LAMINATE	WILSONART V V V	60 MATTE VVVV	ŤUNČSTĚN ĚV 4814	\cdot	
	PL2	PLASTIC LAMINATE	NEVAMAR		WHITE ESSENCE		
	PL3	PLASTIC LAMINATE	WILSONART	38 FINE VELVET TEXTURE	RIVER CHERRY 7937		
	PL4	PLASTIC LAMINATE	WILSONART	38 FINE VELVET TEXTURE	OILED SOAPSTONE 4882		
	PL5	PLASTIC LAMINATE	NOT USED	<u> </u>		~~~{^	~_ <mark>^_</mark> ^_^
	SS1	SOLID SURFACE	CORIAN		NEUTRAL AGGREGATE		
	1		<u>1 · · · · · · · · · · · · · · · · · </u>	<u>I</u>		I	I
MISCELLANEOU	s						
	TRIM1	METAL TRIM	SCHLUTER	RONDEC	SATIN ANODIZED ALUMINUM		
		WOOD DOOR STAIN		WHITE OAK CLEAR STAIN			
	•	•		•	·		•
ETR = EXISTING	TO REMAIN						
		ISTING PAINT IN CLASSROOM	_				

	ICI 1793	DAMAS	κs	ILK				
	CCE COL	ORANT			0Z	32	64	128
	B1-BLAC	K			_	5	_	-
	R2-MARC	ON		_	1	1	_	
	Y3-DEEP	GOLD			-	8	1	1
2.	CUSTOM	COLOR	TO	MATCH	EXISTI	NG DOO	DR FRA	MES.
	ICI 1721	IURRE	I B	ROWN				
	CCE COL	ORANT			0Z	32	64	128
	B1-BLAC	K			2	21	1	1
	N1-RAW	UMBER			_	63	_	1
	R2-MARC	ON			_	40	1	1
	Y3-DEEP	GOLD			4	1	1	1





-11" EQ1	
$\begin{array}{c c} & & & & \\ \hline & & & \\ \hline 52 & & & \\ \hline 52 & & & \\ \hline 52 & & & \\ \hline 54 & & \\ \hline 53 & & \\ \hline 53 & & \\ \hline 53 & & \\ \hline \end{array}$	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$
	8
NORTH ELEVATION 1	1 A-860

GENERAL INTERIOR ELEVATION NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE FLOOR PATTER PLANS, EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
- C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALI SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL B ÍSSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE FINISH WORK HAS PROCEEDED.
- D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- . THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803.

INTERIOR ELEVATION LEGEND:

----- EXISTING OR RELOCATED COMPONENTS, REFER TO FLOOR AND EQUIPMENT PLANS.


----- NEW COMPONENTS, REFER TO FLOOR AND EQUIPMENT PLANS.


INTERIOR ELEVATION NOTES:

- 1 DOOR. 2) WINDOW.
- (3) EXISTING HVAC LOUVERS. CLEAN EXISTING GRILLES AND PAINT, P1.
- (4) EXISTING RAILING. 5) RELOCATED CASEWORK, REFER TO EQUIPMENT PLAN.
- (6) RELOCATED AND/OR REINSTALLED MEDIA SHELVING, REFER TO EQUIPME
- PLAN.
- 7) NEW MILLWORK, REFER TO EQUIPMENT PLAN. 8) MARKERBOARD/TACKBOARD.
- (9) TELEVISION, REFER TO EQUIPMENT PLAN.
- (10) EXISTING PA SYSTEM SPEAKER.
- 11) EXISTING SECURITY CAMERA/DEVICE.
- 12) EXISTING EXIT SIGN.
- (13) EXISTING PLUMBING PIPE. (14) EXPOSED CEILING STRUCTURE.
- (15) EXISTING HVAC
- (16) NOT USED AD-03
- 17 NOT USED
- (18) CUT ACOUSTICAL WALL PANEL TO FIT AROUND PLUMBING PIPE, HVAC, HVAC LOUVERS, AND STRUCTURE AS NEEDED. VERIFY EXISTING CONDITIONS.
- (19) 3/4" STAINED OAK CAP WITH 1/2" OVERHANG. REFER TO DETAIL 1/G-301. ALIGN TOP OF CAP WITH BOTTOM OF EXISTING OAK TRIM. (20) EXISTING CASEWORK.


INTERIOR ELEVATION NEW FINISH

- NOTES:
- \sim (50) PAINT, P1 - AD-03
- $\langle \cdot \cdot \rangle$ 1) WALLCOVERING, WC1
- 2) ACOUSTICAL WALL PANEL, FW-AWP1
- 53) ACOUSTICAL WALL PANEL, FW-AWP2
- (54) ACOUSTICAL WALL PANEL, FW-AWP3
- 55) ACOUSTICAL WALL PANEL, AR-AWP1. CENTER BETWEEN ADJACENT WALLS, JOISTS, AND/OR BEAMS. FIELD VERIFY DIMENSIONS.
- 56) ACOUSTICAL WALL PANEL, AR-AWP2. ALIGN WITH ABOVE ACOUSTICAL WALL PANELS. FIELD VERIFY DIMENSIONS.
- (57) ACOUSTICAL WALL PANEL, AR-AWP3. ALIGN WITH ABOVE ACOUSTICAL WALL PANELS. FIELD VERIFY DIMENSIONS.
- (58) VINYL WALL BASE, B1
- (59) PAINT, P2 AD-03 \sim





	2'-10"	^{3"} 3'-11" ⁸	³ " 4'-0" ⁸	^{3"} 3'-3" ⁸	" <u>3'-3"</u> 8	3 ^{°°} 3'-3" ¹	'-2" 4'-3" ⁸	4'-6"	^{8"} 4'-6" ⁸	³ 4'-6"	^{8"} 4'-6"	^{3"} 4'-0"
2'-6"	55	55	55	55	55	55	- 14 (55)	55	55	55	55	55
2,-6"	57	57	56	57	56	57	L 13 (56)	57	56	57	56	57
			<u> </u>	$\frac{2}{3^{\prime}-11^{\prime\prime}}$	= = = = = = 	 4'-2"	<u> </u>	====== 5'-2"	= = = = = = = = = = = = = = = = = = =	5'-2"	<u>5'-2</u> "	4'-4"
8,-1,	(20)								1)			
		59										
<u>¥</u>						AD-0	13					



GENERAL INTERIOR ELEVATION NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE FLOOR PATTER PLANS, EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
- C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALI SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL B ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE FINISH WORK HAS PROCEEDED.
- D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- F. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803.

INTERIOR ELEVATION LEGEND:

----- EXISTING OR RELOCATED COMPONENTS, REFER TO FLOOR AND EQUIPMENT PLANS.


----- NEW COMPONENTS, REFER TO FLOOR AND EQUIPMENT PLANS.


INTERIOR ELEVATION NOTES:

- (1) DOOR. 2) WINDOW.
- (3) EXISTING HVAC LOUVERS. CLEAN EXISTING GRILLES AND PAINT, P1.
- (4) EXISTING RAILING. 5) RELOCATED CASEWORK, REFER TO EQUIPMENT PLAN.
- (6) RELOCATED AND/OR REINSTALLED MEDIA SHELVING, REFER TO EQUIPME
- PLAN. (7) NEW MILLWORK, REFER TO EQUIPMENT PLAN.
- (8) MARKERBOARD/TACKBOARD.
- (9) TELEVISION, REFER TO EQUIPMENT PLAN.
- (10) EXISTING PA SYSTEM SPEAKER.
- (11) EXISTING SECURITY CAMERA/DEVICE.
- 12) EXISTING EXIT SIGN. (13) EXISTING PLUMBING PIPE.
- (14) EXPOSED CEILING STRUCTURE.
- (15) EXISTING HVAC
- (16 NOT USED AD-03
- (18) CUT ACOUSTICAL WALL PANEL TO FIT AROUND PLUMBING PIPE, HVAC, HVAC LOUVERS, AND STRUCTURE AS NEEDED. VERIFY EXISTING CONDITIONS.
- (19) 3/4" stained oak cap with 1/2" overhang. Refer to detail 1/G-301. ALIGN TOP OF CAP WITH BOTTOM OF EXISTING OAK TRIM. (20) EXISTING CASEWORK.

INTERIOR ELEVATION NEW FINISH

- NOTES:
- \sim 50 PAINT, P1 AD-03
- $\langle \cdot \cdot \rangle$ 51) WALLCOVERING, WC1
- 52) ACOUSTICAL WALL PANEL, FW-AWP1
- 53) ACOUSTICAL WALL PANEL, FW-AWP2 (54) ACOUSTICAL WALL PANEL, FW-AWP3
- 55) ACOUSTICAL WALL PANEL, AR-AWP1. CENTER BETWEEN ADJACENT WALLS,
- JOISTS, AND/OR BEAMS. FIELD VERIFY DIMENSIONS.
- (56) acoustical wall panel, ar-awp2. Align with above acoustical wall panels. Field verify dimensions. (57) ACOUSTICAL WALL PANEL, AR-AWP3. ALIGN WITH ABOVE ACOUSTICAL WALL
- PANELS. FIELD VERIFY DIMENSIONS.
- (58) VINYL WALL BASE, B1
- (59) PAINT, P2 AD-03 \sim





GENERAL REFLECTED CEILING PLAN NOTES:


- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO GI SERIES SHEETS.
- B. THE ARCHITECTURAL REFLECTED CEILING PLAN GOVERN THE LAYOUT OF ALL CEILING ELEMENTS AND PENETRATIONS.
- C. BULKHEAD FRAMING SHALL BE ATTACHED TO STRUCTURAL SUPPORTS AND NOT THE ROOF DECK.
- D. REFER TO FLOOR PLANS FOR WALL TYPES
- E. REFER TO ELECTRICAL DRAWINGS FOR ADDITIONAL CEILING MOUNTED
- ELECTRICAL ITEMS.
- F. REFER TO TECHNOLOGY DRAWINGS FOR ADDITIONAL CEILING MOUNTED TECHNOLOGY ITEMS.
- G. REFER TO MECHANICAL DRAWINGS FOR LOCATION OF CEILING DIFFUSERS, RETURN AIR GRILLS, AND CEILING CABINET HEATERS.
- H. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW CEILING PADS.


REFLECTED CEILING PLAN LEGEND:

2'-0" x 4'-0" ACST. BD. CEILING SEE ROOM FINISH SCHEDULE		2x4 LIGHT FIXTURE
2'-0" x 4'-0" EXISTING GRID TO REMAIN, REPLACE ACOUSTICAL PADS, REFER TO NOTES/ SPEC		SUPPLY AIR DIFFUSER RETURN, EXHAUST, AND TRANSFER AIR GRILLE
2'-0" x 4'-0" EXISTING TO REMAIN REFER TO NOTES WHERE APPLICABLE	OS	OCCUPANCY SENSOR

REFLECTED CEILING PLAN NOTES: (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.

- 1 MODIFY EXISTING CEILING GRID AND SUSPENSION SYSTEM TO RECEIVE NEW GRID AND NEW CONSTRUCTION ADJACENT. REPLACE EXISTING PADS WITH NEW THROUGHOUT. WHERE APPLICABLE, MODIFY TO ACCOMMODATE NEW MECHANICAL, ELECTRICAL, TECHNOLOGY, AND FIRE PROTECTION ABOVE AND AT CEILING,
- 2 EXISTING LAY-IN CEILING GRID AND SUSPENSION SYSTEM TO REMAIN. REPLACE EXISTING CEILING PADS THIS ROOM WITH NEW THROUGHOUT. WHERE APPLICABLE, MODIFY TO ACCOMMODATE NEW MECHANICAL, ELECTRICAL, TECHNOLOGY, AND FIRE PROTECTION ABOVE AND AT CEI
- (3) NEW ACOUSTICAL CEILING GRID, PADS AND SUSPENSION SYSTEM. (4) REPLACE EXISTING LIGHTS WITH NEW. REFER TO ELECTRICAL FOR
- ADDITIONAL INFO. 5 MODIFY EXISTING CEILING GRID AND SUSPENSION SYSTEM TO RECEIVE NEW CONSTRUCTION ADJACENT. REPLACE EXISTING PADS WITH NEW THROUGHOUT. WHERE APPLICABLE, MODIFY TO ACCOMMODATE NEW MECHANICAL, ELECTRICAL, TECHNOLOGY, AND FIRE PROTECTION ABOVE AND AT CEILING.
- 6 existing ceiling pads this room to be replaced with specialty acoustical ceiling pads, refer to specs.
- (7) MOVABLE PARTITION SLOT SUPPORTED FROM EXISTING STRUCTURE ABOVE. 8 NEW ACOUSTICAL BAFFLES TO BE SUSPENDED FROM EXISTING STRUCTURE ABOVE BY HANGER BOLTS, MODIEY ACOUSTICAL PARS AS NEEDED TO ACCOMMODATE CABLES. REFER TO SPECIFICATIONS AND FINISH LEGEND.





UNIT "A" ARCHITECTURAL FIRST FLOOR DEMOLITION PLAN

SCALE: 1/8" = 1'-0"


GENERAL DEMOLITION NOTES

- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS. B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS
- RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS SHEET.
- C. CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
- E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.
- F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION. VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL. REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS.
- G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER. H. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS
- REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE). I. WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION
- AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE PUBLIC. J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER
- OWNERS' DIRECTION, UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEMS ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED.
- K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES
- EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECEIVE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW FINISHES.
- N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED, PATCH OPENINGS AND/OR SURFACES AS REQUIRE TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT OF ITEMS TO REMOVED.
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING. P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE
- FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION. Q. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF
- DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO THEIR SCOPE OF WORK. R. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF
- S. REFER TO THE STRUCTURAL, MECHANICAL, PLUMBING, ELECTRICAL AND TECHNOLOGY DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK.
- T. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING, ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE.
- U. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER TO SPECIFICATIONS AND DRAWINGS FOR REQUIREMENTS AND SPECIAL CONDITIONS. V. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES
- (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW CEILING PADS.

DEMOLITION PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)
- 1 REMOVE TOILET AND URINAL PARTITIONS IN THEIR ENTIRETY. PREP FLOOR AND WALLS TO RECEIVE NEW HARDWARE AND PARTITIONS IN SAME LOCATION. SEE ARCHITECTURAL PLAN
- 2 REMOVE RECEPTION DESK IN ITS ENTIRETY. PREP AREA TO RECEIVE NEW FINISHES AND NEW RECEPTION COUNTER. 3 REMOVE EXISTING CARPET FLOORING AND VINYL WALL BASE SYSTEMS IN
- ITS ENTIRETY INCLUDING ALL MASTICS. PREPARE ALL SURFACES FOR NEW FINISHES.
- REMOVE EXISTING VCT AND VINYL WALL BASE SYSTEMS IN ITS ENTIRETY L' INCLUDING ALL MASTICS. ADHESIVES AND SEALERS. PREPARE ALL SURFACES
- FOR NEW FINISHES. 5 REMOVE CERAMIC OR PORCELAIN TILE FLOORING AND WALL SYSTEM IN ITS
- ENTIRETY. PREPARE FLOOR AND WALL FOR NEW FINISHES. 6 REMOVE EXISTING DOOR, FRAME AND HARDWARE SYSTEM IN ITS ENTIRETY.
- 7 REMOVE WALL COVERING IN ITS ENTIRETY. PREPARE WALL FOR NEW
- └┘ FINISHES. REMOVE EXISTING BASKETBALL BACKSTOPS AND SUPPORTS COMPLETE ALLOW NEW SUPPORTS AND BACKSTOPS. WHERE APPLICABLE, PREP EXISTING STRUCTURE TO BE RETROFITTED FOR NEW BASKETBALL BACKSTOPS AND SUPPORTS
- 9 REMOVE ACOUSTICAL BOARD CEILING, GRID AND SUSPENSION SYSTEM IN ITS ENTIRETY. PREP REMAINING GRID FOR NEW CONSTRUCTION. REFER TO 2/A-102 FOR COORDINATION W/ EXISTING CONDITIONS WHERE PRESENT.
- REMOVE EXISTING SAFETY WALL PADDING, PATCH AND SMOOTH OUT WALL TO ACCEPT NEW.
- REMOVE EXISTING VINYL WALLCOVERING ON FOLDING PARTITION DOOR. L' PREPARE FOR NEW.
- MEDIA CENTER SHELVING TO BE MOVED AND STORED/PROTECTED, THEN
- REINSTALLED AFTER CARPET IS REPLACED. 3 REMOVE METAL STUDS AND GYPSUM BOARD STUD WALL IN ITS ENTIRETY.
- NEW FINISHES. 14 CAREFULLY REMOVE AND STORE EXISTING PLUMBING FIXTURE, THEN REPLACE IN SAME POSITION AFTER NEW FINISHES ARE COMPLETED ON WALLS/ FLOORS ADJACENT. REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
- 15 REMOVE BASE CABINETS, COUNTERTOP, AND WALL CABINETS WHERE PRESENT COMPLETE. PATCH AND REPAIR FLOOR AND WALLS AS REQUIRED TO RECEIVE NEW FINISHES.
- 16 EXISTING WOOD GYM FLOOR TO BE SANDED PER SPECS. REMOVE EXISTING VINYL WALL BASE THIS ROOM COMPLETE, PREP FOR NEW BASE. REFER TO FINISH PLANS AND STRIPING PLAN FOR NEW CONSTRUCTION. 17 EXISTING BLEACHERS WITH UNDERSLUNG SCOREBOARD CONTROLS TO BE
- DISCONNECTED FROM POWER THEN CAREFULLY REMOVED, STORED AND PROTECTED FOR SANDING GYM FLOOR. THEN, REPLACE BLEACHERS IN SAME POSITION AFTER NEW FINISHES ARE PLACED.
- 18 EXISTING VOLLEYBALL SLEEVE LOCATION- CAREFULLY REMOVE FOR SANDING GYM FLOOR THEN REPLACE IN SAME LOCATION. 19 WHERE APPLICABLE, EXISTING THRESHOLD TRANSITION PLATE AND
- HARDWARE TO BE CAREFULLY REMOVED FOR SANDING GYM FLOOR, THEN REPLACED IN SAME POSITION.
- 20 WHERE PRESENT, REMOVE EXISTING FLOOR BOXES, PATCH AND REPAIR FLOOR AS NEEDED TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR ADDITIONAL INFO.
- 21 REMOVE PLUMBING FIXTURES IN THEIR ENTIRETY. CUT AND CAP LINE BELOW WALL OR FLOOR SURFACE. UNLESS NOTED OTHERWISE ON PLUMBING DRAWINGS, REMOVE ALL ACCESSORIES AND WALL AND FLOOR FINISHES. PATCH AND REPAIR FLOOR AND/OR WALL AS REQUIRED TO ACCEPT NEW FINISHES. SEE ELECTRICAL FOR MORE INFORMATION.
- 22 EXISTING DOOR AND FRAME TO BE REMOVED. PREP FOR NEW. 23 REMOVE EXISTING ACOUSTIC PADS. CLEAN GRID AND PREP TO RECEIVE
- NEW ACOUSTIC PADS.
- 24 ALTERNATE: CAREFULLY REMOVE EXISTING PLASTIC LAMINATE COUNTERTOPS IN THEIR ENTIRETY. SECURE AND STORE SINK AND FAUCET ASSEMBLY TO BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING DRAWINGS FOR PLAN ADDITIONAL INFO.
- 25 CUT AND REMOVE EXISTING VCT TILE 4" FROM THE OUTER MOST FLOOR 26 ALTERNATE: REMOVE EXISTING CHALKBOARD ONLY. PREP WALL FOR NEW
- MARKERBOARD.
- 27 ALTERNATE: REMOVE EXISTING TACKBOARD ABOVE CHALKBOARD. PREP WALL FOR NEW TACKBOARD.





GENERAL DEMOLITION NOTES


- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS.B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS
- SHEET. C. CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
 E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE
- TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION. VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL.
- REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS. G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL
- DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER. I. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS REQUIRED TO PREVENT THE OPPEAR OF SHORE WHEN AND A
- REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE). WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE
- PUBLIC. J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER OWNERS' DIRECTION, UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEMS ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED.
- K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR, OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES
- -. EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECEIVE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW FINISHES.
 N. WHERE WALLS OR BUILKHEADS ARE DEMOVED. STRUCTURE
- N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, AN ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED, PATCH OPENINGS AND/OR SURFACES AS REQUIRE TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT OF ITEMS TO REMOVED.
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING.P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE
- FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION. 2. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO
- THEIR SCOPE OF WORK. R. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF SITE.
- S. REFER TO THE STRUCTURAL, MECHANICAL, PLUMBING, ELECTRICAL AND TECHNOLOGY DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK.
 T. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING,
- ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE. U. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER TO SPECIFICATIONS AND DRAWINGS FOR REQUIREMENTS AND SPECIAL
- CONDITIONS. V. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW


CEILING PADS. DEMOLITION PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)
- 1
 REMOVE TOILET AND URINAL PARTITIONS IN THEIR ENTIRETY. PREP FLOOR AND WALLS TO RECEIVE NEW HARDWARE AND PARTITIONS IN SAME LOCATION. SEE ARCHITECTURAL PLAN
- 2REMOVE RECEPTION DESK IN ITS ENTIRETY. PREP AREA TO RECEIVE NEW
FINISHES AND NEW RECEPTION COUNTER.3REMOVE EXISTING CARPET FLOORING AND VINYL WALL BASE SYSTEMS IN
- ITS ENTIRETY INCLUDING ALL MASTICS. PREPARE ALL SURFACES FOR NEW FINISHES.
- REMOVE EXISTING VCT AND VINYL WALL BASE SYSTEMS IN ITS ENTIRETY INCLUDING ALL MASTICS. ADHESIVES AND SEALERS. PREPARE ALL SURFACES FOR NEW FINISHES.
- 5 REMOVE CERAMIC OR PORCELAIN TILE FLOORING AND WALL SYSTEM IN ITS ENTIRETY. PREPARE FLOOR AND WALL FOR NEW FINISHES.
- 6 REMOVE EXISTING DOOR, FRAME AND HARDWARE SYSTEM IN ITS ENTIRETY.
- 7 REMOVE WALL COVERING IN ITS ENTIRETY. PREPARE WALL FOR NEW FINISHES.
- 8 REMOVE EXISTING BASKETBALL BACKSTOPS AND SUPPORTS COMPLETE ALLOW NEW SUPPORTS AND BACKSTOPS. WHERE APPLICABLE, PREP EXISTING STRUCTURE TO BE RETROFITTED FOR NEW BASKETBALL BACKSTOPS AND SUPPORTS
- 9 REMOVE ACOUSTICAL BOARD CEILING, GRID AND SUSPENSION SYSTEM IN ITS ENTIRETY. PREP REMAINING GRID FOR NEW CONSTRUCTION. REFER TO 2/A-102 FOR COORDINATION W/ EXISTING CONDITIONS WHERE PRESENT.
- 10 REMOVE EXISTING SAFETY WALL PADDING, PATCH AND SMOOTH OUT WALL TO ACCEPT NEW.
- REMOVE EXISTING VINYL WALLCOVERING ON FOLDING PARTITION DOOR.

 PREPARE FOR NEW.
- 12 MEDIA CENTER SHELVING TO BE MOVED AND STORED/PROTECTED, THEN REINSTALLED AFTER CARPET IS REPLACED.
- 13 REMOVE METAL STUDS AND GYPSUM BOARD STUD WALL IN ITS ENTIRETY. PATCH AND REPAIR ADJACENT FLOOR AND WALL AS REQUIRED TO ACCEPT NEW FINISHES.
- 14 CAREFULLY REMOVE AND STORE EXISTING PLUMBING FIXTURE, THEN REPLACE IN SAME POSITION AFTER NEW FINISHES ARE COMPLETED ON WALLS/ FLOORS ADJACENT. REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
- 15 REMOVE BASE CABINETS, COUNTERTOP, AND WALL CABINETS WHERE PRESENT COMPLETE. PATCH AND REPAIR FLOOR AND WALLS AS REQUIRED TO RECEIVE NEW FINISHES.
- EXISTING WOOD GYM FLOOR TO BE SANDED PER SPECS. REMOVE EXISTING VINYL WALL BASE THIS ROOM COMPLETE, PREP FOR NEW BASE. REFER TO FINISH PLANS AND STRIPING PLAN FOR NEW CONSTRUCTION.
 EXISTING BLEACHERS WITH UNDERSLUNG SCOREBOARD CONTROLS TO BE DISCONNECTED FROM POWER THEN CAREFULLY REMOVED, STORED AND
- PROTECTED FOR SANDING GYM FLOOR. THEN, REPLACE BLEACHERS IN SAME POSITION AFTER NEW FINISHES ARE PLACED. 18 EXISTING VOLLEYBALL SLEEVE LOCATION- CAREFULLY REMOVE FOR SANDING
- GYM FLOOR THEN REPLACE IN SAME LOCATION. (19) WHERE APPLICABLE, EXISTING THRESHOLD TRANSITION PLATE AND HARDWARE TO BE CAREFULLY REMOVED FOR SANDING GYM FLOOR, THEN
- REPLACED IN SAME POSITION. 20 WHERE PRESENT, REMOVE EXISTING FLOOR BOXES, PATCH AND REPAIR FLOOR AS NEEDED TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR ADDITIONAL INFO.
- 21 REMOVE PLUMBING FIXTURES IN THEIR ENTIRETY. CUT AND CAP LINE BELOW WALL OR FLOOR SURFACE. UNLESS NOTED OTHERWISE ON PLUMBING DRAWINGS, REMOVE ALL ACCESSORIES AND WALL AND FLOOR FINISHES. PATCH AND REPAIR FLOOR AND/OR WALL AS REQUIRED TO ACCEPT NEW FINISHES. SEE ELECTRICAL FOR MORE INFORMATION.
- 22 EXISTING DOOR AND FRAME TO BE REMOVED. PREP FOR NEW. 23 REMOVE EXISTING ACOUSTIC PADS. CLEAN GRID AND PREP TO RECEIVE
- NEW ACOUSTIC PADS.
- ALTERNATE: CAREFULLY REMOVE EXISTING PLASTIC LAMINATE COUNTERTOPS IN THEIR ENTIRETY. SECURE AND STORE SINK AND FAUCET ASSEMBLY TO BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING DRAWINGS FOR ADDITIONAL INFO.
- MARKERBOARD.

 27
 ALTERNATE: REMOVE EXISTING TACKBOARD ABOVE CHALKBOARD. PREP WALL
- FOR NEW TACKBOARD.







- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS.B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS
- RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS SHEET.
- C. CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
- E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.
 F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION.
- VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL. REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS.
- G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER.H. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS
- REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE). I. WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION
- AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE PUBLIC. J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER
- OWNERS' DIRECTION, UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEMS ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED.
- K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR, OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES
- L. EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECEIVE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW FINISHES.
- N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, AN ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED, PATCH OPENINGS AND/OR SURFACES AS REQUIRE TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT OF ITEM TO REMOVED.
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING.P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE
- FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION. Q. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF
- DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO THEIR SCOPE OF WORK. R. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF
- SITE. S. REFER TO THE STRUCTURAL, MECHANICAL, PLUMBING, ELECTRICAL AND TECHNOLOGY DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK.
- T. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING, ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE.
- U. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER TO SPECIFICATIONS AND DRAWINGS FOR REQUIREMENTS AND SPECIAL CONDITIONS.
- V. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW CEILING PADS.


DEMOLITION PLAN NOTES:


- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)

 I
 REMOVE TOILET AND URINAL PARTITIONS IN THEIR ENTIRETY. PREP FLOOR AND WALLS TO RECEIVE NEW HARDWARE AND PARTITIONS IN SAME
- LOCATION. SEE ARCHITECTURAL PLAN

 2
 REMOVE RECEPTION DESK IN ITS ENTIRETY. PREP AREA TO RECEIVE NEW

 FINISHES AND NEW RECEPTION COUNTER.
- 3 REMOVE EXISTING CARPET FLOORING AND VINYL WALL BASE SYSTEMS IN ITS ENTIRETY INCLUDING ALL MASTICS. PREPARE ALL SURFACES FOR NEW
- FINISHES. REMOVE EXISTING VCT AND VINYL WALL BASE SYSTEMS IN ITS ENTIRETY INCLUDING ALL MASTICS. ADHESIVES AND SEALERS. PREPARE ALL SURFACES
- FOR NEW FINISHES.
 5 REMOVE CERAMIC OR PORCELAIN TILE FLOORING AND WALL SYSTEM IN ITS
- ENTIRETY. PREPARE FLOOR AND WALL FOR NEW FINISHES.
 REMOVE EXISTING DOOR, FRAME AND HARDWARE SYSTEM IN ITS ENTIRETY.
- DEMOVE WALL COVERING IN ITS ENTIRETY DREPARE WALL FOR N
- 7 REMOVE WALL COVERING IN ITS ENTIRETY. PREPARE WALL FOR NEW FINISHES.
- REMOVE EXISTING BASKETBALL BACKSTOPS AND SUPPORTS COMPLETE TO ALLOW NEW SUPPORTS AND BACKSTOPS. WHERE APPLICABLE, PREP EXISTING STRUCTURE TO BE RETROFITTED FOR NEW BASKETBALL BACKSTOPS AND SUPPORTS
 REMOVE ACOUSTICAL BOARD CEILING, GRID AND SUSPENSION SYSTEM IN
- ITS ENTIRETY. PREP REMAINING GRID FOR NEW CONSTRUCTION. REFER TO 2/A-102 FOR COORDINATION W/ EXISTING CONDITIONS WHERE PRESENT.
- 10 REMOVE EXISTING SAFETY WALL PADDING, PATCH AND SMOOTH OUT WALL TO ACCEPT NEW.
- 11 REMOVE EXISTING VINYL WALLCOVERING ON FOLDING PARTITION DOOR. PREPARE FOR NEW.
- 12 MEDIA CENTER SHELVING TO BE MOVED AND STORED/PROTECTED, THEN REINSTALLED AFTER CARPET IS REPLACED.
- 13 REMOVE METAL STUDS AND GYPSUM BOARD STUD WALL IN ITS ENTIRETY. PATCH AND REPAIR ADJACENT FLOOR AND WALL AS REQUIRED TO ACCEPT NEW FINISHES.
- 14 CAREFULLY REMOVE AND STORE EXISTING PLUMBING FIXTURE, THEN REPLACE IN SAME POSITION AFTER NEW FINISHES ARE COMPLETED ON WALLS/ FLOORS ADJACENT. REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
- 15 REMOVE BASE CABINETS, COUNTERTOP, AND WALL CABINETS WHERE PRESENT COMPLETE. PATCH AND REPAIR FLOOR AND WALLS AS REQUIRED TO RECEIVE NEW FINISHES.
- 16 EXISTING WOOD GYM FLOOR TO BE SANDED PER SPECS. REMOVE EXISTING VINYL WALL BASE THIS ROOM COMPLETE, PREP FOR NEW BASE. REFER TO FINISH PLANS AND STRIPING PLAN FOR NEW CONSTRUCTION.
 17 EXISTING BLEACHERS WITH UNDERSLUNG SCOREBOARD CONTROLS TO BE
- DISCONNECTED FROM POWER THEN CAREFULLY REMOVED, STORED AND PROTECTED FOR SANDING GYM FLOOR. THEN, REPLACE BLEACHERS IN SAME POSITION AFTER NEW FINISHES ARE PLACED.
- 18 EXISTING VOLLEYBALL SLEEVE LOCATION CAREFULLY REMOVE FOR SANDING GYM FLOOR THEN REPLACE IN SAME LOCATION.
 19 WHERE APPLICABLE, EXISTING THRESHOLD TRANSITION PLATE AND
- HARDWARE TO BE CAREFULLY REMOVED FOR SANDING GYM FLOOR, THEN REPLACED IN SAME POSITION.
- FLOOR AS NEEDED TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR ADDITIONAL INFO.
 21 REMOVE PLUMBING FIXTURES IN THEIR ENTIRETY. CUT AND CAP LINE RELOW WALL OR ELOOP SUPERCE LINE ESS NOTED OTHERWISE ON
- BELOW WALL OR FLOOR SURFACE. UNLESS NOTED OTHERWISE ON PLUMBING DRAWINGS, REMOVE ALL ACCESSORIES AND WALL AND FLOOR FINISHES. PATCH AND REPAIR FLOOR AND/OR WALL AS REQUIRED TO ACCEPT NEW FINISHES. SEE ELECTRICAL FOR MORE INFORMATION.
 [22] EXISTING DOOR AND FRAME TO BE REMOVED. PREP FOR NEW.
- 23 REMOVE EXISTING ACOUSTIC PADS. CLEAN GRID AND PREP TO RECEIVE NEW ACOUSTIC PADS.
- 24 ALTERNATE: CAREFULLY REMOVE EXISTING PLASTIC LAMINATE COUNTERTOPS IN THEIR ENTIRETY. SECURE AND STORE SINK AND FAUCET ASSEMBLY TO BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING DRAWINGS FOR ADDITIONAL INFO.
- 25 CUT AND REMOVE EXISTING VCT TILE 4" FROM THE OUTER MOST FLOOR
- ALTERNATE: REMOVE EXISTING CHALKBOARD ONLY. PREP WALL FOR NEW MARKERBOARD.
 ALTERNATE: REMOVE EXISTING TACKBOARD ABOVE CHALKBOARD. PREP WALL
- FOR NEW TACKBOARD.







GENERAL PLAN NOTES:

- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS. B. PLAN DIMENSIONS TO MASONRY WALLS ARE TO FACE OF ROUGH MASONRY. PLAN DIMENSIONS TO STUD WALLS ARE TO FACE OF FINISHED GYPSUM
- BOARD OR PLASTER. PLAN DIMENSIONS TO STUD WALLS WITH CERAMIC TILE FINISH ARE TO THE FACE OF TILE BACKER BOARD.
- C. PROVIDE WOOD BLOCKING (OR METAL STRAPPING WHERE APPLICABLE) AS REQUIRED WITHIN METAL STUD WALLS FOR WALL MOUNTED ITEMS.
- D. REFER TO DEMOLITION SHEETS FOR ADDITIONAL PATCHING AND REPAIR WORK.
- E. REFER TO FINISH PLANS FOR INTERIOR ELEVATIONS, LOCATION AND EXTENT OF FINISHED FLOOR AND WALL MATERIAL
- F. REFER TO EQUIPMENT PLANS FOR CASEWORK, DISPLAY BOARDS, LOCKERS, AND OTHER ADDITIONAL TYPICAL EQUIPMENT NOTES AND INFORMATION. G. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROOM
- PLANS AND TOILET ACCESSORIES.
- PLAN LEGEND:
- ~~ INDICATES WALL TYPES REFER TO G-301 FOR WALL THICKNESS, HEIGHT, AND COMPOSITION.


PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)
- (1) INSTALL NEW MOTORIZED FORWARD BASKETBALL BACKSTOP AND SUPPORT FRAMING IN SAME LOCATION AS EXISTING. ADJUSTABLE HEIGHT. WHERE APPLICABLE, RETROFIT NEW SUPPORT FRAMING TO UTILIZE EXISTING IN-PLACE BEAMS. (2) NEW RECEPTION COUNTER, SEE EQUIPMENT AND FINISH DRAWINGS.
- (3) NEW SAFETY WALL PADS, REFER TO 1/A-501
- (4) INSTALL NEW TOILET PARTITIONS AND URINAL PARTITIONS IN SAME LOCATION AS EXISTING. INSTALL NEW HARDWARE TO PARTITIONS. OWNER
- TO PROVIDED AND INSTALLED ACCESSORIES. (5) NEW FLOOR AND WALL TILE, SEE TRANSITION DETAILS ON 3/A-501,
- FINISH LEGEND AND ELEVATION 7/A-860 (6) REFINISH EXISTING WOOD FLOOR, COURT MARKINGS AND EQUIPMENT PER
- $^{\prime}$ spec, refer to gymnasium court marking plan on sheet a/840.
- (7) EXISTING DRINKING FOUNTAINS TO BE REINSTALLED IN SAME LOCATION.
- REFER TO PLUMBING PLANS FOR ADDITIONAL INFO. (8) PARTITION DOOR TO RECEIVE NEW WALLCOVERING, SEE FINISH LEGEND.
- (9) REINSTALL EXISTING BLEACHERS IN SAME POSITION AFTER NEW FINISHES
- ARE PLACED.
- (10) ALTERNATE: INSTALL NEW ELECTRIC HAND DRYERS.
- (11) INSTALL NEW 3/4" FIRE RATED PLYWOOD ON ALL WALLS, FULL HEIGHT SEE DETAIL 2/A-501
- (12) ALTERNATE: INSTALL NEW PLASTIC LAMINATE COUNTERTOP ON ALL
- EXISTING CASEWORK COUNTERS. PROVIDE A 4" BACK/SIDE SPLASH.
- (13) INFILL EXISTING DOOR OPENING WITH NEW METAL STUD AND GYPSUM TO MATCH EXISTING ADJACENT WALL CONSTRUCTION.
- (14) CUBICLE CURTAIN AND TRACK (1"-0" RADIUS AT CORNER). SEE DETAIL (15) ALTERNATE: INSTALL NEW MARKERBOARD. SEE EQUIPMENT PLAN AND
- SPECIFICATIONS.
- (16) ALTERNATE: INSTALL NEW TACKBOARD. SEE EQUIPMENT PLAN AND SPECIFICATIONS.
- (17) CASEWORK AND/OR MILLWORK, REFER TO EQUIPMENT PLANS AD-03





Friday, 3/8/2024 - 9:59 AM - LAST SAVED BY:CNELSON Y:\23-118 TRI-CREEK SC -OAK HILL ES IMPROVEMENTS\23-118 OAK HILL ES IMPROVEMENTS\05 ARCH\A-102-OH.DWG





GENERAL PLAN NOTES:

- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS.B. PLAN DIMENSIONS TO MASONRY WALLS ARE TO FACE OF ROUGH MASONRY. PLAN DIMENSIONS TO STUD WALLS ARE TO FACE OF FINISHED GYPSUM
- PLAN DIMENSIONS TO STUD WALLS ARE TO FACE OF FINISHED GYPSUM BOARD OR PLASTER. PLAN DIMENSIONS TO STUD WALLS WITH CERAMIC TILE FINISH ARE TO THE FACE OF TILE BACKER BOARD.
- C. PROVIDE WOOD BLOCKING (OR METAL STRAPPING WHERE APPLICABLE) AS REQUIRED WITHIN METAL STUD WALLS FOR WALL MOUNTED ITEMS.
- D. REFER TO DEMOLITION SHEETS FOR ADDITIONAL PATCHING AND REPAIR WORK.E. REFER TO FINISH PLANS FOR INTERIOR ELEVATIONS, LOCATION AND EXTENT
- OF FINISHED FLOOR AND WALL MATERIAL F. REFER TO EQUIPMENT PLANS FOR CASEWORK, DISPLAY BOARDS, LOCKERS, AND OTHER ADDITIONAL TYPICAL EQUIPMENT NOTES AND INFORMATION.
- AND OTHER ADDITIONAL TYPICAL EQUIPMENT NOTES AND INFORMATION. G. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROOM PLANS AND TOILET ACCESSORIES.
- PLAN LEGEND:
- INDICATES WALL TYPES REFER TO G-301 FOR WALL THICKNESS, HEIGHT, AND COMPOSITION.

PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)
- INSTALL NEW MOTORIZED FORWARD BASKETBALL BACKSTOP AND SUPPORT FRAMING IN SAME LOCATION AS EXISTING. ADJUSTABLE HEIGHT. WHERE APPLICABLE, RETROFIT NEW SUPPORT FRAMING TO UTILIZE EXISTING IN-PLACE BEAMS.
 NEW RECEPTION COUNTER, SEE EQUIPMENT AND FINISH DRAWINGS.
- (3) NEW SAFETY WALL PADS, REFER TO 1/A-501
- 4 INSTALL NEW TOILET PARTITIONS AND URINAL PARTITIONS IN SAME LOCATION AS EXISTING. INSTALL NEW HARDWARE TO PARTITIONS. OWNER TO PROVIDED AND INSTALLED ACCESSORIES.
- (5) NEW FLOOR AND WALL TILE, SEE TRANSITION DETAILS ON 3/A-501,
- FINISH LEGEND AND ELEVATION 7/A-860 (6) REFINISH EXISTING WOOD FLOOR, COURT MARKINGS AND EQUIPMENT PER
- SPEC, REFER TO GYMNASIUM COURT MARKING PLAN ON SHEET A/840.
- (7) EXISTING DRINKING FOUNTAINS TO BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
- (8) PARTITION DOOR TO RECEIVE NEW WALLCOVERING, SEE FINISH LEGEND.
- (9) REINSTALL EXISTING BLEACHERS IN SAME POSITION AFTER NEW FINISHES
- ARE PLACED.
- 10 ALTERNATE: INSTALL NEW ELECTRIC HAND DRYERS.
- (11) INSTALL NEW 3/4" FIRE RATED PLYWOOD ON ALL WALLS, FULL HEIGHT SEE DETAIL 2/A-501
- 12) ALTERNATE: INSTALL NEW PLASTIC LAMINATE COUNTERTOP ON ALL EXISTING CASEWORK COUNTERS. PROVIDE A 4" BACK/SIDE SPLASH.
- (13) INFILL EXISTING DOOR OPENING WITH NEW METAL STUD AND GYPSUM TO MATCH EXISTING ADJACENT WALL CONSTRUCTION.
 (14) CUBICLE CURTAIN AND TRACK (1"-0" RADIUS AT CORNER). SEE DETAIL
- ON SHEET 5/A-501 (15) ALTERNATE: INSTALL NEW MARKERBOARD. SEE EQUIPMENT PLAN AND
- SPECIFICATIONS.
- (16) ALTERNATE: INSTALL NEW TACKBOARD. SEE EQUIPMENT PLAN AND SPECIFICATIONS.
- ((17) CASEWORK AND/OR MILLWORK, REFER TO EQUIPMENT PLANS









- A. REFER TO SPECIFICATIONS AND FINISH LEGEND FOR ADDITIONAL INFORMATION.
- B. FIELD VERIFY ALL DIMENSIONS.
- C. CASEWORK AND/OR MILLWORK INSTALLER TO COORDINATE ELECTRICAL AND PLUMBING WORK. REFER TO ELECTRICAL DRAWINGS AND SCHEDULES FOR ELECTRICAL DEVICE TYPES, HEIGHTS, AND LOCATIONS.
- D. REFER TO G SERIES DRAWINGS FOR MOUNTING HEIGHTS.
- E. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROOM PLANS AND TOILET ROOM ACCESSORIES.
- F. NIGHTLOCK DOOR SECURITY DEVICE PROVIDED BY OWNER, INSTALLED BY CONTRACTOR. CONTRACTOR TO COORDINATE LOCATIONS AND INSTALLATION

WITH OWNER.

EQUIPMENT PLAN LEGEND:

- ------ INDICATES ITEMS TO BE PART OF LOOSE EQUIPMENT PACKAGE BY OWNER. (NOT INCLUDED IN CONSTRUCTION CONTRACT).
- ---- INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS (INCLUDED IN ONSTRUCTION CONTRACTS).

(CG) INDICATES CORNER GUARD. (MB) INDICATES 4' HIGH MARKERBOARD LENGTH AS INDICATED,

REFER TO MOUNTING HEIGHT DRAWING. INDICATES 1' HIGH TACK BOARD LENGTH AS INDICATED, REFER

TO MOUNTING HEIGHT DRAWINGS.

EQUIPMENT PLAN NOTES: (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)

- 1 MOTORIZED FORWARD FOLDING RASKETRALL RACKSTOR SURPORTS
- 1 MOTORIZED FORWARD FOLDING BASKETBALL BACKSTOP SUPPORTS AND BASKETBALL BACKSTOP AND HOOP.
- 2) WALL MOUNTED SAFETY WALL PADS, SEE GYMNASIUM PLAN A840
- MILLWORK, REFER TO A/760 DRAWINGS.
- (4) NEW TOILET PARTITIONS AND ACCESSORIES PLACED IN SAME LOCATION EXISTING, SEE FINISH LEGEND.
- 5 FLOOR AND WALL TILE, SEE FINISH LEGEND AND ELEVATION.
- (6) PRIVACY CURTAIN AND TRACK, REFER TO FINISH LEGEND.


OWNER FURNISHED EQUIPMENT PLAN NOTES:


(50) LOOSE FURNITURE, BY OWNER, INDICATED ON PLAN FOR ROOM LAYOUT

(51) COMPUTER/MONITOR, BY OWNER

(52) PRINTER/COPIER, BY OWNER

- (53) FILE CABINET, BY OWNER
- (54) EXISTING COMMUNICATION RACK TO REMAIN, BY OWNER.





GENERAL EQUIPMENT PLAN NOTES:

- A. REFER TO SPECIFICATIONS AND FINISH LEGEND FOR ADDITIONAL INFORMATION.
- B. FIELD VERIFY ALL DIMENSIONS.
- C. CASEWORK AND/OR MILLWORK INSTALLER TO COORDINATE ELECTRICAL AND PLUMBING WORK. REFER TO ELECTRICAL DRAWINGS AND SCHEDULES FOR ELECTRICAL DEVICE TYPES, HEIGHTS, AND LOCATIONS.
- D. REFER TO G SERIES DRAWINGS FOR MOUNTING HEIGHTS.E. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROOM
- PLANS AND TOILET ROOM ACCESSORIES.
- F. NIGHTLOCK DOOR SECURITY DEVICE PROVIDED BY OWNER, INSTALLED BY CONTRACTOR. CONTRACTOR TO COORDINATE LOCATIONS AND INSTALLATION WITH OWNER.

EQUIPMENT PLAN LEGEND:

- SERIES DRAWINGS FOR ELEVATIONS AND DETAILS. ------ INDICATES ITEMS TO BE PART OF LOOSE EQUIPMENT PACKAGE
- BY OWNER. (NOT INCLUDED IN CONSTRUCTION CONTRACT). ---- INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS (INCLUDED
- IN ONSTRUCTION CONTRACTS).

(7 CG) INDICATES CORNER GUARD. (MB) INDICATES 4' HIGH MARKERBOARD LENGTH AS INDICATED, REFER TO MOUNTING HEIGHT DRAWING.

- INDICATES 1' HIGH TACK BOARD LENGTH AS INDICATED, REFER
- TO MOUNTING HEIGHT DRAWINGS.

EQUIPMENT PLAN NOTES: (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)

- 1 MOTORIZED FORWARD FOUNING RASKETRAUL RACKSTOR SURRORTS
- 1 MOTORIZED FORWARD FOLDING BASKETBALL BACKSTOP SUPPORTS AND BASKETBALL BACKSTOP AND HOOP.
- (2) WALL MOUNTED SAFETY WALL PADS, SEE GYMNASIUM PLAN A840
- (3) MILLWORK, REFER TO A/760 DRAWINGS.
- (4) NEW TOILET PARTITIONS AND ACCESSORIES PLACED IN SAME LOCATION EXISTING, SEE FINISH LEGEND.
- 5 FLOOR AND WALL TILE, SEE FINISH LEGEND AND ELEVATION.
- (6) PRIVACY CURTAIN AND TRACK, REFER TO FINISH LEGEND.

OWNER FURNISHED EQUIPMENT PLAN NOTES:

(50) LOOSE FURNITURE, BY OWNER, INDICATED ON PLAN FOR ROOM LAYOUT

(51) COMPUTER/MONITOR, BY OWNER


(52) PRINTER/COPIER, BY OWNER


(53) FILE CABINET, BY OWNER

(54) EXISTING COMMUNICATION RACK TO REMAIN, BY OWNER.

UNIT "B" FIRST FLOOR EQUIPMENT PLAN

SCALE: 1/8" = 1'-0"





GENERAL EQUIPMENT PLAN NOTES:

- A. REFER TO SPECIFICATIONS AND FINISH LEGEND FOR ADDITIONAL INFORMATION.
- B. FIELD VERIFY ALL DIMENSIONS.
- C. CASEWORK AND/OR MILLWORK INSTALLER TO COORDINATE ELECTRICAL AN PLUMBING WORK. REFER TO ELECTRICAL DRAWINGS AND SCHEDULES FOR ELECTRICAL DEVICE TYPES, HEIGHTS, AND LOCATIONS.
- D. REFER TO G SERIES DRAWINGS FOR MOUNTING HEIGHTS.
- E. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROC PLANS AND TOILET ROOM ACCESSORIES.
- F. NIGHTLOCK DOOR SECURITY DEVICE PROVIDED BY OWNER, INSTALLED BY CONTRACTOR. CONTRACTOR TO COORDINATE LOCATIONS AND INSTALLATION WITH OWNER.

EQUIPMENT PLAN LEGEND:

- SERIES DRAWINGS FOR ELEVATIONS AND DETAILS. ----- INDICATES ITEMS TO BE PART OF LOOSE EQUIPMENT PACKAGE
- BY OWNER. (NOT INCLUDED IN CONSTRUCTION CONTRACT). ---- INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS (INCLUDED
- IN ONSTRUCTION CONTRACTS).

(7 CG) INDICATES CORNER GUARD. (MB) INDICATES 4' HIGH MARKERBOARD LENGTH AS INDICATED, REFER TO MOUNTING HEIGHT DRAWING.

- INDICATES 1' HIGH TACK BOARD LENGTH AS INDICATED, REFER TO MOUNTING HEIGHT DRAWINGS.


EQUIPMENT PLAN NOTES: (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)

- 1 MOTORIZED FORWARD FOLDING BASKETBALL BACKSTOP SUPPORTS AND BASKETBALL BACKSTOP AND HOOP. (2) WALL MOUNTED SAFETY WALL PADS, SEE GYMNASIUM PLAN A840
- 3) MILLWORK, REFER TO A/760 DRAWINGS.
- (4) NEW TOILET PARTITIONS AND ACCESSORIES PLACED IN SAME LOCATION
- EXISTING, SEE FINISH LEGEND. (5) FLOOR AND WALL TILE, SEE FINISH LEGEND AND ELEVATION.
- (6) PRIVACY CURTAIN AND TRACK, REFER TO FINISH LEGEND.


OWNER FURNISHED EQUIPMENT PLAN NOTES:

(50) LOOSE FURNITURE, BY OWNER, INDICATED ON PLAN FOR ROOM LAYO


- (51) COMPUTER/MONITOR, BY OWNER
- (52) PRINTER/COPIER, BY OWNER
- (53) FILE CABINET, BY OWNER



RICAL AND LES FOR LET ROOM LED BY ALLATION	Interversion of the second sec
AD-03 AD-03	PROJECT DISTRICT WIDE - TRI-CREEK ELEMENTARY SCHOOL'S FINISHES, & LOWELL MIDDLE SCHOOL MEDIA CENTER RENOVATION
	KEY PLAN KEY PLAN CORDINATED BY MLR/CLN DRAWN BY CLN CHECKED BY NAS
	NAS Jought 7. Drugs COPYRIGHT NOTICE: THE CONCEPTS, DESIGNS, PLANS, DETAILS, ETC, SHOWN ON THIS DOCUMENT ARE THE PROPERTY OF GIBRALTAR DESIGN AND WERE CREATED FOR USE ON THIS SPECIFIC PROJECT. NONE OF THIS INFORMATION SHALL BE USED BY ANY PERSON OR FIRM FOR ANY PURPOSE WITHOUT THE EXPRESS WRITTEN CONSENT OF GIBRALTAR DESIGN. THE OWNER MAY RETAIN COPIES FOR INFORMATION AND REFERENCE IN CONNECTION ONLY WITH THIS PROJECT. REVISIONS MARK DATE ISSUED FOR AD-02 2/29/24 ADDENDUM 2 AD-03 3/7/24 ADDENDUM 3
	DRAWING OAK HILL ELEMENTARY UNIT "C" FIRST FLOOR EQUIPMENT PLAN
	PROJECT DISTRICT WIDE - TRI-CREEK ELEMENTARY SCHOOL'S FINISHES, AND LOWELL MIDDLE SCHOOL MEDIA CENTER RENOVATION © GIBRALTAR DESIGN SHEET C A-703.0H



ED – LAST HILL ES ES IMPR PM OAK HILL 4:08 SC - (0AK Thursday, 3/7/2024 - 4 Y:\23-118 TRI-CREEK S IMPROVEMENTS\23-118 0 ARCH\A-760-0H.DWG






SCALE: 1/8" = 1'-0"

NORTH

GENERAL FINISH PLAN NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING
- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION. C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE
- FINISH WORK HAS PROCEEDED. D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS
- AND MATERIALS FOR ALL FINISHES. E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD.
- F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION.
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES. H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS
- OTHERWISE NOTED. I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED ON PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED
- TYPE/COLOR WITH ARCHITECT. J. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX
- OF 450 MAXIMUM, PER IBC SECTION 803. K. PAINT NEW DOOR FRAMES TO MATCH EXISTING (CREAM COLOR, P8) - ALL
- SIDES UNLESS NOTED OTHERWISE. PAINT EXISTING DOOR FRAMES IN ADMIN AREA TO MATCH EXISTING (CREAM COLOR, P8). L. UNLESS NOTED OTHERWISE, PAINT GYPSUM BOARD AND OR PLASTER CEIL
- AND BULKHEADS SHERWIN WILLIAMS SW7007. M. EXISTING FABRIC WRAPPED TACKABLE WALLS, TACKABLE PANELS,
- MARKERBOARDS, TACKBOARDS OR SIGNAGE SHALL REMAIN.

FINISH SYMBOL LEGEND:



INDICATES DIRECTION OF FLOOR MATERIAL GRAIN

FINISH PLAN NOTES:


(ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)


- (1) NO NEW FINISHES THIS ROOM, EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES.
- 2 WALL AND FLOOR TILE, REFER TO FINISH LEGEND AND ELEVATION ON SHEET 4/A-861 3 PAINT, P3 AND P4. REFER TO FINISH LEGEND AND ELEVATION ON SHEET 5/A-861.
- 5/A-861.

 4

 SAFETY CUSHION, SC1.

 SEE DETAIL 1/A-501
- (5) GRAPHIC WALLCOVERING, GWC1
- (6) PAINT, P2
- 7) PAINT BULKHEAD, SLANTED WALL AND/OR LIGHT COVE, P6
- 8 EXISTING BRICK TO REMAIN
- (9) ROLLED CARPET ON MEDIA AND MUSIC STEPS, C4.
- 10) CARPET, C5.
- 11) CARPET, C3 END HERE.
- 12) PADDED WALL, SEE DETAIL 2/A-501 SC2. AD-03
- 13) ALTERNATE: PLASTIC LAMINATE COUNTERS, PL4
- (14) EXISTING VCT PATTERN TO REMAIN.





GENERAL FINISH PLAN NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING
- PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE
- FINISH WORK HAS PROCEEDED. D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD.
- F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION.
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES.
- H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED ON PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED TYPE/COLOR WITH ARCHITECT.
- J. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803.
- K. PAINT NEW DOOR FRAMES TO MATCH EXISTING (CREAM COLOR, P8) ALL SIDES UNLESS NOTED OTHERWISE. PAINT EXISTING DOOR FRAMES IN ADMIN AREA TO MATCH EXISTING (CREAM COLOR, P8).
- L. UNLESS NOTED OTHERWISE, PAINT GYPSUM BOARD AND OR PLASTER CEIL AND BULKHEADS SHERWIN WILLIAMS SW7007. M. EXISTING FABRIC WRAPPED TACKABLE WALLS, TACKABLE PANELS,
- MARKERBOARDS, TACKBOARDS OR SIGNAGE SHALL REMAIN.

FINISH SYMBOL LEGEND:

P1 — WALL FINISH	
C1FLOOR FINISH	
B1BASE FINISH	
MISC FINISH INFORI	MATION
	S REQUIRED

INDICATES DIRECTION OF FLOOR MATERIAL GRAIN

FINISH PLAN NOTES:

(ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)

- (1) NO NEW FINISHES THIS ROOM, EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES.
- 2 WALL AND FLOOR TILE, REFER TO FINISH LEGEND AND ELEVATION ON SHEET 4/A-861 (3) PAINT, P3 AND P4. REFER TO FINISH LEGEND AND ELEVATION ON SHEET
- 5/A-861.


 4


 SAFETY CUSHION, SC1.

 SEE DETAIL 1/A-501
- (5) GRAPHIC WALLCOVERING, GWC1
- (6) PAINT, P2
- (7) PAINT BULKHEAD, SLANTED WALL AND/OR LIGHT COVE, P6
- (8) EXISTING BRICK TO REMAIN
- 9) ROLLED CARPET ON MEDIA AND MUSIC STEPS, C4.
- 10) CARPET, C5.
- 11) CARPET, C3 END HERE.
- 2) PADDED WALL, SEE DETAIL 2/A-501 (SC2. AD-03
- 13) ALTERNATE: PLASTIC LAMINATE COUNTERS, PL4
- (14) EXISTING VCT PATTERN TO REMAIN.

UNIT "B" FIRST FLOOR FINISH PLAN

SCALE: 1/8" = 1'-0"





GENERAL FINISH PLAN NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING
- PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION. C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ÍSSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE
- FINISH WORK HAS PROCEEDED. D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS
- AND MATERIALS FOR ALL FINISHES. E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD.
- F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION.
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES. H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS
- OTHERWISE NOTED. I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED
- ON PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED TYPE/COLOR WITH ARCHITECT. J. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX
- OF 450 MAXIMUM, PER IBC SECTION 803. K. PAINT NEW DOOR FRAMES TO MATCH EXISTING (CREAM COLOR, P8) – ALL SIDES UNLESS NOTED OTHERWISE. PAINT EXISTING DOOR FRAMES IN ADMIN
- AREA TO MATCH EXISTING (CREAM COLOR, P8). L. UNLESS NOTED OTHERWISE, PAINT GYPSUM BOARD AND OR PLASTER CE
- AND BULKHEADS SHERWIN WILLIAMS SW7007. M. EXISTING FABRIC WRAPPED TACKABLE WALLS, TACKABLE PANELS,
- MARKERBOARDS, TACKBOARDS OR SIGNAGE SHALL REMAIN.

FINISH SYMBOL LEGEND:


P	I	
C.	1 _	-FLOOR FINISH
B´	I	—BASE FINISH
_X _	FLOOR	TRANSITION STRIP AS REQUIRE

INDICATES DIRECTION OF FLOOR MATERIAL GRAIN

FINISH PLAN NOTES:

(ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)

- (1) NO NEW FINISHES THIS ROOM, EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES.
- (2) WALL AND FLOOR TILE, REFER TO FINISH LEGEND AND ELEVATION ON SHEET 4/A-861(3) PAINT, P3 AND P4. REFER TO FINISH LEGEND AND ELEVATION ON SHEET
- 4 SAFETY CUSHION, SC1. SEE DETAIL 1/A-501
- (5) GRAPHIC WALLCOVERING, GWC1
- (6) PAINT, P2
- (7) PAINT BULKHEAD, SLANTED WALL AND/OR LIGHT COVE, P6
- (8) EXISTING BRICK TO REMAIN
- (9) ROLLED CARPET ON MEDIA AND MUSIC STEPS, C4.
- 10) CARPET, C5.
- 11) CARPET, C3 END HERE.
- 12) PADDED WALL, SEE DETAIL 2/A-501 SC2. AD-03
- 13) ALTERNATE: PLASTIC LAMINATE COUNTERS, PL4
- (14) EXISTING VCT PATTERN TO REMAIN.





Thursday, 3/7/2024 - 3:54 PM - LAST SAVED BY Y:\23-118 TRI-CREEK SC - OAK HILL ES IMPROVEMENTS\23-118 OAK HILL ES IMPROVEMENT: ARCH\A-820-OH.DWG


SURFACE	MARK	DESCRIPTION	MANUFACTURER	PATTERN/FINISH	NUMBER/COLOR	SIZE	COMMENTS
WALL BASE							
	B1	WALL BASE	TARKETT		BURNT UMBER 63	4" COVE	
	B2	WALL BASE	TARKETT		BURNT UMBER 63	6" MILLWORK	
	TB1	TILE BASE	DALTILE	UNGLAZED MOSAICS	STORM GRAY SPECKLED A22	5" BUILT-UP COVE	
FLOOR MATER	IALS						
C1	C1a	CARPET TILE	TARKETT	SQUAREUP II 11549	ELECTRICITY 71604	24" X 24"	INSTALL: VERTICAL ASHLAR
	C1b	CARPET TILE	MANNINGTON	HUB	CUSTOM COLOR	24" X 24"	INSTALL: VERTICAL ASHLAR
C2	C2a	CARPET TILE	TARKETT	CREATE BALANCE 11770	FORWARD 32809	24" X 24"	INSTALL: VERTICAL ASHLAR
	C2b	CARPET TILE	MANNINGTON		VIDEO DECODER 14403	24" X 24"	INSTALL: VERTICAL ASHLAR
C3	C3a	CARPET TILE CARPET TILE	TARKETT MANNINGTON	ABRASIVE ACTION II 02578 FORCE	WINTER GRAY 19103 STATIC 34365	24" X 24" 18" X 36"	INSTALL: MONOLITHIC INSTALL: MONOLITHIC
	C3b C4a	ROLLED CARPET	TARKETT	CREATE BALANCE 11770	FORWARD 32809	1260" X 72"	
C4	C4d C4b	ROLLED CARPET	MANNINGTON	CIRCUIT	VIDEO DECODER 14403	1260 x 72	
	C4b C5a	CARPET TILE	TARKETT	FABRICATE 11498	BASE GREY 36201	24" X 24"	INSTALL: VERTICAL ASHLAR
C5	C56	CARPET TILE			FOGGY 13354	12" X 36"	INSTALL: VERTICAL ASHLAR
	$-\frac{000}{C6}$	CARPET TILE	TARKETT	GABARDINE 115511	BEDSTONE 77204	24" X 24"	INSTALL: VERTICAL ASHLAR – SEE N
(
		+	+				+
	LVT1a	LUXURY VINYL TILE	TARKETT	ENTWINE	OXFORD 10383	36" X 9"	
LVT1	LVT1b	LUXURY VINYL TILE	MANNINGTON	CRISSCROSS	FLASH AL101	36" X 6"	
<u> </u>	FT1	MOSAIC FLOOR TILE	AMERICAN OLEAN	UNGLAZED MOSAICS	STROM GRAY SPECKLED A22	2" X 2"	
							+
	RF	RUBBER FLOORING	MONDO	ADVANCE	LIGHT GRAY L70		
			<u> </u>				
							
	P1	PAINT	SHERWIN WILLIAMS		SW 7029 AGREEABLE GRAY		
	P2	PAINT	SHERWIN WILLIAMS		SW 7017 DORIAN GRAY		SEE NOTE 1
	P3 P4	PAINT PAINT	SHERWIN WILLIAMS SHERWIN WILLIAMS		CUSTOM CUSTOM		SEE NOTE 1 SEE NOTE 2
	P4 P5	PAINT	NOT USED				
	P5	PAINT	SHERWIN WILLIAMS		SW 7004 SNOWBOUND		
	P7	PAINT	SHERWIN WILLIAMS		SW 7757 HIGH REFLECTIVE WHITE		
	P8	PAINT	SHERWIN WILLIAMS		CUSTOM		SEE NOTE 4
	W1	WALLCOATING	SHERWIN WILLIAMS		SW 7029 AGREEABLE GRAY		
	W2	WALLCOATING	SHERWIN WILLIAMS		SW 7017 DORIAN GRAY		
	GWC1	GRAPHIC WALL COVERING	LEVEL	LINDSEY	METRO		SEE NOTE 3
	WT1	CERAMIC WALL TILE	AMERICAN OLEAN	COLOR STORY WALL	ICE WHITE 0025	4" X 12"	
	WT2	CERAMIC WALL TILE	AMERICAN OLEAN	COLOR STORY WALL	STABLE 0053	4" X 12"	
	WT3	CERAMIC WALL TILE	AMERICAN OLEAN	COLOR STORY WALL	DEPENDABLE 0053	4" X 12"	
	WT4	CERAMIC WALL TILE	AMERICAN OLEAN	COLOR STORY WALL	STORM GRAY 40	4" X 12"	
	AR-AWP1	ACOUSTICAL PANEL		TECTUM	SW 7017 DORIAN GRAY		
	AR-AWP2	ACOUSTICAL PANEL		TECTUM	CUSTOM		SEE NOTE 1
	AR-AWP3	ACOUSTICAL PANEL		TECTUM	CUSTOM		SEE NOTE 2
CASEWORK A	ND MILLWORK						
	PL1	PLASTIC LAMINATE	WILSONART	12 SOFTGRAIN	UPTOWN WALNUT 7917		
	PL2	PLASTIC LAMINATE	WILSONART	31 TRACELESS	CHARCOAL VELVET 15504		
	PL3	PLASTIC LAMINATE	WILSONART	38 FINE VELVET TEXTURE	ORGANIC COTTON 4945		
	PL4	PLASTIC LAMINATE	WILSONART	60 MATTE	CANYON ZEPHYR 4842		
	SS1	SOLID SURFACE	CORIAN		PLATINUM		
MISCELLANEC	US						
	TP1	TOLIET PARTITION	ASI	ORANGE PEEL	GRAY 9200		
	TRIM1	METAL TRIM	SCHLUTER	RONDEC	SATIN ANODIZED ALUMINUM		
	WD	WOOD DOOR STAIN					
	SC1	SAFETY WALL CUSHION					
	SC2	SAFETY WALL CUSHION					
	PC	PRIVACY CURTAIN	ARCHITEX		Breezy Rx 7004		
						<u>mhanna</u>	<u> </u>
2. CUSTOM CC 3. GRAPHIC WA GRAPHIC MA	DLOR TO MATCH S DLOR TO MATCH S ALL COVERING TO AY BE CUSTOMIZE	SCHOOL COLOR RED. HEX#E SCHOOL COLOR BLACK. HEX OCOVER EXISTING FOLDING ED (MAKING SCALE AND/OR	X#13110C, TO BE VERIFIE PARTITION DOOR. APPROX COLOR ADJUSTMENTS).	WITH OWNER. ED WITH OWNER. XIMATE SIZE OF DOOR IS 47'-6 WNER BEFORE PURCHASING PROM			


- VINYL COMPOSITION TILE CARPET CARPET TO VINYL DIVIDER STRIP — CARPET -ЦU PROVIDE TAPERED FLOOR LEVELER AS - FLOOR LINE REQUIRED FOR TOP OF CARPET TO BE FLUSH WITH TOP OF TILE CARPET TO PORCELAIN TILE


FLOOR TRANSITION DETAILS SCALE: 6'' = 1' - 0''











55

63

(56)

(52)-

65

61—

63

ALIGN PANEL


TO CENTER ON PANELS

(A-860)

ABOVE.

56


63






SCALE: 1/4" = 1'-0"


GYMNASIUM EAST ELEVATION SCALE: 1/4" = 1'-0"



86'-4"







- GENERAL INTERIOR ELEVATION NOTES:
- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE FLOOR PATTER PLANS, EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
- C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALI SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE FINISH WORK HAS PROCEEDED.
- D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL EXPOSED METAL SURFACES. SUCH AS GRILLES. FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- F. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803. G. EXISTING STAINLESS STEEL COLUMN COVERS SHALL REMAIN. NO NEW FINISH.


INTERIOR ELEVATION NOTES: (ALL ELEVATION NOTES MAY NOT BE INDICATED ON THIS PLAN)

- (1) EXISTING FIRE EXTINGUISHER CABINET, REFER TO EQUIPMENT PLANS.
- 2) EXISTING FOLDING PARTITION.
- 3) EXISTING BLEACHERS.
- (4) BASKETBALL BACKSTOP, REFER TO EQUIPMENT PLAN. (5) SAFETY CUSHION WAINSCOT, REFER TO EQUIPMENT PLAN.
- (6) EXISTING SCOREBOARD.
- 7) EXISTING TACKABLE WALL SURFACE SHALL REMAIN.
- (8) EXISTING DOOR (9) NOT USED.
- 10) EXISTING EXIT SIGN
- 11) EXISTING HVAC.
- (12) EXISTING HVAC LOUVER.
- (13) EXISTING SPEAKER.

INTERIOR ELEVATION FINISH NOTES: (ALL ELEVATION NOTES MAY NOT BE INDICATED ON THIS PLAN)

- (50) PAINT, P1
- (51) PAINT, P2
- (52) PAINT, P3 (53) PAINT, P4
- (54) NOT USED
- (55) PAINT, P6
- (56) WALLCOATING, W1. IN INSTANCES WHERE THERE IS BRICK, BRICK TO
- REMAIN. REFER TO FINISH PLANS. (57) WALLCOATING, W2. IN INSTANCES WHERE THERE IS BRICK, BRICK TO
- REMAIN, REFER TO FINISH PLANS. (58) PAINT, P7
- (59) NOT USED
- (60) GRAPHIC WALLCOVERING, GWC1 (CAFETERIA SIDE ONLY)
- (61) WALL BASE, B1
- 62) WALL BASE, B2 (63) ACOUSTICAL WALL PANEL AR-AWP1
- (64) ACOUSTICAL WALL PANEL AR-AWP2
- (65) ACOUSTICAL WALL PANEL AR-AWP3
- (66) SCHLUTER TRIM, OUTSIDE CORNER OR END OF TILE RUN
- (67) PAINT, P7. EXISTING EXPOSED STRUCTURE AND ROOF DECK.





GENERAL INTERIOR ELEVATION NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION.
 B. REFERENCE FLOOR PATTER PLANS, EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
- C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE FINISH WORK HAS PROCEEDED.
- D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- F. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803.
 G. EXISTING STAINLESS STEEL COLUMN COVERS SHALL REMAIN. NO NEW FINISH.


INTERIOR ELEVATION NOTES: (ALL ELEVATION NOTES MAY NOT BE INDICATED ON THIS PLAN)

- (1) EXISTING FIRE EXTINGUISHER CABINET, REFER TO EQUIPMENT PLANS.
- 2 EXISTING FOLDING PARTITION.
- (3) EXISTING BLEACHERS.
- (4) BASKETBALL BACKSTOP, REFER TO EQUIPMENT PLAN.
 (5) SAFETY CUSHION WAINSCOT, REFER TO EQUIPMENT PLAN.
- 6 EXISTING SCOREBOARD.
- T EXISTING TACKABLE WALL SURFACE SHALL REMAIN.
- 8 EXISTING DOOR
- (9) NOT USED. (10) EXISTING EXIT SIGN
- (11) EXISTING HVAC.
- 12) EXISTING HVAC LOUVER.
- (13) EXISTING SPEAKER.

(ALL ELEVATION NOTES MAY NOT BE INDICATED ON THIS PLAN)

- (50) PAINT, P1
- 51 PAINT, P2
- (52) PAINT, P3
- (53) PAINT, P4 (54) NOT USED
- (55) PAINT, P6
- (56) WALLCOATING, W1. IN INSTANCES WHERE THERE IS BRICK, BRICK TO REMAIN. REFER TO FINISH PLANS.
- (57) WALLCOATING, W2. IN INSTANCES WHERE THERE IS BRICK, BRICK TO REMAIN, REFER TO FINISH PLANS.
- 58) PAINT, P7 (59) NOT USED
- (60) GRAPHIC WALLCOVERING, GWC1 (CAFETERIA SIDE ONLY)
- 61 WALL BASE, B1
- 62 WALL BASE, B2
- (63) ACOUSTICAL WALL PANEL AR-AWP1
- (64) ACOUSTICAL WALL PANEL AR-AWP2
 (65) ACOUSTICAL WALL PANEL AR-AWP3
- (66) SCHLUTER TRIM OUTSIDE CORNER O
- (66) SCHLUTER TRIM, OUTSIDE CORNER OR END OF TILE RUN(67) PAINT, P7. EXISTING EXPOSED STRUCTURE AND ROOF DECK.





GENERAL DEMOLITION NOTES

- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS. B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS
- RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS SHEET.
- C. CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
- E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.
- F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION. VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL. REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS.
- G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER. H. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS
- REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE). I. WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION
- AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE PUBLIC. J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER
- OWNERS' DIRECTION, UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEMS ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED. K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING
- CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES
- L. EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECEIVE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW FINISHES.
- N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED, PATCH OPENINGS AND/OR SURFACES AS REQUIRE TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT OF ITEMS TO REMOVED.
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING. P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE
- FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION. Q. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO
- THEIR SCOPE OF WORK. R. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF
- SITE S. REFER TO THE, MECHANICAL, PLUMBING, AND ELECTRICAL DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK.
- T. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING, ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE. U. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER
- TO SPECIFICATIONS AND DRAWINGS FOR REQUIREMENTS AND SPECIAL CONDITIONS. V. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING


DEMOLITION PLAN NOTES:

CEILING PADS.

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)
- 1 REMOVE TOILET AND URINAL PARTITIONS IN THEIR ENTIRETY. PREP FLOOR AND WALLS FOR NEW PARTITIONS AND NEW HARDWARE IN SAME LOCATION. SEE ARCHITECTURAL PLAN.
- 2 REMOVE RECEPTION DESK IN ITS ENTIRETY. PREP AREA TO RECEIVE NEW FINISHES AND RECEPTION COUNTER.
- 3 REMOVE EXISTING CARPET FLOORING AND VINYL WALL BASE SYSTEMS IN ITS ENTIRETY INCLUDING ALL MASTICS. PREPARE ALL SURFACES FOR NEW FINISHES.
- REMOVE EXISTING VCT AND VINYL WALL BASE SYSTEMS IN ITS ENTIRETY $\stackrel{ au}{\longrightarrow}$ INCLUDING ALL MASTICS. ADHESIVES AND SEALERS. PREPARE ALL SURFACES FOR NEW FINISHES.
- 5 REMOVE CERAMIC OR PORCELAIN TILE FLOORING AND WALL TILE SYSTEM □ ITS ENTIRETY. PREPARE FLOOR AND WALL FOR NEW FINISHES.
- 6 REMOVE METAL STUDS AND GYPSUM BOARD WALL IN ITS ENTIRETY. PATCH AND REPAIR ADJACENT FLOOR AND WALL AS REQUIRED TO ACCEPT NEW
- FINISHES. SALVAGE OWNER METAL CABINET FOR REUSE. 7 REMOVE EXISTING DOOR, FRAME AND HARDWARE SYSTEM IN ITS ENTIRETY.
- 8 REMOVE EXISTING VINYL WALLCOVERING ON FOLDING PARTITION DOOR. PREPARE FOR NEW. CAFETERIA SIDE ONLY.
- 9 REMOVE ACOUSTICAL BOARD CEILING, GRID AND SUSPENSION SYSTEM IN ITS ENTIRETY. PREP REMAINING GRID FOR NEW CONSTRUCTION. REFER TO 2/A-102 FOR COORDINATION W/ EXISTING CONDITIONS WHERE PRESENT.
- MEDIA CENTER SHELVING TO BE MOVED AND STORED/PROTECTED, THEN REINSTALLED AFTER CARPET IS REPLACED.
- 11 REMOVE EXISTING REVOLVING CUBBIE CASEWORK AND OR BASE AND UPPE CABINETS NOTED IN ITS ENTIRETY. PREPARE ALL SURFACES FOR NEW FINISHES.
- REMOVE CABINETS, COUNTERTOP, AND WALL CABINETS WHERE PRESENT COMPLETE. PATCH AND REPAIR FLOOR AND WALLS AS REQUIRED TO RECEIVE NEW FINISHES.
- 13 CAREFULLY REMOVE AND STORE EXISTING PLUMBING FIXTURE, THEN REPLACE IN SAME POSITION AFTER NEW FINISHES ARE COMPLETED ON WALLS/ FLOORS ADJACENT. REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
- 14 WHERE PRESENT, REMOVE EXISTING FLOOR BOXES, PATCH AND REPAIR FLOOR AS NEEDED TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR ADDITIONAL INFO.
- 15 REMOVE EXISTING ACOUSTIC PADS. CLEAN GRID AND PREP TO RECEIVE NEW ACOUSTIC PADS.
- 16 ALTERNATE: CAREFULLY REMOVE EXISTING PLASTIC LAMINATE COUNTERTOPS IN THEIR ENTIRETY. SECURE AND STORE SINK AND FAUCET ASSEMBLY TO BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING DRAWINGS FOR ADDITIONAL INFO.
- 17 CUT AND REMOVE EXISTING VCT TILE 4" FROM THE OUTER MOST FLOOR GRAPHIC LINE. FLOOR GRAPHIC TO REMAIN AND PROTECTED.
- 18 REMOVE EXISTING PLASTIC LAMINATE BASE AND WALL CABINETS IN THEIR ENTIRETY. PREP WALL AND FLOOR FOR NEW. REFER TO PLUMBING DRAWINGS FOR ADDITIONAL INFO.
- 19 ALTERNATE: REMOVE EXISTING BASKETBALL BACKSTOPS AND SUPPORTS COMPLETE TO ALLOW NEW SUPPORTS AND BACKSTOPS. WHERE APPLICABLE PREP EXISTING STRUCTURE TO BE RETROFITTED FOR NEW BASKETBALL BACKSTOPS AND SUPPORTS.
- O ALTERNATE: REMOVE EXISTING CHALKBOARD ONLY. PREP WALL FOR NEW MARKERBOARD.
- 1 ALTERNATE: REMOVE EXISTING TACKBOARD ABOVE CHALKBOARD. PREP WAL J FOR NEW TACKBOARD ·····

TIT C-






AM – LAST SAVED BY C – THREE CREEKS ES HREE CREEKS ES\05 Friday, 3/8/2024 - 9:26 A Y:\23-119 TRI-CREEK SC -IMPROVEMENTS\23-119 THR ARCH\AD102-TC.DWG


GENERAL DEMOLITION NOTES

- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS. B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS
- RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS SHEET. C. CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF
- CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
- E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.
- F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION. VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL. REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS.
- G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER. H. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS
- REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE). I. WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION
- AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE PUBLIC. J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER
- OWNERS' DIRECTION, UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEMS ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED. K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING
- CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES
- EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECEIVE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW FINISHES.
- N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED, PATCH OPENINGS AND/OR SURFACES AS REQUIRE TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT OF ITEMS TO REMOVED.
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING. P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE
- FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION. Q. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF
- DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO THEIR SCOPE OF WORK. R. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF
- SITE S. REFER TO THE, MECHANICAL, PLUMBING, AND ELECTRICAL DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK.
- T. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING, ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE.
- U. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER TO SPECIFICATIONS AND DRAWINGS FOR REQUIREMENTS AND SPECIAL CONDITIONS. V. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES
- (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW CEILING PADS.

DEMOLITION PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.) 1 REMOVE TOILET AND URINAL PARTITIONS IN THEIR ENTIRETY. PREP FLOOR
- AND WALLS FOR NEW PARTITIONS AND NEW HARDWARE IN SAME LOCATION. SEE ARCHITECTURAL PLAN.
- 2 REMOVE RECEPTION DESK IN ITS ENTIRETY. PREP AREA TO RECEIVE NEW FINISHES AND RECEPTION COUNTER. 3 REMOVE EXISTING CARPET FLOORING AND VINYL WALL BASE SYSTEMS IN
- ITS ENTIRETY INCLUDING ALL MASTICS. PREPARE ALL SURFACES FOR NEW FINISHES.
- REMOVE EXISTING VCT AND VINYL WALL BASE SYSTEMS IN ITS ENTIRETY INCLUDING ALL MASTICS. ADHESIVES AND SEALERS. PREPARE ALL SURFACES FOR NEW FINISHES.
- 5 REMOVE CERAMIC OR PORCELAIN TILE FLOORING AND WALL TILE SYSTEM → ITS ENTIRETY. PREPARE FLOOR AND WALL FOR NEW FINISHES.
- 6 REMOVE METAL STUDS AND GYPSUM BOARD WALL IN ITS ENTIRETY. PATCH AND REPAIR ADJACENT FLOOR AND WALL AS REQUIRED TO ACCEPT NEW FINISHES. SALVAGE OWNER METAL CABINET FOR REUSE.
- 7 REMOVE EXISTING DOOR, FRAME AND HARDWARE SYSTEM IN ITS ENTIRETY.
- 8 REMOVE EXISTING VINYL WALLCOVERING ON FOLDING PARTITION DOOR. PREPARE FOR NEW. CAFETERIA SIDE ONLY.
- 9 REMOVE ACOUSTICAL BOARD CEILING, GRID AND SUSPENSION SYSTEM IN ITS ENTIRETY. PREP REMAINING GRID FOR NEW CONSTRUCTION. REFER TO 2/A-102 FOR COORDINATION W/ EXISTING CONDITIONS WHERE PRESENT.
- 10 MEDIA CENTER SHELVING TO BE MOVED AND STORED/PROTECTED, THEN REINSTALLED AFTER CARPET IS REPLACED.
- 11 REMOVE EXISTING REVOLVING CUBBIE CASEWORK AND OR BASE AND UPPER CABINETS NOTED IN ITS ENTIRETY. PREPARE ALL SURFACES FOR NEW FINISHES.
- 12 REMOVE CABINETS, COUNTERTOP, AND WALL CABINETS WHERE PRESENT COMPLETE. PATCH AND REPAIR FLOOR AND WALLS AS REQUIRED TO RECEIVE NEW FINISHES.
- 13 CAREFULLY REMOVE AND STORE EXISTING PLUMBING FIXTURE, THEN REPLACE IN SAME POSITION AFTER NEW FINISHES ARE COMPLETED ON WALLS/ FLOORS ADJACENT. REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
- 14 WHERE PRESENT, REMOVE EXISTING FLOOR BOXES, PATCH AND REPAIR FLOOR AS NEEDED TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR ADDITIONAL INFO.
- 15 REMOVE EXISTING ACOUSTIC PADS. CLEAN GRID AND PREP TO RECEIVE NEW ACOUSTIC PADS.
- [16] ALTERNATE: CAREFULLY REMOVE EXISTING PLASTIC LAMINATE COUNTERTOPS IN THEIR ENTIRETY. SECURE AND STORE SINK AND FAUCET ASSEMBLY TO BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING DRAWINGS FOR ADDITIONAL INFO.
- 17 CUT AND REMOVE EXISTING VCT TILE 4" FROM THE OUTER MOST FLOOR GRAPHIC LINE. FLOOR GRAPHIC TO REMAIN AND PROTECTED.
- 18 REMOVE EXISTING PLASTIC LAMINATE BASE AND WALL CABINETS IN THEIR ENTIRETY. PREP WALL AND FLOOR FOR NEW. REFER TO PLUMBING
- DRAWINGS FOR ADDITIONAL INFO. 19 ALTERNATE: REMOVE EXISTING BASKETBALL BACKSTOPS AND SUPPORTS
- COMPLETE TO ALLOW NEW SUPPORTS AND BACKSTOPS. WHERE APPLICABLE PREP EXISTING STRUCTURE TO BE RETROFITTED FOR NEW BASKETBALL BACKSTOPS AND SUPPORTS.
- ALTERNATE: REMOVE EXISTING CHALKBOARD ONLY. PREP WALL FOR NEW MARKERBOARD. 21 ALTERNATE: REMOVE EXISTING TACKBOARD ABOVE CHALKBOARD. PREP WAI
- ' FOR NEW TACKBOARD
- **UNIT "B" ARCHITECTURAL**
- FIRST FLOOR DEMOLITION PLAN





GENERAL DEMOLITION NOTES:

- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS.B. UNLESS NOTED OTHERWISE ON THIS SHEET, THE GENERAL CONTRACTOR IS
- RESPONSIBLE FOR ALL DEMOLITION AND REMOVAL WORK INDICATED ON THIS SHEET.
- C. CONTRACTORS ENCOUNTERING EXISTING MATERIAL WHICH IS SUSPECTED OF CONTAINING ASBESTOS SHALL STOP WORK IMMEDIATELY AND NOTIFY THE OWNER AND THE OWNERS REPRESENTATIVE.
- D. BOLD DASHED LINES INDICATE EXISTING ITEMS TO BE REMOVED UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXTENT OF DEMOLITION WORK PRIOR TO BIDDING AND FOR COORDINATING THE EXTENT OF DEMOLITION WITH THE INSTALLATION OF NEW SYSTEMS.
- E. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION APPLICABLE TO THEIR SCOPE OF WORK AND AS REQUIRED FOR INSTALLATION OF NEW WORK WHETHER OR NOT IT IS SPECIFICALLY INDICATED OR NOTED IN THESE DOCUMENTS.
 F. REMOVE ALL ITEMS AND FINISHES MADE OBSOLETE BY NEW CONSTRUCTION.
- VERIFY ITEMS DEEMED OBSOLETE WITH ARCHITECT PRIOR TO REMOVAL. REFER TO NEW CONSTRUCTION DRAWINGS FOR DEMOLITION REQUIRED NOT SHOWN ON DEMOLITION PLANS.
- G. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR OFF SITE REMOVAL OF ALL DEMOLITION MATERIALS AND/OR ITEMS UNLESS NOTED OTHERWISE OR DIRECTED BY THE OWNER.
 H. PRIOR TO STARTING DEMOLITION, CONSTRUCT DUST CONTROL BARRIERS AS
- REQUIRED TO PREVENT THE SPREAD OF DUST INTO SURROUNDING AREAS (WHERE APPLICABLE). I. WHERE BUILDING EGRESS IS REQUIRED TO PASS THROUGH DEMOLITION
- AREAS, PROVIDE APPROVED BARRIERS, ETC. TO ENSURE SAFETY OF THE PUBLIC. J. RELOCATED ITEMS SHALL BE CLEANED AND PLACED IN STORAGE, PER
- OWNERS' DIRECTION, UNTIL ITEMS ARE READY TO BE INSTALLED. IF ITEMS ARE DAMAGED DURING DEMOLITION OR RELOCATION, THEY SHALL BE REPAIRED OR REPLACED WITH NEW ITEMS AS APPROVED. K. DEMOLITION SHALL BE PERFORMED WITHOUT DAMAGE TO EXISTING
- CONSTRUCTION TO REMAIN. WHERE SUCH DAMAGE OCCURS, PATCH, REPAIR, OR RESTORE WALLS, FLOORS, CEILING, ETC. NEATLY TO MATCH EXISTING ADJACENT SURFACE. PROVIDE SHORING, BRACING, OR SUPPORT AS REQUIRED TO PREVENT MOVEMENT OR SETTLEMENT OF EXISTING STRUCTURES
- L. EACH CONTRACTOR IS RESPONSIBLE FOR CUTTING, PATCHING, AND DISCONNECTION OF ITEMS APPLICABLE TO THEIR SCOPE OF WORK. WHERE EXISTING SERVICES ARE ABANDONED, CAP AT LEAST 1" BEHIND NEW FINISHES AND/OR EXISTING SURFACE AND PATCH AS REQUIRED TO RECEIVE NEW FINISHES OR MATCH EXISTING FINISH.
- M. ON WALLS THAT ARE TO RECEIVE NEW FINISHES, REMOVE AND REINSTALL EXISTING EQUIPMENT TO REMAIN AS REQUIRED FOR INSTALLATION OF NEW FINISHES.
- N. WHERE WALLS OR BULKHEADS ARE REMOVED, PATCH FLOORS, CEILINGS, AN ADJACENT WALLS AS REQUIRED TO MATCH EXISTING OR RECEIVE NEW FINISHES WHERE APPLICABLE. WHERE EXISTING DUCTWORK, PIPING, OR EQUIPMENT IS REMOVED, PATCH OPENINGS AND/OR SURFACES AS REQUIRED TO MATCH ADJACENT SURFACES OR RECEIVE NEW FINISHES WHERE APPLICABLE. REFER TO ALL DEMOLITION DRAWINGS FOR EXTENT OF ITEMS TO REMOVED.
- O. OVER CUT NEW OPENINGS IN EXISTING WALL AS REQUIRED FOR NEW CONSTRUCTION. PATCH AND REPAIR WALLS AS REQUIRED TO MATCH EXISTING.
 P. ALL EQUIPMENT AND FURNITURE WHICH ARE CONSIDERED LOOSE
- FURNISHING SHALL BE REMOVED BY THE OWNER PRIOR TO DEMOLITION. Q. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR GENERAL REVIEW OF DEMOLITION NOTES AND CENERAL DEMOLITION MOTION AND THE AND CENERAL DEMOLITION MOTION AND THE AND CENERAL DEMOLITION AND THE AND CENERAL DEMOLITION AND THE AND CENERAL DEMOLITION.
- DEMOLITION NOTES AND GENERAL DEMOLITION NOTES AS THEY APPLY TO THEIR SCOPE OF WORK. R. THE OWNER SHALL RESERVE THE RIGHT TO CLAIM ANY MATERIALS THAT ARE BEING DEMOLISHED PRIOR TO THE CONTRACTOR DISPOSING OF THEM OFF
- SITE. S. REFER TO THE, MECHANICAL, PLUMBING, AND ELECTRICAL DOCUMENTS FOR COMPLETE SCOPE OF DEMOLITION WORK.
- T. "FLOORING" DENOTES FLOOR COVERING MATERIALS INCLUDING BACKING, ADHESIVES, AND BASES DOWN TO BUT EXCLUSIVE OF FLOOR SLABS AND STRUCTURAL MATERIALS UNLESS NOTED OTHERWISE.
 U. DEMOLITION IS TO FOLLOW ESTABLISHED CONSTRUCTION SEQUENCE. REFER
- V. CONTRACTOR SHALL SUPPORT ALL EXISTING CEILING MOUNTED DEVICES (SPEAKERS WIRELESS ACCESS POINTS FTC.) TO ACCOMMODATE DEVICES
- (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) TO ACCOMMODATE REMOVAL OF EXISTING CEILING PADS. CONTRACTOR SHALL REINSTALL THE EXISTING CEILING MOUNTED DEVICES (SPEAKERS, WIRELESS ACCESS POINTS, ETC.) INTO NEW CEILING PADS.


DEMOLITION PLAN NOTES:


- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)

 1
 REMOVE TOILET AND URINAL PARTITIONS IN THEIR ENTIRETY. PREP FLOOR
- AND WALLS FOR NEW PARTITIONS AND NEW HARDWARE IN SAME LOCATION. SEE ARCHITECTURAL PLAN.

 2
 REMOVE RECEPTION DESK IN ITS ENTIRETY PREP AREA TO RECEIVE NEW
- REMOVE RECEPTION DESK IN ITS ENTIRETY. PREP AREA TO RECEIVE NEW FINISHES AND RECEPTION COUNTER.
 REMOVE EXISTING CARPET FLOORING AND VINYL WALL BASE SYSTEMS IN
- TIS ENTIRETY INCLUDING ALL MASTICS. PREPARE ALL SURFACES FOR NEW FINISHES.
- HIS INCLUDING ALL MASTICS. ADHESIVES AND SEALERS. PREPARE ALL SURFACES FOR NEW FINISHES.
- 5 REMOVE CERAMIC OR PORCELAIN TILE FLOORING AND WALL TILE SYSTEM ITS ENTIRETY. PREPARE FLOOR AND WALL FOR NEW FINISHES.
- 6 REMOVE METAL STUDS AND GYPSUM BOARD WALL IN ITS ENTIRETY. PATCH AND REPAIR ADJACENT FLOOR AND WALL AS REQUIRED TO ACCEPT NEW FINISHES. SALVAGE OWNER METAL CABINET FOR REUSE.
- 7 REMOVE EXISTING DOOR, FRAME AND HARDWARE SYSTEM IN ITS ENTIRETY.
- 8 REMOVE EXISTING VINYL WALLCOVERING ON FOLDING PARTITION DOOR. PREPARE FOR NEW. CAFETERIA SIDE ONLY.
- 9 REMOVE ACOUSTICAL BOARD CEILING, GRID AND SUSPENSION SYSTEM IN ITS ENTIRETY. PREP REMAINING GRID FOR NEW CONSTRUCTION. REFER TO 2/A-102 FOR COORDINATION W/ EXISTING CONDITIONS WHERE PRESENT.
- 10 MEDIA CENTER SHELVING TO BE MOVED AND STORED/PROTECTED, THEN REINSTALLED AFTER CARPET IS REPLACED.
- 11 REMOVE EXISTING REVOLVING CUBBIE CASEWORK AND OR BASE AND UPPER CABINETS NOTED IN ITS ENTIRETY. PREPARE ALL SURFACES FOR NEW FINISHES.
- 12 REMOVE CABINETS, COUNTERTOP, AND WALL CABINETS WHERE PRESENT COMPLETE. PATCH AND REPAIR FLOOR AND WALLS AS REQUIRED TO RECEIVE NEW FINISHES.
- 13 CAREFULLY REMOVE AND STORE EXISTING PLUMBING FIXTURE, THEN REPLACE IN SAME POSITION AFTER NEW FINISHES ARE COMPLETED ON WALLS/ FLOORS ADJACENT. REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
- 14 WHERE PRESENT, REMOVE EXISTING FLOOR BOXES, PATCH AND REPAIR FLOOR AS NEEDED TO RECEIVE NEW FINISHES. REFER TO ELECTRICAL FOR ADDITIONAL INFO.
- 15 REMOVE EXISTING ACOUSTIC PADS. CLEAN GRID AND PREP TO RECEIVE NEW ACOUSTIC PADS.
- 16 ALTERNATE: CAREFULLY REMOVE EXISTING PLASTIC LAMINATE COUNTERTOPS IN THEIR ENTIRETY. SECURE AND STORE SINK AND FAUCET ASSEMBLY TO BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING DRAWINGS FOR ADDITIONAL INFO.
- 17 CUT AND REMOVE EXISTING VCT TILE 4" FROM THE OUTER MOST FLOOR GRAPHIC LINE. FLOOR GRAPHIC TO REMAIN AND PROTECTED.
- 18 REMOVE EXISTING PLASTIC LAMINATE BASE AND WALL CABINETS IN THEIR ENTIRETY. PREP WALL AND FLOOR FOR NEW. REFER TO PLUMBING
- DRAWINGS FOR ADDITIONAL INFO. 19 ALTERNATE: REMOVE EXISTING BASKETBALL BACKSTOPS AND SUPPORTS COMPLETE TO ALLOW NEW SUPPORTS AND BACKSTOPS. WHERE APPLICABLE PREP EXISTING STRUCTURE TO BE RETROFITTED FOR NEW BASKETBALL BACKSTOPS AND SUPPORTS.
- ALTERNATE: REMOVE EXISTING CHALKBOARD ONLY. PREP WALL FOR NEW MARKERBOARD.
- 21
 ALTERNATE: REMOVE EXISTING TACKBOARD ABOVE CHALKBOARD.

 FOR NEW TACKBOARD.







GENERAL PLAN NOTES:


- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS. B. PLAN DIMENSIONS TO MASONRY WALLS ARE TO FACE OF ROUGH MASONRY. PLAN DIMENSIONS TO STUD WALLS ARE TO FACE OF FINISHED GYPSUM
- BOARD OR PLASTER. PLAN DIMENSIONS TO STUD WALLS WITH CERAMIC TILE FINISH ARE TO THE FACE OF TILE BACKER BOARD. C. PROVIDE WOOD BLOCKING (OR METAL STRAPPING WHERE APPLICABLE) AS
- REQUIRED WITHIN METAL STUD WALLS FOR WALL MOUNTED ITEMS. D. REFER TO DEMOLITION SHEETS FOR ADDITIONAL PATCHING AND REPAIR WORK.
- E. REFER TO FINISH PLANS FOR INTERIOR ELEVATIONS, LOCATION AND EXTENT
- OF FINISHED FLOOR AND WALL MATERIAL F. REFER TO EQUIPMENT PLANS FOR CASEWORK, DISPLAY BOARDS, LOCKERS,
- AND OTHER ADDITIONAL TYPICAL EQUIPMENT NOTES AND INFORMATION. G. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROOM PLANS AND TOILET ACCESSORIES.


PLAN LEGEND:

 \bigcirc INDICATES WALL TYPES REFER TO G-301 FOR WALL THICKNESS, HEIGHT, AND COMPOSITION.


PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)
- (1) ALTERNATE: INSTALL NEW ELECTRIC HAND DRYERS. (2) NEW RECEPTION COUNTER, SEE EQUIPMENT AND FINISH DRAWINGS.
- (3) NOT USED.
- 4 INSTALL NEW TOILET PARTITIONS AND URINAL PARTITIONS IN SAME LOCATION AS EXISTING. INSTALL NEW HARDWARE TO PARTITIONS. OWNER TO PROVIDE AND INSTALLED ACCESSORIES.
- 5 NEW FLOOR AND WALL TILE, SEE TRANSITION DETAILS ON A/820, FINISH
- LEGEND. (6) casework and/or millwork, refer to equipment plans
- 7 EXISTING DRINKING FOUNTAINS TO BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
- 8 ALTERNATE: INSTALL NEW PLASTIC LAMINATE COUNTERTOP ON ALL EXISTING CASEWORK COUNTERS. PROVIDE A 4" BACK/SIDE SPLASH.
- (9) CUBICLE CURTAIN AND TRACK (1'-0" RADIUS AT CORNER). SEE DETAIL ON SHEET A-820.
- 10 INFILL EXISTING DOOR OPENING WITH NEW METAL STUD AND GYPSUM TO MATCH EXISTING ADJACENT WALL CONSTRUCTION.
- 11) ALTERNATE: INSTALL NEW MOTORIZED FORWARD BASKETBALL BACKSTOP AND SUPPORT FRAMING IN SAME LOCATION AS EXISTING. ADJUSTABLE
- HEIGHT. WHERE APPLICABLE, RETROFIT NEW SUPPORT FRAMING TO UT EXISTING IN-PLACE BEAMS. (12) ALTERNATE: INSTALL NEW MARKERBOARD. SEE EQUIPMENT PLAN AND
- AD-03 SPECIFICATIONS. (13) ALTERNATE: INSTALL NEW TACKBOARD. SEE EQUIPMENT PLAN AND
 - SPECIFICATIONS.





Friday, 3/8/2024 – 9:28 AM – LAST SAVED BY:ASC Y:\23-119 TRI-CREEK SC -THREE CREEKS ES IMPROVEMENTS\23-119 THREE CREEKS ES\05 ARCH\A-102-TC.DWG





- A. FOR GENERAL PROJECT NOTES, MATERIAL INDICATIONS LEGEND, SYMBOL LEGEND, ABBREVIATIONS, ETC., REFER TO G SERIES SHEETS.B. PLAN DIMENSIONS TO MASONRY WALLS ARE TO FACE OF ROUGH MASONRY. PLAN DIMENSIONS TO STUD WALLS ARE TO FACE OF FINISHED GYPSUM
- DIAN DIMENSIONS TO MASONICH WALLS ARE TO FACE OF FINISHED GYPSUM
 PLAN DIMENSIONS TO STUD WALLS ARE TO FACE OF FINISHED GYPSUM
 BOARD OR PLASTER. PLAN DIMENSIONS TO STUD WALLS WITH CERAMIC TILE
 FINISH ARE TO THE FACE OF TILE BACKER BOARD.
 C. PROVIDE WOOD BLOCKING (OR METAL STRAPPING WHERE APPLICABLE) AS
- REQUIRED WITHIN METAL STUD WALLS FOR WALL MOUNTED ITEMS.
- D. REFER TO DEMOLITION SHEETS FOR ADDITIONAL PATCHING AND REPAIR WORK.E. REFER TO FINISH PLANS FOR INTERIOR ELEVATIONS, LOCATION AND EXTENT
- OF FINISHED FLOOR AND WALL MATERIAL F. REFER TO EQUIPMENT PLANS FOR CASEWORK, DISPLAY BOARDS, LOCKERS, AND OTHER ADDITIONAL TYPICAL EQUIPMENT NOTES AND INFORMATION.
- AND UTHER ADDITIONAL TYPICAL EQUIPMENT NOTES AND INFORMATION. G. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROOM PLANS AND TOILET ACCESSORIES.

PLAN LEGEND:


 \bigcirc INDICATES WALL TYPES REFER TO G-301 FOR WALL THICKNESS, HEIGHT, AND COMPOSITION.


PLAN NOTES:

- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS SHEET.)
- ALTERNATE: INSTALL NEW ELECTRIC HAND DRYERS.
 NEW RECEPTION COUNTER, SEE EQUIPMENT AND FINISH DRAWINGS.
- 3 NOT USED.

AD-03

- 4 INSTALL NEW TOILET PARTITIONS AND URINAL PARTITIONS IN SAME LOCATION AS EXISTING. INSTALL NEW HARDWARE TO PARTITIONS. OWNER TO PROVIDE AND INSTALLED ACCESSORIES.
- 5 NEW FLOOR AND WALL TILE, SEE TRANSITION DETAILS ON A/820, FINISH LEGEND.
- 6 CASEWORK AND/OR MILLWORK, REFER TO EQUIPMENT PLANS
- 7 EXISTING DRINKING FOUNTAINS TO BE REINSTALLED IN SAME LOCATION. REFER TO PLUMBING PLANS FOR ADDITIONAL INFO.
- 8 ALTERNATE: INSTALL NEW PLASTIC LAMINATE COUNTERTOP ON ALL EXISTING CASEWORK COUNTERS. PROVIDE A 4" BACK/SIDE SPLASH.
- 9 CUBICLE CURTAIN AND TRACK (1'-0" RADIUS AT CORNER). SEE DETAIL ON SHEET A-820.
- 10 INFILL EXISTING DOOR OPENING WITH NEW METAL STUD AND GYPSUM TO MATCH EXISTING ADJACENT WALL CONSTRUCTION.
- 1 ALTERNATE: INSTALL NEW MOTORIZED FORWARD BASKETBALL BACKSTOP AND SUPPORT FRAMING IN SAME LOCATION AS EXISTING. ADJUSTABLE HEIGHT. WHERE APPLICABLE, RETROFIT NEW SUPPORT FRAMING TO UTIL
- EXISTING IN-PLACE BEAMS. (12) ALTERNATE: INSTALL NEW MARKERBOARD. SEE EQUIPMENT PLAN AND SPECIFICATIONS.
- (13) ALTERNATE: INSTALL NEW TACKBOARD. SEE EQUIPMENT PLAN AND SPECIFICATIONS.







UNIT "A" FIRST FLOOR EQUIPMENT PLAN SCALE: 1/8" = 1'-0"

NORTH

GENERAL EQUIPMENT PLAN NOTES:

- A. REFER TO SPECIFICATIONS AND FINISH LEGEND FOR ADDITIONAL INFORMATION.
- B. FIELD VERIFY ALL DIMENSIONS.
- C. CASEWORK AND/OR MILLWORK INSTALLER TO COORDINATE ELECTRICAL AND PLUMBING WORK. REFER TO ELECTRICAL DRAWINGS AND SCHEDULES FOR ELECTRICAL DEVICE TYPES, HEIGHTS, AND LOCATIONS.
- D. REFER TO G SERIES DRAWINGS FOR MOUNTING HEIGHTS.
- E. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROOM PLANS AND TOILET ROOM ACCESSORIES.
- F. NIGHTLOCK DOOR SECURITY DEVICE PROVIDED BY OWNER, INSTALLED BY CONTRACTOR. CONTRACTOR TO COORDINATE LOCATIONS AND INSTALLATION

WITH OWNER.

EQUIPMENT PLAN LEGEND:

- SERIES DRAWINGS FOR ELEVATIONS AND DETAILS.
- ----- INDICATES ITEMS TO BE PART OF LOOSE EQUIPMENT PACKAGE BY OWNER. (NOT INCLUDED IN CONSTRUCTION CONTRACT).
- ---- INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS (NOT INCLUDED IN CONSTRUCTION CONTRACT).

(CG) INDICATES CORNER GUARD. (MB) INDICATES 4' HIGH MARKER BOARD LENGTH AS INDICATED, REFER TO MOUNTING HEIGHT DRAWINGS.


(TB) INDICATES 1' HIGH TACK BOARD LENGTH AS INDICATED, REFER TO MOUNTING HEIGHT DRAWINGS. EQUIPMENT PLAN NOTES:


- (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)
- (1) NOT USED
- 2 NOT USED
- 3) CASEWORK, MILLWORK, REFER CASEWORK DRAWINGS.
- (4) NEW TOILET PARTITIONS, SEE FINISH LEGEND.
- (5) PRIVACY CURTAIN AND TRACK. REFER TO FINISH LEGEND
- 6 ALTERNATE: MOTORIZED FORWARD FOLDING BASKETBALL BACKSTOP SUPPORTS AND BASKETBALL BACKSTOP AND HOOP.

OWNER FURNISHED EQUIPMENT

PLAN NOTES:

- (50) LOOSE FURNITURE, BY OWNER, INDICATED ON PLAN FOR ROOM LAYOUT
- (51) COMPUTER/MONITOR, BY OWNER
- (52) PRINTER/COPIER, BY OWNER
- (53) FILE CABINET, BY OWNER
- (54) EXISTING COMMUNICATION RACK TO REMAIN, BY OWNER





GENERAL EQUIPMENT PLAN NOTES:

- A. REFER TO SPECIFICATIONS AND FINISH LEGEND FOR ADDITIONAL INFORMATION.
- B. FIELD VERIFY ALL DIMENSIONS.
- C. CASEWORK AND/OR MILLWORK INSTALLER TO COORDINATE ELECTRICAL AND PLUMBING WORK. REFER TO ELECTRICAL DRAWINGS AND SCHEDULES FOR ELECTRICAL DEVICE TYPES, HEIGHTS, AND LOCATIONS.
- D. REFER TO G SERIES DRAWINGS FOR MOUNTING HEIGHTS.
- E. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROOM PLANS AND TOILET ROOM ACCESSORIES. F. NIGHTLOCK DOOR SECURITY DEVICE PROVIDED BY OWNER, INSTALLED BY CONTRACTOR. CONTRACTOR TO COORDINATE LOCATIONS AND INSTALLATION
- WITH OWNER.

EQUIPMENT PLAN LEGEND:

- ----- INDICATES ITEMS TO BE PART OF LOOSE EQUIPMENT PACKAGE
- BY OWNER. (NOT INCLUDED IN CONSTRUCTION CONTRACT).
- ---- INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS (NOT INCLUDED IN CONSTRUCTION CONTRACT).

(CG) INDICATES CORNER GUARD. (MB) INDICATES 4' HIGH MARKER BOARD LENGTH AS INDICATED, REFER TO MOUNTING HEIGHT DRAWINGS.

(TB) INDICATES 1' HIGH TACK BOARD LENGTH AS INDICATED, REFER TO MOUNTING HEIGHT DRAWINGS.


EQUIPMENT PLAN NOTES: (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)


- (1) NOT USED
- 2 NOT USED
- 3) CASEWORK, MILLWORK, REFER CASEWORK DRAWINGS.
- 4) NEW TOILET PARTITIONS, SEE FINISH LEGEND.
- (5) PRIVACY CURTAIN AND TRACK. REFER TO FINISH LEGEND
- 6 ALTERNATE: MOTORIZED FORWARD FOLDING BASKETBALL BACKSTOP SUPPORTS AND BASKETBALL BACKSTOP AND HOOP.

OWNER FURNISHED EQUIPMENT

PLAN NOTES:

- (50) LOOSE FURNITURE, BY OWNER, INDICATED ON PLAN FOR ROOM LAYOU
- (51) COMPUTER/MONITOR, BY OWNER
- (52) PRINTER/COPIER, BY OWNER (53) FILE CABINET, BY OWNER
- (54) EXISTING COMMUNICATION RACK TO REMAIN, BY OWNER





GENERAL EQUIPMENT PLAN NOTES:

- A. REFER TO SPECIFICATIONS AND FINISH LEGEND FOR ADDITIONAL INFORMATION.
- B. FIELD VERIFY ALL DIMENSIONS.
- C. CASEWORK AND/OR MILLWORK INSTALLER TO COORDINATE ELECTRICAL AND PLUMBING WORK. REFER TO ELECTRICAL DRAWINGS AND SCHEDULES FOR ELECTRICAL DEVICE TYPES, HEIGHTS, AND LOCATIONS.
- D. REFER TO G SERIES DRAWINGS FOR MOUNTING HEIGHTS.
- E. REFER TO EQUIPMENT PLANS FOR REFERENCE TO ENLARGED TOILET ROOM PLANS AND TOILET ROOM ACCESSORIES.
- F. NIGHTLOCK DOOR SECURITY DEVICE PROVIDED BY OWNER, INSTALLED BY CONTRACTOR. CONTRACTOR TO COORDINATE LOCATIONS AND INSTALLATION WITH OWNER.

EQUIPMENT PLAN LEGEND:


- ------ INDICATES ITEMS TO BE PART OF LOOSE EQUIPMENT PACKAGE
- BY OWNER. (NOT INCLUDED IN CONSTRUCTION CONTRACT).
- ---- INDICATES BULKHEADS OR OTHER OVERHEAD ITEMS (NOT INCLUDED IN CONSTRUCTION CONTRACT).


(7 CG) INDICATES CORNER GUARD. (MB) INDICATES 4' HIGH MARKER BOARD LENGTH AS INDICATED, REFER TO MOUNTING HEIGHT DRAWINGS.


- (TB) INDICATES 1' HIGH TACK BOARD LENGTH AS INDICATED, REFER TO MOUNTING HEIGHT DRAWINGS. EQUIPMENT PLAN NOTES: (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN) (1) NOT USED
- 2 NOT USED
- 3) CASEWORK, MILLWORK, REFER CASEWORK DRAWINGS.
- 4 NEW TOILET PARTITIONS, SEE FINISH LEGEND.
- 5) PRIVACY CURTAIN AND TRACK. REFER TO FINISH LEGEND
- 6 ALTERNATE: MOTORIZED FORWARD FOLDING BASKETBALL BACKSTOP SUPPORTS AND BASKETBALL BACKSTOP AND HOOP.

OWNER FURNISHED EQUIPMENT

- PLAN NOTES:
- (50) LOOSE FURNITURE, BY OWNER, INDICATED ON PLAN FOR ROOM LAYOU
- (51) COMPUTER/MONITOR, BY OWNER
- (52) PRINTER/COPIER, BY OWNER
- (53) FILE CABINET, BY OWNER
- (54) EXISTING COMMUNICATION RACK TO REMAIN, BY OWNER








ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE FINISH WORK HAS PROCEEDED. AND MATERIALS FOR ALL FINISHES. PER MANUFACTURER'S RECOMMENDED METHOD. F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION. OTHERWISE NOTED. I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED TYPE/COLOR WITH ARCHITECT. OF 450 MAXIMUM, PER IBC SECTION 803. AREA TO MATCH EXISTING (BRONZE COLOR, P8). ANDBULKHEADS SHERWIN WILLIAMS SW7007. MARKERBOARDS, TACKBOARDS OR SIGNAGE SHALL REMAIN. FINISH SYMBOL LEGEND: P1 — WALL FINISH C1 ____FLOOR FINISH CLASSROOM B1 — BASE FINISH (A-126) -- MISC FINISH INFORMATION P1,P6 C2,LVT1 B1 -- $\sqrt{7}$ INDICATES DIRECTION OF FLOOR MATERIAL GRAIN FINISH PLAN NOTES: (ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN) CLASSROOM 5/A-861. (4) PAINT, P2 (5) EXISTING BRICK TO REMAIN. (6) GRAPHIC WALLCOVERING, GWC1 B1 $\overline{}$ (8) ROLLED CARPET ON MEDIA AND MUSIC STEPS, C4. (9) CARPET, C5. (10) CARPET, C3 END HERE. (11) ALTERNATE: PLASTIC LAMINATE COUNTERS, PL4 (12) EXISTING VCT PATTERN TO REMAIN. CORRIDOR AD-03 ART (A-128) P1,P6 LVT1 B1 --(7)TORAGE CLASSROO C-101) \longleftrightarrow SPEECH/ HEARING (1)TITLE I CLASSROOM (C-112) STORAGE <u>C-114</u>) V₉ P1 C2 B1 --READING (C-116)


 \longleftrightarrow

P1,P6

GENERAL FINISH PLAN NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE FLOOR PATTERN PLANS, EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
- C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE
- D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS
- E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES. H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER
- CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS
- CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED ON PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED J. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW
- INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX
- K. PAINT NEW DOOR FRAMES TO MATCH EXISTING (BRONZE COLOR, P8)- ALL SIDES UNLESS NOTED OTHERWISE. PAINT EXISTING DOOR FRAMES IN ADMIN
- L. UNLESS NOTED OTHERWISE, PAINT GYPSUM BOARD AND OR PLASTER CEILING L. EXISTING FABRIC WRAPPED TACKABLE WALLS, TACKABLE PANELS,
- 1 NO NEW FINISHES THIS ROOM, EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES. 2 WALL AND FLOOR TILE, REFER TO FINISH LEGEND AND ELEVATION ON SHEET 4/A-861.
- (3) PAINT, P3 AND P4. SEE FINISH LEGEND AND ELEVATION ON SHEET
- (7) paint bulkheads and/or slanted wall and light cove, p6






GENERAL FINISH PLAN NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE FLOOR PATTERN PLANS, EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
- C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ÍSSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE FINISH WORK HAS PROCEEDED.
- D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES. . ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX
- MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD. F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING
- MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION. G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES.
- H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- TYPE/COLOR WITH ARCHITECT. J. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A
- FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803. K. PAINT NEW DOOR FRAMES TO MATCH EXISTING (BRONZE COLOR, P8)- ALL
- SIDES UNLESS NOTED OTHERWISE. PAINT EXISTING DOOR FRAMES IN ADMIN AREA TO MATCH EXISTING (BRONZE COLOR, P8). L. UNLESS NOTED OTHERWISE, PAINT GYPSUM BOARD AND OR PLASTER CEILING
- ANDBULKHEADS SHERWIN WILLIAMS SW7007. L. EXISTING FABRIC WRAPPED TACKABLE WALLS, TACKABLE PANELS, MARKERBOARDS, TACKBOARDS OR SIGNAGE SHALL REMAIN.

FINISH SYMBOL LEGEND:



INDICATES DIRECTION OF FLOOR MATERIAL GRAIN


FINISH PLAN NOTES:


(ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)

- 1 NO NEW FINISHES THIS ROOM, EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES.
- 2 WALL AND FLOOR TILE, REFER TO FINISH LEGEND AND ELEVATION ON SHEET 4/A-861.
- 3 PAINT, P3 AND P4. SEE FINISH LEGEND AND ELEVATION ON SHEET 5/A-861.
- (4) PAINT, P2
- 5) EXISTING BRICK TO REMAIN.
- (6) GRAPHIC WALLCOVERING, GWC1
- 7) PAINT BULKHEADS AND/OR SLANTED WALL AND LIGHT COVE, P6 8) ROLLED CARPET ON MEDIA AND MUSIC STEPS, C4.
- (9) CARPET, C5. 10) CARPET, C3 END HERE.
- 11) ALTERNATE: PLASTIC LAMINATE COUNTERS, PL4
- (12) EXISTING VCT PATTERN TO REMAIN.

UNIT "B" FIRST FLOOR FINISH PLAN

SCALE: 1/8" = 1'-0"






GENERAL FINISH PLAN NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION.
 B. REFERENCE FLOOR PATTERN PLANS, EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
- C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALL SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE FINISH WORK HAS PROCEEDED.
- D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL FLOORING IS TO BE LEVELED WITHIN 1/4" IN 10'-0" WITH LATEX MATERIAL. MOISTURE CONTENT IN AREA IS TO BE TESTED PRIOR TO INSTALLATION OF FLOORING MATERIAL. CONTRACTOR TO INSTALL FLOORING PER MANUFACTURER'S RECOMMENDED METHOD.
 F. FLOORING CONTRACTOR TO SUBMIT A SEAMING DIAGRAM FOR FLOORING
- MATERIAL INCLUDING NOTATION OF MATERIAL DIRECTION.
- G. ALL FLOORING TRANSITIONS SHALL COMPLY WITH ADA GUIDELINES.
 H. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
 CONTRACTOR TO PROVIDE AND INSTANCE FLOORENCE FLOORENCE.
- I. CONTRACTOR TO PROVIDE AND INSTALL FLOORING TRANSITIONS AS INDICATED ON PLANS. WHERE NONE ARE NOTED, CONTRACTOR SHALL VERIFY REQUIRED TYPE/COLOR WITH ARCHITECT.
 J. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A
- K. PAINT NEW DOOR FRAMES TO MATCH EXISTING (BRONZE COLOR, P8)- ALL
- SIDES UNLESS NOTED OTHERWISE. PAINT EXISTING DOOR FRAMES IN ADMIN AREA TO MATCH EXISTING (BRONZE COLOR, P8). L. UNLESS NOTED OTHERWISE, PAINT GYPSUM BOARD AND OR PLASTER CEILING
- ANDBULKHEADS SHERWIN WILLIAMS SW7007. L. EXISTING FABRIC WRAPPED TACKABLE WALLS, TACKABLE PANELS, MARKERBOARDS, TACKBOARDS OR SIGNAGE SHALL REMAIN.

FINISH SYMBOL LEGEND:




INDICATES DIRECTION OF FLOOR MATERIAL GRAIN

FINISH PLAN NOTES:


(ALL PLAN NOTES MAY NOT BE INDICATED ON THIS PLAN)


- 1 NO NEW FINISHES THIS ROOM, EXCLUDING DOOR FRAMES CONNECTED TO OTHER ROOMS THAT RECEIVE NEW FINISHES.
- 2 WALL AND FLOOR TILE, REFER TO FINISH LEGEND AND ELEVATION ON SHEET 4/A-861.
- 3 PAINT, P3 AND P4. SEE FINISH LEGEND AND ELEVATION ON SHEET 5/A-861.
- 4 PAINT, P2
- (5) EXISTING BRICK TO REMAIN.
- 6 GRAPHIC WALLCOVERING, GWC1
- (7) PAINT BULKHEADS AND/OR SLANTED WALL AND LIGHT COVE, P6
- (8) ROLLED CARPET ON MEDIA AND MUSIC STEPS, C4.
- 9 CARPET, C5.
- (10) CARPET, C3 END HERE.
- (11) ALTERNATE: PLASTIC LAMINATE COUNTERS, PL4
- (12) EXISTING VCT PATTERN TO REMAIN.








					FINISH LE			
	SURFACE WALL BASE	MARK	DESCRIPTION	MANUFACTURER	PATTERN/FINISH	NUMBER/COLOR	SIZE	COMMENTS
		B1 B2	WALL BASE WALL BASE	TARKETT TARKETT		BURNT UMBER 63 BURNT UMBER 63	4" COVE 6" MILLWORK	
		TB1	TILE BASE	DALTILE	UNGLAZED MOSAICS	STORM GRAY SPECKLED A22	5" BUILT-UP COVE	
	C1	.S C1a C1b	CARPET TILE CARPET TILE	TARKETT MANNINGTON	SQUAREUP II 11549 HUB	ELECTRICITY 71604 CUSTOM COLOR	24" X 24" 24" X 24"	INSTALL: VERTICAL ASHLAR INSTALL: VERTICAL ASHLAR
	C2		CARPET TILE CARPET TILE	TARKETT MANNINGTON	CREATE BALANCE 11770 CIRCUIT	FORWARD 32809 VIDEO DECODER 14403	24" X 24" 24" X 24"	INSTALL: VERTICAL ASHLAR INSTALL: VERTICAL ASHLAR
	C3	C3a C3b	CARPET TILE CARPET TILE	TARKETT MANNINGTON	ABRASIVE ACTION II 02578 FORCE	WINTER GRAY 19103 STATIC 34365	24" X 24" 18" X 36"	INSTALL: MONOLITHIC INSTALL: MONOLITHIC
	C4	C4a C4b C5a	ROLLED CARPET ROLLED CARPET CARPET TILE	TARKETT MANNINGTON TARKETT	CREATE BALANCE 11770 CIRCUIT FABRICATE 11498	FORWARD 32809 VIDEO DECODER 14403 BASE GREY 36201	1260" X 72" 150" 24" X 24"	 INSTALL: VERTICAL ASHLAR
C	C5 C6	C5b C6	CARPET TILE CARPET TILÉ	MANNINGTON TARKETT	INSIGHT GABARDINE 11511	FOGGY 13354 BEDSTONE 77204	12" X 36" 24" X 24"	INSTALL: VERTICAL ASHLAR INSTALL: VERTICAL ASHLAR – SEE NOTE 5
	LVT1	LVT1a LVT1b	LUXURY VINYL TILE	TARKETT MANNINGTON	ENTWINE CRISSCROSS	OXFORD 10383 FLASH AL101	36" X 9" 36" X 6"	
		FT1	MOSAIC FLOOR TILE	AMERICAN OLEAN	UNGLAZED MOSAICS	STROM GRAY SPECKLED A22	2" X 2"	
	WALL MATERIAL		PAINT	SHERWIN WILLIAMS		SW 7029 AGREEABLE GRAY		I
		P2 P3	PAINT PAINT PAINT	SHERWIN WILLIAMS SHERWIN WILLIAMS SHERWIN WILLIAMS	 	SW 7029 AGREEABLE GRAT SW 7017 DORIAN GRAY CUSTOM	 	 SEE NOTE 1
		P4 P5	PAINT PAINT	SHERWIN WILLIAMS NOT USED	 	CUSTOM	 	SEE NOTE 2
		P6 P7	PAINT PAINT PAINT	SHERWIN WILLIAMS SHERWIN WILLIAMS SHERWIN WILLIAMS	 	SW 7004 SNOWBOUND SW 7757 HIGH REFLECTIVE WHITE CUSTOM	 	 SEE NOTE 4
		P8 W1	PAINT WALLCOATING	SHERWIN WILLIAMS SHERWIN WILLIAMS		SW 7029 AGREEABLE GRAY	 	SEE NOTE 4
		W2	WALLCOATING	SHERWIN WILLIAMS		SW 7017 DORIAN GRAY		
		GWC1	GRAPHIC WALL COVERING			DESERT		SEE NOTE 3
		WT1 WT2 WT3	CERAMIC WALL TILE CERAMIC WALL TILE CERAMIC WALL TILE	AMERICAN OLEAN AMERICAN OLEAN	COLOR STORY WALL COLOR STORY WALL COLOR STORY WALL	ICE WHITE 0025 STABLE 0053 DEPENDABLE 0053	4" X 12" 4" X 12" 4" X 12"	
		WT4	CERAMIC WALL TILE	AMERICAN OLEAN AMERICAN OLEAN	COLOR STORY WALL COLOR STORY WALL	DEPENDABLE 0053 STORM GRAY 40	4" X 12" 4" X 12"	
		AR-AWP1 AR-AWP2	ACOUSTICAL PANEL ACOUSTICAL PANEL		TECTUM TECTUM	SW 7017 DORIAN GRAY CUSTOM	 	 SEE NOTE 1
		AR-AWP3	ACOUSTICAL PANEL		TECTUM	CUSTOM		SEE NOTE 2
	CASEWORK AND	_					1	
		PL1 PL2 PL3	PLASTIC LAMINATE PLASTIC LAMINATE PLASTIC LAMINATE	WILSONART WILSONART WILSONART	12 SOFTGRAIN 31 TRACELESS 38 FINE VELVET TEXTURE	UPTOWN WALNUT 7917 CHARCOAL VELVET 15504 ORGANIC COTTON 4945	 	
		PL4	PLASTIC LAMINATE PLASTIC LAMINATE PLASTIC LAMINATE	WILSONARI WILSONARI WILSONART	60 MATTE	CANYON ZEPHYR 4842		
			SOLID SURFACE					
•	MISCELLANEOUS				•			
· · · · · · · · · · · · · · · · · · ·		CG1 TP1	CORNER GUARD TOLIET PARTITION	ASI	 ORANGE PEEL	 GRAY 9200		
		CG1 TP1 TRIM1 PC	TOLIET PARTITION METAL TRIM PRIVACY CURTAIN	ASI SCHLUTER ARCHITEX	ORANGE PEEL	GRAY 9200 Breezy Rx 7004	 	
	ETR = EXISTING T 1. CUSTOM COLOF 2. CUSTOM COLOF 3. GRAPHIC WALL GRAPHIC MAY E 4. CUSTOM COLOF 5. OWNER HOLDS ONE DIE LOT II	CG1 TP1 TRIM1 PC C COREMAIN TO MATCH SI COVERING TO SE CUSTOMIZED TO MATCH E ATTIC STOCK N A ROOM.	TOLIET PARTITION METAL TRIM PRIVACY CURTAIN CHOOL COLOR BLUE. HEX# CHOOL COLOR SILVER. TO COVER EXISTING FOLDING COVER EXISTING FOLDING (MAKING SCALE AND/OR XISTING DOOR FRAMES (BR OF C6 CARPET FOR USE. 1	ASI SCHLUTER ARCHITEX ARCHITEX 334B77, TO BE VERIFIED BE VERIFIED WITH OWNER PARTITION DOOR. APPROX COLOR ADJUSTMENTS). ONZE COLOR) VERIFY AMOUNT WITH OWN	ORANGE PEEL	GRAY 9200 		
AD-03	ETR = EXISTING T 1. CUSTOM COLOF 2. CUSTOM COLOF 3. GRAPHIC WALL GRAPHIC MAY E 4. CUSTOM COLOF 5. OWNER HOLDS ONE DIE LOT II	CG1 TP1 TRIM1 PC C COREMAIN TO MATCH SI COVERING TO SE CUSTOMIZED TO MATCH E ATTIC STOCK N A ROOM.	TOLIET PARTITION METAL TRIM PRIVACY CURTAIN CHOOL COLOR BLUE. HEX# CHOOL COLOR SILVER. TO COVER EXISTING FOLDING COVER EXISTING FOLDING (MAKING SCALE AND/OR XISTING DOOR FRAMES (BR OF C6 CARPET FOR USE. 1	ASI SCHLUTER ARCHITEX ARCHITEX 334B77, TO BE VERIFIED BE VERIFIED WITH OWNER PARTITION DOOR. APPROX COLOR ADJUSTMENTS). ONZE COLOR) VERIFY AMOUNT WITH OWN	ORANGE PEEL	GRAY 9200		
AD-03	ETR = EXISTING T 1. CUSTOM COLOF 2. CUSTOM COLOF 3. GRAPHIC WALL GRAPHIC MAY E 4. CUSTOM COLOF 5. OWNER HOLDS ONE DIE LOT II	CG1 TP1 TRIM1 PC C COREMAIN TO MATCH SI COVERING TO SE CUSTOMIZED TO MATCH E ATTIC STOCK N A ROOM.	TOLIET PARTITION METAL TRIM PRIVACY CURTAIN CHOOL COLOR BLUE. HEX# CHOOL COLOR SILVER. TO COVER EXISTING FOLDING COVER EXISTING FOLDING (MAKING SCALE AND/OR XISTING DOOR FRAMES (BR OF C6 CARPET FOR USE. 1	ASI SCHLUTER ARCHITEX ARCHITEX 334B77, TO BE VERIFIED BE VERIFIED WITH OWNER PARTITION DOOR. APPROX COLOR ADJUSTMENTS). ONZE COLOR) VERIFY AMOUNT WITH OWN	ORANGE PEEL	GRAY 9200 Breezy Rx 7004 X 12'-0". CCT. INSTALL		
AD-03	ETR = EXISTING T 1. CUSTOM COLOF 2. CUSTOM COLOF 3. GRAPHIC WALL GRAPHIC MAY E 4. CUSTOM COLOS ONE DIE LOT II ONE DIE LOT II CONTINUOL TREATED V	CG1 TP1 TRIM1 PC CONSTRUCT TO MATCH SI COVERING TO SE CUSTOMIZED ATTIC STOCK A ROOM.	TOLIET PARTITION	ASI SCHLUTER ARCHITEX ARCHITEX 334B77, TO BE VERIFIED BE VERIFIED WITH OWNER PARTITION DOOR. APPROX COLOR ADJUSTMENTS). ONZE COLOR) VERIFY AMOUNT WITH OWN	ORANGE PEEL	GRAY 9200 Total Breezy Rx 7004 X 12'-0". CT. INSTALL PLAN CEILING LINE		
	ETR = EXISTING T 1. CUSTOM COLOF 2. CUSTOM COLOF 3. GRAPHIC WALL GRAPHIC MAY E 4. CUSTOM COLOF 5. OWNER HOLDS ONE DIE LOT II	CG1 TP1 TRIM1 PC COREMAIN TO MATCH SI COVERING TO SE CUSTOMIZED ATTIC STOCK A ROOM. COMATCH E ATTIC STOCK A ROOM.	CHOOL COLOR BLUE. HEX# CHOOL COLOR BLUE. HEX# CHOOL COLOR SILVER. TO COVER EXISTING FOLDING D (MAKING SCALE AND/OR XISTING DOOR FRAMES (BR OF C6 CARPET FOR USE.	ASI SCHLUTER ARCHITEX ARCHITEX 334B77, TO BE VERIFIED BE VERIFIED WITH OWNER PARTITION DOOR. APPROX COLOR ADJUSTMENTS). ONZE COLOR) VERIFY AMOUNT WITH OWN	ORANGE PEEL	CRAY 9200 Breezy Rx 7004 X 12'-0". DCT. INSTALL		















A-860/

CAFETERIA SOUTH ELEVATION SCALE: 1/4" = 1'-0"

Thursday, 3/7/2024 - 4:59 PM - LAST SAVED Y:\23-119 TRI-CREEK SC -THREE CREEKS ES IMPROVEMENTS\23-119 THREE CREEKS ES\05 ARCH\A-860-TC.DWG



65

63


63


64

3'-0"


(52)

8






SCALE: 1/4" = 1'-0"




SCALE: 1/4" = 1'-0"



$$\begin{array}{c} \hline \textbf{CAFETERIA EAST ELEVATION} \\ \hline \textbf{SCALE: } 1/4" = 1'-0" \end{array} \qquad \begin{array}{c} 4 \\ \hline \textbf{A-860} \end{array}$$



 $\frac{\text{CAFETERIA WEST ELEVATION}}{\text{SCALE: } 1/4" = 1'-0"}$ $\begin{pmatrix} 3 \\ A-860 \end{pmatrix}$



A-860/

GENERAL INTERIOR ELEVATION NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE FLOOR PATTER PLANS, EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
- C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALI SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE FINISH WORK HAS PROCEEDED.
- D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL EXPOSED METAL SURFACES, SUCH AS GRILLES, FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- F. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803.


INTERIOR ELEVATION NOTES: (ALL ELEVATION NOTES MAY NOT BE INDICATED ON THIS PLAN)

- (1) FIRE EXTINGUISHER CABINET, REFER TO EQUIPMENT PLANS.
- (2) FOLDING PARTITION DOOR.
- (3) BLEACHERS. (4) ALTERNATE: NEW BASKETBALL BACKSTOP AND SUPPORT, REFER TO EQUIPMENT PLAN.
- (5) SAFETY CUSHION WAINSCOT, REFER TO EQUIPMENT PLAN. AD-03 (6) SCOREBOARD.
- 7) TACKABLE WALL SURFACE, REFER TO FINISH PLANS.
- (8) DOOR (9) EXPOSED STRUCTURE AND ROOF DECK.
- (10) EXIT SIGN
- (11) HVAC. (12) HVAC VENT.
- (13) SPEAKER.
- (14) WINDOW.

INTERIOR ELEVATION FINISH NOTES: (ALL ELEVATION NOTES MAY NOT BE INDICATED ON THIS PLAN)

- (50) PAINT, P1
- (51) PAINT, P2
- 52) PAINT, P3
- (53) PAINT, P4 (54) NOT USED
- (55) PAINT, P6
- (56) WALLCOATING, W1. IN INSTANCES WHERE THERE IS BRICK, BRICK TO REMAIN. REFER TO FINISH PLANS.
- (57) WALLCOATING, W2. IN INSTANCES WHERE THERE IS BRICK, BRICK TO REMAIN, REFER TO FINISH PLANS.
- (58) PAINT. P7.
- (59) NOT USED (60) GRAPHIC WALLCOVERING, GWC1
- (61) WALL BASE, B1
- (62) WALL BASE, B2
- (63) ACOUSTICAL WALL PANEL AR-AWP1
- (64) ACOUSTICAL WALL PANEL AR-AWP2 AD-03
- (65) ACOUSTICAL WALL PANEL AR-AWP3
- 66 SCHLUTER TRIM, OUTSIDE CORNER OR END OF TILE RUN





Thursday, 3/7/2024 – 5:06 PM – LAST SAVED Y:\23-119 TRI-CREEK SC -THREE CREEKS ES IMPROVEMENTS\23-119 THREE CREEKS ES\05 ARCH\A-861-TC.DWG

SCALE: 1/4" = 1'-0"

86'-4"								
			9					

		 52	 	 	
		2			_

SCALE: 1/4" = 1'-0"

\A−861

GENERAL INTERIOR ELEVATION NOTES:

- A. REFERENCE FINISH LEGEND FOR FINISH INFORMATION. B. REFERENCE FLOOR PATTER PLANS, EQUIPMENT PLANS, INTERIOR ELEVATIONS, REFLECTED CEILING PLANS AND WRITTEN SPECIFICATIONS FOR ADDITIONAL FINISH INFORMATION.
- C. PRIOR TO INSTALLATION OF NEW FINISHES CONTRACTOR SHALL INSPECT ALI SUBSTRATES. IF A SUBSTRATE IS DEEMED UNACCEPTABLE THE CONTRACTOR SHALL TAKE THE NECESSARY STEPS TO RECTIFY THE SITUATION OR CONTACT THE ARCHITECT WITH THE CONCERN. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND /OR FINISHER HAS ACCEPTED SAID SUBSTRATE. NO CHANGE ORDER WILL B ÍSSUED TO RECTIFY CONCEALED, OR UNSATISFACTORY SUBSTRATE ONCE FINISH WORK HAS PROCEEDED.
- D. PREPARE ALL WALL CONSTRUCTION, NEW AND EXISTING, TO RECEIVE NEW FINISHES AS PER MANUFACTURE'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- E. ALL EXPOSED METAL SURFACES. SUCH AS GRILLES. FIRE EXTINGUISHER CABINETS, ETC, THAT ARE NOTED TO BE PAINTED, SHALL BE PAINTED WITH ALKYD TYPE PAINT. COLOR TO BE COORDINATED WITH DESIGNER UNLESS OTHERWISE NOTED.
- F. THE CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY THAT ALL NEW INTERIOR WALL AND CEILING FINISHES WILL BE CLASS B MINIMUM, WITH A FLAME SPREAD RATING OF 75 MAXIMUM, AND A SMOKE DEVELOPED INDEX OF 450 MAXIMUM, PER IBC SECTION 803.

INTERIOR ELEVATION NOTES: (ALL ELEVATION NOTES MAY NOT BE INDICATED ON THIS PLAN)

- 1) FIRE EXTINGUISHER CABINET, REFER TO EQUIPMENT PLANS. 2) FOLDING PARTITION DOOR. (3) BLEACHERS. (4) ALTERNATE: NEW BASKETBALL BACKSTOP AND SUPPORT, REFER TO EQUIPMENT PLAN. (5) SAFETY CUSHION WAINSCOT, REFER TO EQUIPMENT PLAN. AD-03 (6) SCOREBOARD. 7) TACKABLE WALL SURFACE, REFER TO FINISH PLANS. 8) DOOR (9) EXPOSED STRUCTURE AND ROOF DECK. (10) EXIT SIGN (11) HVAC. (12) HVAC VENT. (13) SPEAKER. (14) WINDOW. **INTERIOR ELEVATION FINISH NOTES:** (ALL ELEVATION NOTES MAY NOT BE INDICATED ON THIS PLAN) (50) PAINT, P1 (51) PAINT, P2 (52) PAINT, P3 (53) PAINT, P4 (54) NOT USED (55) PAINT, P6 (56) WALLCOATING, W1. IN INSTANCES WHERE THERE IS BRICK, BRICK TO REMAIN. REFER TO FINISH PLANS.
- (57) WALLCOATING, W2. IN INSTANCES WHERE THERE IS BRICK, BRICK TO REMAIN, REFER TO FINISH PLANS.
- (58) PAINT. P7. (59) NOT USED
- (60) GRAPHIC WALLCOVERING, GWC1
- (61) WALL BASE, B1
- (62) WALL BASE, B2
- (63) ACOUSTICAL WALL PANEL AR-AWP1
- ƳAD-03| 64) ACOUSTICAL WALL PANEL AR-AWP2 (65) ACOUSTICAL WALL PANEL AR-AWP3
- 66 SCHLUTER TRIM, OUTSIDE CORNER OR END OF TILE RUN

